

SAFETY DATA SHEET

Revision Date 01-April-2024

Revision Number 5

1. Identification

Product Name	Methylithium, 1-2M in ether
Cat No. :	42992
Synonyms	No information available
Recommended Use	Laboratory chemicals.
Uses advised against	Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Importer/Distributor

Fisher Scientific
112 Colonnade Road,
Ottawa, ON K2E 7L6,
Canada
Tel: 1-800-234-7437

Emergency Telephone Number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11

Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99

CHEMTREC Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

WHMIS 2015 Classification Classified as hazardous under the Hazardous Products Regulations (SOR/2015-17)

Flammable liquids	Category 1	
Substances/mixtures which, in contact with water, emit flammable gases	Category 1	Gas(es) = Methane
Pyrophoric liquids	Category 1	
Acute oral toxicity	Category 4	
Skin Corrosion/Irritation	Category 1 B	
Serious Eye Damage/Eye Irritation	Category 1	
Specific target organ toxicity (single exposure)	Category 3	
Target Organs - Respiratory system, Central nervous system (CNS).		
Physical Hazards Not Otherwise Classified	Category 1	
Reacts violently with water		
May form explosive peroxides		
Health Hazards Not Otherwise Classified	Category 1	
Repeated exposure may cause skin dryness or cracking		

Label Elements**Signal Word**

Danger

Hazard Statements

Extremely flammable liquid and vapor

In contact with water releases flammable gases which may ignite spontaneously

Catches fire spontaneously if exposed to air

Harmful if swallowed

Causes severe skin burns and eye damage

May cause respiratory irritation

May cause drowsiness and dizziness

Reacts violently with water

May form explosive peroxides

Repeated exposure may cause skin dryness or cracking

**Precautionary Statements****Prevention**

Do not allow contact with water

Keep container tightly closed

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Do not allow contact with air

Ground/bond container and receiving equipment

Do not breathe dust/fumes/gas/mist/vapours/spray

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Wear protective gloves/protective clothing/eye protection/face protection

Use non-sparking tools

Take action to prevent static discharges

Handle and store contents under inert gas. Protect from moisture

Response

IF ON SKIN: Wash with plenty of soap and water

IF INHALED: Remove person to fresh air and keep comfortable for breathing

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Immediately call a POISON CENTER/doctor

Rinse mouth

Do NOT induce vomiting

Wash contaminated clothing before reuse

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

IF ON SKIN: Immerse in cool water or wrap

Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Store contents under inert gas

Store in a dry place. Store in a closed container

Disposal

Dispose of contents/container to an approved waste disposal plant

3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Ethyl ether	60-29-7	56.06
Lithium, methyl-	917-54-4	43.94

4. First-aid measures

General Advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Call a physician immediately.
Inhalation	If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately.
Ingestion	Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately.
Most important symptoms/effects	Causes burns by all exposure routes. Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting; Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media	CO ₂ , dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.
Unsuitable Extinguishing Media	No information available
Flash Point	-17 °C / 1.4 °F
Method -	No information available
Autoignition Temperature	No information available
Explosion Limits	
Upper	No data available
Lower	No data available
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Reacts violently with water. Extremely flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Methane.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

Health
3

Flammability
4

Instability
2

Physical hazards
W

6. Accidental release measures

Personal Precautions

Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions

Should not be released into the environment. See Section 12 for additional Ecological Information.

Methods for Containment and Clean Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Do not expose spill to water. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7. Handling and storage

Handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Do not allow contact with water. If peroxide formation is suspected, do not open or move container. Keep away from open flames, hot surfaces and sources of ignition. Use spark-proof tools and explosion-proof equipment. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Storage.

Corrosives area. Keep away from water or moist air. Keep containers tightly closed in a dry, cool and well-ventilated place. Containers should be dated when opened and tested periodically for the presence of peroxides. Should crystals form in a peroxidizable liquid, peroxidation may have occurred and the product should be considered extremely dangerous. In this instance, the container should only be opened remotely by professionals. Keep away from heat, sparks and flame.

8. Exposure controls / personal protection

Exposure Guidelines

Component	Alberta	British Columbia	Ontario TWAEV	Quebec	ACGIH TLV	OSHA PEL	NIOSH
Ethyl ether	TWA: 400 ppm TWA: 1210 mg/m ³ STEL: 500 ppm STEL: 1520 mg/m ³	TWA: 400 ppm STEL: 500 ppm	TWA: 400 ppm STEL: 500 ppm	TWA: 400 ppm TWA: 1210 mg/m ³ STEL: 500 ppm STEL: 1520 mg/m ³	TWA: 400 ppm STEL: 500 ppm	(Vacated) TWA: 400 ppm (Vacated) TWA: 1200 mg/m ³ (Vacated) STEL: 500 ppm (Vacated) STEL: 1500 mg/m ³ TWA: 400 ppm TWA: 1200 mg/m ³	IDLH: 1900 ppm

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location.
 Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment.
 Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment**Eye Protection**

Goggles

Hand Protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Glove material	Breakthrough time	Glove thickness	Glove comments
Viton (R)	See manufacturers recommendations	-	Splash protection only

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Recommended Filter type: low boiling organic solvent Type AX Brown conforming to EN371 or Organic gases and vapours filter Type A Brown conforming to EN14387

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

No information available.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

9. Physical and chemical properties

Physical State	Liquid
Appearance	Yellow
Odor	Ether
Odor Threshold	No information available
pH	No information available
Melting Point/Range	No data available
Boiling Point/Range	No information available
Flash Point	-17 °C / 1.4 °F
Evaporation Rate	No information available
Flammability (solid,gas)	Not applicable
Flammability or explosive limits	
Upper	No data available
Lower	No data available
Vapor Pressure	No information available
Vapor Density	No information available
Specific Gravity	0.732 g/cm3
Solubility	No information available
Partition coefficient; n-octanol/water	No data available

Autoignition Temperature	No information available
Decomposition Temperature	No information available
Viscosity	No information available
Molecular Formula	CH ₃ Li
Molecular Weight	21.97

10. Stability and reactivity

Reactive Hazard	Yes
Stability	Stable under normal conditions.
Conditions to Avoid	Exposure to moist air or water. Exposure to moisture. Keep away from open flames, hot surfaces and sources of ignition.
Incompatible Materials	Strong oxidizing agents
Hazardous Decomposition Products	Methane
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing. Reacts violently with water.

11. Toxicological information

Acute Toxicity

Product Information

Oral LD50

Category 4. ATE = 300 - 2000 mg/kg.

Dermal LD50

Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.

Vapor LC50

Based on ATE data, the classification criteria are not met. ATE > 20 mg/l.

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethyl ether	1215 mg/kg (Rat)	20 mL/kg (Rabbit)	32000 ppm (Rat) 4 h

Toxicologically Synergistic Products No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation	No information available
Sensitization	No information available
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Ethyl ether	60-29-7	Not listed	Not listed	Not listed	Not listed	Not listed
Lithium, methyl-	917-54-4	Not listed	Not listed	Not listed	Not listed	Not listed

Mutagenic Effects No information available

Reproductive Effects No information available.

Developmental Effects No information available.

Teratogenicity No information available.

STOT - single exposure Respiratory system Central nervous system (CNS)

STOT - repeated exposure None known

Aspiration hazard No information available

Symptoms / effects, both acute and delayed Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Ethyl ether	Not listed	LC50: > 10000 mg/L, 96h static (Lepomis macrochirus) LC50: = 2560 mg/L, 96h flow-through (Pimephales promelas)	EC50 = 5600 mg/L 15 min	EC50 = 165 mg/L/24h

Persistence and Degradability No information available

Bioaccumulation/ Accumulation No information available.

Mobility No information available.

Component	log Pow
Ethyl ether	0.82

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Ethyl ether - 60-29-7	U117	-

14. Transport information

DOT

UN-No UN3394
 Proper Shipping Name ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE
 Technical Name Ethyl ether, Lithium, methyl-
 Hazard Class 4.2
 Subsidiary Hazard Class 4.3
 Packing Group I

TDG

Forbidden

IATA

FORBIDDEN FOR IATA TRANSPORT

UN-No UN3394
 Proper Shipping Name ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE
 FORBIDDEN FOR IATA TRANSPORT
 Hazard Class 4.2
 Subsidiary Hazard Class 4.3
 Packing Group I

IMDG/IMO

UN-No UN3394
 Proper Shipping Name ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE
 Hazard Class 4.2
 Subsidiary Hazard Class 4.3

Packing Group

I

15. Regulatory information

International Inventories

Component	CAS-No	DSL	NDSL	TSCA	TSCA Inventory notification - Active-Inactive	EINECS	ELINCS	NLP
Ethyl ether	60-29-7	X	-	X	ACTIVE	200-467-2	-	-
Lithium, methyl-	917-54-4	-	X	X	ACTIVE	213-026-4	-	-

Component	CAS-No	IECSC	KECL	ENCS	ISHL	TCSI	AICS	NZIoC	PICCS
Ethyl ether	60-29-7	X	KE-27690	X	X	X	X	X	X
Lithium, methyl-	917-54-4	X	KE-24321	X	X	X	X	X	X

Legend:

X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

Canada

SDS in compliance with provisions of information as set out in Canadian Standard - Part 4, Schedule 1 and 2 of the Hazardous Products Regulations (HPR) and meets the requirements of the HPR (Paragraph 13(1)(a) of the Hazardous Products Act (HPA)).

Component	Canada - National Pollutant Release Inventory (NPRI)	Canadian Environmental Protection Agency (CEPA) - List of Toxic Substances	Canada's Chemicals Management Plan (CEPA)
Ethyl ether	Part 4 Substance		

Other International Regulations

Authorisation/Restrictions according to EU REACH

Not applicable

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS-No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Ethyl ether	60-29-7	Listed	Not applicable	Not applicable	Not applicable
Lithium, methyl-	917-54-4	Not applicable	Not applicable	Not applicable	Not applicable

Component	CAS-No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Ethyl ether	60-29-7	Not applicable	Not applicable	Not applicable	Annex I - Y40 Annex I - Y42
Lithium, methyl-	917-54-4	Not applicable	Not applicable	Not applicable	Not applicable

16. Other information

Prepared By	Product Safety Department Email: chem.techinfo@thermofisher.com www.thermofisher.com
Revision Date	01-April-2024
Print Date	01-April-2024
Revision Summary	New emergency telephone response service provider.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS