

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**
**Product Identifier**

Perihalan Produk:

Ethanol, anhydrous, denatured

Product Description:

Ethanol, anhydrous, denatured

Cat No. :

C46368

**Relevant identified uses of the substance or mixture and uses advised against**

Recommended Use

Laboratory chemicals.

Uses advised against

No Information available

**Company**

 Thermo Fisher Scientific Fisher Scientific (M) Sdn Bhd  
 Hap Seng Business Park, Lot 01-03, 01-04 Aras 1 Unity Square,  
 No 12, Persiaran Perusahaan, Seksyen 23, 40300 Shah Alam,  
 Selangor Darul Ehsan, Malaysia.  
 Main line: +60 3-5525 7888

**Supplier**

E-mail address

Enquiry.my@thermofisher.com

Emergency Telephone Number

 Tel: +03-5525 7888  
 CHEMTREC Malaysia **1-800-815-308** (Malay)  
 CHEMTREC Malaysia (Kuala Lumpur) **+(60)-327884561** (Malay)

**SECTION 2: HAZARDS IDENTIFICATION**
**Classification of the substance or mixture**

|                                   |                   |
|-----------------------------------|-------------------|
| Flammable liquids                 | Category 2 (H225) |
| Serious Eye Damage/Eye Irritation | Category 2 (H319) |

**Label Elements**


Signal Word

Danger

**Hazard Statements**

 H225 - Highly flammable liquid and vapor  
 H319 - Causes serious eye irritation

# SAFETY DATA SHEET

Ethanol, anhydrous, denatured

Revision Date 31-Mar-2025

## Precautionary Statements

### Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P233 - Keep container tightly closed

P240 - Ground and bond container and receiving equipment

P242 - Use non-sparking tools

P243 - Take action to prevent static discharges

P264 - Wash face, hands and any exposed skin thoroughly after handling

P280 - Wear protective gloves/protective clothing/eye protection/face protection

### Response

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P337 + P313 - If eye irritation persists: Get medical advice/attention

P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

### Storage

P403 + P235 - Store in a well-ventilated place. Keep cool

### Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

## Other Hazards

EUH066 - Repeated exposure may cause skin dryness or cracking

Contains a known or suspected endocrine disruptor

Contains a substance on the National Authorities Endocrine Disruptor Lists

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

| Component           | CAS No    | Weight % |
|---------------------|-----------|----------|
| Ethyl alcohol       | 64-17-5   | >95      |
| Methyl ethyl ketone | 78-93-3   | 1        |
| Isopropyl alcohol   | 67-63-0   | 1        |
| Denatonium benzoate | 3734-33-6 | 0.001    |

## SECTION 4: FIRST AID MEASURES

### Description of first aid measures

#### General Advice

If symptoms persist, call a physician.

#### Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

#### Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.

#### Ingestion

Clean mouth with water and drink afterwards plenty of water.

#### Inhalation

Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.

#### Self-Protection of the First Aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

### Most important symptoms and effects, both acute and delayed

# SAFETY DATA SHEET

Ethanol, anhydrous, denatured

Revision Date 31-Mar-2025

Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

## Indication of any immediate medical attention and special treatment needed

### **Notes to Physician**

Treat symptomatically. Symptoms may be delayed.

## **SECTION 5: FIREFIGHTING MEASURES**

### Extinguishing media

#### **Suitable Extinguishing Media**

Water spray, carbon dioxide (CO<sub>2</sub>), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

#### **Extinguishing media which must not be used for safety reasons**

Do not use a solid water stream as it may scatter and spread fire.

### Special hazards arising from the substance or mixture

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

#### **Hazardous Combustion Products**

None under normal use conditions.

### Advice for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### Personal Precautions, Protective Equipment and Emergency Procedures

Ensure adequate ventilation. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges.

### Environmental precautions

Do not flush into surface water or sanitary sewer system.

### Methods and Material for Containment and Cleaning Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

### Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

## **SECTION 7: HANDLING AND STORAGE**

### Precautions for Safe Handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

# SAFETY DATA SHEET

Ethanol, anhydrous, denatured

Revision Date 31-Mar-2025

## Conditions for Safe Storage, Including any Incompatibilities

Keep away from heat, sparks and flame. Flammables area. Keep container tightly closed in a dry and well-ventilated place.

## Specific End Uses

Use in laboratories.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control Parameters

| Component           | Malaysia | ACGIH TLV                     | OSHA PEL                                                                                                                                                                          |
|---------------------|----------|-------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Ethyl alcohol       |          | STEL: 1000 ppm                | (Vacated) TWA: 1000 ppm<br>(Vacated) TWA: 1900 mg/m <sup>3</sup><br>TWA: 1000 ppm<br>TWA: 1900 mg/m <sup>3</sup>                                                                  |
| Methyl ethyl ketone |          | TWA: 200 ppm<br>STEL: 300 ppm | (Vacated) TWA: 200 ppm<br>(Vacated) TWA: 590 mg/m <sup>3</sup><br>(Vacated) STEL: 300 ppm<br>(Vacated) STEL: 885 mg/m <sup>3</sup><br>TWA: 200 ppm<br>TWA: 590 mg/m <sup>3</sup>  |
| Isopropyl alcohol   |          | TWA: 200 ppm<br>STEL: 400 ppm | (Vacated) TWA: 400 ppm<br>(Vacated) TWA: 980 mg/m <sup>3</sup><br>(Vacated) STEL: 500 ppm<br>(Vacated) STEL: 1225 mg/m <sup>3</sup><br>TWA: 400 ppm<br>TWA: 980 mg/m <sup>3</sup> |

| Component           | European Union                                                                                                       | The United Kingdom                                                                                                         | Germany                                                                                                                                                                                                                                                                      |
|---------------------|----------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Ethyl alcohol       |                                                                                                                      | TWA: 1000 ppm TWA; 1920 mg/m <sup>3</sup><br>TWA<br>WEL - STEL: 3000 ppm STEL;<br>5760 mg/m <sup>3</sup> STEL              | 200 ppm TWA MAK; 380 mg/m <sup>3</sup><br>TWA MAK                                                                                                                                                                                                                            |
| Methyl ethyl ketone | TWA: 200 ppm (8h)<br>TWA: 600 mg/m <sup>3</sup> (8h)<br>STEL: 300 ppm (15min)<br>STEL: 900 mg/m <sup>3</sup> (15min) | STEL: 300 ppm 15 min<br>STEL: 899 mg/m <sup>3</sup> 15 min<br>TWA: 200 ppm 8 hr<br>TWA: 600 mg/m <sup>3</sup> 8 hr<br>Skin | TWA: 200 ppm (8 Stunden). AGW -<br>exposure factor 1<br>TWA: 600 mg/m <sup>3</sup> (8 Stunden). AGW<br>- exposure factor 1<br>TWA: 200 ppm (8 Stunden). MAK<br>TWA: 600 mg/m <sup>3</sup> (8 Stunden). MAK<br>Höhepunkt: 200 ppm<br>Höhepunkt: 600 mg/m <sup>3</sup><br>Haut |
| Isopropyl alcohol   |                                                                                                                      | STEL: 500 ppm 15 min<br>STEL: 1250 mg/m <sup>3</sup> 15 min<br>TWA: 400 ppm 8 hr<br>TWA: 999 mg/m <sup>3</sup> 8 hr        | TWA: 200 ppm (8 Stunden). AGW -<br>exposure factor 2<br>TWA: 500 mg/m <sup>3</sup> (8 Stunden). AGW<br>- exposure factor 2<br>TWA: 200 ppm (8 Stunden). MAK<br>TWA: 500 mg/m <sup>3</sup> (8 Stunden). MAK<br>Höhepunkt: 400 ppm<br>Höhepunkt: 1000 mg/m <sup>3</sup>        |

### Exposure Controls

#### Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

### Personal protective equipment

Eye Protection  
Hand Protection

Goggles  
Protective gloves

# SAFETY DATA SHEET

Ethanol, anhydrous, denatured

Revision Date 31-Mar-2025

**Skin and body protection** Long sleeved clothing

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves.  
(Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

**Respiratory Protection** When workers are facing concentrations above the exposure limit they must use appropriate certified respirators  
**Recommended Filter type:** Organic gases and vapours filter Type A Brown conforming to EN14387  
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly  
When RPE is used a face piece Fit Test should be conducted

**Hygiene Measures** Handle in accordance with good industrial hygiene and safety practice

**Environmental exposure controls** Prevent product from entering drains Do not allow material to contaminate ground water system

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

#### Appearance

#### Physical State

Liquid

#### Odor

No information available

#### Odor Threshold

No data available

#### pH

5.7

#### Melting Point/Range

-114.1 °C / -173.4 °F

#### Softening Point

No data available

#### Boiling Point/Range

78 °C / 172.4 °F

@ 760 mmHg

#### Flash Point

12 °C / 53.6 °F

**Method -** No information available

#### Evaporation Rate

No data available

#### Flammability (solid,gas)

Not applicable

Liquid

#### Explosion Limits

**Lower** 2.5

**Upper** 13.5

#### Vapor Pressure

57 hPa @ 20°C

#### Vapor Density

No data available

(Air = 1.0)

#### Specific Gravity / Density

0.79

#### Bulk Density

Not applicable

Liquid

#### Water Solubility

Soluble

#### Solubility in other solvents

No information available

### Partition Coefficient (n-octanol/water)

#### Component

**log Pow**

Ethyl alcohol

-0.32

Methyl ethyl ketone

0.29

Isopropyl alcohol

0.05

# SAFETY DATA SHEET

Ethanol, anhydrous, denatured

Revision Date 31-Mar-2025

Denatonium benzoate 2.2

Autoignition Temperature 363 °C / 685.4 °F

Decomposition Temperature No data available

Viscosity No data available

Explosive Properties

Vapors may form explosive mixtures with air

Oxidizing Properties No information available

## SECTION 10: STABILITY AND REACTIVITY

### Reactivity

None known, based on information available.

### Chemical Stability

Stable under normal conditions.

### Possibility of Hazardous Reactions

Hazardous Polymerization No information available.

Hazardous Reactions None under normal processing.

### Conditions to Avoid

Keep away from open flames, hot surfaces and sources of ignition.

### Incompatible Materials

None known.

### Hazardous Decomposition Products

None under normal use conditions.

## SECTION 11: TOXICOLOGICAL INFORMATION

### Information on Toxicological Effects

#### Product Information

##### (a) acute toxicity;

Oral

Based on available data, the classification criteria are not met

Dermal

Based on available data, the classification criteria are not met

Inhalation

Based on available data, the classification criteria are not met

### Toxicology data for the components

| Component     | LD50 Oral                                                    | LD50 Dermal | LC50 Inhalation                                                   |
|---------------|--------------------------------------------------------------|-------------|-------------------------------------------------------------------|
| Ethyl alcohol | LD50 = 10470 mg/kg<br>OECD 401 (Rat)<br>3450 mg/kg ( Mouse ) | -           | LC50 = 117-125 mg/l (4h)<br>OECD 403 (rat)<br>20000 ppm/10H (rat) |

# SAFETY DATA SHEET

Ethanol, anhydrous, denatured

Revision Date 31-Mar-2025

|                     |                                            |                              |                              |
|---------------------|--------------------------------------------|------------------------------|------------------------------|
| Methyl ethyl ketone | LD50 = 2483 mg/kg ( Rat )                  | LD50 = 5000 mg/kg ( Rabbit ) | LC50 = 11700 ppm ( Rat ) 4 h |
| Isopropyl alcohol   | 5045 mg/kg ( Rat )<br>3600 mg/kg ( Mouse ) | 12800 mg/kg ( Rat )          | 72.6 mg/L ( Rat ) 4 h        |
| Denatonium benzoate | LD50 = 584 mg/kg ( Rat )                   | LD50 > 2000 mg/kg ( Rat )    | LC50 = 0.2 mg/L ( Rat ) 4 h  |

(b) skin corrosion/irritation; Based on available data, the classification criteria are not met

(c) serious eye damage/irritation; Category 2

(d) respiratory or skin sensitization;

Respiratory

Based on available data, the classification criteria are not met

Skin

Based on available data, the classification criteria are not met

| Component                        | Test method                                                | Test species | Study result    |
|----------------------------------|------------------------------------------------------------|--------------|-----------------|
| Ethyl alcohol<br>64-17-5 ( >95 ) | Mouse Ear Swelling Test (MEST)                             | mouse        | non-sensitising |
|                                  | -----<br>OECD Test Guideline 429<br>Local Lymph Node Assay | mouse        | non-sensitising |

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

| Component                        | Test method                                            | Test species          | Study result |
|----------------------------------|--------------------------------------------------------|-----------------------|--------------|
| Ethyl alcohol<br>64-17-5 ( >95 ) | AMES test<br>OECD Test Guideline 471                   | in vitro<br>Bacteria  | negative     |
|                                  | -----<br>Gene cell mutation<br>OECD Test Guideline 476 | in vitro<br>Mammalian | negative     |

(f) carcinogenicity; Based on available data, the classification criteria are not met

The table below indicates whether each agency has listed any ingredient as a carcinogen

(g) reproductive toxicity; Based on available data, the classification criteria are not met

| Component                        | Test method                      | Test species / Duration      | Study result          |
|----------------------------------|----------------------------------|------------------------------|-----------------------|
| Ethyl alcohol<br>64-17-5 ( >95 ) | OECD Test Guideline 416          | Oral / mouse<br>2 Generation | NOAEL = 13.8 g/kg/day |
|                                  | -----<br>OECD Test Guideline 414 | Inhalation / Rat             | NOAEC =<br>16000 ppm  |

(h) STOT-single exposure; Based on available data, the classification criteria are not met

Results / Target organs

Central nervous system (CNS).

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met

Target Organs

None known.

(j) aspiration hazard; Based on available data, the classification criteria are not met

Symptoms / effects, both acute and delayed

Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

# SAFETY DATA SHEET

Ethanol, anhydrous, denatured

Revision Date 31-Mar-2025

## Endocrine Disrupting Properties Assess endocrine disrupting properties for human health

Contains a substance on the National Authorities Endocrine Disruptor Lists

| Component                            | EU National Authorities Endocrine Disruptor Lists - Health |
|--------------------------------------|------------------------------------------------------------|
| Methyl ethyl ketone<br>78-93-3 ( 1 ) | List II                                                    |

## SECTION 12: ECOLOGICAL INFORMATION

### Ecotoxicity effects

Contains a substance which is: Toxic to aquatic organisms. The product contains following substances which are hazardous for the environment.

| Component           | Freshwater Fish                                                                                                                                                                                                                   | Water Flea                                                                                                                                        | Freshwater Algae                                                                                                 | Microtox                                                                                                              |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|
| Ethyl alcohol       | Fathead minnow<br>(Pimephales promelas)<br>LC50 = 14200 mg/l/96h                                                                                                                                                                  | EC50 = 9268 mg/L/48h<br>EC50 = 10800 mg/L/24h                                                                                                     | EC50 (72h) = 275 mg/l<br>(Chlorella vulgaris)                                                                    | Photobacterium<br>phosphoreum:EC50 =<br>34634 mg/L/30 min<br>Photobacterium<br>phosphoreum:EC50 =<br>35470 mg/L/5 min |
| Methyl ethyl ketone | Lepomis macrochirus:<br>LC50=3,22 g/L 96 h                                                                                                                                                                                        | EC50: = 5091 mg/L, 48h<br>(Daphnia magna)<br>EC50: 4025 - 6440<br>mg/L, 48h Static<br>(Daphnia magna)<br>EC50: > 520 mg/L, 48h<br>(Daphnia magna) |                                                                                                                  | EC50 = 3403 mg/L 30<br>min<br>EC50 = 3426 mg/L 5<br>min                                                               |
| Isopropyl alcohol   | LC50: = 9640 mg/L, 96h<br>flow-through<br>(Pimephales promelas)<br>LC50: > 1400000 µg/L,<br>96h (Lepomis<br>macrochirus)<br>LC50: = 11130 mg/L,<br>96h static (Pimephales<br>promelas)<br>LC50: = 10000000 µg/L,<br>96h (Daphnia) | 13299 mg/L EC50 = 48<br>h<br>9714 mg/L EC50 = 24 h                                                                                                | EC50: > 1000 mg/L, 72h<br>(Desmodesmus<br>subspicatus)<br>EC50: > 1000 mg/L, 96h<br>(Desmodesmus<br>subspicatus) | = 35390 mg/L EC50<br>Photobacterium<br>phosphoreum 5 min                                                              |

### Persistence and degradability

#### Persistence

Persistence is unlikely, based on information available.

| Component                            | Degradability   |
|--------------------------------------|-----------------|
| Ethyl alcohol<br>64-17-5 ( >95 )     | OECD 301E = 94% |
| Methyl ethyl ketone<br>78-93-3 ( 1 ) | 98% (28d)       |

#### Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

### Bioaccumulative potential

Bioaccumulation is unlikely

| Component           | log Pow | Bioconcentration factor (BCF) |
|---------------------|---------|-------------------------------|
| Ethyl alcohol       | -0.32   | No data available             |
| Methyl ethyl ketone | 0.29    | No data available             |
| Isopropyl alcohol   | 0.05    | No data available             |
| Denatonium benzoate | 2.2     | No data available             |

### Mobility in soil

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in



# SAFETY DATA SHEET

Ethanol, anhydrous, denatured

Revision Date 31-Mar-2025

air.

**Endocrine Disruptor Information** This product does not contain any known or suspected endocrine disruptors

**Other adverse effects** No information available

## SECTION 13: DISPOSAL CONSIDERATIONS

### Waste treatment methods

**Waste from Residues/Unused Products** Waste is classified as hazardous Dispose of in accordance with the European Directives on waste and hazardous waste Dispose of in accordance with local regulations

**Contaminated Packaging** Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous Keep product and empty container away from heat and sources of ignition

**Other Information** Do not flush to sewer Waste codes should be assigned by the user based on the application for which the product was used Can be landfilled or incinerated, when in compliance with local regulations

## SECTION 14: TRANSPORT INFORMATION

### IMDG/IMO

UN-No UN1170  
Hazard Class 3  
Packing Group II  
Proper Shipping Name ETHANOL

### Road and Rail Transport

UN-No UN1170  
Hazard Class 3  
Packing Group II  
Proper Shipping Name ETHANOL

### IATA

UN-No UN1170  
Hazard Class 3  
Packing Group II  
Proper Shipping Name ETHANOL

**Special Precautions for User** No special precautions required

## SECTION 15: REGULATORY INFORMATION

### Safety, health and environmental regulations/legislation specific for the substance or mixture

**International Inventories** X = listed

| Component     | EINECS    | TSCA | DSL | PICCS | ENCS | ISHL | IECSC | AICS | KECL     |
|---------------|-----------|------|-----|-------|------|------|-------|------|----------|
| Ethyl alcohol | 200-578-6 | X    | X   | X     | X    | X    | X     | X    | KE-13217 |

# SAFETY DATA SHEET

Ethanol, anhydrous, denatured

Revision Date 31-Mar-2025

|                     |           |   |   |   |   |   |   |   |          |
|---------------------|-----------|---|---|---|---|---|---|---|----------|
| Methyl ethyl ketone | 201-159-0 | X | X | X | X | X | X | X | KE-24094 |
| Isopropyl alcohol   | 200-661-7 | X | X | X | X | X | X | X | KE-29363 |
| Denatonium benzoate | 223-095-2 | X | X | X | X |   | X | X | KE-11775 |

| Component           | Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification | Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements | Rotterdam Convention (PIC) | Basel Convention (Hazardous Waste) |
|---------------------|-------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|----------------------------|------------------------------------|
| Ethyl alcohol       |                                                                                           |                                                                                          |                            | Annex I - Y42                      |
| Methyl ethyl ketone |                                                                                           |                                                                                          |                            | Annex I - Y42                      |
| Isopropyl alcohol   |                                                                                           |                                                                                          |                            | Annex I - Y42                      |

## National Regulations

**Persistent Organic Pollutant**  
**Ozone Depletion Potential**

This product does not contain any known or suspected substance  
This product does not contain any known or suspected substance

## SECTION 16: OTHER INFORMATION

### Legend

**CAS** - Chemical Abstracts Service

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List

**ENCS** - Japanese Existing and New Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**NZIoC** - New Zealand Inventory of Chemicals

**WEL** - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**RPE** - Respiratory Protective Equipment

**LC50** - Lethal Concentration 50%

**POW** - Partition coefficient Octanol:Water

**TWA** - Time Weighted Average

**IARC** - International Agency for Research on Cancer

**LD50** - Lethal Dose 50%

**EC50** - Effective Concentration 50%

**ADR** - European Agreement Concerning the International Carriage of Dangerous Goods by Road

**IMO/IMDG** - International Maritime Organization/International Maritime Dangerous Goods Code

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

**ICAO/IATA** - International Civil Aviation Organization/International Air Transport Association

**MARPOL** - International Convention for the Prevention of Pollution from Ships

**ATE** - Acute Toxicity Estimate

**VOC** - (Volatile Organic Compound)

### Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadviser - LOLI, Merck index, RTECS

**Prepared By**

**Revision Date**

**Revision Summary**

Health, Safety and Environmental Department

31-Mar-2025

Not applicable.

**In accordance with local and national regulations: Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013**

### Disclaimer

# SAFETY DATA SHEET

Ethanol, anhydrous, denatured

Revision Date 31-Mar-2025

---

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**