

Australian statement of hazardous nature : Classified as hazardous according to criteria of Safe Work Australia

Section 1 - Identification

Product Name 2-Butanone

CAS No 78-93-3

Synonyms Methyl ethyl ketone; MEK; Ethyl methyl ketone

Product Code 444170000; 444170050

Address ThermoFisher Scientific Australia Pty Ltd
5 Caribbean Drive, Scoresby
VICTORIA 3179, Australia

Emergency Tel. **CHEMTREC®**
03 9757 4559 or +613 9757 4559

Telephone / Fax Numbers Tel: 1300 735 292
Fax: 1800 067 639

E-mail address ANZinfo@thermofisher.com

Recommended Use Laboratory chemicals.

Uses advised against This product contains one or more substance(s) on the Illicit Drug Precursors/Reagents list. Verify requirements related to using, handling and storing these substances. This product does not contain any substance(s) subject to Prohibition, Authorization or Restriction. This product does not contain any substance(s) listed on the voluntary National Code of Practice for Chemicals of Security Concern.

Section 2 - Hazard(s) Identification

Classification under Safe Work Australia

Classified as hazardous according to criteria of Safe Work Australia

Physical hazards

Flammable liquids

Category 2

Health hazards

Serious Eye Damage/Eye Irritation
Specific target organ toxicity - (single exposure)

Category 2
Category 3

Environmental hazards

No hazards identified

Label Elements



Flame



Exclamation Mark

Signal Word**Danger****Hazard Statements**

H225 - Highly flammable liquid and vapor

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

AUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P233 - Keep container tightly closed

P240 - Ground and bond container and receiving equipment

P241 - Use explosion-proof electrical/ ventilating/ lighting equipment

P242 - Use non-sparking tools

P243 - Take action to prevent static discharges

P264 - Wash face, hands and any exposed skin thoroughly after handling

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P312 - Call a POISON CENTER or doctor if you feel unwell

P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

P501 - Dispose of contents/ container to an approved waste disposal plant

Other information

Contains a substance on the National Authorities Endocrine Disruptor Lists

Contains a known or suspected endocrine disruptor

Section 3 - Composition and Information on Ingredients

Component	CAS No	Weight %
Methyl ethyl ketone	78-93-3	<=100

Section 4 - First Aid Measures

Inhalation

Remove to fresh air. Get medical attention if symptoms occur. If not breathing, give artificial respiration.

Ingestion

Do NOT induce vomiting. Get medical attention.

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. Get medical attention if symptoms occur.

Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.
First Aid Facilities	Eyewash, safety shower and washroom.
Most important symptoms and effects	Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
Notes to Physician	Treat symptomatically. Symptoms may be delayed.

Section 5 - Fire Fighting Measures

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

Hazardous Decomposition Products

Carbon monoxide (CO), Carbon dioxide (CO₂).

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition.

Special protective equipment and precautions for fire fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6 - Accidental Release Measures

Emergency procedures

Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation.

Environmental Precautions

Avoid release to the environment. See Section 12 for additional Ecological Information.

Methods for Containment and Clean Up

Clean-up methods - small spillage

Remove all sources of ignition. Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Use spark-proof tools and explosion-proof equipment.

Clean-up methods - large spillage

Typically only supplied in small quantities as packaged goods.

If extremely toxic or used in large quantities ensure a spillage action plan is in place. Evacuate area. Control the source and/or contain the spill if safe and able to do so. Use temporary diking, sand bags, dry sand, earth or proprietary booms/absorbent pads if available. Obtain advice on containment, neutralisation and clean-up from local emergency responders.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

Section 7 - Handling and Storage

Precautions for Safe Handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Use spark-proof tools and explosion-proof equipment. Avoid contact with skin, eyes or clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Conditions for Safe Storage, Including any Incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area.

AS/NZS 2243.10:2004, Safety in laboratories - Storage of chemicals

AS 1940-2004 - The storage and handling of flammable and combustible liquids

Section 8 - Exposure Controls and Personal Protection

Exposure limits

AUS - Exposure Standards for Atmospheric Contaminants in the Occupational Environment - Guidance Note on the Interpretation of Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:3008(1995)]

Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)]

updated in August, 2005. Safe Work Australia **ACGIH** - Threshold Limit Values - Ceiling (TLV-C) guidelines by the American Conference of Governmental Industrial Hygienists (ACGIH) for controlling worker exposure to airborne chemical concentrations in the workplace. **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **DE** - MAK and BAT values of Hazardous Chemical Compounds in the Work Area. Published by German Research Foundation on July 1, 2011

Component	Australia	New Zealand WEL	ACGIH TLV	The United Kingdom	Germany
Methyl ethyl ketone	STEL: 300 ppm STEL: 890 mg/m ³ TWA: 150 ppm TWA: 445 mg/m ³	TWA: 150 ppm TWA: 445 mg/m ³ STEL: 300 ppm STEL: 890 mg/m ³	TWA: 200 ppm STEL: 300 ppm	STEL: 300 ppm 15 min STEL: 899 mg/m ³ 15 min TWA: 200 ppm 8 hr TWA: 600 mg/m ³ 8 hr Skin	TWA: 200 ppm (8 Stunden). AGW - exposure factor 1 TWA: 600 mg/m ³ (8 Stunden). AGW - exposure factor 1 TWA: 200 ppm (8 Stunden). MAK TWA: 600 mg/m ³ (8 Stunden). MAK Höhepunkt: 200 ppm Höhepunkt: 600 mg/m ³ Haut

Biological limit values

UK - Biological Monitoring Guidance Values provided by the UK's Health and Safety Executive (HSE) Control of Substances Hazardous to Health Regulations (COSHH) 2002 (as amended) and EH40/2005; **NZ** - Substances assigned Biological Exposure Indices in the New Zealand Workplace Exposure Standards and Biological Exposure Indices (6th edition). New Zealand Department of Labor

Component	Australia	New Zealand	European Union	United Kingdom	Germany
Methyl ethyl ketone		2 mg/L (urine) end of shift (MEK)		Butan-2-one: 70 µmol/L urine post shift	2-Butanone: 2 mg/L urine (end of shift)

Exposure Controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles (Australian/New Zealand Standard AS/NZS 1337 - Eye protectors for Industrial applications)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	AUS/NZ Standard	Glove comments
Butyl rubber	< 60 minutes	0.5 mm	AS/NZS 2161	Permeation rate 36 µg/cm ² /min As tested under EN374-3 Determination of Resistance to Permeation by Chemicals

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves.
(Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatibility, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure

Respiratory Protection

Use an AS/NZS 1716 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained in line with AS/NZS 1715 on the use and maintenance of respiratory protective devices

Recommended Filter type:

Type A Organic gases and vapours filter Brown conforming to EN14387 (or AUS/NZ equivalent)

Recommended half mask:-

Valve filtering: EN405 or Half mask: EN140 plus filter, EN 141 (or AUS/NZ equivalent)

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

Environmental exposure controls

No information available.

Section 9 - Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance	Colorless	
Physical State	Liquid	
Odor	Characteristic - sweet	
Odor Threshold	No data available	
pH	No information available	
Melting Point/Range	-87 °C / -124.6 °F	
Softening Point	No data available	
Boiling Point/Range	80 °C / 176 °F	
Flash Point	-7 °C / 19.4 °F	Method - CC (closed cup)
Evaporation Rate	3.7	(Butyl Acetate = 1.0)
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	Lower 1.8 Vol%	
	Upper 11.5 Vol%	
Vapor Pressure	105 mbar @ 20 °C	
Vapor Density	2.41	(Air = 1.0)
Specific Gravity / Density	0.806	
Bulk Density	Not applicable	Liquid
Water Solubility	290 g/L (20°C)	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Methyl ethyl ketone	0.29	
Autoignition Temperature	404 °C / 759.2 °F	
Decomposition Temperature	No data available	
Viscosity	0.42 mPa.s @ 15°C	
Explosive Properties	Not explosive	Vapors may form explosive mixtures with air
Oxidizing Properties	Not oxidising	

Other information**Molecular Formula**C₄ H₈ O**Molecular Weight**

72.11

Section 10 - Stability and Reactivity

Reactivity	None known, based on information available
Stability	Hygroscopic.
Conditions to Avoid	Incompatible products, Excess heat, Keep away from open flames, hot surfaces and sources of ignition, Exposure to moist air or water.
Incompatible Materials	Strong oxidizing agents, Strong acids, Strong bases, Strong reducing agents, Ammonia, copper, Amines.
Hazardous Decomposition Products	Carbon monoxide (CO). Carbon dioxide (CO ₂).
Hazardous Polymerization	Hazardous polymerization does not occur.

Section 11 - Toxicological Information**Information on Toxicological Effects****Product Information****(a) acute toxicity;****Oral**

Based on available data, the classification criteria are not met

Dermal

Based on available data, the classification criteria are not met

Inhalation

Based on available data, the classification criteria are not met

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methyl ethyl ketone	LD50 = 2483 mg/kg (Rat)	LD50 = 5000 mg/kg (Rabbit)	LC50 = 11700 ppm (Rat) 4 h

(b) skin corrosion/irritation; Based on available data, the classification criteria are not met**(c) serious eye damage/irritation;** Category 2**(d) respiratory or skin sensitization;****Respiratory**

Based on available data, the classification criteria are not met

Skin

Based on available data, the classification criteria are not met

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

Not mutagenic in AMES Test

(f) carcinogenicity; Based on available data, the classification criteria are not met
There are no known carcinogenic chemicals in this product**(g) reproductive toxicity;** Based on available data, the classification criteria are not met**(h) STOT-single exposure;** Category 3**Results / Target organs**

Central nervous system (CNS)

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met

Target Organs

None known.

(j) aspiration hazard; Based on available data, the classification criteria are not met

Symptoms / effects, both acute and delayed Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

Section 12 - Ecological Information

Ecotoxicity effects

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Methyl ethyl ketone	Lepomis macrochirus: LC50=3,22 g/L 96 h	EC50: = 5091 mg/L, 48h (Daphnia magna) EC50: 4025 - 6440 mg/L, 48h Static (Daphnia magna) EC50: > 520 mg/L, 48h (Daphnia magna)		EC50 = 3403 mg/L 30 min EC50 = 3426 mg/L 5 min

Persistence and Degradability Readily biodegradable
Persistence Persistence is unlikely, based on information available.

Component	Degradability
Methyl ethyl ketone 78-93-3 (≤100)	98% (28d)

Bioaccumulative Potential Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Methyl ethyl ketone	0.29	No data available

Mobility The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Will likely be mobile in the environment due to its volatility Disperses rapidly in air

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

Persistent Organic Pollutant This product does not contain any known or suspected substance

Ozone Depletion Potential This product does not contain any known or suspected substance

Section 13 - Disposal Considerations

Waste from Residues/Unused Products Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with all federal, E.P.A., state and local regulations. Assure conformity with all applicable regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

Other Information Chemical wastes should be disposed through a licensed commercial waste collection service. Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with local regulations.

Section 14 - Transport Information

IMDG/IMO

UN-No UN1193
Proper Shipping Name Ethyl methyl ketone (Methyl ethyl ketone)
Hazard Class 3
Packing Group II

ADG

UN-No UN1193
Proper Shipping Name Ethyl methyl ketone (Methyl ethyl ketone)
Hazard Class 3
Packing Group II

Component	Hazchem Code
Methyl ethyl ketone 78-93-3 (<=100)	2YE

IATA

UN-No UN1193
Proper Shipping Name Methyl ethyl ketone
Hazard Class 3
Packing Group II

Environmental hazards No hazards identified

Special Precautions No special precautions required

Additional information None known

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture**National Regulations** Australia

See section 8 for national exposure control parameters.

Standard for the Uniform Scheduling of Medicines and Poisons

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons.

Component	Standard for the Uniform Scheduling of Medicines and Poisons
Methyl ethyl ketone - 78-93-3	Schedule 5 listed - except in preparations containing <=25% of designated solvents

Australian Industrial Chemicals Introduction Scheme (AICIS)

Component	Australian Industrial Chemicals Introduction Scheme (AICIS)	Additional information
Methyl ethyl ketone - 78-93-3	Present	-

Australian - Illicit Drug Precursors/Reagents Substance List

This product contains one or more substance(s) on the Illicit Drug Precursors/Reagents list. Verify requirements related to using, handling and storing these substances.

Chemicals of Security Concern

This product does not contain any substance(s) listed on the voluntary National Code of Practice for Chemicals of Security Concern

Component	Australian - Illicit Drug Precursors/Reagents Substance List	Chemicals of Security Concern
Methyl ethyl ketone - 78-93-3	Category 3	

Legend

Category 3 - Chemicals and apparatus that may be used in the illicit production of drugs. Purchases from this list should alert companies or organizations to seek further indicators of any suspicious orders or enquiries. No official reporting is required for items on this list unless considered warranted

National pollutant inventory Subject to reporting requirements

Component	National pollutant inventory
Methyl ethyl ketone - 78-93-3	10 tonne/yr. Threshold category 1

Prohibition or notification/licensing requirements

Shown below are details of specific prohibition/notifications or licencing requirements when they apply.

This product does not contain any substance(s) subject to Prohibition, Authorization or Restriction.

International Inventories

Component	AICS	NZIoC	EINECS	ELINCS	TSCA	DSL	NDSL	PICCS	ENCS	ISHL	IECSC	KECL
Methyl ethyl ketone	X	X	201-159-0	-	X	X	-	X	X	X	X	KE-24094

Legend: X - Listed. '-' - Not Listed. **KECL** - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

International Regulations

Ozone Depletion Potential This product does not contain any known or suspected substance

Persistent Organic Pollutant This product does not contain any known or suspected substance

Rotterdam Convention (PIC) Not applicable

Basel convention on the control of transboundary movements of hazardous wastes and their disposal

Take note that wastes may be subject to export, import, or transit controls pursuant to the Basel convention and/or local regulations implementing the Basel convention.

Component	Basel Convention (Hazardous Waste)	Australian Hazardous Waste Act - Categories of Wastes to Be Controlled
Methyl ethyl ketone - 78-93-3	Annex I - Y42	Y42 except Halogenated solvents

Component	CAS No	OECD HPV	Restriction of Hazardous Substances (RoHS)	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Methyl ethyl ketone	78-93-3	Listed	Not applicable	Not applicable	Not applicable

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Methyl ethyl ketone	-	Use restricted. See item 75.	-

	(see link for restriction details)	
--	------------------------------------	--

<https://echa.europa.eu/substances-restricted-under-reach>

Section 16 - Other Information

Legend

AICS - Australian Inventory of Chemical Substances	NZIoC - New Zealand Inventory of Chemicals
TSCA - United States Toxic Substances Control Act Section 8(b) Inventory	EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List	ENCS - Japanese Existing and New Chemical Substances
IECSC - Chinese Inventory of Existing Chemical Substances	KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances	CAS - Chemical Abstracts Service
TWA - Time Weighted Average	ACGIH - American Conference of Governmental Industrial Hygienists
IARC - International Agency for Research on Cancer	Predicted No Effect Concentration (PNEC)
ICAO/IATA - International Civil Aviation Organization/International Air Transport Association	IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code
MARPOL - International Convention for the Prevention of Pollution from Ships	ADG Australian Code for the Transport of Dangerous Goods by Road and Rail
NZS 5433:2012 - Transport of Dangerous Goods on Land	OECD - Organisation for Economic Co-operation and Development
LD50 - Lethal Dose 50%	LC50 - Lethal Concentration 50%
EC50 - Effective Concentration 50%	ATE - Acute Toxicity Estimate
WEL - Workplace Exposure Limit	RPE - Respiratory Protective Equipment
DNEL - Derived No Effect Level	NOEC - No Observed Effect Concentration
POW - Partition coefficient Octanol:Water	BCF - Bioconcentration factor
vPvB - very Persistent, very Bioaccumulative	PBT - Persistent, Bioaccumulative, Toxic
VOC - (Volatile Organic Compound)	

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>
Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Revision Date	17-Nov-2022
Revision Summary	Not applicable.

This Safety Data Sheet (SDS) is prepared in accordance to and complies with the requirements of Safe Work Australia - Work Health and Safety Regulations (WHS Regulations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet