

Creation Date 23-Nov-2009

Revision Date 11-Apr-2025

Revision Number 6

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

Product Description: **Petroleum ether, boiling range 100-120°C**  
Cat No. : **SP/2967/27; SP/2967/99; SP/2967/99V**  
REACH registration number **01-2119473851-33**

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

|                                       |                                                                                             |
|---------------------------------------|---------------------------------------------------------------------------------------------|
| <b>Recommended Use</b>                | Laboratory chemicals.                                                                       |
| <b>Sector of use</b>                  | SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites    |
| <b>Product category</b>               | PC21 - Laboratory chemicals                                                                 |
| <b>Process categories</b>             | PROC15 - Use as a laboratory reagent                                                        |
| <b>Environmental release category</b> | ERC6a - Industrial use resulting in manufacture of another substance (use of intermediates) |
| <b>Uses advised against</b>           | No Information available                                                                    |

### 1.3. Details of the supplier of the safety data sheet

#### Company

**UK entity/business name**  
Fisher Scientific UK  
Bishop Meadow Road, Loughborough,  
Leicestershire LE11 5RG, United Kingdom

**EU entity/business name**  
Thermo Fisher Scientific  
Janssen Pharmaceuticaaan 3a  
2440 Geel, Belgium

**E-mail address** [begin.sdsdesk@thermofisher.com](mailto:begin.sdsdesk@thermofisher.com)

### 1.4. Emergency telephone number

Tel: 01509 231166  
Chemtrec US: (800) 424-9300  
Chemtrec EU: 001-703-527-3887

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

**GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567**

#### Physical hazards

Flammable liquids

Category 2 (H225)

# SAFETY DATA SHEET

Petroleum ether, boiling range 100-120°C

Revision Date 11-Apr-2025

## Health hazards

Aspiration Toxicity  
Specific target organ toxicity - (single exposure)

Category 1 (H304)  
Category 3 (H336)

## Environmental hazards

Chronic aquatic toxicity

Category 2 (H411)

Full text of Hazard Statements: see section 16

## 2.2. Label elements



Signal Word

Danger

## Hazard Statements

H225 - Highly flammable liquid and vapor  
H304 - May be fatal if swallowed and enters airways  
H336 - May cause drowsiness or dizziness  
H411 - Toxic to aquatic life with long lasting effects  
EUH066 - Repeated exposure may cause skin dryness or cracking

## Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray  
P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
P331 - Do NOT induce vomiting  
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower  
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing  
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

## 2.3. Other hazards

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)  
This product does not contain any known or suspected endocrine disruptors

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substances

| Component                                           | CAS No | EC No | Weight % | GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567   |
|-----------------------------------------------------|--------|-------|----------|-------------------------------------------------------------------------------------------|
| HYDROCARBONS, C7-C9, n-alkanes, isoalkanes, cyclics | N/A    |       | <=100    | Flam. Liq. 2 (H225)<br>Asp. Tox. 1 (H304)<br>STOT SE 3 (H336)<br>Aquatic Chronic 2 (H411) |

# SAFETY DATA SHEET

Petroleum ether, boiling range 100-120°C

Revision Date 11-Apr-2025

|  |  |  |  |          |
|--|--|--|--|----------|
|  |  |  |  | (EUH066) |
|--|--|--|--|----------|

## Note

UVCB Hydrocarbons

CAS No. 64742-49-0: TSCA, DSL, AICS, ENCS, PICCS, CHINA, KECL

EC No. 920-750-0

|                           |                  |
|---------------------------|------------------|
| REACH registration number | 01-2119473851-33 |
|---------------------------|------------------|

Full text of Hazard Statements: see section 16

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

|                                    |                                                                                                                                                                                                     |
|------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General Advice                     | If symptoms persist, call a physician.                                                                                                                                                              |
| Eye Contact                        | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.                                                                                     |
| Skin Contact                       | Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.                                                                                   |
| Ingestion                          | Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward. |
| Inhalation                         | Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur. Risk of serious damage to the lungs (by aspiration).                                   |
| Self-Protection of the First Aider | Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.                                                    |

### 4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

### 4.3. Indication of any immediate medical attention and special treatment needed

|                    |                                                 |
|--------------------|-------------------------------------------------|
| Notes to Physician | Treat symptomatically. Symptoms may be delayed. |
|--------------------|-------------------------------------------------|

## SECTION 5: FIREFIGHTING MEASURES

### 5.1. Extinguishing media

#### Suitable Extinguishing Media

Water spray, carbon dioxide (CO<sub>2</sub>), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

#### Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

# SAFETY DATA SHEET

Petroleum ether, boiling range 100-120°C

Revision Date 11-Apr-2025

## **5.2. Special hazards arising from the substance or mixture**

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Do not allow run-off from fire-fighting to enter drains or water courses.

### **Hazardous Combustion Products**

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>), Hydrocarbons, Aldehydes.

## **5.3. Advice for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### **6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

### **6.2. Environmental precautions**

Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

### **6.3. Methods and material for containment and cleaning up**

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

### **6.4. Reference to other sections**

Refer to protective measures listed in Sections 8 and 13.

## **SECTION 7: HANDLING AND STORAGE**

### **7.1. Precautions for safe handling**

Wear personal protective equipment/face protection. Ensure adequate ventilation. Avoid ingestion and inhalation. Do not get in eyes, on skin, or on clothing. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

### **Hygiene Measures**

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

### **7.2. Conditions for safe storage, including any incompatibilities**

Keep containers tightly closed in a dry, cool and well-ventilated place. Flammables area. Keep away from heat, sparks and flame.

**Technical Rules for Hazardous Substances (TRGS) 510**  
**Storage Class (LGK) (Germany)**

Class 3

# SAFETY DATA SHEET

Petroleum ether, boiling range 100-120°C

Revision Date 11-Apr-2025

## 7.3. Specific end use(s)

Use in laboratories

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

#### Exposure limits

This product, as supplied, does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies

#### Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

#### Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

#### Predicted No Effect Concentration (PNEC)

According to our experience and to the information provided to us, the product does not have any harmful effects if it is used and handled as specified.

### 8.2. Exposure controls

#### Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

#### Personal protective equipment

##### Eye Protection

Wear safety glasses with side shields (or goggles) (European standard - EN 166)

##### Hand Protection

Protective gloves

| Glove material  | Breakthrough time | Glove thickness | EU standard | Glove comments                           |
|-----------------|-------------------|-----------------|-------------|------------------------------------------|
| Nitrile rubber  | > 480 minutes     | 0.38 - 0.55 mm  | Level 6     | As tested under EN374-3 Determination of |
| Viton (R)       | > 480 minutes     | 0.30 mm         | EN 374      | Resistance to Permeation by Chemicals    |
| Neoprene gloves | < 100 minutes     | 0.45 mm         |             |                                          |

##### Skin and body protection

Long sleeved clothing.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatibility, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

# SAFETY DATA SHEET

Petroleum ether, boiling range 100-120°C

Revision Date 11-Apr-2025

|                                        |                                                                                                                                                                                                                                                                       |
|----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Respiratory Protection</b>          | When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.                                                                                                                                                      |
| <b>Large scale/emergency use</b>       | Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced<br><b>Recommended Filter type:</b> Type A                                                                         |
| <b>Small scale/Laboratory use</b>      | Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.<br><b>Recommended half mask:-</b> Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 149 and 143 |
| <b>Environmental exposure controls</b> | Prevent product from entering drains. Do not allow material to contaminate ground water system. Local authorities should be advised if significant spillages cannot be contained.                                                                                     |

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

|                                                |                                              |                                           |
|------------------------------------------------|----------------------------------------------|-------------------------------------------|
| <b>Physical State</b>                          | Liquid                                       |                                           |
| <b>Appearance</b>                              | Colorless                                    |                                           |
| <b>Odor</b>                                    | Petroleum distillates                        |                                           |
| <b>Odor Threshold</b>                          | No data available                            |                                           |
| <b>Melting Point/Range</b>                     | No data available                            |                                           |
| <b>Softening Point</b>                         | No data available                            |                                           |
| <b>Boiling Point/Range</b>                     | 100 - 120 °C / 212 - 248 °F                  | @ 760mmHg                                 |
| <b>Flammability (liquid)</b>                   | Highly flammable                             | On basis of test data                     |
| <b>Flammability (solid,gas)</b>                | Not applicable                               | Liquid                                    |
| <b>Explosion Limits</b>                        | <b>Lower</b> 0.8 vol%<br><b>Upper</b> 8 vol% |                                           |
| <b>Flash Point</b>                             | 2 °C / 35.6 °F                               | <b>Method -</b> Tag Closed Cup (ASTM D56) |
| <b>Autoignition Temperature</b>                | 250 °C / 482 °F                              |                                           |
| <b>Decomposition Temperature</b>               | No data available                            |                                           |
| <b>pH</b>                                      | Not applicable                               |                                           |
| <b>Viscosity</b>                               | 0.7 m2/s @ 25°C                              |                                           |
| <b>Water Solubility</b>                        | Immiscible                                   |                                           |
| <b>Solubility in other solvents</b>            | No information available                     |                                           |
| <b>Partition Coefficient (n-octanol/water)</b> |                                              |                                           |
| <b>Vapor Pressure</b>                          | 45 mbar @ 20°C                               |                                           |
| <b>Density / Specific Gravity</b>              | 0.735                                        |                                           |
| <b>Bulk Density</b>                            | Not applicable                               | Liquid                                    |
| <b>Vapor Density</b>                           | No data available                            | (Air = 1.0)                               |
| <b>Particle characteristics</b>                | Not applicable (liquid)                      |                                           |

### 9.2. Other information

|                             |                                             |
|-----------------------------|---------------------------------------------|
| <b>Explosive Properties</b> | Vapors may form explosive mixtures with air |
| <b>Evaporation Rate</b>     | 6 - (Ether = 1.0)                           |

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

None known, based on information available

# SAFETY DATA SHEET

Petroleum ether, boiling range 100-120°C

Revision Date 11-Apr-2025

## 10.2. Chemical stability

Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

### Hazardous Polymerization Hazardous Reactions

Hazardous polymerization does not occur.  
None under normal processing.

## 10.4. Conditions to avoid

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition.

## 10.5. Incompatible materials

Strong oxidizing agents.

## 10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Hydrocarbons. Aldehydes.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Product Information

#### (a) acute toxicity;

Oral

Based on available data, the classification criteria are not met

Dermal

Based on available data, the classification criteria are not met

Inhalation

Based on available data, the classification criteria are not met

| Component                                           | LD50 Oral           | LD50 Dermal            | LC50 Inhalation          |
|-----------------------------------------------------|---------------------|------------------------|--------------------------|
| HYDROCARBONS, C7-C9, n-alkanes, isoalkanes, cyclics | >5840 mg/kg ( Rat ) | >2920 mg/kg ( Rabbit ) | > 23300 mg/l ( Rat ) 4 h |

#### (b) skin corrosion/irritation;

Based on available data, the classification criteria are not met

#### (c) serious eye damage/irritation;

Based on available data, the classification criteria are not met

#### (d) respiratory or skin sensitization;

Respiratory

Based on available data, the classification criteria are not met

Skin

Based on available data, the classification criteria are not met

#### (e) germ cell mutagenicity;

Based on available data, the classification criteria are not met

#### (f) carcinogenicity;

Based on available data, the classification criteria are not met

There are no known carcinogenic chemicals in this product

#### (g) reproductive toxicity;

Based on available data, the classification criteria are not met

#### (h) STOT-single exposure;

Category 3

Results / Target organs

Central nervous system (CNS).

#### (i) STOT-repeated exposure;

Based on available data, the classification criteria are not met

# SAFETY DATA SHEET

Petroleum ether, boiling range 100-120°C

Revision Date 11-Apr-2025

**Target Organs** None known.

**(j) aspiration hazard;** Category 1

**Symptoms / effects, both acute and delayed** Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

## 11.2. Information on other hazards

**Endocrine Disrupting Properties** Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

#### **Ecotoxicity effects**

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment.

| Component                                           | Freshwater Fish         | Water Flea                | Freshwater Algae       |
|-----------------------------------------------------|-------------------------|---------------------------|------------------------|
| HYDROCARBONS, C7-C9, n-alkanes, isoalkanes, cyclics | 3 - 10 mg/L LC50 = 48 h | 4.6 - 10 mg/L LC50 = 96 h | 10-30 mg/L EC50 = 72 h |

### 12.2. Persistence and degradability

#### **Persistence**

#### **Degradation in sewage treatment plant**

Readily biodegradable  
Immiscible with water, Persistence is unlikely, based on information available.  
Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

### 12.3. Bioaccumulative potential

Bioaccumulation is unlikely

### 12.4. Mobility in soil

The product is insoluble and floats on water. The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Spillage unlikely to penetrate soil. Will likely be mobile in the environment due to its volatility.

### 12.5. Results of PBT and vPvB assessment

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB).

### 12.6. Endocrine disrupting properties

#### **Endocrine Disruptor Information**

This product does not contain any known or suspected endocrine disruptors

### 12.7. Other adverse effects

#### **Persistent Organic Pollutant**

#### **Ozone Depletion Potential**

This product does not contain any known or suspected substance

This product does not contain any known or suspected substance

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods



# SAFETY DATA SHEET

Petroleum ether, boiling range 100-120°C

Revision Date 11-Apr-2025

|                                            |                                                                                                                                                                                                                                                                                   |
|--------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Waste from Residues/Unused Products</b> | Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.                                                                                                            |
| <b>Contaminated Packaging</b>              | Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.                                          |
| <b>European Waste Catalogue (EWC)</b>      | According to the European Waste Catalog, Waste Codes are not product specific, but application specific.                                                                                                                                                                          |
| <b>Other Information</b>                   | Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not let this chemical enter the environment. Do not empty into drains. |

## SECTION 14: TRANSPORT INFORMATION

### IMDG/IMO

|                                         |                               |
|-----------------------------------------|-------------------------------|
| <b>14.1. UN number</b>                  | UN1268                        |
| <b>14.2. UN proper shipping name</b>    | Petroleum distillates, n.o.s. |
| <b>14.3. Transport hazard class(es)</b> | 3                             |
| <b>14.4. Packing group</b>              | II                            |

### ADR

|                                         |                               |
|-----------------------------------------|-------------------------------|
| <b>14.1. UN number</b>                  | UN1268                        |
| <b>14.2. UN proper shipping name</b>    | Petroleum distillates, n.o.s. |
| <b>14.3. Transport hazard class(es)</b> | 3                             |
| <b>14.4. Packing group</b>              | II                            |

### IATA

|                                         |                               |
|-----------------------------------------|-------------------------------|
| <b>14.1. UN number</b>                  | UN1268                        |
| <b>14.2. UN proper shipping name</b>    | Petroleum distillates, n.o.s. |
| <b>14.3. Transport hazard class(es)</b> | 3                             |
| <b>14.4. Packing group</b>              | II                            |

|                                    |                                                                                                          |
|------------------------------------|----------------------------------------------------------------------------------------------------------|
| <b>14.5. Environmental hazards</b> | Dangerous for the environment<br>Product is a marine pollutant according to the criteria set by IMDG/IMO |
|------------------------------------|----------------------------------------------------------------------------------------------------------|

|                                           |                                  |
|-------------------------------------------|----------------------------------|
| <b>14.6. Special precautions for user</b> | No special precautions required. |
|-------------------------------------------|----------------------------------|

|                                                                      |                                |
|----------------------------------------------------------------------|--------------------------------|
| <b>14.7. Maritime transport in bulk according to IMO instruments</b> | Not applicable, packaged goods |
|----------------------------------------------------------------------|--------------------------------|

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

# SAFETY DATA SHEET

Petroleum ether, boiling range 100-120°C

Revision Date 11-Apr-2025

| Component                                              | CAS No | EINECS | ELINCS | NLP | IECSC | TCSI | KECL | ENCS | ISHL |
|--------------------------------------------------------|--------|--------|--------|-----|-------|------|------|------|------|
| HYDROCARBONS, C7-C9,<br>n-alkanes, isoalkanes, cyclics | N/A    | -      | -      | -   | -     | -    | -    | -    | -    |

| Component                                              | CAS No | TSCA | TSCA Inventory<br>notification -<br>Active-Inactive | DSL | NDSL | AICS | NZIoC | PICCS |
|--------------------------------------------------------|--------|------|-----------------------------------------------------|-----|------|------|-------|-------|
| HYDROCARBONS, C7-C9,<br>n-alkanes, isoalkanes, cyclics | N/A    | -    | -                                                   | -   | -    | -    | -     | -     |

**Legend:** X - Listed '-' - Not Listed

**KECL** - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

**Authorisation/Restrictions according to EU REACH**

Not applicable

| Component                                              | CAS No | REACH (1907/2006) -<br>Annex XIV - Substances<br>Subject to Authorization | REACH (1907/2006) -<br>Annex XVII - Restrictions<br>on Certain Dangerous<br>Substances | REACH Regulation (EC<br>1907/2006) article 59 -<br>Candidate List of<br>Substances of Very High<br>Concern (SVHC) |
|--------------------------------------------------------|--------|---------------------------------------------------------------------------|----------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------|
| HYDROCARBONS, C7-C9,<br>n-alkanes, isoalkanes, cyclics | N/A    | -                                                                         | -                                                                                      | -                                                                                                                 |

**Seveso III Directive (2012/18/EC)**

| Component                                                 | CAS No | Seveso III Directive (2012/18/EC) -<br>Qualifying Quantities for Major Accident<br>Notification | Seveso III Directive (2012/18/EC) -<br>Qualifying Quantities for Safety Report<br>Requirements |
|-----------------------------------------------------------|--------|-------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|
| HYDROCARBONS, C7-C9,<br>n-alkanes, isoalkanes,<br>cyclics | N/A    | Not applicable                                                                                  | Not applicable                                                                                 |

**Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals**

Not applicable

**Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?**

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

**National Regulations**

**UK** - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

**WGK Classification**

Water endangering class = 2 (self classification)

## 15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has been conducted by the manufacturer/importer

# SAFETY DATA SHEET

Petroleum ether, boiling range 100-120°C

Revision Date 11-Apr-2025

## SECTION 16: OTHER INFORMATION

### Full text of H-Statements referred to under sections 2 and 3

H225 - Highly flammable liquid and vapor  
H304 - May be fatal if swallowed and enters airways  
H336 - May cause drowsiness or dizziness  
H411 - Toxic to aquatic life with long lasting effects  
EUH066 - Repeated exposure may cause skin dryness or cracking

### Legend

**CAS** - Chemical Abstracts Service

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**ENCS** - Japanese Existing and New Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**NZIoC** - New Zealand Inventory of Chemicals

**WEL** - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

**RPE** - Respiratory Protective Equipment

**LC50** - Lethal Concentration 50%

**NOEC** - No Observed Effect Concentration

**PBT** - Persistent, Bioaccumulative, Toxic

**TWA** - Time Weighted Average

**IARC** - International Agency for Research on Cancer  
Predicted No Effect Concentration (PNEC)

**LD50** - Lethal Dose 50%

**EC50** - Effective Concentration 50%

**POW** - Partition coefficient Octanol:Water

**vPvB** - very Persistent, very Bioaccumulative

**ADR** - European Agreement Concerning the International Carriage of Dangerous Goods by Road

**IMO/IMDG** - International Maritime Organization/International Maritime Dangerous Goods Code

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

**ICAO/IATA** - International Civil Aviation Organization/International Air Transport Association

**MARPOL** - International Convention for the Prevention of Pollution from Ships

**ATE** - Acute Toxicity Estimate

**VOC** - (Volatile Organic Compound)

### Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

### Training Advice

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts. Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

**Creation Date** 23-Nov-2009  
**Revision Date** 11-Apr-2025  
**Revision Summary** Not applicable.

**This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.**

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

# **SAFETY DATA SHEET**

Petroleum ether, boiling range 100-120°C

Revision Date 11-Apr-2025

---

materials or in any process, unless specified in the text

**End of Safety Data Sheet**