

Creation Date 12-Jan-2010

Revision Date 20-Oct-2023

Revision Number 10

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

Product Description: **Aqualine™ Water Standard 10 mg/g**  
Cat No. : **AL2720-80**

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.  
Uses advised against No Information available

### 1.3. Details of the supplier of the safety data sheet

#### Company

**EU entity/business name**  
Thermo Fisher Scientific  
Janssen Pharmaceuticaaan 3a  
2440 Geel, Belgium

**UK entity/business name**  
Fisher Scientific UK  
Bishop Meadow Road, Loughborough,  
Leicestershire LE11 5RG, United Kingdom

**Swiss distributor** - Fisher Scientific AG  
Neuhofstrasse 11, CH 4153 Reinach  
Tel: +41 (0) 56 618 41 11  
e-mail - infoch@thermofisher.com

E-mail address begel.sdsdesk@thermofisher.com

### 1.4. Emergency telephone number

Chemtrec US: (800) 424-9300  
Chemtrec EU: 001-703-527-3887

For customers in Switzerland:  
Tox Info Suisse Emergency Number: **145 (24hr)**  
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)  
Chemtrec (24h) Toll-Free: 0800 564 402  
Chemtrec Local: +41-43 508 20 11 (Zurich)  
Tel: 01509 231166

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

**CLP Classification - Regulation (EC) No 1272/2008**

# SAFETY DATA SHEET

Aqualine™ Water Standard 10 mg/g

Revision Date 20-Oct-2023

## Physical hazards

Flammable liquids

Category 3 (H226)

## Health hazards

Aspiration Toxicity

Category 1 (H304)

Acute oral toxicity

Category 4 (H302)

Acute Inhalation Toxicity - Vapors

Category 4 (H332)

Skin Corrosion/Irritation

Category 2 (H315)

Serious Eye Damage/Eye Irritation

Category 1 (H318)

Specific target organ toxicity - (single exposure)

Category 3 (H335) (H336)

Specific target organ toxicity - (repeated exposure)

Category 2 (H373)

## Environmental hazards

Chronic aquatic toxicity

Category 3 (H412)

Full text of Hazard Statements: see section 16

## 2.2. Label elements



Signal Word

**Danger**

## Hazard Statements

H226 - Flammable liquid and vapor

H302 + H332 - Harmful if swallowed or if inhaled

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H318 - Causes serious eye damage

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness

H373 - May cause damage to organs through prolonged or repeated exposure

H412 - Harmful to aquatic life with long lasting effects

## Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301 + P330 + P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting

P331 - Do NOT induce vomiting

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/physician

# SAFETY DATA SHEET

Aqualine™ Water Standard 10 mg/g

Revision Date 20-Oct-2023

## 2.3. Other hazards

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

| Component                    | CAS No    | EC No             | Weight % | CLP Classification - Regulation (EC) No 1272/2008                                                                                                                                                          |
|------------------------------|-----------|-------------------|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Propylene carbonate          | 108-32-7  | EEC No. 203-572-1 | 40-50    | Eye Irrit. 2 (H319)                                                                                                                                                                                        |
| Xylenes (o-, m-, p- isomers) | 1330-20-7 | EEC No. 215-535-7 | 20-30    | Flam. Liq. 3 (H226)<br>Asp. Tox. 1 (H304)<br>Acute Tox. 4 (H312)<br>Acute Tox. 4 (H332)<br>Skin Irrit. 2 (H315)<br>Eye Irrit. 2 (H319)<br>STOT SE 3 (H335)<br>STOT RE 2 (H373)<br>Aquatic Chronic 3 (H412) |
| 1-Butanol                    | 71-36-3   | EEC No. 200-751-6 | 20-30    | Flam. Liq. 3 (H226)<br>Acute Tox. 4 (H302)<br>Skin Irrit. 2 (H315)<br>Eye Dam. 1 (H318)<br>STOT SE 3 (H335)<br>STOT SE 3 (H336)                                                                            |

| Components                   | Reach Registration Number |
|------------------------------|---------------------------|
| Xylenes (o-, m-, p- isomers) | 01-2119486136-34          |
| n-Butyl alcohol              | 01-2119484630-38          |

Full text of Hazard Statements: see section 16

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

|                                           |                                                                                                                                                                                                                                                                                                                                                                                     |
|-------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Eye Contact</b>                        | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.                                                                                                                                                                                                                                                   |
| <b>Skin Contact</b>                       | Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.                                                                                                                                                                                                                                                                         |
| <b>Ingestion</b>                          | Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.                                                                                                                                                                                                                                              |
| <b>Inhalation</b>                         | Remove to fresh air. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required. Risk of serious damage to the lungs (by aspiration). If not breathing, give artificial respiration. |
| <b>Self-Protection of the First Aider</b> | Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.                                                                                                                                                                                                                                    |

### 4.2. Most important symptoms and effects, both acute and delayed

# SAFETY DATA SHEET

Aqualine™ Water Standard 10 mg/g

Revision Date 20-Oct-2023

Difficulty in breathing. Causes severe eye damage. Causes eye burns. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

## 4.3. Indication of any immediate medical attention and special treatment needed

### Notes to Physician

Treat symptomatically. Symptoms may be delayed.

## SECTION 5: FIREFIGHTING MEASURES

### 5.1. Extinguishing media

#### Suitable Extinguishing Media

Water spray, carbon dioxide (CO<sub>2</sub>), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

#### Extinguishing media which must not be used for safety reasons

No information available.

### 5.2. Special hazards arising from the substance or mixture

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Vapors may form explosive mixtures with air.

#### Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>).

### 5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges. Do not get in eyes, on skin, or on clothing.

### 6.2. Environmental precautions

Should not be released into the environment. See Section 12 for additional Ecological Information. Do not flush into surface water or sanitary sewer system. Avoid release to the environment. Collect spillage.

### 6.3. Methods and material for containment and cleaning up

Remove all sources of ignition. Soak up with inert absorbent material. Take precautionary measures against static discharges. Keep in suitable, closed containers for disposal. Use spark-proof tools and explosion-proof equipment.

### 6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for safe handling

# SAFETY DATA SHEET

Aqualine™ Water Standard 10 mg/g

Revision Date 20-Oct-2023

Use only under a chemical fume hood. Use spark-proof tools and explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not breathe mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Wash hands before breaks and immediately after handling the product. Use only non-sparking tools.

## Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

## 7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area.

Technical Rules for Hazardous Substances (TRGS) 510  
Storage Class (LGK) (Germany)

Class 3

Switzerland - Storage of hazardous substances

Storage class - SC 3

<https://www.kvu.ch/de/themen/stoffe-und-produkte>

<https://www.kvu.ch/fr/themes/substances-et-produits>

<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

## 7.3. Specific end use(s)

Use in laboratories

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

#### Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

| Component                   | European Union                                                                                                              | The United Kingdom                                                                                                        | France                                                                                                                                                                                                                                                                                                                   | Belgium                                                                                                                               | Spain                                                                                                                                                                                 |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Xylenes (o-, m-, p-isomers) | TWA: 50 ppm (8h)<br>TWA: 221 mg/m <sup>3</sup> (8h)<br>STEL: 100 ppm (15min)<br>STEL: 442 mg/m <sup>3</sup> (15min)<br>Skin | STEL: 100 ppm 15 min<br>STEL: 441 mg/m <sup>3</sup> 15 min<br>TWA: 50 ppm 8 hr<br>TWA: 220 mg/m <sup>3</sup> 8 hr<br>Skin | TWA / VME: 50 ppm (8 heures). restrictive limit<br>TWA / VME: 221 mg/m <sup>3</sup> (8 heures). restrictive limit<br>TWA / VME: 1000 mg/m <sup>3</sup> (8 heures).<br>STEL / VLCT: 100 ppm. restrictive limit<br>STEL / VLCT: 442 mg/m <sup>3</sup> . restrictive limit<br>STEL / VLCT: 1500 mg/m <sup>3</sup> .<br>Peau | TWA: 50 ppm 8 uren<br>TWA: 221 mg/m <sup>3</sup> 8 uren<br>STEL: 100 ppm 15 minuten<br>STEL: 442 mg/m <sup>3</sup> 15 minuten<br>Huid | STEL / VLA-EC: 100 ppm (15 minutos).<br>STEL / VLA-EC: 442 mg/m <sup>3</sup> (15 minutos).<br>TWA / VLA-ED: 50 ppm (8 horas)<br>TWA / VLA-ED: 221 mg/m <sup>3</sup> (8 horas)<br>Piel |
| 1-Butanol                   |                                                                                                                             | 50ppm STEL; 154mg/m <sup>3</sup> STEL                                                                                     | STEL / VLCT: 50 ppm.<br>STEL / VLCT: 150 mg/m <sup>3</sup> .                                                                                                                                                                                                                                                             | 50ppm VLE; 154mg/m <sup>3</sup> VLE                                                                                                   | STEL / VLA-EC: 50 ppm (15 minutos).<br>STEL / VLA-EC: 154 mg/m <sup>3</sup> (15 minutos).<br>TWA / VLA-ED: 20 ppm (8 horas)<br>TWA / VLA-ED: 61 mg/m <sup>3</sup> (8 horas)           |

| Component | Italy | Germany | Portugal | The Netherlands | Finland |
|-----------|-------|---------|----------|-----------------|---------|
|-----------|-------|---------|----------|-----------------|---------|

# SAFETY DATA SHEET

**Aqualine™ Water Standard 10 mg/g**

**Revision Date 20-Oct-2023**

|                             |                                                                                                                                                                                                                                    |                                                                                                                                                                                                                                                                                                                  |                                                                                                                                         |                                                                                     |                                                                                                                                                      |
|-----------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| Propylene carbonate         |                                                                                                                                                                                                                                    | TWA: 2 ppm (8 Stunden). AGW - exposure factor 1<br>TWA: 8.5 mg/m <sup>3</sup> (8 Stunden). AGW - exposure factor 1<br>TWA: 2 ppm (8 Stunden). MAK<br>TWA: 8.5 mg/m <sup>3</sup> (8 Stunden). MAK<br>Höhepunkt: 2 ppm<br>Höhepunkt: 8.5 mg/m <sup>3</sup>                                                         |                                                                                                                                         |                                                                                     |                                                                                                                                                      |
| Xylenes (o-, m-, p-isomers) | TWA: 50 ppm 8 ore.<br>Time Weighted Average pure<br>TWA: 221 mg/m <sup>3</sup> 8 ore.<br>Time Weighted Average pure<br>STEL: 100 ppm 15 minuti. Short-term pure<br>STEL: 442 mg/m <sup>3</sup> 15 minuti. Short-term pure<br>Pelle | TWA: 50 ppm (8 Stunden). AGW - exposure factor 2<br>TWA: 220 mg/m <sup>3</sup> (8 Stunden). AGW - exposure factor 2<br>TWA: 50 ppm (8 Stunden). MAK all isomers<br>TWA: 220 mg/m <sup>3</sup> (8 Stunden). MAK all isomers<br>Höhepunkt: 100 ppm<br>Höhepunkt: 440 mg/m <sup>3</sup><br>Haut<br>Haut all isomers | STEL: 100 ppm 15 minutos<br>STEL: 442 mg/m <sup>3</sup> 15 minutos<br>TWA: 50 ppm 8 horas<br>TWA: 221 mg/m <sup>3</sup> 8 horas<br>Pele | huid<br>STEL: 442 mg/m <sup>3</sup> 15 minuten<br>TWA: 210 mg/m <sup>3</sup> 8 uren | TWA: 50 ppm 8 tunteina<br>TWA: 220 mg/m <sup>3</sup> 8 tunteina<br>STEL: 100 ppm 15 minuutteina<br>STEL: 440 mg/m <sup>3</sup> 15 minuutteina<br>Iho |
| 1-Butanol                   |                                                                                                                                                                                                                                    | 100ppm TWA;<br>310mg/m <sup>3</sup> TWA                                                                                                                                                                                                                                                                          | TWA: 20 ppm 8 horas                                                                                                                     | 15ppm STEL; 45mg/m <sup>3</sup> STEL                                                | TWA: 50 ppm 8 tunteina<br>TWA: 150 mg/m <sup>3</sup> 8 tunteina<br>STEL: 75 ppm 15 minuutteina<br>STEL: 230 mg/m <sup>3</sup> 15 minuutteina<br>Iho  |

| Component                   | Austria                                                                                                                                             | Denmark                                                                                                                                  | Switzerland                                                                                                                                      | Poland                                                                            | Norway                                                                                                                                                                        |
|-----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Propylene carbonate         |                                                                                                                                                     |                                                                                                                                          | STEL: 6 ppm 15 Minuten<br>STEL: 25.5 mg/m <sup>3</sup> 15 Minuten<br>TWA: 6 ppm 8 Stunden<br>TWA: 25.5 mg/m <sup>3</sup> 8 Stunden               |                                                                                   |                                                                                                                                                                               |
| Xylenes (o-, m-, p-isomers) | MAK-KZGW: 100 ppm 15 Minuten<br>MAK-KZGW: 442 mg/m <sup>3</sup> 15 Minuten<br>MAK-TMW: 50 ppm 8 Stunden<br>MAK-TMW: 221 mg/m <sup>3</sup> 8 Stunden | TWA: 25 ppm 8 timer<br>TWA: 109 mg/m <sup>3</sup> 8 timer<br>STEL: 442 mg/m <sup>3</sup> 15 minutter<br>STEL: 100 ppm 15 minutter<br>Hud | Haut/Peau<br>STEL: 100 ppm 15 Minuten<br>STEL: 440 mg/m <sup>3</sup> 15 Minuten<br>TWA: 50 ppm 8 Stunden<br>TWA: 220 mg/m <sup>3</sup> 8 Stunden | STEL: 200 mg/m <sup>3</sup> 15 minutach<br>TWA: 100 mg/m <sup>3</sup> 8 godzinach | TWA: 25 ppm 8 timer<br>TWA: 108 mg/m <sup>3</sup> 8 timer<br>STEL: 37.5 ppm 15 minutter. value calculated<br>STEL: 135 mg/m <sup>3</sup> 15 minutter. value calculated<br>Hud |
| 1-Butanol                   | MAK-KZGW: 200 ppm 15 Minuten<br>MAK-KZGW: 600 mg/m <sup>3</sup> 15 Minuten<br>MAK-TMW: 50 ppm 8 Stunden<br>MAK-TMW: 150 mg/m <sup>3</sup> 8 Stunden | Ceiling: 50 ppm<br>Ceiling: 150 mg/m <sup>3</sup><br>Hud                                                                                 | STEL: 100 ppm 15 Minuten<br>STEL: 310 mg/m <sup>3</sup> 15 Minuten<br>TWA: 100 ppm 8 Stunden<br>TWA: 310 mg/m <sup>3</sup> 8 Stunden             | STEL: 150 mg/m <sup>3</sup> 15 minutach<br>TWA: 50 mg/m <sup>3</sup> 8 godzinach  | Hud<br>Ceiling: 25 ppm<br>Ceiling: 75 mg/m <sup>3</sup>                                                                                                                       |

| Component                   | Bulgaria                                                                                                       | Croatia                                                                       | Ireland                                                                                                             | Cyprus                                                                                                 | Czech Republic                                                                                                 |
|-----------------------------|----------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------|
| Xylenes (o-, m-, p-isomers) | TWA: 50 ppm<br>TWA: 221.0 mg/m <sup>3</sup><br>STEL : 100 ppm<br>STEL : 442 mg/m <sup>3</sup><br>Skin notation | kože<br>TWA-GVI: 50 ppm 8 satima.<br>TWA-GVI: 221 mg/m <sup>3</sup> 8 satima. | TWA: 50 ppm 8 hr.<br>TWA: 221 mg/m <sup>3</sup> 8 hr.<br>STEL: 100 ppm 15 min<br>STEL: 442 mg/m <sup>3</sup> 15 min | Skin-potential for cutaneous absorption<br>STEL: 100 ppm<br>STEL: 442 mg/m <sup>3</sup><br>TWA: 50 ppm | TWA: 200 mg/m <sup>3</sup> 8 hodinách.<br>Potential for cutaneous absorption<br>Ceiling: 400 mg/m <sup>3</sup> |

# SAFETY DATA SHEET

Aqualine™ Water Standard 10 mg/g

Revision Date 20-Oct-2023

|           |                                                            |                                                                                               |                                                  |                            |                                                                                                                      |
|-----------|------------------------------------------------------------|-----------------------------------------------------------------------------------------------|--------------------------------------------------|----------------------------|----------------------------------------------------------------------------------------------------------------------|
|           |                                                            | STEL-KGVI: 100 ppm<br>15 minutama.<br>STEL-KGVI: 442 mg/m <sup>3</sup><br>15 minutama.        | Skin                                             | TWA: 221 mg/m <sup>3</sup> |                                                                                                                      |
| 1-Butanol | TWA: 100 mg/m <sup>3</sup><br>STEL : 150 mg/m <sup>3</sup> | kože<br>STEL-KGVI: 50 ppm 15<br>minutama.<br>STEL-KGVI: 154 mg/m <sup>3</sup><br>15 minutama. | TWA: 20 ppm 8 hr.<br>STEL: 60 ppm 15 min<br>Skin |                            | TWA: 300 mg/m <sup>3</sup> 8<br>hodinách.<br>Potential for cutaneous<br>absorption<br>Ceiling: 600 mg/m <sup>3</sup> |

| Component                       | Estonia                                                                                                                                                           | Gibraltar                                                                                                                                                       | Greece                                                                                                                                     | Hungary                                                                                                                                     | Iceland                                                                                                                                            |
|---------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| Xylenes (o-, m-, p-<br>isomers) | Nahk<br>TWA: 50 ppm 8<br>tundides.<br>TWA: 200 mg/m <sup>3</sup> 8<br>tundides.<br>STEL: 100 ppm 15<br>minutites.<br>STEL: 450 mg/m <sup>3</sup> 15<br>minutites. | Skin notation<br>TWA: 50 ppm 8 hr pure<br>TWA: 221 mg/m <sup>3</sup> 8 hr<br>pure<br>STEL: 100 ppm 15 min<br>pure<br>STEL: 442 mg/m <sup>3</sup> 15<br>min pure | skin - potential for<br>cutaneous absorption<br>STEL: 150 ppm<br>STEL: 650 mg/m <sup>3</sup><br>TWA: 100 ppm<br>TWA: 435 mg/m <sup>3</sup> | STEL: 442 mg/m <sup>3</sup> 15<br>percekben. CK<br>TWA: 221 mg/m <sup>3</sup> 8<br>órában. AK<br>lehetséges borón<br>keresztüli felszívódás | STEL: 100 ppm<br>STEL: 442 mg/m <sup>3</sup><br>TWA: 25 ppm 8<br>klukkustundum.<br>TWA: 109 mg/m <sup>3</sup> 8<br>klukkustundum.<br>Skin notation |
| 1-Butanol                       | Nahk<br>TWA: 15 ppm 8<br>tundides.<br>TWA: 45 mg/m <sup>3</sup> 8<br>tundides.<br>STEL: 30 ppm 15<br>minutites.<br>STEL: 90 mg/m <sup>3</sup> 15<br>minutites.    |                                                                                                                                                                 | skin - potential for<br>cutaneous absorption<br>STEL: 100 ppm<br>STEL: 300 mg/m <sup>3</sup><br>TWA: 100 ppm<br>TWA: 300 mg/m <sup>3</sup> | STEL: 90 mg/m <sup>3</sup> 15<br>percekben. CK<br>TWA: 45 mg/m <sup>3</sup> 8<br>órában. AK<br>lehetséges borón<br>keresztüli felszívódás   | STEL: 50 ppm<br>STEL: 150 mg/m <sup>3</sup><br>Skin notation                                                                                       |

| Component                       | Latvia                                                                                                                                  | Lithuania                                                                                                                                                | Luxembourg                                                                                                                                                                                               | Malta                                                                                                                                                                        | Romania                                                                                                                                          |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| Propylene carbonate             | TWA: 2 mg/m <sup>3</sup>                                                                                                                | TWA: 7 mg/m <sup>3</sup> IPRD                                                                                                                            |                                                                                                                                                                                                          |                                                                                                                                                                              |                                                                                                                                                  |
| Xylenes (o-, m-, p-<br>isomers) | skin - potential for<br>cutaneous exposure<br>STEL: 100 ppm<br>STEL: 442 mg/m <sup>3</sup><br>TWA: 50 ppm<br>TWA: 221 mg/m <sup>3</sup> | TWA: 221 mg/m <sup>3</sup> IPRD<br>mixed isomers, pure<br>TWA: 50 ppm IPRD<br>mixed isomers, pure<br>Oda<br>STEL: 442 mg/m <sup>3</sup><br>STEL: 100 ppm | Possibility of significant<br>uptake through the skin<br>TWA: 50 ppm 8<br>Stunden<br>TWA: 221 mg/m <sup>3</sup> 8<br>Stunden<br>STEL: 100 ppm 15<br>Minuten<br>STEL: 442 mg/m <sup>3</sup> 15<br>Minuten | possibility of significant<br>uptake through the skin<br>TWA: 50 ppm<br>TWA: 221 mg/m <sup>3</sup><br>STEL: 100 ppm 15<br>minuti<br>STEL: 442 mg/m <sup>3</sup> 15<br>minuti | Skin notation<br>TWA: 50 ppm 8 ore<br>TWA: 221 mg/m <sup>3</sup> 8 ore<br>STEL: 100 ppm 15<br>minute<br>STEL: 442 mg/m <sup>3</sup> 15<br>minute |
| 1-Butanol                       | TWA: 10 mg/m <sup>3</sup>                                                                                                               | Ceiling: 30 ppm<br>Ceiling: 90 mg/m <sup>3</sup><br>TWA: 15 ppm IPRD<br>TWA: 45 mg/m <sup>3</sup> IPRD<br>Oda                                            |                                                                                                                                                                                                          |                                                                                                                                                                              | TWA: 33 ppm 8 ore<br>TWA: 100 mg/m <sup>3</sup> 8 ore<br>STEL: 66 ppm 15<br>minute<br>STEL: 200 mg/m <sup>3</sup> 15<br>minute                   |

| Component                       | Russia                                                                                           | Slovak Republic                                                                                                      | Slovenia                                                                                                                                    | Sweden                                                                                                                                                                         | Turkey                                                                                                                                    |
|---------------------------------|--------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| Propylene carbonate             | MAC: 7 mg/m <sup>3</sup>                                                                         |                                                                                                                      |                                                                                                                                             |                                                                                                                                                                                |                                                                                                                                           |
| Xylenes (o-, m-, p-<br>isomers) | TWA: 50 mg/m <sup>3</sup> 0741<br>mixture of 2-, 3-, 4-<br>isomers<br>MAC: 150 mg/m <sup>3</sup> | Ceiling: 442 mg/m <sup>3</sup><br>Potential for cutaneous<br>absorption<br>TWA: 50 ppm<br>TWA: 221 mg/m <sup>3</sup> | TWA: 50 ppm 8 urah<br>TWA: 221 mg/m <sup>3</sup> 8 urah<br>Koža<br>STEL: 100 ppm 15<br>minutah<br>STEL: 442 mg/m <sup>3</sup> 15<br>minutah | Binding STEL: 100 ppm<br>15 minuter<br>Binding STEL: 442<br>mg/m <sup>3</sup> 15 minuter<br>TLV: 50 ppm 8 timmar.<br>NGV<br>TLV: 221 mg/m <sup>3</sup> 8<br>timmar. NGV<br>Hud | Deri<br>TWA: 50 ppm 8 saat<br>TWA: 221 mg/m <sup>3</sup> 8 saat<br>STEL: 100 ppm 15<br>dakika<br>STEL: 442 mg/m <sup>3</sup> 15<br>dakika |
| 1-Butanol                       | TWA: 10 mg/m <sup>3</sup> 0418<br>MAC: 30 mg/m <sup>3</sup>                                      | Ceiling: 310 mg/m <sup>3</sup><br>TWA: 100 ppm<br>TWA: 310 mg/m <sup>3</sup>                                         | TWA: 100 ppm 8 urah<br>TWA: 310 mg/m <sup>3</sup> 8 urah<br>STEL: 100 ppm 15<br>minutah<br>STEL: 310 mg/m <sup>3</sup> 15<br>minutah        | Binding STEL: 30 ppm<br>15 minuter<br>Binding STEL: 90<br>mg/m <sup>3</sup> 15 minuter<br>TLV: 15 ppm 8 timmar.<br>NGV<br>TLV: 45 mg/m <sup>3</sup> 8<br>timmar. NGV           |                                                                                                                                           |

# SAFETY DATA SHEET

Aqualine™ Water Standard 10 mg/g

Revision Date 20-Oct-2023

|  |  |  |  |     |  |
|--|--|--|--|-----|--|
|  |  |  |  | Hud |  |
|--|--|--|--|-----|--|

## Biological limit values

List source(s): **UK** - Biological Monitoring Guidance Values provided by the UK's Health and Safety Executive (HSE) Control of Substances Hazardous to Health Regulations (COSHH) 2002 (as amended) and EH40/2005.

| Component                    | European Union | United Kingdom                                                 | France                                                       | Spain                                                     | Germany                                                                                                                                                           |
|------------------------------|----------------|----------------------------------------------------------------|--------------------------------------------------------------|-----------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Xylenes (o-, m-, p- isomers) |                | Methyl hippuric acid: 650 mmol/mol creatinine urine post shift | Methylhippuric acid: 1500 mg/g creatinine urine end of shift | Methylhippuric acids: 1 g/g Creatinine urine end of shift | Methylhippuric(tolur-)acid (all isomers): 2000 mg/L urine (end of shift all isomers)                                                                              |
| 1-Butanol                    |                |                                                                |                                                              |                                                           | 1-Butanol (after hydrolysis): 10 mg/g Creatinine urine (end of shift )<br>1-Butanol (after hydrolysis): 2 mg/g Creatinine urine (before beginning of next shift ) |

| Component                    | Italy | Finland                                                | Denmark | Bulgaria | Romania                                       |
|------------------------------|-------|--------------------------------------------------------|---------|----------|-----------------------------------------------|
| Xylenes (o-, m-, p- isomers) |       | Methylhippuric acid: 5.0 mmol/L urine after the shift. |         |          | Methylhippuric acid: 3 g/L urine end of shift |

| Component                    | Gibraltar | Latvia | Slovak Republic                                                                                                                                                  | Luxembourg | Turkey |
|------------------------------|-----------|--------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|--------|
| Xylenes (o-, m-, p- isomers) |           |        | Xylene: 1.5 mg/L blood end of exposure or work shift all isomers<br>Methylhippuric acid: 2000 mg/L urine end of exposure or work shift                           |            |        |
| 1-Butanol                    |           |        | n-Butyl alcohol: 2 mg/g creatinine urine after all work shifts for long-term exposure<br>n-Butyl alcohol: 10 mg/g creatinine urine end of exposure or work shift |            |        |

## Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

## Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

| Component                                           | Acute effects local (Dermal) | Acute effects systemic (Dermal) | Chronic effects local (Dermal) | Chronic effects systemic (Dermal) |
|-----------------------------------------------------|------------------------------|---------------------------------|--------------------------------|-----------------------------------|
| Propylene carbonate<br>108-32-7 ( 40-50 )           |                              |                                 | DNEL = 10mg/cm2                | DNEL = 20mg/kg bw/day             |
| Xylenes (o-, m-, p- isomers)<br>1330-20-7 ( 20-30 ) |                              |                                 |                                | DNEL = 212mg/kg bw/day            |

| Component | Acute effects local (Inhalation) | Acute effects systemic (Inhalation) | Chronic effects local (Inhalation) | Chronic effects systemic (Inhalation) |
|-----------|----------------------------------|-------------------------------------|------------------------------------|---------------------------------------|
|-----------|----------------------------------|-------------------------------------|------------------------------------|---------------------------------------|



# SAFETY DATA SHEET

Aqualine™ Water Standard 10 mg/g

Revision Date 20-Oct-2023

|                                                     |                             |                             |                             |                               |
|-----------------------------------------------------|-----------------------------|-----------------------------|-----------------------------|-------------------------------|
| Propylene carbonate<br>108-32-7 ( 40-50 )           |                             |                             | DNEL = 20mg/m <sup>3</sup>  | DNEL = 70.53mg/m <sup>3</sup> |
| Xylenes (o-, m-, p- isomers)<br>1330-20-7 ( 20-30 ) | DNEL = 442mg/m <sup>3</sup> | DNEL = 442mg/m <sup>3</sup> | DNEL = 221mg/m <sup>3</sup> | DNEL = 221mg/m <sup>3</sup>   |
| 1-Butanol<br>71-36-3 ( 20-30 )                      |                             |                             | DNEL = 310mg/m <sup>3</sup> |                               |

## Predicted No Effect Concentration (PNEC)

See values below.

| Component                                           | Fresh water      | Fresh water sediment          | Water Intermittent | Microorganisms in sewage treatment | Soil (Agriculture)         |
|-----------------------------------------------------|------------------|-------------------------------|--------------------|------------------------------------|----------------------------|
| Propylene carbonate<br>108-32-7 ( 40-50 )           | PNEC = 0.9mg/L   |                               | PNEC = 9mg/L       | PNEC = 7400mg/L                    | PNEC = 0.81mg/kg soil dw   |
| Xylenes (o-, m-, p- isomers)<br>1330-20-7 ( 20-30 ) | PNEC = 0.327mg/L | PNEC = 12.46mg/kg sediment dw | PNEC = 0.327mg/L   | PNEC = 6.58mg/L                    | PNEC = 2.31mg/kg soil dw   |
| 1-Butanol<br>71-36-3 ( 20-30 )                      | PNEC = 0.082mg/L | PNEC = 0.324mg/kg sediment dw | PNEC = 2.25mg/L    | PNEC = 2476mg/L                    | PNEC = 0.0166mg/kg soil dw |

| Component                                           | Marine water      | Marine water sediment          | Marine water Intermittent | Food chain | Air |
|-----------------------------------------------------|-------------------|--------------------------------|---------------------------|------------|-----|
| Propylene carbonate<br>108-32-7 ( 40-50 )           | PNEC = 0.09mg/L   |                                | PNEC = 0.9mg/L            |            |     |
| Xylenes (o-, m-, p- isomers)<br>1330-20-7 ( 20-30 ) | PNEC = 0.327mg/L  | PNEC = 12.46mg/kg sediment dw  |                           |            |     |
| 1-Butanol<br>71-36-3 ( 20-30 )                      | PNEC = 0.0082mg/L | PNEC = 0.0324mg/kg sediment dw |                           |            |     |

## 8.2. Exposure controls

### Engineering Measures

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

### Personal protective equipment

#### Eye Protection

Goggles (European standard - EN 166)

#### Hand Protection

Protective gloves

| Glove material | Breakthrough time                 | Glove thickness | EU standard | Glove comments        |
|----------------|-----------------------------------|-----------------|-------------|-----------------------|
| Viton (R)      | See manufacturers recommendations | -               | EN 374      | (minimum requirement) |

#### Skin and body protection

Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

#### Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.  
To protect the wearer, respiratory protective equipment must be the correct fit and be used

# SAFETY DATA SHEET

Aqualine™ Water Standard 10 mg/g

Revision Date 20-Oct-2023

and maintained properly

|                                        |                                                                                                                                                                                                                                                                                                                             |
|----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Large scale/emergency use</b>       | Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced<br><b>Recommended Filter type:</b> low boiling organic solvent Type AX Brown conforming to EN371 or Organic gases and vapours filter Type A Brown conforming to EN14387 |
| <b>Small scale/Laboratory use</b>      | Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.<br><b>Recommended half mask:-</b> Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141<br>When RPE is used a face piece Fit Test should be conducted |
| <b>Environmental exposure controls</b> | Prevent product from entering drains. Do not allow material to contaminate ground water system. Local authorities should be advised if significant spillages cannot be contained.                                                                                                                                           |

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

|                                                |                          |                                          |
|------------------------------------------------|--------------------------|------------------------------------------|
| <b>Physical State</b>                          | Liquid                   |                                          |
| <b>Appearance</b>                              |                          |                                          |
| <b>Odor</b>                                    | No information available |                                          |
| <b>Odor Threshold</b>                          | No data available        |                                          |
| <b>Melting Point/Range</b>                     | No data available        |                                          |
| <b>Softening Point</b>                         | No data available        |                                          |
| <b>Boiling Point/Range</b>                     | No information available |                                          |
| <b>Flammability (liquid)</b>                   | Flammable                | On basis of test data                    |
| <b>Flammability (solid,gas)</b>                | Not applicable           | Liquid                                   |
| <b>Explosion Limits</b>                        | No data available        |                                          |
| <b>Flash Point</b>                             | 32.2 °C / 90 °F          | <b>Method -</b> No information available |
| <b>Autoignition Temperature</b>                | No data available        |                                          |
| <b>Decomposition Temperature</b>               | No data available        |                                          |
| <b>pH</b>                                      | No information available |                                          |
| <b>Viscosity</b>                               | No data available        |                                          |
| <b>Water Solubility</b>                        | Partially soluble        |                                          |
| <b>Solubility in other solvents</b>            | No information available |                                          |
| <b>Partition Coefficient (n-octanol/water)</b> |                          |                                          |
| <b>Component</b>                               | <b>log Pow</b>           |                                          |
| Propylene carbonate                            | -0.5                     |                                          |
| Xylenes (o-, m-, p- isomers)                   | 3.15                     |                                          |
| 1-Butanol                                      | 1                        |                                          |
| <b>Vapor Pressure</b>                          | No data available        |                                          |
| <b>Density / Specific Gravity</b>              | 1                        |                                          |
| <b>Bulk Density</b>                            | Not applicable           | Liquid                                   |
| <b>Vapor Density</b>                           | No data available        | (Air = 1.0)                              |
| <b>Particle characteristics</b>                | Not applicable (liquid)  |                                          |

### 9.2. Other information

|                             |                                        |
|-----------------------------|----------------------------------------|
| <b>Explosive Properties</b> | explosive air/vapour mixtures possible |
|-----------------------------|----------------------------------------|

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

None known, based on information available

# SAFETY DATA SHEET

Aqualine™ Water Standard 10 mg/g

Revision Date 20-Oct-2023

## 10.2. Chemical stability

Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

### **Hazardous Polymerization Hazardous Reactions**

No information available.

No information available.

## 10.4. Conditions to avoid

Incompatible products. Heat, flames and sparks. Keep away from open flames, hot surfaces and sources of ignition.

## 10.5. Incompatible materials

Strong oxidizing agents.

## 10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Product Information**

#### **(a) acute toxicity;**

**Oral**

No data available

**Dermal**

No data available

**Inhalation**

No data available

#### Toxicology data for the components

| Component                    | LD50 Oral                  | LD50 Dermal                  | LC50 Inhalation                              |
|------------------------------|----------------------------|------------------------------|----------------------------------------------|
| Propylene carbonate          | LD50 = 29000 mg/kg ( Rat ) | LD50 > 3000 mg/kg ( Rabbit ) | -                                            |
| Xylenes (o-, m-, p- isomers) | LD50 = 3500 mg/kg ( Rat )  | LD50 > 4350 mg/kg ( Rabbit ) | 29.08 mg/L [MOE Risk Assessment Vol.1, 2002] |
| 1-Butanol                    | LD50 = 700 mg/kg ( Rat )   | LD50 = 3402 mg/kg ( Rabbit ) | LC50 > 8000 ppm ( Rat ) 4 h                  |

#### **(b) skin corrosion/irritation;**

No data available

#### **(c) serious eye damage/irritation;**

No data available

#### **(d) respiratory or skin sensitization;**

**Respiratory**

No data available

**Skin**

No data available

#### **(e) germ cell mutagenicity;**

No data available

#### **(f) carcinogenicity;**

No data available

There are no known carcinogenic chemicals in this product

#### **(g) reproductive toxicity;**

No data available

# SAFETY DATA SHEET

Aqualine™ Water Standard 10 mg/g

Revision Date 20-Oct-2023

(h) STOT-single exposure; No data available

Results / Target organs Central nervous system (CNS), Respiratory system.

(i) STOT-repeated exposure; No data available

Target Organs Liver, Kidney, Blood.

(j) aspiration hazard; Category 1

Symptoms / effects, both acute and delayed Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

## 11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

Ecotoxicity effects Contains a substance which is: Toxic to aquatic organisms.

| Component                    | Freshwater Fish                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Water Flea                                                                                                                                              | Freshwater Algae                                                                                                                                                               |
|------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Propylene carbonate          | Leuciscus idus: LC50: 5300 mg/L/96h                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | EC50: > 500 mg/L, 48h (Daphnia magna)                                                                                                                   | EC50: > 500 mg/L, 72h (Desmodesmus subspicatus)                                                                                                                                |
| Xylenes (o-, m-, p- isomers) | LC50: 30.26 - 40.75 mg/L, 96h static (Poecilia reticulata)<br>LC50: = 780 mg/L, 96h semi-static (Cyprinus carpio)<br>LC50: 23.53 - 29.97 mg/L, 96h static (Pimephales promelas)<br>LC50: > 780 mg/L, 96h (Cyprinus carpio)<br>LC50: 7.711 - 9.591 mg/L, 96h static (Lepomis macrochirus)<br>LC50: = 19 mg/L, 96h (Lepomis macrochirus)<br>LC50: 13.1 - 16.5 mg/L, 96h flow-through (Lepomis macrochirus)<br>LC50: 13.5 - 17.3 mg/L, 96h (Oncorhynchus mykiss)<br>LC50: 2.661 - 4.093 mg/L, 96h static (Oncorhynchus mykiss)<br>LC50: = 13.4 mg/L, 96h flow-through (Pimephales promelas) | LC50: = 0.6 mg/L, 48h (Gammarus lacustris)<br>EC50: = 3.82 mg/L, 48h (water flea)                                                                       |                                                                                                                                                                                |
| 1-Butanol                    | LC50: 1376 mg/L, 96h (Pimephales promelas) OECD Guideline 203 : 100000 - 500000 µg/L, 96h static (Lepomis macrochirus)<br>LC50: = 1740 mg/L, 96h flow-through (Pimephales promelas)<br>LC50: = 1910000 µg/L, 96h static (Pimephales promelas)<br>LC50: 1730 - 1910 mg/L, 96h                                                                                                                                                                                                                                                                                                             | EC50: 1328 mg/L, 48h (Daphnia magna) OECD Guideline 202<br>EC50: 1897 - 2072 mg/L, 48h Static (Daphnia magna)<br>EC50: = 1983 mg/L, 48h (Daphnia magna) | EC50: 225 mg/L, 96h (Pseudokirchneriella subcapitata) OECD Guideline 201<br>EC50: > 500 mg/L, 72h (Desmodesmus subspicatus)<br>EC50: > 500 mg/L, 96h (Desmodesmus subspicatus) |

# SAFETY DATA SHEET

Aqualine™ Water Standard 10 mg/g

Revision Date 20-Oct-2023

|  |                              |  |  |
|--|------------------------------|--|--|
|  | static (Pimephales promelas) |  |  |
|--|------------------------------|--|--|

| Component                    | Microtox                                                                                              | M-Factor |
|------------------------------|-------------------------------------------------------------------------------------------------------|----------|
| Propylene carbonate          | EC50 > 10000 mg/L 17 h                                                                                |          |
| Xylenes (o-, m-, p- isomers) | EC50 = 0.0084 mg/L 24 h                                                                               |          |
| 1-Butanol                    | EC50 = 2041.4 mg/L 5 min<br>EC50 = 2186 mg/L 30 min<br>EC50 = 3980 mg/L 24 h<br>EC50 = 4400 mg/L 17 h |          |

## 12.2. Persistence and degradability

| Component                      | Degradability |
|--------------------------------|---------------|
| 1-Butanol<br>71-36-3 ( 20-30 ) | 70 %          |

**Degradation in sewage treatment plant**

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

## 12.3. Bioaccumulative potential

| Component                    | log Pow | Bioconcentration factor (BCF) |
|------------------------------|---------|-------------------------------|
| Propylene carbonate          | -0.5    | No data available             |
| Xylenes (o-, m-, p- isomers) | 3.15    | 0.6 - 15 dimensionless        |
| 1-Butanol                    | 1       | 0.64 dimensionless            |

## 12.4. Mobility in soil

No information available .

## 12.5. Results of PBT and vPvB assessment

No data available for assessment.

## 12.6. Endocrine disrupting properties

**Endocrine Disruptor Information**

This product does not contain any known or suspected endocrine disruptors

## 12.7. Other adverse effects Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance  
This product does not contain any known or suspected substance

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

**Waste from Residues/Unused Products**

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

**Contaminated Packaging**

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

**European Waste Catalogue (EWC)**

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

**Other Information**

Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains.

# SAFETY DATA SHEET

Aqualine™ Water Standard 10 mg/g

Revision Date 20-Oct-2023

**Switzerland - Waste Ordinance** Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600  
<https://www.fedlex.admin.ch/eli/cc/2015/891/en>

## SECTION 14: TRANSPORT INFORMATION

### IMDG/IMO

**14.1. UN number** UN1993  
**14.2. UN proper shipping name** Flammable liquid, n.o.s.  
**Technical Shipping Name** (Contains xylene and n-butanol)  
**14.3. Transport hazard class(es)** 3  
**14.4. Packing group** III

### ADR

**14.1. UN number** UN1993  
**14.2. UN proper shipping name** Flammable liquid, n.o.s.  
**Technical Shipping Name** (Contains xylene and n-butanol)  
**14.3. Transport hazard class(es)** 3  
**14.4. Packing group** III

### IATA

**14.1. UN number** UN1993  
**14.2. UN proper shipping name** Flammable liquid, n.o.s.  
**Technical Shipping Name** (Contains xylene and n-butanol)  
**14.3. Transport hazard class(es)** 3  
**14.4. Packing group** III

**14.5. Environmental hazards** No hazards identified  
**14.6. Special precautions for user** No special precautions required.  
**14.7. Maritime transport in bulk according to IMO instruments** Not applicable, packaged goods

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

| Component                    | CAS No    | EINECS    | ELINCS | NLP | IECSC | TCSI | KECL     | ENCS | ISHL |
|------------------------------|-----------|-----------|--------|-----|-------|------|----------|------|------|
| Propylene carbonate          | 108-32-7  | 203-572-1 | -      | -   | X     | X    | KE-23785 | X    | X    |
| Xylenes (o-, m-, p- isomers) | 1330-20-7 | 215-535-7 | -      | -   | X     | X    | KE-35427 | X    | X    |
| 1-Butanol                    | 71-36-3   | 200-751-6 | -      | -   | X     | X    | KE-03867 | X    | X    |

| Component                    | CAS No    | TSCA | TSCA Inventory notification - Active-Inactive | DSL | NDSL | AICS | NZIoC | PICCS |
|------------------------------|-----------|------|-----------------------------------------------|-----|------|------|-------|-------|
| Propylene carbonate          | 108-32-7  | X    | ACTIVE                                        | X   | -    | X    | X     | X     |
| Xylenes (o-, m-, p- isomers) | 1330-20-7 | X    | ACTIVE                                        | X   | -    | X    | X     | X     |
| 1-Butanol                    | 71-36-3   | X    | ACTIVE                                        | X   | -    | X    | X     | X     |

# SAFETY DATA SHEET

Aqualine™ Water Standard 10 mg/g

Revision Date 20-Oct-2023

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

## Authorisation/Restrictions according to EU REACH

| Component                    | CAS No    | REACH (1907/2006) - Annex XIV - Substances Subject to Authorization | REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances | REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC) |
|------------------------------|-----------|---------------------------------------------------------------------|-------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------|
| Propylene carbonate          | 108-32-7  | -                                                                   | Use restricted. See item 75.<br>(see link for restriction details)            | -                                                                                                     |
| Xylenes (o-, m-, p- isomers) | 1330-20-7 | -                                                                   | Use restricted. See item 75.<br>(see link for restriction details)            | -                                                                                                     |
| 1-Butanol                    | 71-36-3   | -                                                                   | Use restricted. See item 75.<br>(see link for restriction details)            | -                                                                                                     |

## REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

## Seveso III Directive (2012/18/EC)

| Component                    | CAS No    | Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification | Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements |
|------------------------------|-----------|-------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|
| Propylene carbonate          | 108-32-7  | Not applicable                                                                            | Not applicable                                                                           |
| Xylenes (o-, m-, p- isomers) | 1330-20-7 | Not applicable                                                                            | Not applicable                                                                           |
| 1-Butanol                    | 71-36-3   | Not applicable                                                                            | Not applicable                                                                           |

## Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

## Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

## National Regulations

**UK** - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

## WGK Classification

Water endangering class = 2 (self classification)

| Component                    | Germany - Water Classification (AwSV) | Germany - TA-Luft Class |
|------------------------------|---------------------------------------|-------------------------|
| Propylene carbonate          | WGK1                                  |                         |
| Xylenes (o-, m-, p- isomers) | WGK2                                  |                         |
| 1-Butanol                    | WGK1                                  |                         |

| Component | France - INRS (Tables of occupational diseases) |
|-----------|-------------------------------------------------|
|-----------|-------------------------------------------------|

# SAFETY DATA SHEET

Aqualine™ Water Standard 10 mg/g

Revision Date 20-Oct-2023

|                              |                                                               |
|------------------------------|---------------------------------------------------------------|
| Xylenes (o-, m-, p- isomers) | Tableaux des maladies professionnelles (TMP) - RG 4bis, RG 84 |
| 1-Butanol                    | Tableaux des maladies professionnelles (TMP) - RG 84          |

## Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

| Component                                           | Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81) | Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC) | Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure |
|-----------------------------------------------------|----------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|
| Xylenes (o-, m-, p- isomers)<br>1330-20-7 ( 20-30 ) | Prohibited and Restricted Substances                                                                           | Group II                                                                        |                                                                                             |
| 1-Butanol<br>71-36-3 ( 20-30 )                      |                                                                                                                | Group I                                                                         |                                                                                             |

## 15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

## SECTION 16: OTHER INFORMATION

### Full text of H-Statements referred to under sections 2 and 3

H302 - Harmful if swallowed  
H304 - May be fatal if swallowed and enters airways  
H332 - Harmful if inhaled  
H315 - Causes skin irritation  
H318 - Causes serious eye damage  
H373 - May cause damage to organs through prolonged or repeated exposure  
H335 - May cause respiratory irritation  
H336 - May cause drowsiness or dizziness  
H412 - Harmful to aquatic life with long lasting effects

### Legend

**CAS** - Chemical Abstracts Service

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**ENCS** - Japanese Existing and New Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**NZIoC** - New Zealand Inventory of Chemicals

**WEL** - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

**RPE** - Respiratory Protective Equipment

**LC50** - Lethal Concentration 50%

**NOEC** - No Observed Effect Concentration

**PBT** - Persistent, Bioaccumulative, Toxic

**TWA** - Time Weighted Average

**IARC** - International Agency for Research on Cancer  
Predicted No Effect Concentration (PNEC)

**LD50** - Lethal Dose 50%

**EC50** - Effective Concentration 50%

**POW** - Partition coefficient Octanol:Water

**vPvB** - very Persistent, very Bioaccumulative

**ADR** - European Agreement Concerning the International Carriage of Dangerous Goods by Road

**IMO/IMDG** - International Maritime Organization/International Maritime Dangerous Goods Code

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

### Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadviser - LOLI, Merck index, RTECS

**ICAO/IATA** - International Civil Aviation Organization/International Air Transport Association

**MARPOL** - International Convention for the Prevention of Pollution from Ships

**ATE** - Acute Toxicity Estimate

**VOC** - (volatile organic compound)



# SAFETY DATA SHEET

Aqualine™ Water Standard 10 mg/g

Revision Date 20-Oct-2023

**Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:**

|                              |                       |
|------------------------------|-----------------------|
| <b>Physical hazards</b>      | On basis of test data |
| <b>Health Hazards</b>        | Calculation method    |
| <b>Environmental hazards</b> | Calculation method    |

## Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

|                         |                 |
|-------------------------|-----------------|
| <b>Creation Date</b>    | 12-Jan-2010     |
| <b>Revision Date</b>    | 20-Oct-2023     |
| <b>Revision Summary</b> | Not applicable. |

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.  
COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No  
1907/2006 .**

**For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2,  
Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and  
Preparations).**

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**