

Creation Date 26-Oct-2009

Revision Date 03-May-2024

Revision Number 15

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description:	Hexanes, 95% N-hexane
Cat No. :	H/0403/17, H/0403/15, H/0403/17CN
Synonyms	Hex
Index No	601-037-00-0
CAS No	110-54-3
EC No	203-777-6
Molecular Formula	C6 H14
REACH registration number	01-2119480412-44

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use	Laboratory chemicals.
Sector of use	SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites
Product category	PC21 - Laboratory chemicals
Process categories	PROC15 - Use as a laboratory reagent
Environmental release category	ERC6a - Industrial use resulting in manufacture of another substance (use of intermediates)
Uses advised against	No Information available

1.3. Details of the supplier of the safety data sheet

Company

EU entity/business name

Thermo Fisher Scientific
Janssen Pharmaceuticaaan 3a
2440 Geel, Belgium

UK entity/business name

Fisher Scientific UK
Bishop Meadow Road, Loughborough,
Leicestershire LE11 5RG, United Kingdom

Swiss distributor - Fisher Scientific AG

Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
e-mail - infoch@thermofisher.com

E-mail address

begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

Tel: 01509 231166
Chemtrec US: (800) 424-9300
Chemtrec EU: 001-703-527-3887

For customers in Switzerland:

Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

SAFETY DATA SHEET

Hexanes, 95% N-hexane

Revision Date 03-May-2024

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Flammable liquids

Category 2 (H225)

Health hazards

Aspiration Toxicity

Category 1 (H304)

Skin Corrosion/Irritation

Category 2 (H315)

Reproductive Toxicity

Category 2 (H361f)

Specific target organ toxicity - (single exposure)

Category 3 (H336)

Specific target organ toxicity - (repeated exposure)

Category 2 (H373)

Environmental hazards

Chronic aquatic toxicity

Category 2 (H411)

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H336 - May cause drowsiness or dizziness

H361f - Suspected of damaging fertility

H373 - May cause damage to organs through prolonged or repeated exposure

H411 - Toxic to aquatic life with long lasting effects

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

P331 - Do NOT induce vomiting

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

SAFETY DATA SHEET

Hexanes, 95% N-hexane

Revision Date 03-May-2024

2.3. Other hazards

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)

This product does not contain any known or suspected endocrine disruptors
Toxic to terrestrial vertebrates

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Hexane	110-54-3	EEC No. 203-777-6	<=100	Flam. Liq. 2 (H225) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) STOT SE 3 (H336) Repr. 2 (H361f) STOT RE 2 (H373) Aquatic Chronic 2 (H411)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Hexane	STOT RE 2 (H373) :: C>=5%	-	-

REACH registration number	01-2119480412-44
---------------------------	------------------

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice	If symptoms persist, call a physician.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur. Risk of serious damage to the lungs (by aspiration).
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

SAFETY DATA SHEET

Hexanes, 95% N-hexane

Revision Date 03-May-2024

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂).

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Ensure adequate ventilation. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

SAFETY DATA SHEET

Hexanes, 95% N-hexane

Revision Date 03-May-2024

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Class 3

Switzerland - Storage of hazardous substances

Storage class - SC 3
<https://www.kvu.ch/de/themen/stoffe-und-produkte>
<https://www.kvu.ch/fr/themes/substances-et-produits>
<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Hexane	TWA: 20 ppm (8hr) TWA: 72 mg/m ³ (8hr)	TWA: 72 mg/m ³ TWA: 20 ppm STEL: 60 ppm STEL: 216 mg/m ³	TWA / VME: 20 ppm (8 heures). restrictive limit TWA / VME: 72 mg/m ³ (8 heures). restrictive limit TWA / VME: 1000 mg/m ³ (8 heures). STEL / VLCT: 1500 mg/m ³ .	TWA: 20 ppm 8 uren TWA: 72 mg/m ³ 8 uren	TWA / VLA-ED: 20 ppm (8 horas) TWA / VLA-ED: 72 mg/m ³ (8 horas)

Component	Italy	Germany	Portugal	The Netherlands	Finland
Hexane	TWA: 20 ppm 8 ore. Time Weighted Average TWA: 72 mg/m ³ 8 ore. Time Weighted Average	TWA: 180 mg/m ³ TWA: 50 ppm	TWA: 20 ppm 8 horas TWA: 72 mg/m ³ 8 horas Pele	STEL: 144 mg/m ³ 15 minuten TWA: 72 mg/m ³ 8 uren	TWA: 20 ppm 8 tunteina TWA: 72 mg/m ³ 8 tunteina Iho

Component	Austria	Denmark	Switzerland	Poland	Norway
Hexane	MAK-KZGW: 80 ppm 15 Minuten MAK-KZGW: 288 mg/m ³ 15 Minuten MAK-TMW: 20 ppm 8 Stunden MAK-TMW: 72 mg/m ³ 8 Stunden	TWA: 20 ppm 8 timer TWA: 72 mg/m ³ 8 timer STEL: 40 ppm 15 minutter STEL: 144 mg/m ³ 15 minutter	Haut/Peau STEL: 400 ppm 15 Minuten STEL: 1440 mg/m ³ 15 Minuten TWA: 50 ppm 8 Stunden TWA: 180 mg/m ³ 8 Stunden	TWA: 72 mg/m ³ 8 godzinach	TWA: 20 ppm 8 timer TWA: 72 mg/m ³ 8 timer TWA: 40 ppm 8 timer TWA: 275 mg/m ³ 8 timer STEL: 30 ppm 15 minutter. value calculated STEL: 108 mg/m ³ 15 minutter. value calculated

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
-----------	----------	---------	---------	--------	----------------

SAFETY DATA SHEET

Hexanes, 95% N-hexane

Revision Date 03-May-2024

Hexane	TWA: 20 ppm TWA: 72.0 mg/m ³	kože TWA-GVI: 20 ppm 8 satima. TWA-GVI: 72 mg/m ³ 8 satima.	TWA: 20 ppm 8 hr. TWA: 72 mg/m ³ 8 hr. STEL: 60 ppm 15 min STEL: 216 mg/m ³ 15 min Skin	TWA: 20 ppm TWA: 72 mg/m ³	TWA: 70 mg/m ³ 8 hodinách. Potential for cutaneous absorption Ceiling: 200 mg/m ³
--------	--	--	--	--	---

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Hexane	TWA: 20 ppm 8 tundides. TWA: 72 mg/m ³ 8 tundides.	TWA: 20 ppm 8 hr TWA: 72 mg/m ³ 8 hr	TWA: 20 ppm TWA: 72 mg/m ³	TWA: 72 mg/m ³ 8 óraban. AK lehetséges borön keresztüli felszívódás	TWA: 20 ppm 8 klukkustundum. TWA: 72 mg/m ³ 8 klukkustundum. Ceiling: 40 ppm Ceiling: 144 mg/m ³

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Hexane	TWA: 20 ppm TWA: 72 mg/m ³	TWA: 20 ppm IPRD TWA: 72 mg/m ³ IPRD	TWA: 20 ppm 8 Stunden TWA: 72 mg/m ³ 8 Stunden	TWA: 20 ppm TWA: 72 mg/m ³	TWA: 20 ppm 8 ore TWA: 72 mg/m ³ 8 ore

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Hexane	TWA: 300 mg/m ³ 0780 MAC: 900 mg/m ³	Ceiling: 140 mg/m ³ TWA: 20 mg/m ³ TWA: 72 mg/m ³	TWA: 20 ppm 8 urah TWA: 72 mg/m ³ 8 urah STEL: 576 mg/m ³ 15 minutah STEL: 160 ppm 15 minutah	Binding STEL: 50 ppm 15 minuter Binding STEL: 180 mg/m ³ 15 minuter TLV: 20 ppm 8 timmar. NGV TLV: 72 mg/m ³ 8 timmar. NGV	TWA: 20 ppm 8 saat TWA: 72 mg/m ³ 8 saat

Biological limit values

List source(s):

Component	European Union	United Kingdom	France	Spain	Germany
Hexane			2,5-Hexanedione: 5 mg/g creatinine urine end of shift	2,5-Hexanedione: 0.2 mg/L urine end of workweek	2,5-Hexanedione plus 4,5-Dihydroxy-2-hexano ne (after hydrolysis): 5 mg/L urine (end of shift)

Component	Italy	Finland	Denmark	Bulgaria	Romania
Hexane					2,5-Hexandione: 5 mg/g Creatinine urine end of shift

Component	Gibraltar	Latvia	Slovak Republic	Luxembourg	Turkey
Hexane			2,5-Hexanedione: 5 mg/L urine end of exposure or work shift 4,5-Dihydroxy-2-hexano ne: 5 mg/L urine end of exposure or work shift		

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

SAFETY DATA SHEET

Hexanes, 95% N-hexane

Revision Date 03-May-2024

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Hexane 110-54-3 (≤100)				DNEL = 11mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Hexane 110-54-3 (≤100)				DNEL = 75mg/m ³

Predicted No Effect Concentration (PNEC)

No information available.

8.2. Exposure controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting/equipment. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Wear safety glasses with side shields (or goggles) (European standard - EN 166)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Nitrile rubber	> 480 minutes	0.38 - 0.56 mm	Level 6	As tested under EN374-3 Determination of
Viton (R)	> 480 minutes	0.7 mm	EN 374	Resistance to Permeation by Chemicals
Neoprene gloves	< 180 minutes	0.45 mm		

Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced
Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to EN14387

Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141
When RPE is used a face piece Fit Test should be conducted

SAFETY DATA SHEET

Hexanes, 95% N-hexane

Revision Date 03-May-2024

Environmental exposure controls Prevent product from entering drains. Do not allow material to contaminate ground water system.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance	Colorless	
Odor	Petroleum distillates	
Odor Threshold	No data available	
Melting Point/Range	-95 °C / -139 °F	
Softening Point	No data available	
Boiling Point/Range	69 °C / 156.2 °F	@ 760 mmHg
Flammability (liquid)	Highly flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	Lower 1.1 vol% Upper 7.5 vol%	
Flash Point	-22 °C / -7.6 °F	Method - No information available
Autoignition Temperature	223 °C / 433.4 °F	
Decomposition Temperature	No data available	
pH	Not applicable	
Viscosity	0.31 mPa s at 20 °C	
Water Solubility	Immiscible	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Hexane	4.11	
Vapor Pressure	160 mbar @ 20 °C	
Density / Specific Gravity	0.659	
Bulk Density	Not applicable	Liquid
Vapor Density	2.97	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

Molecular Formula	C6 H14
Molecular Weight	86.18
Explosive Properties	Not explosive Vapors may form explosive mixtures with air

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization	No information available.
Hazardous Reactions	None under normal processing.

10.4. Conditions to avoid

Incompatible products. Heat, flames and sparks. Exposure to light. Keep away from open flames, hot surfaces and sources of ignition.

SAFETY DATA SHEET

Hexanes, 95% N-hexane

Revision Date 03-May-2024

10.5. Incompatible materials

Strong oxidizing agents. Halogens.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral

Based on available data, the classification criteria are not met

Dermal

Based on available data, the classification criteria are not met

Inhalation

Based on available data, the classification criteria are not met

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Hexane	LD50 = 25 g/kg (Rat)	LD50 = 3000 mg/kg (Rabbit)	LC50 = 48000 ppm (Rat) 4 h

(b) skin corrosion/irritation;

Category 2

(c) serious eye damage/irritation;

Based on available data, the classification criteria are not met

(d) respiratory or skin sensitization;

Respiratory

Based on available data, the classification criteria are not met

Skin

Based on available data, the classification criteria are not met

(e) germ cell mutagenicity;

Based on available data, the classification criteria are not met

Mutagenic effects have occurred in experimental animals

(f) carcinogenicity;

Based on available data, the classification criteria are not met

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity;

Reproductive Effects

Category 2

Developmental Effects

Experiments have shown reproductive toxicity effects on laboratory animals.

Teratogenicity

Developmental effects have occurred in experimental animals.

Teratogenic effects have occurred in experimental animals.

(h) STOT-single exposure;

Category 3

Results / Target organs

Central nervous system (CNS).

(i) STOT-repeated exposure;

Category 2

Target Organs

Skin, Respiratory system, Eyes, Central nervous system (CNS), Heart, Blood, Liver, Reproductive System, Peripheral Nervous System (PNS).

(j) aspiration hazard;

Category 1

Other Adverse Effects

Tumorigenic effects have been reported in experimental animals.

SAFETY DATA SHEET

Hexanes, 95% N-hexane

Revision Date 03-May-2024

Symptoms / effects, both acute and delayed Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Hexane	LC50: 2.1 - 2.98 mg/L, 96h flow-through (Pimephales promelas)	EC50: 3.87 mg/L/48h	

12.2. Persistence and degradability

Persistence

Persistence is unlikely, based on information available.

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Hexane	4.11	No data available

12.4. Mobility in soil

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in air.

12.5. Results of PBT and vPvB assessment

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB).

12.6. Endocrine disrupting properties

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance
This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused

Waste is classified as hazardous. Dispose of in accordance with the European Directives

SAFETY DATA SHEET

Hexanes, 95% N-hexane

Revision Date 03-May-2024

Products	on waste and hazardous waste. Dispose of in accordance with local regulations.
Contaminated Packaging	Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.
European Waste Catalogue (EWC)	According to the European Waste Catalog, Waste Codes are not product specific, but application specific.
Other Information	Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not let this chemical enter the environment. Do not empty into drains.
Switzerland - Waste Ordinance	Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600 https://www.fedlex.admin.ch/eli/cc/2015/891/en

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

<u>14.1. UN number</u>	UN1208
<u>14.2. UN proper shipping name</u>	Hexanes
<u>14.3. Transport hazard class(es)</u>	3
<u>14.4. Packing group</u>	II

ADR

<u>14.1. UN number</u>	UN1208
<u>14.2. UN proper shipping name</u>	Hexanes
<u>14.3. Transport hazard class(es)</u>	3
<u>14.4. Packing group</u>	II

IATA

<u>14.1. UN number</u>	UN1208
<u>14.2. UN proper shipping name</u>	Hexanes
<u>14.3. Transport hazard class(es)</u>	3
<u>14.4. Packing group</u>	II

<u>14.5. Environmental hazards</u>	Dangerous for the environment Product is a marine pollutant according to the criteria set by IMDG/IMO
---	--

<u>14.6. Special precautions for user</u>	No special precautions required.
--	----------------------------------

<u>14.7. Maritime transport in bulk according to IMO instruments</u>	Not applicable, packaged goods
---	--------------------------------

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

SAFETY DATA SHEET

Hexanes, 95% N-hexane

Revision Date 03-May-2024

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Hexane	110-54-3	203-777-6	438-390-3	-	X	X	KE-18626	X	X
Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS	
Hexane	110-54-3	X	ACTIVE	X	-	X	X	X	

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Hexane	110-54-3	-	Use restricted. See item 75. (see link for restriction details)	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Hexane	110-54-3	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

Take note of Directive 94/33/EC on the protection of young people at work

Take note of Dir 92/85/EC on the protection of pregnant and breastfeeding women at work

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

See table for values

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Hexane	WGK2	

Component	France - INRS (Tables of occupational diseases)
Hexane	Tableaux des maladies professionnelles (TMP) - RG 59, RG 84

Swiss Regulations

FSUH0403

SAFETY DATA SHEET

Hexanes, 95% N-hexane

Revision Date 03-May-2024

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Hexane 110-54-3 (<=100)	Prohibited and Restricted Substances	Group I	

15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has been conducted by the manufacturer/importer

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H336 - May cause drowsiness or dizziness

H361f - Suspected of damaging fertility

H373 - May cause damage to organs through prolonged or repeated exposure

H411 - Toxic to aquatic life with long lasting effects

H225 - Highly flammable liquid and vapor

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadviser - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

First aid for chemical exposure, including the use of eye wash and safety showers.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

SAFETY DATA SHEET

Hexanes, 95% N-hexane

Revision Date 03-May-2024

Creation Date	26-Oct-2009
Revision Date	03-May-2024
Revision Summary	SDS sections updated.

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.
COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No
1907/2006 .**

**For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2,
Number 3, Chemo (SR 813.11 - Ordinance on Protection against Dangerous Substances and
Preparations).**

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet