

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: **Graphite conductive adhesive, aqueous based**
Cat No. : **42466**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

Thermo Fisher (Kandel) GmbH
Erlenbachweg 2, 76870 Kandel, Germany
Tel: +49 (0) 721 84007 280
Fax: +49 (0) 721 84007 300

Swiss distributor - Fisher Scientific AG
Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
<https://www.fishersci.ch/ch/en/customer-help-support/forms/email-us.html>

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

Poison Centre - Emergency information services

Ireland : National Poisons Information Centre (NPIC) -
01 809 2166 (8am-10pm, 7 days a week)
Malta : +356 2395 2000
Cyprus : +357 2240 5611

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

SAFETY DATA SHEET

Graphite conductive adhesive, aqueous based

Revision Date 30-Nov-2024

Physical hazards

Based on available data, the classification criteria are not met

Health hazards

Serious Eye Damage/Eye Irritation
Specific target organ toxicity - (single exposure)

Category 2 (H319)
Category 3 (H335)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Warning

Hazard Statements

H319 - Causes serious eye irritation
H335 - May cause respiratory irritation

Precautionary Statements

P280 - Wear eye protection/ face protection
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P312 - Call a POISON CENTER or doctor if you feel unwell

2.3. Other hazards

This product does not contain any known or suspected endocrine disruptors
Toxic to terrestrial vertebrates

Section 3: Composition/information on ingredients

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Water	7732-18-5	231-791-2	75.00	-
Graphite	7782-42-5	EEC No. 231-955-3	20	Eye Irrit. 2 (H319) STOT SE 3 (H335)
Carbon black	1333-86-4	215-609-9	3.00	-

SAFETY DATA SHEET

Graphite conductive adhesive, aqueous based

Revision Date 30-Nov-2024

2-Butoxyethanol	111-76-2	EEC No. 203-905-0	2.00	Acute Tox. 4 (H302) Acute Tox. 3 (H331) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319)
-----------------	----------	-------------------	------	---

Component	ECHA (RAC) ATE (Oral)	ECHA (RAC) ATE (Dermal)	ECHA (RAC) ATE (Inhalation)
2-Butoxyethanol	ATE = 1200 mg/kg bw	-	ATE = 3 mg/L (vapour)

ECHA (RAC) - Committee for Risk Assessment - European Chemicals Agency
ATE - Acute Toxicity Estimate; mg/kg bw - milligrams per kilogram of body weight

Full text of Hazard Statements: see section 16

Section 4: First aid measures

4.1. Description of first aid measures

General Advice	If symptoms persist, call a physician.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
Ingestion	Clean mouth with water and drink afterwards plenty of water.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.
Self-Protection of the First Aider	No special precautions required.

4.2. Most important symptoms and effects, both acute and delayed

None reasonably foreseeable.

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically.
---------------------------	------------------------

Section 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media

Carbon dioxide (CO₂). Powder. Water spray. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂).

SAFETY DATA SHEET

Graphite conductive adhesive, aqueous based

Revision Date 30-Nov-2024

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required.

6.2. Environmental precautions

Should not be released into the environment.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

Section 7: Handling and storage

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Avoid ingestion and inhalation. Do not get in eyes, on skin, or on clothing.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Storage Class/LGK 10

Switzerland - Storage of hazardous substances

Storage class - SC 10/12
<https://www.kvu.ch/de/themen/stoffe-und-produkte>
<https://www.kvu.ch/fr/themes/substances-et-produits>
<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

Section 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits

SAFETY DATA SHEET

Graphite conductive adhesive, aqueous based

Revision Date 30-Nov-2024

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Graphite		STEL: 30 mg/m ³ 15 min STEL: 12 mg/m ³ 15 min TWA: 10 mg/m ³ 8 hr TWA: 4 mg/m ³ 8 hr	TWA / VME: 2 mg/m ³ (8 heures).	TWA: 2 mg/m ³ 8 uren	TWA / VLA-ED: 2 mg/m ³ (8 horas)
Carbon black		STEL: 7 mg/m ³ 15 min TWA: 3.5 mg/m ³ 8 hr	TWA / VME: 3.5 mg/m ³ (8 heures).	TWA: 3 mg/m ³ 8 uren	TWA / VLA-ED: 3.5 mg/m ³ (8 horas)
2-Butoxyethanol	TWA: 20 ppm (8h) TWA: 98 mg/m ³ (8h) STEL: 50 ppm (15min) STEL: 246 mg/m ³ (15min) Skin	STEL: 50 ppm 15 min STEL: 246 mg/m ³ 15 min TWA: 25 ppm 8 hr TWA: 123 mg/m ³ 8 hr Skin	TWA / VME: 10 ppm (8 heures). restrictive limit TWA / VME: 49 mg/m ³ (8 heures). restrictive limit STEL / VLCT: 50 ppm. restrictive limit STEL / VLCT: 246 mg/m ³ . restrictive limit Peau	TWA: 20 ppm 8 uren TWA: 98 mg/m ³ 8 uren STEL: 50 ppm 15 minuten STEL: 246 mg/m ³ 15 minuten Huid	STEL / VLA-EC: 50 ppm (15 minutos). STEL / VLA-EC: 245 mg/m ³ (15 minutos). TWA / VLA-ED: 20 ppm (8 horas) TWA / VLA-ED: 98 mg/m ³ (8 horas) Piel

Component	Italy	Germany	Portugal	The Netherlands	Finland
Graphite		TWA: 1.25 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 10 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 0.3 mg/m ³ (8 Stunden). MAK multiplied by the material density;except ultrafine particles TWA: 4 mg/m ³ (8 Stunden). MAK Höhepunkt: 2.4 mg/m ³	TWA: 2 mg/m ³ 8 horas		TWA: 2 mg/m ³ 8 tunteina
Carbon black			TWA: 3 mg/m ³ 8 horas		TWA: 3.5 mg/m ³ 8 tunteina STEL: 7 mg/m ³ 15 minuutteina
2-Butoxyethanol	TWA: 20 ppm 8 ore. Time Weighted Average TWA: 98 mg/m ³ 8 ore. Time Weighted Average STEL: 50 ppm 15 minuti. Short-term STEL: 246 mg/m ³ 15 minuti. Short-term Pelle	TWA: 10 ppm (8 Stunden). AGW - exposure factor 2 TWA: 49 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 10 ppm (8 Stunden). MAK applies for the sum of the concentrations of 2-Butoxyethanol and its Acetate in air TWA: 49 mg/m ³ (8 Stunden). MAK applies for the sum of the concentrations of 2-Butoxyethanol and its Acetate in air Höhepunkt: 20 ppm Höhepunkt: 98 mg/m ³ Haut	STEL: 50 ppm 15 minutos STEL: 246 mg/m ³ 15 minutos TWA: 20 ppm 8 horas TWA: 98 mg/m ³ 8 horas Pele	huid STEL: 50 ppm 15 minuten STEL: 246 mg/m ³ 15 minuten TWA: 20.4 ppm 8 uren TWA: 100 mg/m ³ 8 uren	TWA: 20 ppm 8 tunteina TWA: 98 mg/m ³ 8 tunteina STEL: 50 ppm 15 minuutteina STEL: 250 mg/m ³ 15 minuutteina Iho

Component	Austria	Denmark	Switzerland	Poland	Norway
-----------	---------	---------	-------------	--------	--------

SAFETY DATA SHEET

Graphite conductive adhesive, aqueous based

Revision Date 30-Nov-2024

Graphite	MAK-KZGW: 10 mg/m ³ 15 Minuten MAK-TMW: 5 mg/m ³ 8 Stunden	TWA: 2.5 mg/m ³ 8 timer STEL: 5 mg/m ³ 15 minutter	TWA: 3 mg/m ³ 8 Stunden TWA: 10 mg/m ³ 8 Stunden	TWA: 4.0 mg/m ³ 8 godzinach TWA: 1.0 mg/m ³ 8 godzinach TWA: 6 mg/m ³ 8 godzinach	TWA: 5 mg/m ³ 8 timer TWA: 2 mg/m ³ 8 timer TWA: 10 mg/m ³ 8 timer TWA: 4 mg/m ³ 8 timer STEL: 10 mg/m ³ 15 minutter. natural;value calculated total dust STEL: 4 mg/m ³ 15 minutter. natural;value calculated respirable dust STEL: 20 mg/m ³ 15 minutter. synthetic;value calculated total dust STEL: 8 mg/m ³ 15 minutter. synthetic;value calculated respirable dust
Carbon black		TWA: 3.5 mg/m ³ 8 timer STEL: 7 mg/m ³ 15 minutter		TWA: 4 mg/m ³ 8 godzinach	TWA: 3.5 mg/m ³ 8 timer STEL: 7 mg/m ³ 15 minutter. value calculated
2-Butoxyethanol	Haut MAK-KZGW: 40 ppm 15 Minuten MAK-KZGW: 200 mg/m ³ 15 Minuten MAK-TMW: 20 ppm 8 Stunden MAK-TMW: 98 mg/m ³ 8 Stunden	TWA: 20 ppm 8 timer TWA: 98 mg/m ³ 8 timer STEL: 246 mg/m ³ 15 minutter STEL: 50 ppm 15 minutter Hud	Haut/Peau STEL: 20 ppm 15 Minuten STEL: 98 mg/m ³ 15 Minuten TWA: 10 ppm 8 Stunden TWA: 49 mg/m ³ 8 Stunden	STEL: 200 mg/m ³ 15 minutach TWA: 98 mg/m ³ 8 godzinach	TWA: 10 ppm 8 timer TWA: 50 mg/m ³ 8 timer STEL: 20 ppm 15 minutter. value calculated STEL: 75 mg/m ³ 15 minutter. value calculated Hud

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Graphite	TWA: 5.0 mg/m ³	TWA-GVI: 4 mg/m ³ 8 satima. respirable dust TWA-GVI: 10 mg/m ³ 8 satima. total dust, inhalable particles	TWA: 2 mg/m ³ 8 hr. all forms except fibres; respirable fraction STEL: 6 mg/m ³ 15 min		TWA: 2.0 mg/m ³ 8 hodinách. respirable fraction, <=5% Silica, Cristobalite, Tridymite and .gamma.-Aluminium oxide dust
Carbon black		TWA-GVI: 3.5 mg/m ³ 8 satima. STEL-KGVI: 7 mg/m ³ 15 minutama.	TWA: 3 mg/m ³ 8 hr. inhalable fraction STEL: 15 mg/m ³ 15 min		TWA: 2.0 mg/m ³ 8 hodinách. dust
2-Butoxyethanol	TWA: 20 ppm TWA: 98 mg/m ³ STEL : 50 ppm STEL : 246 mg/m ³ Skin notation	kože TWA-GVI: 20 ppm 8 satima. TWA-GVI: 98 mg/m ³ 8 satima. STEL-KGVI: 50 ppm 15 minutama. STEL-KGVI: 246 mg/m ³ 15 minutama.	TWA: 20 ppm 8 hr. TWA: 98 mg/m ³ 8 hr. STEL: 50 ppm 15 min STEL: 246 mg/m ³ 15 min Skin	Skin-potential for cutaneous absorption STEL: 50 ppm STEL: 246 mg/m ³ TWA: 20 ppm TWA: 98 mg/m ³	TWA: 100 mg/m ³ 8 hodinách. Potential for cutaneous absorption Ceiling: 200 mg/m ³ biological test

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Graphite	TWA: 5 mg/m ³ 8 tundides. total dust		TWA: 10 mg/m ³ TWA: 5 mg/m ³	TWA: 5 mg/m ³ 8 óraban. AK TWA: 2 mg/m ³ 8 óraban. AK	TWA: 5 mg/m ³ 8 klukkustundum. total dust TWA: 2.5 mg/m ³ 8 klukkustundum. inhalable fraction Ceiling: 10 mg/m ³ total dust Ceiling: 5 mg/m ³ inhalable fraction
Carbon black	TWA: 3 mg/m ³ 8 tundides.		STEL: 7 mg/m ³ TWA: 3.5 mg/m ³	TWA: 3 mg/m ³ 8 óraban. AK	TWA: 3.5 mg/m ³ 8 klukkustundum. Ceiling: 7 mg/m ³
2-Butoxyethanol	Nahk TWA: 20 ppm 8	Skin notation TWA: 20 ppm 8 hr	skin - potential for cutaneous absorption	STEL: 50 ppm 15 percekben. CK	STEL: 50 ppm see footnote 14 for

SAFETY DATA SHEET

Graphite conductive adhesive, aqueous based

Revision Date 30-Nov-2024

	tundides. TWA: 98 mg/m ³ 8 tundides. STEL: 50 ppm 15 minutites. STEL: 246 mg/m ³ 15 minutites.	TWA: 98 mg/m ³ 8 hr STEL: 50 ppm 15 min STEL: 246 mg/m ³ 15 min	TWA: 25 ppm TWA: 120 mg/m ³	STEL: 246 mg/m ³ 15 percekben. CK TWA: 20 ppm 8 órában. AK TWA: 98 mg/m ³ 8 órában. AK lehetséges borön keresztüli felszívódás	calculations of mixture of glycol ethers and other solvents STEL: 246 mg/m ³ see footnote 14 for calculations of mixture of glycol ethers and other solvents TWA: 20 ppm 8 klukkustundum. see footnote 14 for calculations of mixture of glycol ethers and other solvents TWA: 100 mg/m ³ 8 klukkustundum. see footnote 14 for calculations of mixture of glycol ethers and other solvents TWA: 25 ppm 8 klukkustundum. regulated under Butyl cellosolve; see footnote 14 for calculations of mixture of glycol ethers and other solvents Skin notation
--	--	--	---	---	--

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Graphite	TWA: 2 mg/m ³	TWA: 5 mg/m ³ dust IPRD			TWA: 2 mg/m ³ 8 ore
2-Butoxyethanol	skin - potential for cutaneous exposure STEL: 50 ppm STEL: 246 mg/m ³ TWA: 20 ppm TWA: 98 mg/m ³	TWA: 10 ppm IPRD TWA: 50 mg/m ³ IPRD Oda STEL: 20 ppm STEL: 100 mg/m ³	Possibility of significant uptake through the skin TWA: 20 ppm 8 Stunden TWA: 98 mg/m ³ 8 Stunden STEL: 50 ppm 15 Minuten STEL: 246 mg/m ³ 15 Minuten	possibility of significant uptake through the skin TWA: 20 ppm TWA: 98 mg/m ³ STEL: 50 ppm 15 minuti STEL: 246 mg/m ³ 15 minuti	Skin notation TWA: 20 ppm 8 ore TWA: 98 mg/m ³ 8 ore STEL: 50 ppm 15 minute STEL: 246 mg/m ³ 15 minute

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Graphite		TWA: 10 mg/m ³ total aerosol TWA: 2 mg/m ³ respirable fraction			
Carbon black		TWA: 2 mg/m ³ respirable fraction, 5% or less fibrogenic component TWA: 10 mg/m ³ respirable fraction, greater than 5% fibrogenic component TWA: 10 mg/m ³ total aerosol		TLV: 3 mg/m ³ 8 timmar. NGV	
2-Butoxyethanol	MAC: 5 mg/m ³	Ceiling: 246 mg/m ³ Potential for cutaneous absorption TWA: 20 ppm TWA: 98 mg/m ³	TWA: 20 ppm 8 urah TWA: 98 mg/m ³ 8 urah Koža STEL: 50 ppm 15 minutah STEL: 246 mg/m ³ 15 minutah	Binding STEL: 50 ppm 15 minuter Binding STEL: 246 mg/m ³ 15 minuter TLV: 10 ppm 8 timmar. NGV TLV: 50 mg/m ³ 8 timmar. NGV Hud	Deri TWA: 20 ppm 8 saat TWA: 98 mg/m ³ 8 saat STEL: 50 ppm 15 dakika STEL: 246 mg/m ³ 15 dakika

Biological limit values

SAFETY DATA SHEET

Graphite conductive adhesive, aqueous based

Revision Date 30-Nov-2024

List source(s): **UK** - Biological Monitoring Guidance Values provided by the UK's Health and Safety Executive (HSE) Control of Substances Hazardous to Health Regulations (COSHH) 2002 (as amended) and EH40/2005.

Component	European Union	United Kingdom	France	Spain	Germany
2-Butoxyethanol		Butoxyacetic acid: 240 mmol/mol creatinine urine post shift		Butoxyacetic acid (with hydrolysis): 200 mg/g Creatinine urine end of shift	Butoxyacetic acid (after hydrolysis): 150 mg/g Creatinine urine (for long-term exposures: at the end of the shift after several shifts) Butoxyacetic acid (after hydrolysis): 150 mg/g Creatinine urine (end of shift)

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
2-Butoxyethanol 111-76-2 (2.00)		DNEL = 89mg/kg bw/day		DNEL = 125mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Graphite 7782-42-5 (20)			DNEL = 1.2mg/m ³	DNEL = 1.2mg/m ³
Carbon black 1333-86-4 (3.00)			DNEL = 0.5mg/m ³	DNEL = 1mg/m ³
2-Butoxyethanol 111-76-2 (2.00)	DNEL = 246mg/m ³	DNEL = 1091mg/m ³		DNEL = 98mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
2-Butoxyethanol 111-76-2 (2.00)	PNEC = 8.8mg/L	PNEC = 34.6mg/kg sediment dw	PNEC = 26.4mg/L	PNEC = 463mg/L	PNEC = 2.33mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
2-Butoxyethanol 111-76-2 (2.00)	PNEC = 0.88mg/L	PNEC = 3.46mg/kg sediment dw		PNEC = 0.02g/kg food	

8.2. Exposure controls

Engineering Measures

None under normal use conditions. Ensure that eyewash stations and safety showers are close to the workstation location.

SAFETY DATA SHEET

Graphite conductive adhesive, aqueous based

Revision Date 30-Nov-2024

Personal protective equipment

Eye Protection Goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Nitrile rubber	See manufacturers	-	EN 374	(minimum requirement)
Neoprene	recommendations			
Natural rubber				
PVC				

Skin and body protection Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection No protective equipment is needed under normal use conditions.

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced
Recommended Filter type: Particle filter

Small scale/Laboratory use Maintain adequate ventilation
Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141

Environmental exposure controls No information available.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance	Black	
Odor	sweet	
Odor Threshold	No data available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	100 °C / 212 °F	
Flammability (liquid)	No data available	
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Flash Point	No information available	Method - No information available
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
pH	Not applicable	
Viscosity	No data available	
Water Solubility	Miscible	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
2-Butoxyethanol	0.81	
Vapor Pressure	<=1100 hPa @ 50 °C	
Density / Specific Gravity	1.16 g/cm3	@ 20 °C
Bulk Density	Not applicable	Liquid

SAFETY DATA SHEET

Graphite conductive adhesive, aqueous based

Revision Date 30-Nov-2024

Vapor Density No data available (Air = 1.0)
Particle characteristics Not applicable (liquid)

9.2. Other information

Section 10: Stability and reactivity

10.1. Reactivity
None known, based on information available

10.2. Chemical stability
Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization No information available.
Hazardous Reactions None under normal processing.

10.4. Conditions to avoid
Incompatible products. Excess heat.

10.5. Incompatible materials
Oxidizing agent.

10.6. Hazardous decomposition products
Carbon monoxide (CO). Carbon dioxide (CO₂).

Section 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;
Oral Based on available data, the classification criteria are not met
Dermal Based on available data, the classification criteria are not met
Inhalation Based on available data, the classification criteria are not met

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Water	-	-	-
Graphite	-	-	LC50 > 2000 mg/m ³ (Rat) 4 h
Carbon black	LD50 > 15400 mg/kg (Rat)	LD50 > 3 g/kg (Rabbit)	LC50 > 4.6 mg/m ³ (Rat) 4 h
2-Butoxyethanol	1746 mg/kg (Rat)	LD50 > 2000 mg/kg (Guinea pig) OCED 402	LC50 = 486 ppm (Rat) 4 h LC50 = 450 ppm (Rat) 4 h

Component	ECHA (RAC) ATE (Oral)	ECHA (RAC) ATE (Dermal)	ECHA (RAC) ATE (Inhalation)
2-Butoxyethanol	ATE = 1200 mg/kg bw	-	ATE = 3 mg/L (vapour)

ECHA (RAC) - Committee for Risk Assessment - European CHemicals Agency
ATE - Acute Toxicity Estimate; mg/kg bw - milligrams per kilogram of body weight

(b) skin corrosion/irritation; No data available

SAFETY DATA SHEET

Graphite conductive adhesive, aqueous based

Revision Date 30-Nov-2024

(c) serious eye damage/irritation; Category 2

(d) respiratory or skin sensitization;

Respiratory No data available
Skin No data available

Component	Test method	Test species	Study result
2-Butoxyethanol 111-76-2 (2.00)	Guinea Pig Maximisation Test (GPMT)	guinea pig	- non-sensitising

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; No data available

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Carbon black			Cat. 3B	Group 2B

(g) reproductive toxicity; No data available

(h) STOT-single exposure; Category 3

Results / Target organs Respiratory system.

(i) STOT-repeated exposure; No data available

Target Organs None known.

(j) aspiration hazard; No data available

Symptoms / effects, both acute and delayed No information available.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity effects

Component	Freshwater Fish	Water Flea	Freshwater Algae
Graphite	LC50: > 100 mg/L, 96h semi-static (Danio rerio)		
Carbon black		EC50: > 5600 mg/L, 24h (Daphnia magna)	
2-Butoxyethanol	1490 mg/L LC50 96 h 2950 mg/L LC50 96 h	1550 mg/l EC50 48 hr >1000 mg/L EC50 48 h 1698 - 1940 mg/L EC50 24 h	1840 mg/l EC50 72 hr

SAFETY DATA SHEET

Graphite conductive adhesive, aqueous based

Revision Date 30-Nov-2024

12.2. Persistence and degradability

Persistence Miscible with water, Persistence is unlikely, based on information available.

Component	Degradability
2-Butoxyethanol 111-76-2 (2.00)	90% (28d) OECD 301B

12.3. Bioaccumulative potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
2-Butoxyethanol	0.81	No data available

12.4. Mobility in soil

The product is water soluble, and may spread in water systems Will likely be mobile in the environment due to its water solubility. Highly mobile in soils

12.5. Results of PBT and vPvB assessment

No data available for assessment.

12.6. Endocrine disrupting properties

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance

This product does not contain any known or suspected substance

Section 13: Disposal considerations

13.1. Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point.

European Waste Catalogue (EWC)

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information

Waste codes should be assigned by the user based on the application for which the product was used. Do not empty into drains.

Switzerland - Waste Ordinance

Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600
<https://www.fedlex.admin.ch/eli/cc/2015/891/en>

Section 14: Transport information

IMDG/IMO

Not regulated

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

SAFETY DATA SHEET

Graphite conductive adhesive, aqueous based

Revision Date 30-Nov-2024

ADR Not regulated

- 14.1. UN number**
14.2. UN proper shipping name
14.3. Transport hazard class(es)
14.4. Packing group

IATA Not regulated

- 14.1. UN number**
14.2. UN proper shipping name
14.3. Transport hazard class(es)
14.4. Packing group

- 14.5. Environmental hazards** No hazards identified
14.6. Special precautions for user No special precautions required.
14.7. Maritime transport in bulk according to IMO instruments Not applicable, packaged goods

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

China, X = listed, Australia, U.S.A. (TSCA), Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Australia (AICS), Korea (KECL), China (IECSC), Japan (ENCS), Philippines (PICCS), Taiwan (TCSI), Japan (ISHL), New Zealand (NZIoC), Japan (ISHL). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Water	7732-18-5	231-791-2	-	-	X	X	KE-35400	X	-
Graphite	7782-42-5	231-955-3	-	-	X	X	KE-18101	-	-
Carbon black	1333-86-4	215-609-9	435-640-3	-	X	X	X	X	X
2-Butoxyethanol	111-76-2	203-905-0	-	-	X	X	KE-04134	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Water	7732-18-5	X	ACTIVE	X	-	X	X	X
Graphite	7782-42-5	X	ACTIVE	X	-	X	X	X
Carbon black	1333-86-4	X	ACTIVE	X	-	X	X	X
2-Butoxyethanol	111-76-2	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Water	7732-18-5	-	-	-
Graphite	7782-42-5	-	-	-
Carbon black	1333-86-4	-	Use restricted. See entry 75. (see link for restriction details)	-

SAFETY DATA SHEET

Graphite conductive adhesive, aqueous based

Revision Date 30-Nov-2024

2-Butoxyethanol	111-76-2	-	Use restricted. See entry 75. (see link for restriction details)	-
-----------------	----------	---	---	---

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Water	7732-18-5	Not applicable	Not applicable
Graphite	7782-42-5	Not applicable	Not applicable
Carbon black	1333-86-4	Not applicable	Not applicable
2-Butoxyethanol	111-76-2	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 3 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Graphite	nwg	
Carbon black	nwg	
2-Butoxyethanol	WGK1	

Component	France - INRS (Tables of occupational diseases)
Graphite	Tableaux des maladies professionnelles (TMP) - RG 16 Tableaux des maladies professionnelles (TMP) - RG 25
Carbon black	Tableaux des maladies professionnelles (TMP) - RG 16,RG 16bis
2-Butoxyethanol	Tableaux des maladies professionnelles (TMP) - RG 84

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
2-Butoxyethanol 111-76-2 (2.00)		Group I	

SAFETY DATA SHEET

Graphite conductive adhesive, aqueous based

Revision Date 30-Nov-2024

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

Section 16: Other information

Full text of H-Statements referred to under sections 2 and 3

H319 - Causes serious eye irritation

H302 - Harmful if swallowed

H315 - Causes skin irritation

H331 - Toxic if inhaled

H335 - May cause respiratory irritation

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data

Health Hazards Calculation method

Environmental hazards Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Prepared By Health, Safety and Environmental Department

Revision Date 30-Nov-2024

Revision Summary SDS sections updated.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006. COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No 1907/2006 .

For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2, Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and

SAFETY DATA SHEET

Graphite conductive adhesive, aqueous based

Revision Date 30-Nov-2024

Preparations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet