

Australian statement of hazardous nature : Classified as hazardous according to criteria of Safe Work Australia

Section 1 - Identification

Product Name Lithium aluminium hydride, 4.0M solution in diethyl ether

Synonyms Lithiumalanate; LAH; Lithium tetrahydridoaluminate

Product Code	199510000; 199511000; 199518000
Address	ThermoFisher Scientific Australia Pty Ltd 5 Caribbean Drive, Scoresby VICTORIA 3179, Australia
Emergency Tel.	CHEMTREC® 03 9757 4559 or +613 9757 4559
Telephone / Fax Numbers	Tel: 1300 735 292 Fax: 1800 067 639
E-mail address	ANZinfo@thermofisher.com

Recommended Use Laboratory chemicals.

Uses advised against Verify requirements related to using, handling and storing these substances. This product contains one or more substance(s) on the Illicit Drug Precursors/Reagents list. This product does not contain any substance(s) subject to Prohibition, Authorization or Restriction. This product does not contain any substance(s) listed on the voluntary National Code of Practice for Chemicals of Security Concern.

Section 2 - Hazard(s) Identification

Classification under Safe Work Australia

Classified as hazardous according to criteria of Safe Work Australia

Physical hazards

Flammable liquids	Category 1
Substances/mixtures which, in contact with water, emit flammable gases	Category 1

Health hazards

Acute Oral Toxicity	Category 4
Skin Corrosion/Irritation	Category 1 A
Serious Eye Damage/Eye Irritation	Category 1
Specific target organ toxicity - (single exposure)	Category 3

Environmental hazards

No hazards identified

Label Elements



Flame



Exclamation Mark



Corrosion

Signal Word

Danger

Hazard Statements

H224 - Extremely flammable liquid and vapor
H260 - In contact with water releases flammable gases which may ignite spontaneously
H302 - Harmful if swallowed
H336 - May cause drowsiness or dizziness
H314 - Causes severe skin burns and eye damage
AUH019 - May form explosive peroxides
AUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary Statements

P231 + P232 - Handle and store contents under inert gas. Protect from moisture
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P223 - Do not allow contact with water
P240 - Ground and bond container and receiving equipment
P233 - Keep container tightly closed
P242 - Use non-sparking tools
P243 - Take action to prevent static discharges
P264 - Wash face, hands and any exposed skin thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P330 - Rinse mouth
P363 - Wash contaminated clothing before reuse
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a POISON CENTER or doctor
P331 - Do NOT induce vomiting
P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish
P302 + P335 + P334 - IF ON SKIN: Brush off loose particles from skin. Immerse in cool water
P402 + P404 - Store in a dry place. Store in a closed container
P501 - Dispose of contents/ container to an approved waste disposal plant

Other information

Toxic to terrestrial vertebrates

Section 3 - Composition and Information on Ingredients

Component	CAS No	Weight %
Lithium aluminum hydride	16853-85-3	20-25
Ethyl ether	60-29-7	75-80

Section 4 - First Aid Measures

Inhalation	Remove to fresh air. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required. If not breathing, give artificial respiration.
Ingestion	Do NOT induce vomiting. Call a physician or poison control center immediately.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.
First Aid Facilities	Eyewash, safety shower and washroom.
Most important symptoms and effects	Difficulty in breathing. Causes burns by all exposure routes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting; Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation
Notes to Physician	Treat symptomatically. Symptoms may be delayed.

Section 5 - Fire Fighting Measures

Suitable Extinguishing Media

Dry chemical. Dry chemical, soda ash, lime or sand. approved class D extinguishers. clay. sodium carbonate. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Water. Carbon dioxide (CO₂). Foam.

Hazardous Decomposition Products

Carbon monoxide (CO), Carbon dioxide (CO₂), Hydrogen.

Specific Hazards Arising from the Chemical

Contact with water liberates toxic gas. Water reactive. Produce flammable gases on contact with water. Extremely flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Special protective equipment and precautions for fire fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6 - Accidental Release Measures

Emergency procedures

Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions

Should not be released into the environment.

Methods for Containment and Clean Up

Clean-up methods - small spillage

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Clean-up methods - large spillage

Typically only supplied in small quantities as packaged goods.

If extremely toxic or used in larger quantities ensure a spillage action plan is in place. Evacuate area. Control the source and/or contain the spill if safe and able to do so. Use temporary diking, sand bags, dry sand, earth or proprietary booms/absorbent pads if available. Obtain advice on containment, neutralisation and clean-up from local emergency responders.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

Section 7 - Handling and Storage

Precautions for Safe Handling

Wear personal protective equipment/face protection. Do not breathe mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Handle product only in closed system or provide appropriate exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Use only non-sparking tools. If peroxide formation is suspected, do not open or move container. Keep away from open flames, hot surfaces and sources of ignition. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Conditions for Safe Storage, Including any Incompatibilities

Keep in a dry, cool and well-ventilated place. Keep container tightly closed. Keep away from heat, sparks and flame. Protect from direct sunlight. Keep from any possible contact with water. Flammables area. Keep under nitrogen. Keep containers tightly closed in a dry, cool and well-ventilated place. Corrosives area. Containers should be dated when opened and tested periodically for the presence of peroxides. Should crystals form in a peroxidizable liquid, peroxidation may have occurred and the product should be considered extremely dangerous. In this instance, the container should only be opened remotely by professionals.

AS/NZS 2243.10:2004, Safety in laboratories - Storage of chemicals

AS 1940-2004 - The storage and handling of flammable and combustible liquids

Section 8 - Exposure Controls and Personal Protection

Exposure limits

AUS - Exposure Standards for Atmospheric Contaminants in the Occupational Environment - Guidance Note on the Interpretation of Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:3008(1995)]

Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)] updated in August, 2005. Safe Work Australia **ACGIH** - Threshold Limit Values - Ceiling (TLV-C) guidelines by the American Conference of Governmental Industrial Hygienists (ACGIH) for controlling worker exposure to airborne chemical concentrations in the workplace. **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **DE** - MAK and BAT values of Hazardous Chemical Compounds in the Work Area. Published by German Research Foundation on July 1, 2011

Component	Australia	New Zealand WEL	ACGIH TLV	The United Kingdom	Germany
Lithium aluminium hydride					TWA: 0.2 mg/m ³ (8 Stunden). MAK inorganic compounds, except Lithium and strong irritant Lithium compounds such as Lithium amide, Lithium hydride, Lithium hydroxide, Lithium nitride, Lithium oxide, Lithium tetrahydroaluminate, Lithium tetrahydroborate Höhepunkt: 0.2 mg/m ³
Ethyl ether	STEL: 500 ppm STEL: 1520 mg/m ³ TWA: 400 ppm TWA: 1210 mg/m ³	TWA: 400 ppm TWA: 1210 mg/m ³ STEL: 500 ppm STEL: 1520 mg/m ³	TWA: 400 ppm STEL: 500 ppm	STEL: 200 ppm 15 min STEL: 620 mg/m ³ 15 min TWA: 100 ppm 8 hr TWA: 310 mg/m ³ 8 hr	TWA: 400 ppm (8 Stunden). AGW - exposure factor 1 TWA: 1200 mg/m ³ (8 Stunden). AGW -

					exposure factor 1 TWA: 400 ppm (8 Stunden). MAK TWA: 1200 mg/m ³ (8 Stunden). MAK Höhepunkt: 400 ppm Höhepunkt: 1200 mg/m ³
--	--	--	--	--	---

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Exposure Controls

Engineering Measures

Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles (Australian/New Zealand Standard AS/NZS 1337 - Eye protectors for Industrial applications)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	AUS/NZ Standard	Glove comments
Nitrile rubber Viton (R)	See manufacturers recommendations	-	AS/NZS 2161	(minimum requirement)

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves.

(Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure

Respiratory Protection

Use an AS/NZS 1716 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained in line with AS/NZS 1715 on the use and maintenance of respiratory protective devices

Recommended Filter type:

low boiling organic solvent Type AX Brown conforming to EN371 or Organic gases and vapours filter Type A Brown conforming to EN14387 (or AUS/NZ equivalent)

Recommended half mask:-

Valve filtering: EN405 or Half mask: EN140 plus filter, EN 141 (or AUS/NZ equivalent)
When RPE is used a face piece Fit Test should be conducted

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

Environmental exposure controls

No information available.

Section 9 - Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance

Colorless

Physical State

Liquid

Odor

Petroleum distillates

Odor Threshold

No data available

pH	7	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flash Point	-17 °C / 1.4 °F	Method - No information available
Evaporation Rate	No data available	
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Vapor Pressure	No data available	
Vapor Density	No data available	(Air = 1.0)
Specific Gravity / Density	0.76	
Bulk Density	Not applicable	Liquid
Water Solubility	vigorous reaction	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Ethyl ether	0.82	
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
Viscosity	No data available	
Explosive Properties		Vapors may form explosive mixtures with air
Oxidizing Properties	No information available	
Other information		
Molecular Formula	Al H4 Li	
Molecular Weight	37.95	

Section 10 - Stability and Reactivity

Reactivity	Yes
Stability	Stable. Decomposes in contact with water. Light sensitive. Moisture sensitive. Air sensitive.
Conditions to Avoid	Keep away from open flames, hot surfaces and sources of ignition, Excess heat, Exposure to air, Exposure to light, Incompatible products, Exposure to moist air or water.
Incompatible Materials	Acids, Water, Alcohols, Carbon dioxide (CO ₂), Oxidizing agent.
Hazardous Decomposition Products	Carbon monoxide (CO). Carbon dioxide (CO ₂). Hydrogen.
Hazardous Polymerization	No information available.

Section 11 - Toxicological Information

Information on Toxicological Effects

Product Information

(a) acute toxicity;

Oral	Category 4
Dermal	Based on available data, the classification criteria are not met
Inhalation	Based on available data, the classification criteria are not met

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethyl ether	1215 mg/kg (Rat)	20 mL/kg (Rabbit)	32000 ppm (Rat) 4 h

(b) skin corrosion/irritation;	Category 1 A
(c) serious eye damage/irritation;	Category 1
(d) respiratory or skin sensitization;	
Respiratory	No data available
Skin	No data available
(e) germ cell mutagenicity;	No data available
(f) carcinogenicity;	No data available There are no known carcinogenic chemicals in this product
(g) reproductive toxicity;	No data available
(h) STOT-single exposure;	Category 3
Results / Target organs	Central nervous system (CNS)
(i) STOT-repeated exposure;	No data available
Target Organs	No information available.
(j) aspiration hazard;	No data available
Other Adverse Effects	The toxicological properties have not been fully investigated.
Symptoms / effects, both acute and delayed	Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation

Section 12 - Ecological Information

Ecotoxicity effects

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Ethyl ether	LC50: > 10000 mg/L, 96h static (Lepomis macrochirus) LC50: = 2560 mg/L, 96h flow-through (Pimephales promelas)	EC50 = 165 mg/L/24h		EC50 = 5600 mg/L 15 min

Persistence and Degradability

Persistence	Soluble in water, Persistence is unlikely, based on information available.
Bioaccumulative Potential	Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Ethyl ether	0.82	No data available

Mobility	The product is water soluble, and may spread in water systems. : Will likely be mobile in the environment due to its water solubility Highly mobile in soils
Endocrine Disruptor Information	This product does not contain any known or suspected endocrine disruptors
Persistent Organic Pollutant	This product does not contain any known or suspected substance
Ozone Depletion Potential	This product does not contain any known or suspected substance

Section 13 - Disposal Considerations

Waste from Residues/Unused Products

Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with all federal, E.P.A., state and local regulations. Assure conformity with all applicable regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

Other Information

Chemical wastes should be disposed through a licensed commercial waste collection service. Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms.

Section 14 - Transport Information

IMDG/IMO

UN-No UN1411
Proper Shipping Name LITHIUM ALUMINIUM HYDRIDE, ETHEREAL
Hazard Class 4.3
Subsidiary Hazard Class 3
Packing Group I

ADG

UN-No UN1411
Proper Shipping Name LITHIUM ALUMINIUM HYDRIDE, ETHEREAL
Hazard Class 4.3
Subsidiary Hazard Class 3
Packing Group I

Component	Hazchem Code
Lithium aluminum hydride	4W
16853-85-3 (20-25)	4WE
Ethyl ether	3YE
60-29-7 (75-80)	

IATA

UN-No UN1411
Proper Shipping Name LITHIUM ALUMINIUM HYDRIDE, ETHEREAL
Hazard Class 4.3
Subsidiary Hazard Class 3
Packing Group I

Environmental hazards

No hazards identified

Special Precautions

No special precautions required

Additional information

None known

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National Regulations**Australia**

See section 8 for national exposure control parameters.

Standard for the Uniform Scheduling of Medicines and Poisons

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons.

Component	Standard for the Uniform Scheduling of Medicines and Poisons
Ethyl ether - 60-29-7	Schedule 2 listed Schedule 4 listed - for use in anaesthesia Schedule 5 listed - in preparations for use in internal combustion engines Schedule 6 listed - except when included in Schedule 2, 4 or 5, or in preparations containing <=10% of Ether

Australian Industrial Chemicals Introduction Scheme (AICIS)

Component	Australian Industrial Chemicals Introduction Scheme (AICIS)	Additional information
Lithium aluminum hydride - 16853-85-3	Present	-
Ethyl ether - 60-29-7	Present	-

Australian - Illicit Drug Precursors/Reagents Substance List

Verify requirements related to using, handling and storing these substances. This product contains one or more substance(s) on the Illicit Drug Precursors/Reagents list.

Chemicals of Security Concern

This product does not contain any substance(s) listed on the voluntary National Code of Practice for Chemicals of Security Concern

Component	Australian - Illicit Drug Precursors/Reagents Substance List	Chemicals of Security Concern
Lithium aluminum hydride - 16853-85-3	Category 1	
Ethyl ether - 60-29-7	Category 3	

Legend

Category 1 - Chemicals that require an End User Declaration with each purchase and may only be sold to 'account customers' or customers that are prepared to open an account. Supply of these chemicals to End Users or Distributors must be delayed for a period of not less than 24 hours
Category 3 - Chemicals and apparatus that may be used in the illicit production of drugs. Purchases from this list should alert companies or organizations to seek further indicators of any suspicious orders or enquiries. No official reporting is required for items on this list unless considered warranted

National pollutant inventory

Not applicable

Prohibition or notification/licensing requirements

Shown below are details of specific prohibition/notifications or licencing requirements when they apply.

This product does not contain any substance(s) subject to Prohibition, Authorization or Restriction.

International Inventories

Component	AICS	NZIoC	EINECS	ELINCS	TSCA	DSL	NDSL	PICCS	ENCS	ISHL	IECSC	KECL
Lithium aluminum hydride	X	X	240-877-9	-	X	-	X	X	X	X	X	KE-00990
Ethyl ether	X	X	200-467-2	-	X	X	-	X	X	X	X	KE-27690

Legend: X - Listed. '-' - Not Listed. **KECL** - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

International Regulations

Ozone Depletion Potential	This product does not contain any known or suspected substance
Persistent Organic Pollutant	This product does not contain any known or suspected substance
Rotterdam Convention (PIC)	Not applicable

Basel convention on the control of transboundary movements of hazardous wastes and their disposal

Take note that wastes may be subject to export, import, or transit controls pursuant to the Basel convention and/or local regulations implementing the Basel convention.

Component	Basel Convention (Hazardous Waste)	Australian Hazardous Waste Act - Categories of Wastes to Be Controlled
Ethyl ether - 60-29-7	Annex I - Y40 Annex I - Y42	Y40 Y42 except Halogenated solvents

Component	CAS No	OECD HPV	Restriction of Hazardous Substances (RoHS)	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Lithium aluminum hydride	16853-85-3	Not applicable	Not applicable	Not applicable	Not applicable
Ethyl ether	60-29-7	Listed	Not applicable	Not applicable	Not applicable

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Lithium aluminum hydride	-	Use restricted. See item 75. (see link for restriction details)	-

<https://echa.europa.eu/substances-restricted-under-reach>

Section 16 - Other Information**Legend**

AICS - Australian Inventory of Chemical Substances
TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List
IECSC - Chinese Inventory of Existing Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
TWA - Time Weighted Average
IARC - International Agency for Research on Cancer
ICAO/IATA - International Civil Aviation Organization/International Air Transport Association
MARPOL - International Convention for the Prevention of Pollution from Ships
NZS 5433:2012 - Transport of Dangerous Goods on Land
LD50 - Lethal Dose 50%
EC50 - Effective Concentration 50%
WEL - Workplace Exposure Limit
DNEL - Derived No Effect Level

NZIoC - New Zealand Inventory of Chemicals
EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
ENCS - Japanese Existing and New Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
CAS - Chemical Abstracts Service
ACGIH - American Conference of Governmental Industrial Hygienists
Predicted No Effect Concentration (PNEC)
IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code
ADG Australian Code for the Transport of Dangerous Goods by Road and Rail
OECD - Organisation for Economic Co-operation and Development
LC50 - Lethal Concentration 50%
ATE - Acute Toxicity Estimate
RPE - Respiratory Protective Equipment
NOEC - No Observed Effect Concentration

POW - Partition coefficient Octanol:Water
vPvB - very Persistent, very Bioaccumulative
VOC - (Volatile Organic Compound)

BCF - Bioconcentration factor
PBT - Persistent, Bioaccumulative, Toxic

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>
Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health Hazards	Calculation method
Environmental hazards	Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Chemical incident response training.

Revision Date	17-Nov-2022
Revision Summary	Not applicable.

This Safety Data Sheet (SDS) is prepared in accordance to and complies with the requirements of Safe Work Australia - Work Health and Safety Regulations (WHS Regulations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet