

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**1.1. Product identifier**

Product Description: Lead naphthenate, 61% in mineral spirits
Cat No. : 38593

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet**Company**

Thermo Fisher (Kandel) GmbH
Erlenbachweg 2, 76870 Kandel, Germany
Tel: +49 (0) 721 84007 280
Fax: +49 (0) 721 84007 300

Swiss distributor - Fisher Scientific AG
Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
<https://www.fishersci.ch/ch/en/customer-help-support/forms/email-us.html>

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

SECTION 2: HAZARDS IDENTIFICATION**2.1. Classification of the substance or mixture**

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

SAFETY DATA SHEET

Lead naphthenate, 61% in mineral spirits

Revision Date 17-Mar-2024

Flammable liquids	Category 3 (H226)
<u>Health hazards</u>	
Aspiration Toxicity	Category 1 (H304)
Acute oral toxicity	Category 4 (H302)
Acute Inhalation Toxicity - Vapors	Category 4 (H332)
Germ Cell Mutagenicity	Category 1B (H340)
Carcinogenicity	Category 1B (H350)
Reproductive Toxicity	Category 1A (H360Df)
Specific target organ toxicity - (repeated exposure)	Category 1 (H372)
<u>Environmental hazards</u>	
Acute aquatic toxicity	Category 1 (H400)
Chronic aquatic toxicity	Category 1 (H410)

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H226 - Flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H340 - May cause genetic defects
H350 - May cause cancer
H360Df - May damage the unborn child. Suspected of damaging fertility
H372 - Causes damage to organs through prolonged or repeated exposure
H410 - Very toxic to aquatic life with long lasting effects
H302 + H332 - Harmful if swallowed or if inhaled
EUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary Statements

P301 + P330 + P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting
P264 - Wash face, hands and any exposed skin thoroughly after handling
P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
P331 - Do NOT induce vomiting
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Additional EU labelling

Restricted to professional users

2.3. Other hazards

This product does not contain any known or suspected endocrine disruptors

SAFETY DATA SHEET

Lead naphthenate, 61% in mineral spirits

Revision Date 17-Mar-2024

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Lead naphthenate	61790-14-5	EEC No. 263-109-4	61.00	Acute Tox. 4 (H302) Acute Tox. 4 (H332) Repr. 1A (H360Df) STOT RE 2 (H373) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)
Stoddard solvent	8052-41-3	EEC No. 232-489-3	39.00	Flam. Liq. 3 (H226) Muta. 1B (H340) Carc. 1B (H350) Asp. Tox. 1 (H304) STOT RE 1 (H372) Aquatic Tox. 2 (H411) (EUH066)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Lead naphthenate	Repr. 2 (H361f) :: C>=2.5% STOT RE 2 (H373) :: C>=0.5%	-	-

Note

Note 1: The concentration stated or, in the absence of such concentrations, the generic concentrations of this Regulation (Table 3.1) or the generic concentrations of Directive 1999/45/EC (Table 3.2), are the percentages by weight of the metallic element calculated with reference to the total weight of the mixture

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice	If symptoms persist, call a physician.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur. Risk of serious damage to the lungs (by aspiration).
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

4.3. Indication of any immediate medical attention and special treatment needed

SAFETY DATA SHEET

Lead naphthenate, 61% in mineral spirits

Revision Date 17-Mar-2024

Notes to Physician

Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Do not allow run-off from fire-fighting to enter drains or water courses.

Hazardous Combustion Products

None under normal use conditions.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

SAFETY DATA SHEET

Lead naphthenate, 61% in mineral spirits

Revision Date 17-Mar-2024

7.2. Conditions for safe storage, including any incompatibilities

Store under an inert atmosphere. Keep container tightly closed in a dry and well-ventilated place. Keep away from heat, sparks and flame.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Class 3

Switzerland - Storage of hazardous substances

Storage class - SC 3
<https://www.kvu.ch/de/themen/stoffe-und-produkte>
<https://www.kvu.ch/fr/themes/substances-et-produits>
<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Lead naphthenate		STEL: 0.45 mg/m ³ 15 min TWA: 0.15 mg/m ³ 8 hr	TWA / VME: 0.1 mg/m ³ (8 heures). restrictive limit		
Stoddard solvent				TWA: 100 ppm 8 uren TWA: 533 mg/m ³ 8 uren	

Component	Italy	Germany	Portugal	The Netherlands	Finland
Stoddard solvent			TWA: 100 ppm 8 horas		

Component	Austria	Denmark	Switzerland	Poland	Norway
Lead naphthenate	MAK-KZGW: 0.4 mg/m ³ 15 Minuten MAK-TMW: 0.1 mg/m ³ 8 Stunden		STEL: 0.8 mg/m ³ 15 Minuten TWA: 0.1 mg/m ³ 8 Stunden		
Stoddard solvent		TWA: 25 ppm 8 timer TWA: 145 mg/m ³ 8 timer STEL: 50 ppm 15 minutter STEL: 290 mg/m ³ 15 minutter		STEL: 900 mg/m ³ 15 minutach TWA: 300 mg/m ³ 8 godzinach	

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Stoddard solvent			TWA: 100 ppm 8 hr. TWA: 573 mg/m ³ 8 hr.		TWA: 200 mg/m ³ 8 hodinách. Ceiling: 1000 mg/m ³

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Stoddard solvent	TWA: 50 ppm 8 tundides. TWA: 300 mg/m ³ 8 tundides. STEL: 100 ppm 15 minutites. STEL: 600 mg/m ³ 15 minutites.		STEL: 125 ppm STEL: 720 mg/m ³ TWA: 100 ppm TWA: 575 mg/m ³		TWA: 25 ppm 8 klukkustundum. TWA: 145 mg/m ³ 8 klukkustundum. Skin notation Ceiling: 50 ppm Ceiling: 290 mg/m ³

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Stoddard solvent		TWA: 50 ppm IPRD			

SAFETY DATA SHEET

Lead naphthenate, 61% in mineral spirits

Revision Date 17-Mar-2024

		approximate value TWA: 300 mg/m ³ IPRD STEL: 600 mg/m ³ STEL: 100 ppm			
--	--	--	--	--	--

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Stoddard solvent	TWA: 300 mg/m ³ 2119 MAC: 900 mg/m ³			Indicative STEL: 100 ppm 15 minuter Indicative STEL: 600 mg/m ³ 15 minuter Indicative STEL: 60 ppm 15 minuter Indicative STEL: 350 mg/m ³ 15 minuter TLV: 300 mg/m ³ 8 timmar. NGV TLV: 50 ppm 8 timmar. NGV TLV: 175 mg/m ³ 8 timmar. NGV TLV: 30 ppm 8 timmar. NGV Hud	

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Stoddard solvent 8052-41-3 (39.00)		DNEL = 30mg/kg bw/day	DNEL = 7.56mg/cm2	DNEL = 80mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Stoddard solvent 8052-41-3 (39.00)	DNEL = 55mg/m ³	DNEL = 55mg/m ³	DNEL = 44mg/m ³	DNEL = 44mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Stoddard solvent 8052-41-3 (39.00)	PNEC = 0.14mg/L	PNEC = 1.14mg/kg sediment dw	PNEC = 0.014mg/L		

Component	Marine water	Marine water	Marine water	Food chain	Air
-----------	--------------	--------------	--------------	------------	-----

SAFETY DATA SHEET

Lead naphthenate, 61% in mineral spirits

Revision Date 17-Mar-2024

		sediment	Intermittent		
Stoddard solvent 8052-41-3 (39.00)	PNEC = 0.35mg/L	PNEC = 0.14mg/kg sediment dw			PNEC = 10mg/m ³

8.2. Exposure controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Wear safety glasses with side shields (or goggles) (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Viton (R)	See manufacturers recommendations	-	EN 374	(minimum requirement)

Skin and body protection Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced
Recommended Filter type: low boiling organic solvent Type AX Brown conforming to EN371 or Organic gases and vapours filter Type A Brown conforming to EN14387

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141
When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls Prevent product from entering drains. Do not allow material to contaminate ground water system. Local authorities should be advised if significant spillages cannot be contained.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance	Brown	
Odor	oily	
Odor Threshold	No data available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flammability (liquid)	Flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Flash Point	40 °C / 104 °F	Method - No information available

SAFETY DATA SHEET

Lead naphthenate, 61% in mineral spirits

Revision Date 17-Mar-2024

Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
pH	No information available	
Viscosity	No data available	
Water Solubility	Immiscible	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Stoddard solvent	6.4	
Vapor Pressure	No data available	
Density / Specific Gravity	1.13 g/cm ³	@ 20 °C
Bulk Density	Not applicable	Liquid
Vapor Density	No data available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

Explosive Properties explosive air/vapour mixtures possible

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity None known, based on information available

10.2. Chemical stability Air sensitive.

10.3. Possibility of hazardous reactions

Hazardous Polymerization No information available.
Hazardous Reactions None under normal processing.

10.4. Conditions to avoid Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials None known.

10.6. Hazardous decomposition products None under normal use conditions.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;
Oral Category 4
Dermal No data available
Inhalation Category 4

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Lead naphthenate	LD50 = 5100 mg/kg (Rat)	-	-
Stoddard solvent	5000 mg/kg (orl, rat)	LD50 > 3000 mg/kg (Rabbit)	LC50 > 5.5 mg/L (Rat) 4 h

SAFETY DATA SHEET

Lead naphthenate, 61% in mineral spirits

Revision Date 17-Mar-2024

(b) skin corrosion/irritation; No data available

(c) serious eye damage/irritation; No data available

(d) respiratory or skin sensitization;
Respiratory No data available
Skin No data available

(e) germ cell mutagenicity; Category 1B

(f) carcinogenicity; Category 1B

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Stoddard solvent	Carc Cat. 1B			

(g) reproductive toxicity; Category 1A

(h) STOT-single exposure; No data available

(i) STOT-repeated exposure; Category 1
Target Organs Central nervous system (CNS).

(j) aspiration hazard; Category 1

Symptoms / effects, both acute and delayed Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment.

12.2. Persistence and degradability

Persistence

Immiscible with water.

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential

May have some potential to bioaccumulate

Component	log Pow	Bioconcentration factor (BCF)
Stoddard solvent	6.4	No data available

SAFETY DATA SHEET

Lead naphthenate, 61% in mineral spirits

Revision Date 17-Mar-2024

<u>12.4. Mobility in soil</u>	Spillage unlikely to penetrate soil The product is insoluble and sinks in water Is not likely mobile in the environment due its low water solubility.
<u>12.5. Results of PBT and vPvB assessment</u>	No data available for assessment.
<u>12.6. Endocrine disrupting properties</u> Endocrine Disruptor Information	This product does not contain any known or suspected endocrine disruptors
<u>12.7. Other adverse effects</u> Persistent Organic Pollutant Ozone Depletion Potential	This product does not contain any known or suspected substance This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products	Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.
Contaminated Packaging	Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.
European Waste Catalogue (EWC)	According to the European Waste Catalog, Waste Codes are not product specific, but application specific.
Other Information	Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not let this chemical enter the environment. Do not empty into drains.
Switzerland - Waste Ordinance	Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600 https://www.fedlex.admin.ch/eli/cc/2015/891/en

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

<u>14.1. UN number</u>	UN1993
<u>14.2. UN proper shipping name</u> Technical Shipping Name	Flammable liquid, n.o.s. (lead naphthenate in mineral spirits)
<u>14.3. Transport hazard class(es)</u>	3
<u>14.4. Packing group</u>	III

ADR

<u>14.1. UN number</u>	UN1993
<u>14.2. UN proper shipping name</u> Technical Shipping Name	Flammable liquid, n.o.s. (lead naphthenate in mineral spirits)
<u>14.3. Transport hazard class(es)</u>	3
<u>14.4. Packing group</u>	III

IATA

SAFETY DATA SHEET

Lead naphthenate, 61% in mineral spirits

Revision Date 17-Mar-2024

14.1. UN number UN1993
14.2. UN proper shipping name Flammable liquid, n.o.s.
Technical Shipping Name (lead naphthenate in mineral spirits)
14.3. Transport hazard class(es) 3
14.4. Packing group III

14.5. Environmental hazards Dangerous for the environment
Product is a marine pollutant according to the criteria set by IMDG/IMO

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Lead naphthenate	61790-14-5	263-109-4	-	-	X	X	KE-25672	X	X
Stoddard solvent	8052-41-3	232-489-3	-	-	X	X	KE-32199	-	-

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Lead naphthenate	61790-14-5	X	ACTIVE	X	-	X	X	X
Stoddard solvent	8052-41-3	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Lead naphthenate	61790-14-5	-	Use restricted. See item 30. (see link for restriction details) Use restricted. See item 63. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-
Stoddard solvent	8052-41-3	-	Use restricted. See item 28. (see link for restriction details) Use restricted. See item 29. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-

SAFETY DATA SHEET

Lead naphthenate, 61% in mineral spirits

Revision Date 17-Mar-2024

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Lead naphthenate	61790-14-5	Not applicable	Not applicable
Stoddard solvent	8052-41-3	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Component	ANNEX I - PART 1 List of chemicals subject to export notification procedure (referred to in Article 8)	ANNEX I - PART 2 List of chemicals qualifying for PIC notification (referred to in Article 11)	ANNEX I - PART 3 List of chemicals subject to the PIC procedure (referred to in Articles 13 and 14)
Lead naphthenate 61790-14-5 (61.00)	sr — severe restriction i(2) — industrial chemical for public	-	-

<https://eur-lex.europa.eu/legal-content/EN/TXT/?uri=CELEX%3A32012R0649&qid=1604065742303>.

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 94/33/EC on the protection of young people at work

Take note of Dir 92/85/EC on the protection of pregnant and breastfeeding women at work

Take note of Dir 76/769/EEC relating to restrictions on the marketing and use of certain dangerous substances and preparations

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 3 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Stoddard solvent	WGK2	

Component	France - INRS (Tables of occupational diseases)
Stoddard solvent	Tableaux des maladies professionnelles (TMP) - RG 84

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Lead naphthenate 61790-14-5 (61.00)	Prohibited and Restricted Substances		

15.2. Chemical safety assessment

SAFETY DATA SHEET

Lead naphthenate, 61% in mineral spirits

Revision Date 17-Mar-2024

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H302 - Harmful if swallowed
H304 - May be fatal if swallowed and enters airways
H332 - Harmful if inhaled
H340 - May cause genetic defects
H350 - May cause cancer
H360Df - May damage the unborn child. Suspected of damaging fertility
H372 - Causes damage to organs through prolonged or repeated exposure
H400 - Very toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects
EUH066 - Repeated exposure may cause skin dryness or cracking
H226 - Flammable liquid and vapor
H411 - Toxic to aquatic life with long lasting effects

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data

Health Hazards Calculation method

Environmental hazards Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Prepared By

Health, Safety and Environmental Department

Revision Date

17-Mar-2024

Revision Summary

New emergency telephone response service provider.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.

SAFETY DATA SHEET

Lead naphthenate, 61% in mineral spirits

Revision Date 17-Mar-2024

COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No 1907/2006

For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2, Number 3, Chemo (SR 813.11 - Ordinance on Protection against Dangerous Substances and Preparations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet