

Australian statement of hazardous nature : Classified as hazardous according to criteria of Safe Work Australia

Section 1 - Identification

Product Name Silver conductive adhesive paste

Product Code	44075
Address	ThermoFisher Scientific Australia Pty Ltd 5 Caribbean Drive, Scoresby VICTORIA 3179, Australia
Emergency Tel.	CHEMTREC® 03 9757 4559 or +613 9757 4559
Telephone / Fax Numbers	Tel: 1300 735 292 Fax: 1800 067 639
E-mail address	ANZinfo@thermofisher.com

Recommended Use Laboratory chemicals.

Uses advised against This product contains one or more substance(s) on the Illicit Drug Precursors/Reagents list. Verify requirements related to using, handling and storing these substances. This product does not contain any substance(s) subject to Prohibition, Authorization or Restriction. This product does not contain any substance(s) listed on the voluntary National Code of Practice for Chemicals of Security Concern.

Section 2 - Hazard(s) Identification

Classification under Safe Work Australia

Classified as hazardous according to criteria of Safe Work Australia

Physical hazards
No hazards identified

Health hazards

Skin Corrosion/Irritation
Serious Eye Damage/Eye Irritation
Specific target organ toxicity - (single exposure)

Category 2
Category 2
Category 3

Environmental hazards
No hazards identified

Label Elements



Exclamation Mark

Signal Word**Warning****Hazard Statements**

H315 - Causes skin irritation
H319 - Causes serious eye irritation
H335 - May cause respiratory irritation
AUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary Statements

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray
P264 - Wash face, hands and any exposed skin thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P302 + P352 - IF ON SKIN: Wash with plenty of soap and water
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P312 - Call a POISON CENTER or doctor if you feel unwell
P362 + P364 - Take off contaminated clothing and wash it before reuse
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed
P501 - Dispose of contents/ container to an approved waste disposal plant

Other information

This product does not contain any known or suspected endocrine disruptors
Toxic to terrestrial vertebrates

Section 3 - Composition and Information on Ingredients

Component	CAS No	Weight %
Silver	7440-22-4	66.5
Epoxy cresol novolac	29690-82-2	20
Ethylene glycol, monobutyl ether acetate	112-07-2	7.5
Proprietary fatty acid derivative	N/A	2.5
Acetone	67-64-1	2.5
Propylene glycol monomethyl ether acetate	108-65-6	0.5
Proprietary acrylic resin	N/A	0.5

Section 4 - First Aid Measures

Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Get medical attention if symptoms occur.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
General Advice	If symptoms persist, call a physician.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

First Aid Facilities	Eyewash, safety shower and washroom.
Most important symptoms and effects	None reasonably foreseeable. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting
Notes to Physician	Treat symptomatically.

Section 5 - Fire Fighting Measures

Suitable Extinguishing Media

Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

No information available.

Hazardous Decomposition Products

Metal fumes and oxides, Carbon monoxide (CO), Carbon dioxide (CO₂).

Specific Hazards Arising from the Chemical

Combustible material. Containers may explode when heated.

Special protective equipment and precautions for fire fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6 - Accidental Release Measures

Emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Avoid dust formation. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions

Do not flush into surface water or sanitary sewer system.

Methods for Containment and Clean Up

Clean-up methods - small spillage

Keep in suitable, closed containers for disposal. Sweep up and shovel into suitable containers for disposal. Remove all sources of ignition.

Clean-up methods - large spillage

Typically only supplied in small quantities as packaged goods.

If extremely toxic or used in larger quantities ensure a spillage action plan is in place. Evacuate area. Control the source and/or contain the spill if safe and able to do so. Use temporary diking, sand bags, dry sand, earth or proprietary booms/absorbent pads if available. Obtain advice on containment, neutralisation and clean-up from local emergency responders.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

Section 7 - Handling and Storage

Precautions for Safe Handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Avoid dust formation. Keep away from open flames, hot surfaces and sources of ignition.

Conditions for Safe Storage, Including any Incompatibilities

Keep away from heat, sparks and flame. Keep refrigerated. Keep containers tightly closed in a dry, cool and well-ventilated place.

AS/NZS 2243.10:2004, Safety in laboratories - Storage of chemicals
AS 1940-2004 - The storage and handling of flammable and combustible liquids

Section 8 - Exposure Controls and Personal Protection

Exposure limits

AUS - Exposure Standards for Atmospheric Contaminants in the Occupational Environment - Guidance Note on the Interpretation of Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:3008(1995)]

Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)] updated in August, 2005. Safe Work Australia

ACGIH - Threshold Limit Values - Ceiling (TLV-C) guidelines by the American Conference of Governmental Industrial Hygienists (ACGIH) for controlling worker exposure to airborne chemical concentrations in the workplace.

UK - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020.

DE - MAK and BAT values of Hazardous Chemical Compounds in the Work Area. Published by German Research Foundation on July 1, 2011

NZ - Workplace Exposure Standards and Biological Exposure Indices (6th edition). New Zealand Department of Labor

Component	Australia	New Zealand WEL	ACGIH TLV	The United Kingdom	Germany
Silver	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³	STEL: 0.3 mg/m ³ 15 min TWA: 0.1 mg/m ³ 8 hr	TWA: 0.1 mg/m ³ (8 Stunden). AGW - exposure factor 8 TWA: 0.1 mg/m ³ (8 Stunden). MAK Höhepunkt: 0.8 mg/m ³
Ethylene glycol, monobutyl ether acetate	STEL: 50 ppm STEL: 333 mg/m ³ TWA: 20 ppm TWA: 133 mg/m ³		TWA: 20 ppm	STEL: 50 ppm 15 min STEL: 332 mg/m ³ 15 min TWA: 20 ppm 8 hr TWA: 133 mg/m ³ 8 hr Skin	TWA: 10 ppm (8 Stunden). AGW - exposure factor 2 TWA: 65 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 10 ppm (8 Stunden). MAK applies for the sum of the concentrations of 2-Butoxyethanol and its Acetate in air; can occur as vapor and aerosol at the same time TWA: 66 mg/m ³ (8 Stunden). MAK applies for the sum of the concentrations of 2-Butoxyethanol and its Acetate in air; can occur as vapor and aerosol at the same time Höhepunkt: 20 ppm Höhepunkt: 132 mg/m ³ Haut
Acetone	STEL: 1000 ppm STEL: 2375 mg/m ³ TWA: 500 ppm TWA: 1185 mg/m ³	TWA: 500 ppm TWA: 1185 mg/m ³ STEL: 1000 ppm STEL: 2375 mg/m ³	TWA: 250 ppm STEL: 500 ppm	TWA: 500 ppm TWA: 1210 mg/m ³ STEL: 1500 ppm STEL: 3620 mg/m ³	TWA: 500 ppm TWA: 1200 mg/m ³
Propylene glycol monomethyl ether acetate	STEL: 100 ppm STEL: 548 mg/m ³ TWA: 50 ppm TWA: 274 mg/m ³			STEL: 100 ppm 15 min STEL: 548 mg/m ³ 15 min TWA: 50 ppm 8 hr TWA: 274 mg/m ³ 8 hr Skin	TWA: 50 ppm (8 Stunden). AGW - exposure factor 1 TWA: 270 mg/m ³ (8 Stunden). AGW - exposure factor 1 TWA: 50 ppm (8 Stunden). MAK TWA: 270 mg/m ³ (8 Stunden). MAK Höhepunkt: 50 ppm Höhepunkt: 270 mg/m ³

Biological limit values

NZ - Substances assigned Biological Exposure Indices in the New Zealand Workplace Exposure Standards and Biological Exposure Indices (6th edition). New Zealand Department of Labor

Component	Australia	New Zealand	European Union	United Kingdom	Germany
Ethylene glycol, monobutyl ether acetate					Butoxyacetic acid (after hydrolysis): 150 mg/g Creatinine urine (for long-term exposures: at the end of the shift after several shifts) Butoxyacetic acid (after hydrolysis): 150 mg/g Creatinine urine (end of shift)
Acetone		50 mg/L (urine) end of shift (Acetone)			Acetone: 80 mg/L urine (end of shift)

Exposure Controls**Engineering Measures**

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment**Eye Protection**

Goggles (Australian/New Zealand Standard AS/NZS 1337 - Eye protectors for Industrial applications)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	AUS/NZ Standard	Glove comments
Natural rubber	See manufacturers	-	AS/NZS 2161	(minimum requirement)
Nitrile rubber	recommendations			
Neoprene				
PVC				

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatibility, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Skin and body protection

Long sleeved clothing

Respiratory Protection

Use an AS/NZS 1716 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained in line with AS/NZS 1715 on the use and maintenance of respiratory protective devices

Recommended Filter type:

Particulates filter conforming to EN 143 or Inorganic gases and vapours filter Type B Grey conforming to EN14387 (or AUS/NZ equivalent)

Recommended half mask:-

Particle filtering: EN149:2001 (or AUS/NZ equivalent)
When RPE is used a face piece Fit Test should be conducted

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

Environmental exposure controls

Prevent product from entering drains. Do not allow material to contaminate ground water system. Local authorities should be advised if significant spillages cannot be contained.

Section 9 - Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance	Silver	
Physical State	Solid paste	
Odor	No information available	
Odor Threshold	No data available	
pH	Not applicable	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flash Point	71 °C / 159.8 °F	Method - No information available
Evaporation Rate	Not applicable	Solid
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Vapor Pressure	No data available	
Vapor Density	Not applicable	Solid
Specific Gravity / Density	1.21 g/cm3	
Bulk Density	Not applicable	Liquid
Water Solubility	Insoluble	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Ethylene glycol, monobutyl ether acetate	1.51	
Acetone	-0.24	
Propylene glycol monomethyl ether acetate	1.2	
Autoignition Temperature	280 °C / 536 °F	
Decomposition Temperature	No data available	
Viscosity	Not applicable	Solid
Explosive Properties		explosive air/vapour mixtures possible
Oxidizing Properties	No information available	

Other information**Section 10 - Stability and Reactivity**

Reactivity	None known, based on information available
Stability	Stable under normal conditions.
Conditions to Avoid	Keep away from open flames, hot surfaces and sources of ignition.
Incompatible Materials	Acids, Bases, Strong oxidizing agents.
Hazardous Decomposition Products	Metal fumes and oxides. Carbon monoxide (CO). Carbon dioxide (CO ₂).
Hazardous Polymerization	No information available.

Section 11 - Toxicological Information

Information on Toxicological Effects

Product Information

(a) acute toxicity;

Oral	Based on available data, the classification criteria are not met
Dermal	Based on available data, the classification criteria are not met
Inhalation	Based on available data, the classification criteria are not met

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Silver	> 2000 mg/kg (Rat)	LD50 > 2000 mg/kg (rat)	LC50 > 5.16 mg/L (Rat) 4 h
Ethylene glycol, monobutyl ether acetate	LD50 = 2400 mg/kg (Rat)	LD50 = 1500 mg/kg (Rabbit)	LC50 > 400 ppm (Rat) 4 h
Acetone	5800 mg/kg (Rat)	> 15800 mg/kg (rabbit) > 7400 mg/kg (rat)	76 mg/l, 4 h, (rat)
Propylene glycol monomethyl ether acetate	LD50 = 8532 mg/kg (Rat)	LD50 > 5 g/kg (Rabbit)	LC50 = 16000 mg/m ³ (Rat) 6 h

(b) skin corrosion/irritation; Category 2

(c) serious eye damage/irritation; Category 2

(d) respiratory or skin sensitization;

Respiratory No data available
Skin No data available

Component	Test method	Test species	Study result
Acetone 67-64-1 (2.5)	Guinea Pig Maximisation Test (GPMT)	guinea pig	non-sensitising

(e) germ cell mutagenicity; No data available

Component	Test method	Test species	Study result
Acetone 67-64-1 (2.5)	OECD Test Guideline 471 AMES test	in vivo	negative
	OECD Test Guideline 476 Mammalian Gene cell mutation	in vitro	negative

(f) carcinogenicity; No data available

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; No data available

(h) STOT-single exposure; Category 3

Results / Target organs
 Respiratory system
 Central nervous system (CNS)

(i) STOT-repeated exposure; No data available

Target Organs
 None known.

(j) aspiration hazard;
 Not applicable
 Solid

Symptoms / effects, both acute and delayed Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

Section 12 - Ecological Information

Ecotoxicity effects Contains a substance which is: Very toxic to aquatic organisms. The product contains

following substances which are hazardous for the environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Silver	LC50: = 0.064 mg/L, 96h static (Lepomis macrochirus) LC50: = 0.0062 mg/L, 96h flow-through (Oncorhynchus mykiss) LC50: 0.00155 - 0.00293 mg/L, 96h static (Pimephales promelas)	EC50: = 0.00024 mg/L, 48h Static (Daphnia magna)		
Ethylene glycol, monobutyl ether acetate	LC50: 20 - 40 mg/L, 96h (Oncorhynchus mykiss)	EC50 = 37 mg/L, 48h (Daphnia magna)	EC50 > 500 mg/L, 72h (Desmodesmus subspicatus)	
Acetone	Oncorhynchus mykiss: LC50 = 5540 mg/l 96h Alburnus alburnus: LC50 = 11000 mg/l 96h Leuciscus idus: LC50 = 11300 mg/L/48h Salmo gairdneri: LC50 = 6100 mg/L/24h	EC50 = 8800 mg/L/48h EC50 = 12700 mg/L/48h EC50 = 12600 mg/L/48h	NOEC = 430 mg/l (algae; 96 h)	EC50 = 14500 mg/L/15 min
Propylene glycol monomethyl ether acetate	LC50: = 161 mg/L, 96h static (Pimephales promelas)	EC50: > 500 mg/L, 48h (Daphnia magna)		

Persistence and Degradability**Persistence**

Insoluble in water.

Degradability

Not relevant for inorganic substances.

Component	Degradability
Acetone 67-64-1 (2.5)	91 % (28 d) (OECD 301 B)

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

Bioaccumulative Potential

May have some potential to bioaccumulate

Component	log Pow	Bioconcentration factor (BCF)
Ethylene glycol, monobutyl ether acetate	1.51	No data available
Acetone	-0.24	0.69 dimensionless
Propylene glycol monomethyl ether acetate	1.2	No data available

Mobility

Spillage unlikely to penetrate soil. Is not likely mobile in the environment due its low water solubility

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

Persistent Organic Pollutant

This product does not contain any known or suspected substance

Ozone Depletion Potential

This product does not contain any known or suspected substance

Section 13 - Disposal Considerations

Waste from Residues/Unused Products

Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with all federal, E.P.A., state and local regulations. Assure conformity with all applicable regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point.

Other Information

Chemical wastes should be disposed through a licensed commercial waste collection service. Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Do not empty into drains.

Section 14 - Transport Information

IMDG/IMO Not regulated

ADG Not regulated

Component	Hazchem Code
Acetone 67-64-1 (2.5)	2YE

IATA Not regulated

Environmental hazards No hazards identified

Special Precautions No special precautions required

Additional information None known

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National Regulations Australia

See section 8 for national exposure control parameters.

Standard for the Uniform Scheduling of Medicines and Poisons

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons.

Component	Standard for the Uniform Scheduling of Medicines and Poisons
Silver - 7440-22-4	Schedule 2 listed
Ethylene glycol, monobutyl ether acetate - 112-07-2	Schedule 6 listed - except in plant growth regulator preparations containing <=20% of such substances, or in other preparations containing <=10% of such substances
Acetone - 67-64-1	Schedule 5 listed - except in preparations containing <=25% of designated solvents

Australian Industrial Chemicals Introduction Scheme (AICIS)

Component	Australian Industrial Chemicals Introduction Scheme (AICIS)	Additional information
Silver - 7440-22-4	Present	-
Epoxy cresol novolac - 29690-82-2	Present	-
Ethylene glycol, monobutyl ether acetate - 112-07-2	Present	-
Acetone - 67-64-1	Present	-
Propylene glycol monomethyl ether acetate - 108-65-6	Present	-

Australian - Illicit Drug Precursors/Reagents Substance List

This product contains one or more substance(s) on the Illicit Drug Precursors/Reagents list. Verify requirements related to using, handling and storing these substances.

Chemicals of Security Concern

This product does not contain any substance(s) listed on the voluntary National Code of Practice for Chemicals of Security Concern

Component	Australian - Illicit Drug	Chemicals of Security Concern
-----------	---------------------------	-------------------------------

	Precursors/Reagents Substance List	
Acetone - 67-64-1	Category 3	

Legend

Category 3 - Chemicals and apparatus that may be used in the illicit production of drugs. Purchases from this list should alert companies or organizations to seek further indicators of any suspicious orders or enquiries. No official reporting is required for items on this list unless considered warranted

National pollutant inventory Subject to reporting requirements

Component	National pollutant inventory
Acetone - 67-64-1	10 tonne/yr. Threshold category 1

Prohibition or notification/licensing requirements

Shown below are details of specific prohibition/notifications or licensing requirements when they apply.

This product does not contain any substance(s) subject to Prohibition, Authorization or Restriction.

International Inventories

Component	AICS	NZIoC	EINECS	ELINCS	TSCA	DSL	NDSL	PICCS	ENCS	ISHL	IECSC	KECL
Silver	X	X	231-131-3	-	X	X	-	X	X		X	KE-31261
Epoxy cresol novolac	X	X	-	-	X	X	-	X	X	X	X	KE-17105
Ethylene glycol, monobutyl ether acetate	X	X	203-933-3	-	X	X	-	X	X	X	X	KE-04135
Acetone	X	X	200-662-2	-	X	X	-	X	X	X	X	KE-29367
Propylene glycol monomethyl ether acetate	X	X	203-603-9	-	X	X	-	X	X	X	X	KE-23315

Legend: X - Listed. '-' - Not Listed. PMN - Indicates a commenced PMN substance. XU - Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B)). **KECL** - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

International Regulations

Ozone Depletion Potential This product does not contain any known or suspected substance

Persistent Organic Pollutant This product does not contain any known or suspected substance

Rotterdam Convention (PIC) Not applicable

Basel convention on the control of transboundary movements of hazardous wastes and their disposal

Take note that wastes may be subject to export, import, or transit controls pursuant to the Basel convention and/or local regulations implementing the Basel convention.

Component	Basel Convention (Hazardous Waste)	Australian Hazardous Waste Act - Categories of Wastes to Be Controlled
Acetone - 67-64-1	Annex I - Y42	Y42 except Halogenated solvents

Component	CAS No	OECD HPV	Restriction of Hazardous Substances (RoHS)	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements

Silver	7440-22-4	Listed	Not applicable	Not applicable	Not applicable
Epoxy cresol novolac	29690-82-2	Listed	Not applicable	Not applicable	Not applicable
Ethylene glycol, monobutyl ether acetate	112-07-2	Listed	Not applicable	Not applicable	Not applicable
Proprietary fatty acid derivative	N/A	Not applicable	Not applicable	Not applicable	Not applicable
Acetone	67-64-1	Listed	Not applicable	Not applicable	Not applicable
Propylene glycol monomethyl ether acetate	108-65-6	Listed	Not applicable	Not applicable	Not applicable
Proprietary acrylic resin	N/A	Not applicable	Not applicable	Not applicable	Not applicable

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Silver	-	Use restricted. See item 75. (see link for restriction details)	-
Acetone	-	Use restricted. See item 75. (see link for restriction details)	-

<https://echa.europa.eu/substances-restricted-under-reach>

Section 16 - Other Information

Legend

AICS - Australian Inventory of Chemical Substances	NZIoC - New Zealand Inventory of Chemicals
TSCA - United States Toxic Substances Control Act Section 8(b) Inventory	EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List	ENCS - Japanese Existing and New Chemical Substances
IECSC - Chinese Inventory of Existing Chemical Substances	KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances	CAS - Chemical Abstracts Service
TWA - Time Weighted Average	ACGIH - American Conference of Governmental Industrial Hygienists
IARC - International Agency for Research on Cancer	Predicted No Effect Concentration (PNEC)
ICAO/IATA - International Civil Aviation Organization/International Air Transport Association	IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code
MARPOL - International Convention for the Prevention of Pollution from Ships	ADG - Australian Code for the Transport of Dangerous Goods by Road and Rail
NZS 5433:2020 - Transport of Dangerous Goods on Land	OECD - Organisation for Economic Co-operation and Development
LD50 - Lethal Dose 50%	LC50 - Lethal Concentration 50%
EC50 - Effective Concentration 50%	ATE - Acute Toxicity Estimate
WEL - Workplace Exposure Limit	RPE - Respiratory Protective Equipment
DNEL - Derived No Effect Level	NOEC - No Observed Effect Concentration
POW - Partition coefficient Octanol:Water	BCF - Bioconcentration factor
vPvB - very Persistent, very Bioaccumulative	PBT - Persistent, Bioaccumulative, Toxic
VOC - (Volatile Organic Compound)	

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>
Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health Hazards	Calculation method
Environmental hazards	Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Revision Date 26-May-2023
Revision Summary SDS sections updated.

This Safety Data Sheet (SDS) is prepared in accordance to and complies with the requirements of Safe Work Australia - Work Health and Safety Regulations (WHS Regulations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet