

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
Product Identifier

Perihal Produk:

Product Description:

Cat No. :

Graphite conductive adhesive, alcohol based
Graphite conductive adhesive, alcohol based

42465

Relevant identified uses of the substance or mixture and uses advised against

Recommended Use

Laboratory chemicals.

Uses advised against

No Information available

Company

 Thermo Fisher Scientific Fisher Scientific (M) Sdn Bhd
 Hap Seng Business Park, Lot 01-03, 01-04 Aras 1 Unity Square,
 No 12, Persiaran Perusahaan, Seksyen 23, 40300 Shah Alam,
 Selangor Darul Ehsan, Malaysia.
 Main line: +60 3-5525 7888

Supplier

E-mail address

Enquiry.my@thermofisher.com

Emergency Telephone Number

Tel: +03-5525 7888

 CHEMTREC Malaysia **1-800-815-308** (Malay)

 CHEMTREC Malaysia (Kuala Lumpur) **+(60)-327884561** (Malay)

SECTION 2: HAZARDS IDENTIFICATION
Classification of the substance or mixture

Flammable liquids	Category 2 (H225)
Serious Eye Damage/Eye Irritation	Category 1 (H318)
Specific target organ toxicity - (single exposure)	Category 3 (H336)

Label Elements


Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H318 - Causes serious eye damage

SAFETY DATA SHEET

Graphite conductive adhesive, alcohol based

Revision Date 31-Mar-2025

H336 - May cause drowsiness or dizziness

Precautionary Statements

Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P240 - Ground and bond container and receiving equipment

P242 - Use non-sparking tools

P243 - Take action to prevent static discharges

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves/protective clothing/eye protection/face protection

Response

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor

P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Other Hazards

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No	Weight %
Isopropyl alcohol	67-63-0	70.00
Graphite	7782-42-5	15.00
n-Butyl alcohol	71-36-3	5.0
Propylene glycol monomethyl ether	107-98-2	5.00
Hexylene glycol	107-41-5	5.00

SECTION 4: FIRST AID MEASURES

Description of first aid measures

General Advice

If symptoms persist, call a physician.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.

Ingestion

Clean mouth with water and drink afterwards plenty of water.

Inhalation

Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.

Self-Protection of the First Aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

SAFETY DATA SHEET

Graphite conductive adhesive, alcohol based

Revision Date 31-Mar-2025

Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Causes eye burns. Causes severe eye damage. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing media

Suitable Extinguishing Media

Carbon dioxide (CO₂). Powder. Water spray. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

No information available.

Special hazards arising from the substance or mixture

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂).

Advice for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Ensure adequate ventilation. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental precautions

Should not be released into the environment. See Section 12 for additional Ecological Information.

Methods and Material for Containment and Cleaning Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid

SAFETY DATA SHEET

Graphite conductive adhesive, alcohol based

Revision Date 31-Mar-2025

ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Conditions for Safe Storage, Including any Incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat, sparks and flame.

Specific End Uses

Use in laboratories.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Component	Malaysia	ACGIH TLV	OSHA PEL
Isopropyl alcohol		TWA: 200 ppm STEL: 400 ppm	(Vacated) TWA: 400 ppm (Vacated) TWA: 980 mg/m ³ (Vacated) STEL: 500 ppm (Vacated) STEL: 1225 mg/m ³ TWA: 400 ppm TWA: 980 mg/m ³
Graphite		TWA: 2 mg/m ³	(Vacated) TWA: 2.5 mg/m ³ (Vacated) TWA: 10 mg/m ³ (Vacated) TWA: 5 mg/m ³ TWA: 15 mg/m ³ TWA: 5 mg/m ³ TWA: 15 mppcf
n-Butyl alcohol		TWA: 20 ppm	Skin (Vacated) Ceiling: 50 ppm (Vacated) Ceiling: 150 mg/m ³ TWA: 100 ppm TWA: 300 mg/m ³
Propylene glycol monomethyl ether		TWA: 50 ppm STEL: 100 ppm	(Vacated) TWA: 100 ppm (Vacated) TWA: 360 mg/m ³ (Vacated) STEL: 150 ppm (Vacated) STEL: 540 mg/m ³
Hexylene glycol		TWA: 25 ppm STEL: 50 ppm STEL: 10 mg/m ³	(Vacated) Ceiling: 25 ppm (Vacated) Ceiling: 125 mg/m ³

Component	European Union	The United Kingdom	Germany
Isopropyl alcohol		STEL: 500 ppm 15 min STEL: 1250 mg/m ³ 15 min TWA: 400 ppm 8 hr TWA: 999 mg/m ³ 8 hr	TWA: 200 ppm (8 Stunden). AGW - exposure factor 2 TWA: 500 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 200 ppm (8 Stunden). MAK TWA: 500 mg/m ³ (8 Stunden). MAK Höhepunkt: 400 ppm Höhepunkt: 1000 mg/m ³
Graphite		STEL: 30 mg/m ³ 15 min STEL: 12 mg/m ³ 15 min TWA: 10 mg/m ³ 8 hr TWA: 4 mg/m ³ 8 hr	TWA: 1.5 mg/m ³ (8 Stunden) MAKTWA: 4 mg/m ³ (8Stunden). MAK
n-Butyl alcohol		50ppm STEL; 154mg/m ³ STEL	100ppm TWA; 310mg/m ³ TWA
Propylene glycol monomethyl ether	TWA: 100 ppm (8h) TWA: 375 mg/m ³ (8h) STEL: 150 ppm (15min) STEL: 568 mg/m ³ (15min) Skin	STEL: 150 ppm 15 min STEL: 560 mg/m ³ 15 min TWA: 100 ppm 8 hr TWA: 375 mg/m ³ 8 hr Skin	TWA: 100 ppm (8 Stunden). AGW - exposure factor 2 TWA: 370 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 100 ppm (8 Stunden). MAK TWA: 370 mg/m ³ (8 Stunden). MAK Höhepunkt: 200 ppm Höhepunkt: 740 mg/m ³
Hexylene glycol		STEL: 25 ppm 15 min	TWA: 10 ppm (8 Stunden). MAK

SAFETY DATA SHEET

Graphite conductive adhesive, alcohol based

Revision Date 31-Mar-2025

		STEL: 123 mg/m ³ 15 min TWA: 25 ppm 8 hr TWA: 123 mg/m ³ 8 hr	can occur as vapor and aerosol at the same time TWA: 49 mg/m ³ (8 Stunden). MAK can occur as vapor and aerosol at the same time Höhepunkt: 20 ppm Höhepunkt: 98 mg/m ³
--	--	---	---

Exposure Controls

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles

Hand Protection

Protective gloves

Skin and body protection

Long sleeved clothing

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators

Recommended Filter type:

Organic gases and vapours filter Type A Brown conforming to EN14387

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

When RPE is used a face piece Fit Test should be conducted

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice

Environmental exposure controls

No information available

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance

Physical State

Liquid

Odor

No information available

Odor Threshold

No data available

pH

No information available

Melting Point/Range

No data available

Softening Point

No data available

Boiling Point/Range

82 °C / 179.6 °F

Flash Point

11 °C / 51.8 °F

Method - No information available

SAFETY DATA SHEET

Graphite conductive adhesive, alcohol based

Revision Date 31-Mar-2025

Evaporation Rate	No data available	
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Vapor Pressure	23 hPa @ 20 °C	
Vapor Density	No data available	(Air = 1.0)
Specific Gravity / Density	0.9 g/cm3	@ 20 °C
Bulk Density	Not applicable	Liquid
Water Solubility	Immiscible	
Solubility in other solvents	No information available	

Partition Coefficient (n-octanol/water)

Component	log Pow
Isopropyl alcohol	0.05
n-Butyl alcohol	1
Propylene glycol monomethyl ether	<1
Hexylene glycol	<0.14

Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
Viscosity	No data available	
Explosive Properties		Vapors may form explosive mixtures with air
Oxidizing Properties	No information available	

SECTION 10: STABILITY AND REACTIVITY

Reactivity

None known, based on information available.

Chemical Stability

Stable under normal conditions.

Possibility of Hazardous Reactions

Hazardous Polymerization	No information available.
Hazardous Reactions	None under normal processing.

Conditions to Avoid

Keep away from open flames, hot surfaces and sources of ignition.

Incompatible Materials

Oxidizing agent.

Hazardous Decomposition Products

Carbon monoxide (CO). Carbon dioxide (CO₂).

SAFETY DATA SHEET

Graphite conductive adhesive, alcohol based

Revision Date 31-Mar-2025

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects

Product Information

(a) acute toxicity;

Oral

Based on available data, the classification criteria are not met

Dermal

Based on available data, the classification criteria are not met

Inhalation

Based on available data, the classification criteria are not met

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Isopropyl alcohol	5045 mg/kg (Rat) 3600 mg/kg (Mouse)	12800 mg/kg (Rat)	72.6 mg/L (Rat) 4 h
Graphite	-	-	LC50 > 2000 mg/m ³ (Rat) 4 h
n-Butyl alcohol	LD50 = 700 mg/kg (Rat)	LD50 = 3402 mg/kg (Rabbit)	LC50 > 8000 ppm (Rat) 4 h
Propylene glycol monomethyl ether	LD50 = 5000 mg/kg (Rat)	LD50 = 13 g/kg (Rabbit)	LC50 > 7559 ppm (Rat) 6 h
Hexylene glycol	LD50 = 3700 mg/kg (Rat)	LD50 = 12300 mg/kg (Rabbit)	LC50 > 310 mg/m ³ (Rat) 1 h

(b) skin corrosion/irritation; No data available

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;

Respiratory

No data available

Skin

No data available

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; No data available

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; No data available

(h) STOT-single exposure; Category 3

Results / Target organs

Central nervous system (CNS), Respiratory system.

(i) STOT-repeated exposure; No data available

Target Organs

No information available.

(j) aspiration hazard; No data available

Symptoms / effects, both acute and delayed Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

SAFETY DATA SHEET

Graphite conductive adhesive, alcohol based

Revision Date 31-Mar-2025

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity effects

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Isopropyl alcohol	LC50: = 9640 mg/L, 96h flow-through (Pimephales promelas) LC50: > 1400000 µg/L, 96h (Lepomis macrochirus) LC50: = 11130 mg/L, 96h static (Pimephales promelas) LC50: = 10000000 µg/L, 96h (Daphnia)	13299 mg/L EC50 = 48 h 9714 mg/L EC50 = 24 h	EC50: > 1000 mg/L, 72h (Desmodesmus subspicatus) EC50: > 1000 mg/L, 96h (Desmodesmus subspicatus)	= 35390 mg/L EC50 Photobacterium phosphoreum 5 min
Graphite	LC50: > 100 mg/L, 96h semi-static (Danio rerio)			
n-Butyl alcohol	LC50: 1376 mg/L, 96h (Pimephales promelas) OECD Guideline 203 : 100000 - 500000 µg/L, 96h static (Lepomis macrochirus) LC50: = 1740 mg/L, 96h flow-through (Pimephales promelas) LC50: = 1910000 µg/L, 96h static (Pimephales promelas) LC50: 1730 - 1910 mg/L, 96h static (Pimephales promelas)	EC50: 1328 mg/L, 48h (Daphnia magna) OECD Guideline 202 EC50: 1897 - 2072 mg/L, 48h Static (Daphnia magna) EC50: = 1983 mg/L, 48h (Daphnia magna)	EC50: 225 mg/L, 96h (Pseudokirchneriella subcapitata) OECD Guideline 201 EC50: > 500 mg/L, 72h (Desmodesmus subspicatus) EC50: > 500 mg/L, 96h (Desmodesmus subspicatus)	EC50 = 2041.4 mg/L 5 min EC50 = 2186 mg/L 30 min EC50 = 3980 mg/L 24 h EC50 = 4400 mg/L 17 h
Propylene glycol monomethyl ether	LC50: = 20.8 g/L, 96h static (Pimephales promelas)	EC50: = 23300 mg/L, 48h (Daphnia magna)		
Hexylene glycol	LC50: 10500 - 11000 mg/L, 96h flow-through (Pimephales promelas) LC50: = 10000 mg/L, 96h static (Lepomis macrochirus) LC50: = 8690 mg/L, 96h flow-through (Pimephales promelas) LC50: = 10700 mg/L, 96h static (Pimephales promelas)	EC50: 2700 - 3700 mg/L, 48h (Daphnia magna)		EC50 = 3038 mg/L 5 min

Persistence and degradability

Persistence

Persistence is unlikely, based on information available.

Component	Degradability
n-Butyl alcohol 71-36-3 (5.0)	70 %

SAFETY DATA SHEET

Graphite conductive adhesive, alcohol based

Revision Date 31-Mar-2025

Bioaccumulative potential		Bioaccumulation is unlikely
Component	log Pow	Bioconcentration factor (BCF)
Isopropyl alcohol	0.05	No data available
n-Butyl alcohol	1	0.64 dimensionless
Propylene glycol monomethyl ether	<1	<2 dimensionless
Hexylene glycol	<0.14	No data available

Mobility in soil

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in air.

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

Other adverse effects

No information available

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous Dispose of in accordance with the European Directives on waste and hazardous waste Dispose of in accordance with local regulations

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous Keep product and empty container away from heat and sources of ignition

Other Information

Waste codes should be assigned by the user based on the application for which the product was used Do not flush to sewer Can be landfilled or incinerated, when in compliance with local regulations Do not empty into drains

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

UN-No UN1133
Hazard Class 3
Packing Group II
Proper Shipping Name ADHESIVES

Road and Rail Transport

UN-No UN1133
Hazard Class 3
Packing Group II
Proper Shipping Name ADHESIVES

IATA

UN-No UN1133
Hazard Class 3
Packing Group II
Proper Shipping Name ADHESIVES

Special Precautions for User

No special precautions required

SECTION 15: REGULATORY INFORMATION

SAFETY DATA SHEET

Graphite conductive adhesive, alcohol based

Revision Date 31-Mar-2025

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

X = listed

Component	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	IECSC	AICS	KECL
Isopropyl alcohol	200-661-7	X	X	X	X	X	X	X	KE-29363
Graphite	231-955-3	X	X	X	-		X	X	X
n-Butyl alcohol	200-751-6	X	X	X	X	X	X	X	KE-03867
Propylene glycol monomethyl ether	203-539-1	X	X	X	X	X	X	X	KE-23379
Hexylene glycol	203-489-0	X	X	X	X	X	X	X	KE-24702

Component	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Isopropyl alcohol				Annex I - Y42

National Regulations

Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance
This product does not contain any known or suspected substance

SECTION 16: OTHER INFORMATION

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

POW - Partition coefficient Octanol:Water

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Prepared By

Health, Safety and Environmental Department

SAFETY DATA SHEET

Graphite conductive adhesive, alcohol based

Revision Date 31-Mar-2025

Revision Date	31-Mar-2025
Revision Summary	Not applicable.

In accordance with local and national regulations: Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet