

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description:	Beryllium disc, 0.02+/-0.002in thick, 0.900+/-0.003in dia
Cat No. :	S37055
Index No	004-001-00-7
CAS No	7440-41-7
EC No	231-150-7
Molecular Formula	Be

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use	Laboratory chemicals.
Uses advised against	No Information available

1.3. Details of the supplier of the safety data sheet

Company

Thermo Fisher (Kandel) GmbH
Erlenbachweg 2, 76870 Kandel, Germany
Tel: +49 (0) 721 84007 280
Fax: +49 (0) 721 84007 300

Swiss distributor - Fisher Scientific AG
Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
<https://www.fishersci.ch/ch/en/customer-help-support/forms/email-us.html>

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

SAFETY DATA SHEET

Beryllium disc, 0.02+/-0.002in thick, 0.900+/-0.003in dia

Revision Date 11-Jun-2025

Physical hazards

Based on available data, the classification criteria are not met

Health hazards

Acute oral toxicity	Category 3 (H301)
Acute Inhalation Toxicity - Dusts and Mists	Category 2 (H330)
Skin Corrosion/Irritation	Category 2 (H315)
Serious Eye Damage/Eye Irritation	Category 2 (H319)
Skin Sensitization	Category 1 (H317)
Carcinogenicity	Category 1B (H350i)
Specific target organ toxicity - (single exposure)	Category 3 (H335)
Specific target organ toxicity - (repeated exposure)	Category 1 (H372)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H319 - Causes serious eye irritation
H330 - Fatal if inhaled
H315 - Causes skin irritation
H335 - May cause respiratory irritation
H301 - Toxic if swallowed
H372 - Causes damage to organs through prolonged or repeated exposure
H317 - May cause an allergic skin reaction
H350i - May cause cancer by inhalation

Precautionary Statements

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P260 - Do not breathe dust/fume/gas/mist/vapors/spray
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P302 + P352 - IF ON SKIN: Wash with plenty of soap and water
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P201 - Obtain special instructions before use

Additional EU labelling

Restricted to professional users

2.3. Other hazards

ALFAAS37055

SAFETY DATA SHEET

Beryllium disc, 0.02+/-0.002in thick, 0.900+/-0.003in dia

Revision Date 11-Jun-2025

In accordance with Annex XIII of the REACH Regulation, inorganic substances do not require assessment

This product does not contain any known or suspected endocrine disruptors

Section 3: Composition/information on ingredients

3.1. Substances

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Beryllium	7440-41-7	EEC No. 231-150-7	> 99	Acute Tox. 3 (H301) Acute Tox. 2 (H330) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Skin Sens. 1 (H317) Carc. 1B (H350i) STOT SE 3 (H335) STOT RE 1 (H372)

Full text of Hazard Statements: see section 16

Section 4: First aid measures

4.1. Description of first aid measures

General Advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Eye Contact	In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.
Ingestion	Do NOT induce vomiting. Call a physician or poison control center immediately.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

None reasonably foreseeable. May cause allergic skin reaction. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically.
---------------------------	------------------------

SAFETY DATA SHEET

Beryllium disc, 0.02+/-0.002in thick, 0.900+/-0.003in dia

Revision Date 11-Jun-2025

Section 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media

Dry chemical.

Extinguishing media which must not be used for safety reasons

Carbon dioxide (CO₂).

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors.

Hazardous Combustion Products

Beryllium oxide.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Avoid dust formation. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas.

6.2. Environmental precautions

Should not be released into the environment. Do not allow material to contaminate ground water system. Do not flush into surface water or sanitary sewer system.

6.3. Methods and material for containment and cleaning up

Sweep up and shovel into suitable containers for disposal. Avoid dust formation.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

Section 7: Handling and storage

7.1. Precautions for safe handling

Do not get in eyes, on skin, or on clothing. Wear personal protective equipment/face protection. Avoid dust formation. Use only under a chemical fume hood. Do not breathe (dust, vapor, mist, gas). Do not ingest. If swallowed then seek immediate medical assistance.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

SAFETY DATA SHEET

Beryllium disc, 0.02+/-0.002in thick, 0.900+/-0.003in dia

Revision Date 11-Jun-2025

Keep in a dry, cool and well-ventilated place. Keep container tightly closed.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Storage Class/LGK 6.1B

Switzerland - Storage of hazardous substances

Storage class - SC 6.1
<https://www.kvu.ch/de/themen/stoffe-und-produkte>
<https://www.kvu.ch/fr/themes/substances-et-produits>
<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

Section 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits

List source(s): **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund). **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC

Component	European Union	The United Kingdom	France	Belgium	Spain
Beryllium	TWA: 0.0002 mg/m ³ (8h) TWA: 0.0006 mg/m ³ (8h) Skin	STEL: 0.006 mg/m ³ 15 min TWA: 0.002 mg/m ³ 8 hr Carc.	TWA / VME: 0.0006 mg/m ³ (8 heures). restrictive limit	TWA: 0.00005 mg/m ³ 8 uren STEL: 0.01 mg/m ³ 15 minuten Huid	TWA / VLA-ED: 0.0002 mg/m ³ (8 horas)

Component	Italy	Germany	Portugal	The Netherlands	Finland
Beryllium	TWA: 0.0002 mg/m ³ 8 ore. Time Weighted Average TWA: 0.0006 mg/m ³ 8 ore. Time Weighted Average until July 11, 2026 Pelle	TWA: 0.00006 mg/m ³ (8 Stunden). AGW - exposure factor 1 TWA: 0.00014 mg/m ³ (8 Stunden). AGW - exposure factor 1	STEL: 0.01 mg/m ³ 15 minutos TWA: 0.0002 mg/m ³ 8 horas TWA: 0.0006 mg/m ³ 8 horas Pele	huid TWA: 0.0006 mg/m ³ 8 uren	TWA: 0.0001 mg/m ³ 8 tunteina TWA: 0.0006 mg/m ³ 8 tunteina STEL: 0.0004 mg/m ³ 15 minuutteina Iho

Component	Austria	Denmark	Switzerland	Poland	Norway
Beryllium	TRK-KZGW: 0.0024 mg/m ³ 15 Minuten TRK-TMW: 0.0006 mg/m ³ MAK-KZGW: 0.0002 mg/m ³ 15 Minuten MAK-TMW: 0.00002 mg/m ³ 8 Stunden	TWA: 0.00002 mg/m ³ 8 timer STEL: 0.00004 mg/m ³ 15 minutter	TWA: 0.0006 mg/m ³ 8 Stunden	TWA: 0.0002 mg/m ³ 8 godzinach	TWA: 0.0002 mg/m ³ 8 timer STEL: 0.0006 mg/m ³ 15 minutter. value calculated; valid until July 11, 2026 inhalable fraction

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Beryllium	TWA: 0.0006 mg/m ³	kože TWA-GVI: 0.002 mg/m ³ 8 satima.	TWA: 0.0002 mg/m ³ 8 hr. STEL: 0.0006 mg/m ³ 15 min Skin	TWA: 0.0002 mg/m ³	TWA: 0.0006 mg/m ³ 8 hodinách. Ceiling: 0.002 mg/m ³

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Beryllium	TWA: 0.0006 mg/m ³ 8		TWA: 0.0002 mg/m ³	TWA: 0.0006 mg/m ³ 8	TWA: 0.0002 mg/m ³ 8

ALFAAS37055

SAFETY DATA SHEET

Beryllium disc, 0.02+/-0.002in thick, 0.900+/-0.003in dia

Revision Date 11-Jun-2025

	tundides. valid until July 10, 2026 inhalable fraction			órában. AK lehetséges borön keresztüli felszívódás	klukkustundum. valid from July 12, 2026;irritates respiratory system inhalable fraction TWA: 0.0006 mg/m³ 8 klukkustundum. valid until July 11, 2026;irritates respiratory system inhalable fraction Skin notation Ceiling: 0.0004 mg/m³ valid from July 12, 2026;irritates respiratory system inhalable fraction Ceiling: 0.0012 mg/m³ valid until July 11, 2026;irritates respiratory system inhalable fraction
--	--	--	--	--	---

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Beryllium	TWA: 0.001 mg/m³ TWA: 0.0002 mg/m³	TWA: 0.0006 mg/m³ inhalable fraction IPRD substance may affect skin and respiratory tract			TWA: 0.0002 mg/m³ 8 ore

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Beryllium	TWA: 0.001 mg/m³ 0300 MAC: 0.003 mg/m³	TWA: 0.005 mg/m³ 8 hodinách treated metal and alloy TWA: 0.002 mg/m³ 8 hodinách others STEL: 0.025 mg/m³ 15 minútach treated metal and alloy STEL: 0.01 mg/m³ 15 minútach	TWA: 0.0006 mg/m³ 8 urah applies until July 11, 2026 inhalable fraction	TLV: 0.0002 mg/m³ 8 timmar. NGV TLV: 0.0006 mg/m³ 8 timmar. NGV	

Biological limit values

List source(s):

Component	Italy	Finland	Denmark	Bulgaria	Romania
Beryllium					Beryllium: 2 µg/L urine end of shift

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

No information available

Predicted No Effect Concentration (PNEC)

SAFETY DATA SHEET

Beryllium disc, 0.02+/-0.002in thick, 0.900+/-0.003in dia

Revision Date 11-Jun-2025

No information available.

8.2. Exposure controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Nitrile rubber	See manufacturers	-	EN 374	(minimum requirement)
Neoprene	recommendations			
PVC				
Natural rubber				

Skin and body protection Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Recommended Filter type: Particulates filter conforming to EN 143

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Recommended half mask:- Particle filtering: EN149:2001
When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls No information available.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State disc

Appearance Dark grey

Odor Odorless

Odor Threshold No data available

Melting Point/Range 1278 °C / 2332.4 °F

Softening Point No data available

Boiling Point/Range 2970 °C / 5378 °F @ 5 mmHg

SAFETY DATA SHEET

Beryllium disc, 0.02+/-0.002in thick, 0.900+/-0.003in dia

Revision Date 11-Jun-2025

Flammability (liquid)	Not applicable	Solid
Flammability (solid,gas)	No information available	
Explosion Limits	No data available	
Flash Point	No information available	Method - No information available
Autoignition Temperature	Not applicable	
Decomposition Temperature	No data available	
pH	No information available	Solid
Viscosity	Not applicable	
Water Solubility	Insoluble	
Solubility in other solvents	No information available	Solid
Partition Coefficient (n-octanol/water)		
Vapor Pressure	1.85 mmHg	
Density / Specific Gravity	No data available	Solid
Bulk Density	1.85 @ 20°C	
Vapor Density	Not applicable	
Particle characteristics	No data available	

9.2. Other information

Molecular Formula	Be
Molecular Weight	9.01
Evaporation Rate	Not applicable - Solid

Section 10: Stability and reactivity

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

10.4. Conditions to avoid

Incompatible products.

10.5. Incompatible materials

Acids. Bases. Halogens. Metals.

10.6. Hazardous decomposition products

Beryllium oxide.

Section 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;	
Oral	Category 3
Dermal	No data available
Inhalation	Category 2

SAFETY DATA SHEET

Beryllium disc, 0.02+/-0.002in thick, 0.900+/-0.003in dia

Revision Date 11-Jun-2025

(b) skin corrosion/irritation; Category 2

(c) serious eye damage/irritation; Category 2

(d) respiratory or skin sensitization;

Respiratory No data available
Skin Category 1

May cause sensitization by skin contact

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; Category 1B

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Beryllium	Carc Cat. 1B		Cat. 1	Group 1

(g) reproductive toxicity; No data available

(h) STOT-single exposure; Category 3

Results / Target organs Respiratory system.

(i) STOT-repeated exposure; Category 1

Route of exposure Inhalation
Target Organs Lungs.

(j) aspiration hazard; Not applicable
Solid

Symptoms / effects, both acute and delayed Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity effects May cause long-term adverse effects in the environment. Do not allow material to contaminate ground water system.

12.2. Persistence and degradability Product contains heavy metals. Discharge into the environment must be avoided. Special pre-treatment is necessary

SAFETY DATA SHEET

Beryllium disc, 0.02+/-0.002in thick, 0.900+/-0.003in dia

Revision Date 11-Jun-2025

Persistence	Insoluble in water, May persist.
Degradability	Not relevant for inorganic substances.
Degradation in sewage treatment plant	Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential May have some potential to bioaccumulate; Product has a high potential to bioconcentrate

12.4. Mobility in soil Spillage unlikely to penetrate soil Is not likely mobile in the environment due its low water solubility.

12.5. Results of PBT and vPvB assessment In accordance with Annex XIII of the REACH Regulation, inorganic substances do not require assessment.

12.6. Endocrine disrupting properties
Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects
Persistent Organic Pollutant This product does not contain any known or suspected substance
Ozone Depletion Potential This product does not contain any known or suspected substance

Section 13: Disposal considerations

13.1. Waste treatment methods

Waste from Residues/Unused Products	Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.
Contaminated Packaging	Dispose of this container to hazardous or special waste collection point.
European Waste Catalogue (EWC)	According to the European Waste Catalog, Waste Codes are not product specific, but application specific.
Other Information	Waste codes should be assigned by the user based on the application for which the product was used. Do not empty into drains.
Switzerland - Waste Ordinance	Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600 https://www.fedlex.admin.ch/eli/cc/2015/891/en

Section 14: Transport information

IMDG/IMO Not regulated

14.1. UN number
14.2. UN proper shipping name
14.3. Transport hazard class(es)
14.4. Packing group

ADR Not regulated

14.1. UN number
14.2. UN proper shipping name

SAFETY DATA SHEET

Beryllium disc, 0.02+/-0.002in thick, 0.900+/-0.003in dia

Revision Date 11-Jun-2025

14.3. Transport hazard class(es)

14.4. Packing group

IATA

Not regulated

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

14.5. Environmental hazards

No hazards identified

14.6. Special precautions for user

No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable, packaged goods

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Beryllium	7440-41-7	231-150-7	-	-	X	X	KE-02829	X	-

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Beryllium	7440-41-7	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Beryllium	7440-41-7	-	Use restricted. See entry 28. (see link for restriction details) Use restricted. See entry 75. (see link for restriction details)	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Beryllium	7440-41-7	Not applicable	Not applicable

SAFETY DATA SHEET

Beryllium disc, 0.02+/-0.002in thick, 0.900+/-0.003in dia

Revision Date 11-Jun-2025

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

Take note of Dir 76/769/EEC relating to restrictions on the marketing and use of certain dangerous substances and preparations

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Beryllium		Krebserzeugende Stoffe - Class I : 0.05 mg/m ³ (Massenkonzentration)

Component	France - INRS (Tables of occupational diseases)
Beryllium	Tableaux des maladies professionnelles (TMP) - RG 33

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has not been conducted

Section 16: Other information

Full text of H-Statements referred to under sections 2 and 3

H301 - Toxic if swallowed

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H330 - Fatal if inhaled

H335 - May cause respiratory irritation

H350i - May cause cancer by inhalation

H372 - Causes damage to organs through prolonged or repeated exposure

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

SAFETY DATA SHEET

Beryllium disc, 0.02+/-0.002in thick, 0.900+/-0.003in dia

Revision Date 11-Jun-2025

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Prepared By

Health, Safety and Environmental Department

Revision Date

11-Jun-2025

Revision Summary

Initial Release.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.

COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No 1907/2006 .

For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2, Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and Preparations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet