

Creation Date 21-May-2012

Revision Date 17-Jul-2025

Revision Number 13

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: **Aqualine™ Electrolyte AG (Halogen free anolyte for general use)**
Cat No. : **K/2520/08**
Synonyms Karl Fischer reagent

Unique Formula Identifier (UFI) **KJXH-J2AT-4X0S-UUR2**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

EU entity/business name
Thermo Fisher Scientific
Janssen Pharmaceuticaaan 3a
2440 Geel, Belgium

UK entity/business name
Fisher Scientific UK
Bishop Meadow Road, Loughborough,
Leicestershire LE11 5RG, United Kingdom

Swiss distributor - Fisher Scientific AG
Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
e-mail - infoch@thermofisher.com

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

Tel: 01509 231166
Chemtrec US: (800) 424-9300
Chemtrec EU: 001-703-527-3887

For customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

Poison Centre - Emergency information services

Ireland : National Poisons Information Centre (NPIC) -
01 809 2166 (8am-10pm, 7 days a week)
Malta : +356 2395 2000
Cyprus : +357 2240 5611

SAFETY DATA SHEET

Aqualine™ Electrolyte AG (Halogen free anolyte for general use)

Revision Date 17-Jul-2025

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Flammable liquids

Category 2 (H225)

Health hazards

Acute oral toxicity

Category 3 (H301)

Acute dermal toxicity

Category 3 (H311)

Acute Inhalation Toxicity - Vapors

Category 3 (H331)

Skin Corrosion/Irritation

Category 1 B (H314)

Serious Eye Damage/Eye Irritation

Category 1 (H318)

Specific target organ toxicity - (single exposure)

Category 1 (H370)

Specific target organ toxicity - (repeated exposure)

Category 2 (H373)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H314 - Causes severe skin burns and eye damage

H370 - Causes damage to organs

H373 - May cause damage to organs through prolonged or repeated exposure

H301 + H311 + H331 - Toxic if swallowed, in contact with skin or if inhaled

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/physician

SAFETY DATA SHEET

Aqualine™ Electrolyte AG (Halogen free anolyte for general use)

Revision Date 17-Jul-2025

2.3. Other hazards

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

Section 3: Composition/information on ingredients

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Methanol	67-56-1	200-659-6	50-75	Flam. Liq. 2 (H225) Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370)
2-Amino-2-methyl-1-propanol	124-68-5	EEC No. 204-709-8	10-20	Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Aquatic Chronic 3 (H412)
Pyridine, 2,4,6-trimethyl-	108-75-8	EEC No. 203-613-3	10-15	Flam Liq. 3 (H226) Acute Tox. 4 (H302) Acute Tox. 3 (H311) Acute Tox. 4 (H332) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) STOT SE 3 (H335)
Sulfur dioxide	7446-09-5	EEC No. 231-195-2	5-10	Press. Gas (H280) Skin Corr. 1B (H314) Eye Dam. 1 (H318) Acute Tox. 3 (H331) STOT SE 1 (H370)
Iodine	7553-56-2	231-442-4	5-10	Acute Tox. 4 (H302) Acute Tox. 4 (H312) Acute Tox. 4 (H332) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) STOT SE 3 (H335) STOT RE 1 (H372) Aquatic Acute 1 (H400)
p-Toluenesulfonic acid	104-15-4	EEC No. 203-180-0	0.1-1	Skin Corr. 1C (H314) Eye Dam. 1 (H318)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Methanol	STOT Single Exp. 1 :: >= 10 STOT Single Exp. 2 :: 3 - < 10	-	-
Iodine	-	1	-
p-Toluenesulfonic acid	STOT SE 3 (H335) :: C>=20%	-	-

Components	Reach Registration Number
Methanol	01-2119433307-44
2-Amino-2-methyl-1-propanol	01-2119475788-16
Sulfur dioxide	01-2119485028-34
Iodine	01-2119485285-30

Full text of Hazard Statements: see section 16

Section 4: First aid measures

SAFETY DATA SHEET

Aqualine™ Electrolyte AG (Halogen free anolyte for general use)

Revision Date 17-Jul-2025

4.1. Description of first aid measures

General Advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.
Ingestion	Do NOT induce vomiting. Call a physician or poison control center immediately.
Inhalation	If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Remove to fresh air. Immediate medical attention is required.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. Symptoms may be delayed.

Section 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Water may be ineffective.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂), Nitrogen oxides (NO_x), Hydrogen iodide, Formaldehyde, Sulfur oxides.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SAFETY DATA SHEET

Aqualine™ Electrolyte AG (Halogen free anolyte for general use)

Revision Date 17-Jul-2025

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

Section 7: Handling and storage

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area. Corrosives area.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Class 3

Switzerland - Storage of hazardous substances

Storage class - SC 3
<https://www.kvu.ch/de/themen/stoffe-und-produkte>
<https://www.kvu.ch/fr/themes/substances-et-produits>
<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

Section 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational

SAFETY DATA SHEET

Aqualine™ Electrolyte AG (Halogen free anolyte for general use)

Revision Date 17-Jul-2025

exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Methanol	TWA: 200 ppm 8 hr TWA: 260 mg/m ³ 8 hr Skin	WEL - TWA: 200 ppm TWA: 266 mg/m ³ TWA WEL - STEL: 250 ppm STEL: 333 mg/m ³ STEL	TWA / VME: 200 ppm (8 heures). restrictive limit TWA / VME: 260 mg/m ³ (8 heures). restrictive limit STEL / VLCT: 1000 ppm. restrictive limit: this value is not set by regulation and comes from a circular published by the Ministry of Labor. STEL / VLCT: 1300 mg/m ³ . restrictive limit: this value is not set by regulation and comes from a circular published by the Ministry of Labor. Peau	TWA: 200 ppm 8 uren TWA: 266 mg/m ³ 8 uren STEL: 250 ppm 15 minuten STEL: 333 mg/m ³ 15 minuten Huid	TWA / VLA-ED: 200 ppm (8 horas) TWA / VLA-ED: 266 mg/m ³ (8 horas) Piel
Sulfur dioxide	TWA: 1.3 mg/m ³ (8h) TWA: 0.5 ppm (8h) STEL: 2.7 mg/m ³ (15min) STEL: 1 ppm (15min)	STEL: 1 ppm 15 min STEL: 2.7 mg/m ³ 15 min TWA: 0.5 ppm 8 hr TWA: 1.3 mg/m ³ 8 hr	TWA / VME: 0.5 ppm (8 heures). TWA / VME: 1.3 mg/m ³ (8 heures). STEL / VLCT: 1 ppm. indicative limit STEL / VLCT: 2.7 mg/m ³ . indicative limit	TWA: 0.5 ppm 8 uren TWA: 1.3 mg/m ³ 8 uren STEL: 1 ppm 15 minuten STEL: 2.7 mg/m ³ 15 minuten	STEL / VLA-EC: 2 ppm (15 minutos). STEL / VLA-EC: 5.28 mg/m ³ (15 minutos). TWA / VLA-ED: 0.5 ppm (8 horas) TWA / VLA-ED: 1.32 mg/m ³ (8 horas)
Iodine		STEL: 0.1 ppm 15 min STEL: 1.1 mg/m ³ 15 min	STEL / VLCT: 0.1 ppm. STEL / VLCT: 1 mg/m ³ .	TWA: 0.01 ppm 8 uren TWA: 0.1 mg/m ³ 8 uren STEL: 0.1 ppm 15 minuten STEL: 1 mg/m ³ 15 minuten	STEL / VLA-EC: 0.1 ppm (15 minutos). STEL / VLA-EC: 1 mg/m ³ (15 minutos). TWA / VLA-ED: 0.01 ppm (8 horas) TWA / VLA-ED: 0.1 mg/m ³ (8 horas)

Component	Italy	Germany	Portugal	The Netherlands	Finland
Methanol	TWA: 200 ppm 8 ore. Time Weighted Average TWA: 260 mg/m ³ 8 ore. Time Weighted Average Pelle	100 ppm TWA MAK; 130 mg/m ³ TWA MAKSkin absorber	STEL: 250 ppm 15 minutos TWA: 200 ppm 8 horas TWA: 260 mg/m ³ 8 horas Pele	huid TWA: 100 ppm 8 uren TWA: 133 mg/m ³ 8 uren	TWA: 200 ppm 8 tunteina TWA: 270 mg/m ³ 8 tunteina STEL: 250 ppm 15 minuutteina STEL: 330 mg/m ³ 15 minuutteina Iho
2-Amino-2-methyl-1-propanol		TWA: 1 ppm (8 Stunden). AGW - exposure factor 2 TWA: 3.7 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 1 ppm (8 Stunden). MAK can occur as vapor and aerosol at the same time TWA: 3.7 mg/m ³ (8 Stunden). MAK can occur as vapor and aerosol at the same			

SAFETY DATA SHEET

Aqualine™ Electrolyte AG (Halogen free anolyte for general use)

Revision Date 17-Jul-2025

		time Höhepunkt: 2 ppm Höhepunkt: 7.4 mg/m ³ Haut			
Sulfur dioxide	TWA: 1.3 mg/m ³ 8 ore. Time Weighted Average TWA: 0.5 ppm 8 ore. Time Weighted Average STEL: 2.7 mg/m ³ 15 minuti. Short-term STEL: 1 ppm 15 minuti. Short-term	TWA: 1 ppm TWA: 2.5 mg/m ³	STEL: 1 ppm 15 minutos STEL: 2.7 mg/m ³ 15 minutos TWA: 0.5 ppm 8 horas TWA: 1.3 mg/m ³ 8 horas	STEL: 0.7 mg/m ³ MAC: 2 ppm MAC: 5 mg/m ³	TWA: 0.5 ppm 8 tunteina TWA: 1.3 mg/m ³ 8 tunteina STEL: 1 ppm 15 minuutteina STEL: 2.7 mg/m ³ 15 minuutteina
Iodine		Haut	STEL: 0.1 ppm 15 minutos TWA: 0.01 ppm 8 horas		STEL: 0.1 ppm 15 minuutteina STEL: 1.1 mg/m ³ 15 minuutteina Iho

Component	Austria	Denmark	Switzerland	Poland	Norway
Methanol	Haut MAK-KZGW: 800 ppm 15 Minuten MAK-KZGW: 1040 mg/m ³ 15 Minuten MAK-TMW: 200 ppm 8 Stunden MAK-TMW: 260 mg/m ³ 8 Stunden	TWA: 200 ppm 8 timer TWA: 260 mg/m ³ 8 timer STEL: 400 ppm 15 minutter STEL: 520 mg/m ³ 15 minutter Hud	Haut/Peau STEL: 400 ppm 15 Minuten STEL: 520 mg/m ³ 15 Minuten TWA: 200 ppm 8 Stunden TWA: 260 mg/m ³ 8 Stunden	STEL: 300 mg/m ³ 15 minutach TWA: 100 mg/m ³ 8 godzinach	TWA: 100 ppm 8 timer TWA: 130 mg/m ³ 8 timer STEL: 150 ppm 15 minutter. value calculated STEL: 162.5 mg/m ³ 15 minutter. value calculated Hud
2-Amino-2-methyl-1-propanol			Haut/Peau STEL: 4.8 ppm 15 Minuten STEL: 17.4 mg/m ³ 15 Minuten TWA: 2.4 ppm 8 Stunden TWA: 8.7 mg/m ³ 8 Stunden		
Sulfur dioxide	MAK-KZGW: 1 ppm 15 Minuten MAK-KZGW: 2.7 mg/m ³ 15 Minuten MAK-TMW: 0.5 ppm 8 Stunden MAK-TMW: 1.3 mg/m ³ 8 Stunden	TWA: 0.5 ppm 8 timer TWA: 1.3 mg/m ³ 8 timer STEL: 2.7 mg/m ³ 15 minutter STEL: 1 ppm 15 minutter	STEL: 1 ppm 15 Minuten STEL: 2.7 mg/m ³ 15 Minuten TWA: 0.5 ppm 8 Stunden TWA: 1.3 mg/m ³ 8 Stunden	STEL: 2.7 mg/m ³ 15 minutach TWA: 1.3 mg/m ³ 8 godzinach	TWA: 0.5 ppm 8 timer TWA: 1.3 mg/m ³ 8 timer STEL: 1 ppm 15 minutter. value from the regulation STEL: 2.7 mg/m ³ 15 minutter. value from the regulation
Iodine	Haut MAK-KZGW: 0.1 ppm 15 Minuten MAK-KZGW: 1 mg/m ³ 15 Minuten MAK-TMW: 0.1 ppm 8 Stunden MAK-TMW: 1 mg/m ³ 8 Stunden Ceiling: 0.1 ppm Ceiling: 1 mg/m ³	Ceiling: 0.1 ppm Ceiling: 1 mg/m ³	Haut/Peau STEL: 0.1 ppm 15 Minuten STEL: 1 mg/m ³ 15 Minuten TWA: 0.1 ppm 8 Stunden TWA: 1 mg/m ³ 8 Stunden	STEL: 1 mg/m ³ 15 minutach TWA: 0.5 mg/m ³ 8 godzinach	Ceiling: 0.1 ppm Ceiling: 1 mg/m ³

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Methanol	TWA: 200 ppm TWA: 260.0 mg/m ³ Skin notation	kože TWA-GVI: 200 ppm 8 satima. TWA-GVI: 260 mg/m ³ 8 satima.	TWA: 200 ppm 8 hr. TWA: 260 mg/m ³ 8 hr. STEL: 600 ppm 15 min STEL: 780 mg/m ³ 15 min Skin	Skin-potential for cutaneous absorption TWA: 200 ppm TWA: 260 mg/m ³	TWA: 250 mg/m ³ 8 hodinách. Potential for cutaneous absorption Ceiling: 1000 mg/m ³
Sulfur dioxide	TWA: 1.3 mg/m ³ TWA: 0.5 ppm STEL : 2.7 mg/m ³ STEL : 1 ppm	TWA-GVI: 0.5 ppm 8 satima. TWA-GVI: 1.3 mg/m ³ 8 satima. STEL-KGVI: 1 ppm 15	TWA: 0.5 ppm 8 hr. TWA: 1.3 mg/m ³ 8 hr. STEL: 2.7 mg/m ³ 15 min STEL: 1 ppm 15 min	STEL: 2.7 mg/m ³ STEL: 1 ppm TWA: 1.3 mg/m ³ TWA: 0.5 ppm	TWA: 1.3 mg/m ³ 8 hodinách. Ceiling: 2.7 mg/m ³

SAFETY DATA SHEET

Aqualine™ Electrolyte AG (Halogen free anolyte for general use)

Revision Date 17-Jul-2025

		minutama. STEL-KGVI: 2.7 mg/m ³ 15 minutama.			
Iodine	TWA: 3.0 mg/m ³	STEL-KGVI: 0.1 ppm 15 minutama. STEL-KGVI: 1.1 mg/m ³ 15 minutama.	TWA: 0.01 ppm 8 hr. inhalable fraction and vapour TWA: 0.01 mg/m ³ 8 hr. STEL: 0.1 ppm 15 min		TWA: 0.1 mg/m ³ 8 hodinách. Ceiling: 1 mg/m ³

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Methanol	Nahk TWA: 200 ppm 8 tundides. TWA: 250 mg/m ³ 8 tundides. STEL: 250 ppm 15 minutites. STEL: 350 mg/m ³ 15 minutites.	Skin notation TWA: 200 ppm 8 hr TWA: 260 mg/m ³ 8 hr	skin - potential for cutaneous absorption STEL: 250 ppm STEL: 325 mg/m ³ TWA: 200 ppm TWA: 260 mg/m ³	TWA: 260 mg/m ³ 8 órában. AK TWA: 200 ppm 8 órában. AK lehetséges borón keresztüli felszívódás	TWA: 200 ppm 8 klukkustundum. TWA: 260 mg/m ³ 8 klukkustundum. Skin notation Ceiling: 400 ppm Ceiling: 520 mg/m ³
Sulfur dioxide	TWA: 0.5 ppm 8 tundides. TWA: 1.3 mg/m ³ 8 tundides. STEL: 1 ppm 15 minutites. STEL: 2.7 mg/m ³ 15 minutites.	TWA: 1.3 mg/m ³ 8 hr TWA: 0.5 ppm 8 hr STEL: 2.7 mg/m ³ 15 min STEL: 1 ppm 15 min	STEL: 1 ppm STEL: 2.7 mg/m ³ TWA: 0.5 ppm TWA: 1.3 mg/m ³	STEL: 2.7 mg/m ³ 15 percekben. CK STEL: 1 ppm 15 percekben. CK TWA: 1.3 mg/m ³ 8 órában. AK TWA: 0.5 ppm 8 órában. AK	STEL: 1 ppm STEL: 2.7 mg/m ³ TWA: 0.5 ppm 8 klukkustundum. TWA: 1.3 mg/m ³ 8 klukkustundum.
Iodine	STEL: 0.1 ppm 15 minutites. STEL: 1 mg/m ³ 15 minutites.		STEL: 0.1 ppm STEL: 1 mg/m ³ TWA: 0.1 ppm TWA: 1 mg/m ³	STEL: 1 mg/m ³ 15 percekben. CK STEL: 0.1 ppm 15 percekben. CK TWA: 1 mg/m ³ 8 órában. AK TWA: 0.1 ppm 8 órában. AK lehetséges borón keresztüli felszívódás	STEL: 0.1 ppm STEL: 1 mg/m ³

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Methanol	skin - potential for cutaneous exposure TWA: 200 ppm TWA: 260 mg/m ³	TWA: 200 ppm IPRD TWA: 260 mg/m ³ IPRD Oda	Possibility of significant uptake through the skin TWA: 200 ppm 8 Stunden TWA: 260 mg/m ³ 8 Stunden	possibility of significant uptake through the skin TWA: 200 ppm TWA: 260 mg/m ³	Skin notation TWA: 200 ppm 8 ore TWA: 260 mg/m ³ 8 ore
Sulfur dioxide	STEL: 2.7 mg/m ³ STEL: 1 ppm TWA: 1.3 mg/m ³ TWA: 0.5 ppm	TWA: 1.3 mg/m ³ IPRD TWA: 0.5 ppm IPRD STEL: 2.7 mg/m ³ STEL: 1 ppm	TWA: 1.3 mg/m ³ 8 Stunden TWA: 0.5 ppm 8 Stunden STEL: 2.7 mg/m ³ 15 Minuten STEL: 1 ppm 15 Minuten	TWA: 0.5 ppm TWA: 1.3 mg/m ³ STEL: 1 ppm 15 minuti STEL: 2.7 mg/m ³ 15 minuti	TWA: 0.5 ppm 8 ore TWA: 1.3 mg/m ³ 8 ore STEL: 1 ppm 15 minute STEL: 2.7 mg/m ³ 15 minute
Iodine	TWA: 1 mg/m ³	Ceiling: 0.1 ppm Ceiling: 1 mg/m ³			TWA: 0.09 ppm 8 ore TWA: 0.5 mg/m ³ 8 ore STEL: 0.2 ppm 15 minute STEL: 1 mg/m ³ 15 minute

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Methanol	TWA: 5 mg/m ³ 1250 Skin notation MAC: 15 mg/m ³	Potential for cutaneous absorption TWA: 200 ppm TWA: 260 mg/m ³	TWA: 200 ppm 8 urah TWA: 260 mg/m ³ 8 urah Koža STEL: 800 ppm 15 minutah STEL: 1040 mg/m ³ 15 minutah	Indicative STEL: 250 ppm 15 minuter Indicative STEL: 350 mg/m ³ 15 minuter TLV: 200 ppm 8 timmar. NGV TLV: 250 mg/m ³ 8 timmar. NGV	Deri TWA: 200 ppm 8 saat TWA: 260 mg/m ³ 8 saat

SAFETY DATA SHEET

Aqualine™ Electrolyte AG (Halogen free anolyte for general use)

Revision Date 17-Jul-2025

				Hud	
2-Amino-2-methyl-1-propanol			TWA: 3.7 mg/m ³ 8 urah TWA: 1 ppm 8 urah Koža STEL: 2 ppm 15 minutah STEL: 7.4 mg/m ³ 15 minutah		
Sulfur dioxide	Skin notation MAC: 10 mg/m ³	Ceiling: 2.7 mg/m ³ TWA: 0.5 ppm TWA: 1.3 mg/m ³	TWA: 0.5 ppm 8 urah TWA: 1.3 mg/m ³ 8 urah STEL: 1 ppm 15 minutah STEL: 2.7 mg/m ³ 15 minutah	Binding STEL: 1 ppm 15 minuter Binding STEL: 2.7 mg/m ³ 15 minuter TLV: 0.5 ppm 8 timmar. NGV TLV: 1.3 mg/m ³ 8 timmar. NGV	
Iodine	Skin notation MAC: 1 mg/m ³	Ceiling: 1.1 mg/m ³ TWA: 0.1 ppm TWA: 1.1 mg/m ³		Binding STEL: 0.1 ppm 15 minuter Binding STEL: 1 mg/m ³ 15 minuter	

Biological limit values

List source(s):

Component	European Union	United Kingdom	France	Spain	Germany
Methanol			Methanol: urine end of shift	Methanol: 15 mg/L urine end of shift	Methanol: 15 mg/L urine (end of shift) Methanol: 15 mg/L urine (for long-term exposures: at the end of the shift after several shifts)

Component	Italy	Finland	Denmark	Bulgaria	Romania
Methanol					Methanol: 6 mg/L urine end of shift

Component	Gibraltar	Latvia	Slovak Republic	Luxembourg	Turkey
Methanol			Methanol: 30 mg/L urine end of exposure or work shift Methanol: 30 mg/L urine after all work shifts for long-term exposure		

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Methanol 67-56-1 (50-75)		DNEL = 20mg/kg bw/day		DNEL = 20mg/kg bw/day
2-Amino-2-methyl-1-propanol				DNEL = 7.3mg/kg

SAFETY DATA SHEET

Aqualine™ Electrolyte AG (Halogen free anolyte for general use)

Revision Date 17-Jul-2025

124-68-5 (10-20)				bw/day
Iodine 7553-56-2 (5-10)				DNEL = 0.01mg/kg bw/day
p-Toluenesulfonic acid 104-15-4 (0.1-1)				DNEL = 7.6mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Methanol 67-56-1 (50-75)	DNEL = 130mg/m ³	DNEL = 130mg/m ³	DNEL = 130mg/m ³	DNEL = 130mg/m ³
2-Amino-2-methyl-1-propanol 124-68-5 (10-20)				DNEL = 6.5mg/m ³
Sulfur dioxide 7446-09-5 (5-10)	DNEL = 2.7mg/m ³		DNEL = 2.7mg/m ³	
Iodine 7553-56-2 (5-10)				DNEL = 0.07mg/m ³
p-Toluenesulfonic acid 104-15-4 (0.1-1)				DNEL = 53.6mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Methanol 67-56-1 (50-75)	PNEC = 20.8mg/L	PNEC = 77mg/kg sediment dw	PNEC = 1540mg/L	PNEC = 100mg/L	PNEC = 100mg/kg soil dw
2-Amino-2-methyl-1-propanol 124-68-5 (10-20)	PNEC = 0.188mg/L	PNEC = 0.71mg/kg sediment dw	PNEC = 1.88mg/L	PNEC = 10mg/L	PNEC = 0.03mg/kg soil dw
Iodine 7553-56-2 (5-10)	PNEC = 18.13µg/L	PNEC = 3.99mg/kg sediment dw		PNEC = 11mg/L	PNEC = 5.95mg/kg soil dw
p-Toluenesulfonic acid 104-15-4 (0.1-1)	PNEC = 0.073mg/L	PNEC = 0.0577mg/kg sediment dw	PNEC = 0.73mg/L	PNEC = 58mg/L	PNEC = 0.016mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Methanol 67-56-1 (50-75)	PNEC = 2.08mg/L	PNEC = 7.7mg/kg sediment dw			
2-Amino-2-methyl-1-propanol 124-68-5 (10-20)	PNEC = 0.0188mg/L	PNEC = 0.071mg/kg sediment dw			
Iodine 7553-56-2 (5-10)	PNEC = 60.01µg/L	PNEC = 20.22mg/kg sediment dw			
p-Toluenesulfonic acid 104-15-4 (0.1-1)	PNEC = 0.0073mg/L	PNEC = 0.00577mg/kg sediment dw			

8.2. Exposure controls

Engineering Measures

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

SAFETY DATA SHEET

Aqualine™ Electrolyte AG (Halogen free anolyte for general use)

Revision Date 17-Jul-2025

Personal protective equipment

Eye Protection Goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Viton (R)	See manufacturers recommendations	-	EN 374	(minimum requirement)

Skin and body protection Wear appropriate protective gloves and clothing to prevent skin exposure.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Recommended Filter type: low boiling organic solvent Type AX Brown conforming to EN371

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141
When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls Prevent product from entering drains. Do not allow material to contaminate ground water system.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance	Colorless	
Odor	Alcohol-like	
Odor Threshold	No data available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flammability (liquid)	Highly flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Flash Point	10 °C / 50 °F	Method - No information available
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
pH	No information available	
Viscosity	No data available	
Water Solubility	Miscible	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Methanol	-0.74	
2-Amino-2-methyl-1-propanol	-0.63	

SAFETY DATA SHEET

Aqualine™ Electrolyte AG (Halogen free anolyte for general use)

Revision Date 17-Jul-2025

Iodine	2.49	
p-Toluenesulfonic acid	0.784	
Vapor Pressure	No data available	
Density / Specific Gravity	0.94	
Bulk Density	Not applicable	Liquid
Vapor Density	No data available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

Explosive Properties Vapors may form explosive mixtures with air

Section 10: Stability and reactivity

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization Hazardous polymerization does not occur.
Hazardous Reactions None under normal processing.

10.4. Conditions to avoid

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents. Strong bases.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂). Nitrogen oxides (NO_x). Hydrogen iodide. Formaldehyde. Sulfur oxides.

Section 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral	Category 3
Dermal	Category 3
Inhalation	Category 3

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methanol	LD50 = 1187 – 2769 mg/kg (Rat)	LD50 = 17100 mg/kg (Rabbit)	LC50 = 128.2 mg/L (Rat) 4 h
2-Amino-2-methyl-1-propanol	LD50 = 2900 mg/kg (Rat)	>2000 mg/kg (Rabbit)	-
Pyridine, 2,4,6-trimethyl-	400 mg/kg (Rat)	1000 mg/kg (Guinea Pig)	-
Sulfur dioxide	-	-	Per CGA P-20: 2500 ppm/1hr (Rat)
Iodine	315 mg/kg (Rat)	1425 mg/kg (Rabbit)	4.588 mg/L 4h (Rat)

SAFETY DATA SHEET

Aqualine™ Electrolyte AG (Halogen free anolyte for general use)

Revision Date 17-Jul-2025

p-Toluenesulfonic acid	LD50 = 1410 mg/kg (Rat)	-	-
------------------------	---------------------------	---	---

(b) skin corrosion/irritation; Category 1 B

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;

Respiratory

No data available

Skin

No data available

Component	Test method	Test species	Study result
Methanol 67-56-1 (50-75)	OECD Test Guideline 406 Guinea Pig Maximisation Test (GPMT)	guinea pig	non-sensitising
Iodine 7553-56-2 (5-10)	OECD Test Guideline 429 Local Lymph Node Assay	mouse	non-sensitising

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; No data available

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; No data available

Component	Test method	Test species / Duration	Study result
Methanol 67-56-1 (50-75)	OECD Test Guideline 416	Rat / Inhalation 2 Generation	NOAEC = 1.3 mg/l (air)

(h) STOT-single exposure; Category 1

Results / Target organs

Optic nerve, Central nervous system (CNS).

(i) STOT-repeated exposure; Category 2

Target Organs

Thyroid, Central nervous system (CNS).

(j) aspiration hazard; No data available

Symptoms / effects, both acute and delayed

Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation.

11.2. Information on other hazards

Endocrine Disrupting Properties

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity effects

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

SAFETY DATA SHEET

Aqualine™ Electrolyte AG (Halogen free anolyte for general use)

Revision Date 17-Jul-2025

environment. The product contains following substances which are hazardous for the environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Methanol	Pimephales promelas: LC50 > 10000 mg/L 96h	EC50 > 10000 mg/L 24h	
2-Amino-2-methyl-1-propanol	LC50: = 190 mg/L, 96h static (Lepomis macrochirus)	EC50: = 193 mg/L, 48h (Daphnia magna)	EC50: = 520 mg/L, 72h (Desmodesmus subspicatus)
Iodine	LC50 = 1.67 mg/L 96h	EC50 = 0.55 mg/L 48h	EC50 = 0.13 mg/L 72h
p-Toluenesulfonic acid			EC50 = 245 g/L 24h

Component	Microtox	M-Factor
Methanol	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	
2-Amino-2-methyl-1-propanol	EC50: = 342.9 mg/L, 3 h (Activated Sludge) OECD 209	
Iodine	EC50 = 280 mg/L 3h	1

12.2. Persistence and degradability

Persistence Miscible with water, Persistence is unlikely, based on information available.

Component	Degradability
Methanol 67-56-1 (50-75)	DT50 ~ 17.2d >94% after 20d

Degradation in sewage treatment plant Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Methanol	-0.74	<10 dimensionless
2-Amino-2-methyl-1-propanol	-0.63	<1 dimensionless
Iodine	2.49	No data available
p-Toluenesulfonic acid	0.784	No data available

12.4. Mobility in soil

The product is water soluble, and may spread in water systems . Will likely be mobile in the environment due to its water solubility. Highly mobile in soils

12.5. Results of PBT and vPvB assessment

No data available for assessment.

12.6. Endocrine disrupting properties

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance
This product does not contain any known or suspected substance

Section 13: Disposal considerations

13.1. Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

SAFETY DATA SHEET

Aqualine™ Electrolyte AG (Halogen free anolyte for general use)

Revision Date 17-Jul-2025

Contaminated Packaging	Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.
European Waste Catalogue (EWC)	According to the European Waste Catalog, Waste Codes are not product specific, but application specific.
Other Information	Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms.
Switzerland - Waste Ordinance	Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600 https://www.fedlex.admin.ch/eli/cc/2015/891/en

Section 14: Transport information

IMDG/IMO

14.1. UN number	UN1992
14.2. UN proper shipping name	FLAMMABLE LIQUID, TOXIC, N.O.S.
Technical Shipping Name	(Contains methanol and 2,4,6-collidine)
14.3. Transport hazard class(es)	3
Subsidiary Hazard Class	6.1
14.4. Packing group	II

ADR

14.1. UN number	UN1992
14.2. UN proper shipping name	FLAMMABLE LIQUID, TOXIC, N.O.S.
Technical Shipping Name	(Contains methanol and 2,4,6-collidine)
14.3. Transport hazard class(es)	3
Subsidiary Hazard Class	6.1
14.4. Packing group	II

IATA

14.1. UN number	UN1992
14.2. UN proper shipping name	FLAMMABLE LIQUID, TOXIC, N.O.S.
Technical Shipping Name	(Contains methanol and 2,4,6-collidine)
14.3. Transport hazard class(es)	3
Subsidiary Hazard Class	6.1
14.4. Packing group	II

14.5. Environmental hazards	No hazards identified
14.6. Special precautions for user	No special precautions required.
14.7. Maritime transport in bulk according to IMO instruments	Not applicable, packaged goods

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

SAFETY DATA SHEET

Aqualine™ Electrolyte AG (Halogen free anolyte for general use)

Revision Date 17-Jul-2025

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Methanol	67-56-1	200-659-6	-	-	X	X	KE-23193	X	X
2-Amino-2-methyl-1-propanol	124-68-5	204-709-8	-	-	X	X	KE-01473	X	X
Pyridine, 2,4,6-trimethyl-	108-75-8	203-613-3	-	-	X	X	-	X	X
Sulfur dioxide	7446-09-5	231-195-2	-	-	X	X	KE-32567	X	X
Iodine	7553-56-2	231-442-4	-	-	X	X	KE-21023	X	-
p-Toluenesulfonic acid	104-15-4	203-180-0	-	-	X	X	KE-23476	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Methanol	67-56-1	X	ACTIVE	X	-	X	X	X
2-Amino-2-methyl-1-propanol	124-68-5	X	ACTIVE	X	-	X	X	X
Pyridine, 2,4,6-trimethyl-	108-75-8	X	ACTIVE	X	-	X	X	X
Sulfur dioxide	7446-09-5	X	ACTIVE	X	-	X	X	X
Iodine	7553-56-2	X	ACTIVE	X	-	X	X	X
p-Toluenesulfonic acid	104-15-4	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Methanol	67-56-1	-	Use restricted. See entry 69. (see link for restriction details) Use restricted. See entry 75. (see link for restriction details)	-
2-Amino-2-methyl-1-propanol	124-68-5	-	Use restricted. See entry 75. (see link for restriction details)	-
Pyridine, 2,4,6-trimethyl-	108-75-8	-	-	-
Sulfur dioxide	7446-09-5	-	Use restricted. See entry 75. (see link for restriction details)	-
Iodine	7553-56-2	-	Use restricted. See entry 75. (see link for restriction details)	-
p-Toluenesulfonic acid	104-15-4	-	Use restricted. See entry 75. (see link for restriction details)	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements

SAFETY DATA SHEET

Aqualine™ Electrolyte AG (Halogen free anolyte for general use)

Revision Date 17-Jul-2025

Methanol	67-56-1	500 tonne	5000 tonne
2-Amino-2-methyl-1-propanol	124-68-5	Not applicable	Not applicable
Pyridine, 2,4,6-trimethyl-	108-75-8	Not applicable	Not applicable
Sulfur dioxide	7446-09-5	Not applicable	Not applicable
Iodine	7553-56-2	Not applicable	Not applicable
p-Toluenesulfonic acid	104-15-4	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 2 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Methanol	WGK 2	Class I : 20 mg/m³ (Massenkonzentration)
2-Amino-2-methyl-1-propanol	WGK1	
Sulfur dioxide	WGK1	
Iodine	WGK2	
p-Toluenesulfonic acid	WGK1	

Component	France - INRS (Tables of occupational diseases)
Methanol	Tableaux des maladies professionnelles (TMP) - RG 84

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Methanol 67-56-1 (50-75)	Prohibited and Restricted Substances	Group I	
Iodine 7553-56-2 (5-10)	Prohibited and Restricted Substances		
p-Toluenesulfonic acid 104-15-4 (0.1-1)	Prohibited and Restricted Substances		

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

Section 16: Other information

SAFETY DATA SHEET

Aqualine™ Electrolyte AG (Halogen free anolyte for general use)

Revision Date 17-Jul-2025

Full text of H-Statements referred to under sections 2 and 3

H301 - Toxic if swallowed
H311 - Toxic in contact with skin
H331 - Toxic if inhaled
H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage
H370 - Causes damage to organs
H373 - May cause damage to organs through prolonged or repeated exposure
H225 - Highly flammable liquid and vapor
H226 - Flammable liquid and vapor
H302 - Harmful if swallowed
H312 - Harmful in contact with skin
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H332 - Harmful if inhaled
H335 - May cause respiratory irritation
H372 - Causes damage to organs through prolonged or repeated exposure
H400 - Very toxic to aquatic life
H412 - Harmful to aquatic life with long lasting effects

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data

Health Hazards Calculation method

Environmental hazards Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

SAFETY DATA SHEET

Aqualine™ Electrolyte AG (Halogen free anolyte for general use)

Revision Date 17-Jul-2025

Creation Date	21-May-2012
Revision Date	17-Jul-2025
Revision Summary	SDS sections updated, 3, 5, 8, 10.

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.
COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No
1907/2006 .**

**For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2,
Number 3, Chemo (SR 813.11 - Ordinance on Protection against Dangerous Substances and
Preparations).**

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet