

Creation Date 06-Oct-2011

Revision Date 08-Jul-2025

Revision Number 10

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: **Aqualine™ Solvent CM**
Cat No. : **K/2110/15, K/2110/17**

Unique Formula Identifier (UFI) **H2QK-X2MV-NX01-VMS1**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

EU entity/business name
Thermo Fisher Scientific
Janssen Pharmaceuticaaan 3a
2440 Geel, Belgium

UK entity/business name
Fisher Scientific UK
Bishop Meadow Road, Loughborough,
Leicestershire LE11 5RG, United Kingdom

Swiss distributor - Fisher Scientific AG
Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
e-mail - infoch@thermofisher.com

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

Tel: 01509 231166
Chemtrec US: (800) 424-9300
Chemtrec EU: 001-703-527-3887

For customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

Poison Centre - Emergency information services

Ireland : National Poisons Information Centre (NPIC) -
01 809 2166 (8am-10pm, 7 days a week)
Malta : +356 2395 2000
Cyprus : +357 2240 5611

Section 2: HAZARDS IDENTIFICATION

SAFETY DATA SHEET

Aqualine™ Solvent CM

Revision Date 08-Jul-2025

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Flammable liquids

Category 2 (H225)

Health hazards

Acute oral toxicity

Category 3 (H301)

Acute dermal toxicity

Category 3 (H311)

Acute Inhalation Toxicity - Vapors

Category 3 (H331)

Skin Corrosion/Irritation

Category 1 (H314) B

Serious Eye Damage/Eye Irritation

Category 1 (H318)

Carcinogenicity

Category 2 (H351)

Reproductive Toxicity

Category 1B (H360D)

Specific target organ toxicity - (single exposure)

Category 1 (H370)

Specific target organ toxicity - (repeated exposure)

Category 3 (H336)

Category 1 (H372)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H314 - Causes severe skin burns and eye damage

H370 - Causes damage to organs

H336 - May cause drowsiness or dizziness

H351 - Suspected of causing cancer

H360D - May damage the unborn child

H372 - Causes damage to organs through prolonged or repeated exposure

H301 + H311 + H331 - Toxic if swallowed, in contact with skin or if inhaled

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

SAFETY DATA SHEET

Aqualine™ Solvent CM

Revision Date 08-Jul-2025

easy to do. Continue rinsing
P310 - Immediately call a POISON CENTER or doctor/physician

Additional EU labelling

Restricted to professional users
For use in industrial installations only

2.3. Other hazards

Toxic to terrestrial vertebrates
This product does not contain any known or suspected endocrine disruptors

Section 3: Composition/information on ingredients

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Chloroform	67-66-3	200-663-8	50 - 75	Acute Tox. 4 (H302) Acute Tox. 3 (H331) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) STOT SE 3 (H336) Carc. 2 (H351) Repr. 2 (H361d) STOT RE 1 (H372)
Methanol	67-56-1	200-659-6	20 - 40	Flam. Liq. 2 (H225) Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370)
Sulfur dioxide	7446-09-5	EEC No. 231-195-2	5 - 10	Press. Gas (H280) Skin Corr. 1B (H314) Eye Dam. 1 (H318) Acute Tox. 3 (H331) STOT SE 1 (H370)
1-Imidazole	288-32-4	EEC No. 206-019-2	2.5 - 5	Acute Tox. 4 (H302) Skin Corr. 1C (H314) Eye Dam. 1 (H318) Repr. 1B (H360D)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Chloroform	STOT RE 2 : C ≥ 5 %	-	-
Methanol	STOT Single Exp. 1 :: ≥ 10 STOT Single Exp. 2 :: 3 - < 10	-	-

Components	Reach Registration Number
Chloroform	01-2119486657-20
Methanol	01-2119433307-44
Sulfur dioxide	01-2119485028-34
1-Imidazole	01-2119485825-24

Full text of Hazard Statements: see section 16

Section 4: First aid measures

4.1. Description of first aid measures

SAFETY DATA SHEET

Aqualine™ Solvent CM

Revision Date 08-Jul-2025

General Advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.
Ingestion	Do NOT induce vomiting. Call a physician or poison control center immediately.
Inhalation	If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Remove to fresh air. Immediate medical attention is required.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. Symptoms may be delayed.

Section 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Do not use water jetstream.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂), Nitrogen oxides (NO_x), Sulfur oxides, Hydrogen chloride gas.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

Section 6: ACCIDENTAL RELEASE MEASURES

SAFETY DATA SHEET

Aqualine™ Solvent CM

Revision Date 08-Jul-2025

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Should not be released into the environment. Do not flush into surface water or sanitary sewer system.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

Section 7: Handling and storage

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Flammables area. Keep away from heat, sparks and flame. Do not store in metal containers. Corrosives area.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Class 3

Switzerland - Storage of hazardous substances

Storage class - SC 3
<https://www.kvu.ch/de/themen/stoffe-und-produkte>
<https://www.kvu.ch/fr/themes/substances-et-produits>
<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

Section 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of

SAFETY DATA SHEET

Aqualine™ Solvent CM

Revision Date 08-Jul-2025

Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Chloroform	TWA: 2 ppm 8 hr TWA: 10 mg/m ³ 8 hr Possibility of significant uptake through the skin	TWA: 2 ppm TWA: 9.9 mg/m ³ STEL: 6 ppm STEL: 29.7 mg/m ³	TWA / VME: 2 ppm (8 heures). restrictive limit TWA / VME: 10 mg/m ³ (8 heures). restrictive limit STEL / VLCT: 50 ppm. STEL / VLCT: 250 mg/m ³ . Peau	TWA: 2 ppm 8 uren TWA: 10 mg/m ³ 8 uren Huid	TWA / VLA-ED: 2 ppm (8 horas) TWA / VLA-ED: 10 mg/m ³ (8 horas) Piel
Methanol	TWA: 200 ppm 8 hr TWA: 260 mg/m ³ 8 hr Skin	WEL - TWA: 200 ppm TWA: 266 mg/m ³ TWA WEL - STEL: 250 ppm STEL: 333 mg/m ³ STEL	TWA / VME: 200 ppm (8 heures). restrictive limit TWA / VME: 260 mg/m ³ (8 heures). restrictive limit STEL / VLCT: 1000 ppm. restrictive limit: this value is not set by regulation and comes from a circular published by the Ministry of Labor. STEL / VLCT: 1300 mg/m ³ . restrictive limit: this value is not set by regulation and comes from a circular published by the Ministry of Labor. Peau	TWA: 200 ppm 8 uren TWA: 266 mg/m ³ 8 uren STEL: 250 ppm 15 minuten STEL: 333 mg/m ³ 15 minuten Huid	TWA / VLA-ED: 200 ppm (8 horas) TWA / VLA-ED: 266 mg/m ³ (8 horas) Piel
Sulfur dioxide	TWA: 1.3 mg/m ³ (8h) TWA: 0.5 ppm (8h) STEL: 2.7 mg/m ³ (15min) STEL: 1 ppm (15min)	STEL: 1 ppm 15 min STEL: 2.7 mg/m ³ 15 min TWA: 0.5 ppm 8 hr TWA: 1.3 mg/m ³ 8 hr	TWA / VME: 0.5 ppm (8 heures). TWA / VME: 1.3 mg/m ³ (8 heures). STEL / VLCT: 1 ppm. indicative limit STEL / VLCT: 2.7 mg/m ³ . indicative limit	TWA: 0.5 ppm 8 uren TWA: 1.3 mg/m ³ 8 uren STEL: 1 ppm 15 minuten STEL: 2.7 mg/m ³ 15 minuten	STEL / VLA-EC: 2 ppm (15 minutos). STEL / VLA-EC: 5.28 mg/m ³ (15 minutos). TWA / VLA-ED: 0.5 ppm (8 horas) TWA / VLA-ED: 1.32 mg/m ³ (8 horas)

Component	Italy	Germany	Portugal	The Netherlands	Finland
Chloroform	TWA: 2 ppm 8 ore. Media Ponderata nel Tempo TWA: 10 mg/m ³ 8 ore. Media Ponderata nel Tempo Pelle	0.5 ppm TWA MAK 2.5 mg/m ³ TWA MAK	TWA: 2 ppm 8 horas TWA: 10 mg/m ³ 8 horas Pele	STEL: 25 mg/m ³ 15 minuten TWA: 5 mg/m ³ 8 uren	TWA: 2 ppm 8 tunteina TWA: 10 mg/m ³ 8 tunteina STEL: 4 ppm 15 minuutteina STEL: 20 mg/m ³ 15 minuutteina Iho
Methanol	TWA: 200 ppm 8 ore. Time Weighted Average TWA: 260 mg/m ³ 8 ore. Time Weighted Average Pelle	100 ppm TWA MAK; 130 mg/m ³ TWA MAKSkin absorber	STEL: 250 ppm 15 minutos TWA: 200 ppm 8 horas TWA: 260 mg/m ³ 8 horas Pele	huid TWA: 100 ppm 8 uren TWA: 133 mg/m ³ 8 uren	TWA: 200 ppm 8 tunteina TWA: 270 mg/m ³ 8 tunteina STEL: 250 ppm 15 minuutteina STEL: 330 mg/m ³ 15 minuutteina Iho
Sulfur dioxide	TWA: 1.3 mg/m ³ 8 ore. Time Weighted Average TWA: 0.5 ppm 8 ore. Time Weighted Average STEL: 2.7 mg/m ³ 15 minuti. Short-term STEL: 1 ppm 15 minuti. Short-term	TWA: 1 ppm TWA: 2.5 mg/m ³	STEL: 1 ppm 15 minutos STEL: 2.7 mg/m ³ 15 minutos TWA: 0.5 ppm 8 horas TWA: 1.3 mg/m ³ 8 horas	STEL: 0.7 mg/m ³ MAC: 2 ppm MAC: 5 mg/m ³	TWA: 0.5 ppm 8 tunteina TWA: 1.3 mg/m ³ 8 tunteina STEL: 1 ppm 15 minuutteina STEL: 2.7 mg/m ³ 15 minuutteina

Component	Austria	Denmark	Switzerland	Poland	Norway
-----------	---------	---------	-------------	--------	--------

SAFETY DATA SHEET

Aqualine™ Solvent CM

Revision Date 08-Jul-2025

Chloroform	Haut MAK-TMW: 2 ppm 8 Stunden MAK-TMW: 10 mg/m ³ 8 Stunden	TWA: 2 ppm 8 timer TWA: 10 mg/m ³ 8 timer Hud	Haut/Peau STEL: 1 ppm 15 Minuten STEL: 5 mg/m ³ 15 Minuten TWA: 0.5 ppm 8 Stunden TWA: 2.5 mg/m ³ 8 Stunden	TWA: 8 mg/m ³ 8 godzinach	TWA: 2 ppm 8 timer TWA: 10 mg/m ³ 8 timer 4 ppm STEL (value calculated) 15 mg/m ³ STEL (value calculated) Hud
Methanol	Haut MAK-KZGW: 800 ppm 15 Minuten MAK-KZGW: 1040 mg/m ³ 15 Minuten MAK-TMW: 200 ppm 8 Stunden MAK-TMW: 260 mg/m ³ 8 Stunden	TWA: 200 ppm 8 timer TWA: 260 mg/m ³ 8 timer STEL: 400 ppm 15 minutter STEL: 520 mg/m ³ 15 minutter Hud	Haut/Peau STEL: 400 ppm 15 Minuten STEL: 520 mg/m ³ 15 Minuten TWA: 200 ppm 8 Stunden TWA: 260 mg/m ³ 8 Stunden	STEL: 300 mg/m ³ 15 minutach TWA: 100 mg/m ³ 8 godzinach	TWA: 100 ppm 8 timer TWA: 130 mg/m ³ 8 timer STEL: 150 ppm 15 minutter. value calculated STEL: 162.5 mg/m ³ 15 minutter. value calculated Hud
Sulfur dioxide	MAK-KZGW: 1 ppm 15 Minuten MAK-KZGW: 2.7 mg/m ³ 15 Minuten MAK-TMW: 0.5 ppm 8 Stunden MAK-TMW: 1.3 mg/m ³ 8 Stunden	TWA: 0.5 ppm 8 timer TWA: 1.3 mg/m ³ 8 timer STEL: 2.7 mg/m ³ 15 minutter STEL: 1 ppm 15 minutter	STEL: 1 ppm 15 Minuten STEL: 2.7 mg/m ³ 15 Minuten TWA: 0.5 ppm 8 Stunden TWA: 1.3 mg/m ³ 8 Stunden	STEL: 2.7 mg/m ³ 15 minutach TWA: 1.3 mg/m ³ 8 godzinach	TWA: 0.5 ppm 8 timer TWA: 1.3 mg/m ³ 8 timer STEL: 1 ppm 15 minutter. value from the regulation STEL: 2.7 mg/m ³ 15 minutter. value from the regulation

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Chloroform	TWA: 2 ppm TWA: 10.0 mg/m ³ Skin notation	kože TWA-GVI: 2 ppm 8 satima. TWA-GVI: 10 mg/m ³ 8 satima.	TWA: 2 ppm 8 hr. TWA: 9.8 mg/m ³ 8 hr. STEL: 6 ppm 15 min STEL: 29.4 mg/m ³ 15 min Skin	Skin-potential for cutaneous absorption TWA: 2 ppm TWA: 10 mg/m ³	TWA: 10 mg/m ³ 8 hodinách. Potential for cutaneous absorption Ceiling: 20 mg/m ³
Methanol	TWA: 200 ppm TWA: 260.0 mg/m ³ Skin notation	kože TWA-GVI: 200 ppm 8 satima. TWA-GVI: 260 mg/m ³ 8 satima.	TWA: 200 ppm 8 hr. TWA: 260 mg/m ³ 8 hr. STEL: 600 ppm 15 min STEL: 780 mg/m ³ 15 min Skin	Skin-potential for cutaneous absorption TWA: 200 ppm TWA: 260 mg/m ³	TWA: 250 mg/m ³ 8 hodinách. Potential for cutaneous absorption Ceiling: 1000 mg/m ³
Sulfur dioxide	TWA: 1.3 mg/m ³ TWA: 0.5 ppm STEL : 2.7 mg/m ³ STEL : 1 ppm	TWA-GVI: 0.5 ppm 8 satima. TWA-GVI: 1.3 mg/m ³ 8 satima. STEL-KGVI: 1 ppm 15 minutama. STEL-KGVI: 2.7 mg/m ³ 15 minutama.	TWA: 0.5 ppm 8 hr. TWA: 1.3 mg/m ³ 8 hr. STEL: 2.7 mg/m ³ 15 min STEL: 1 ppm 15 min	STEL: 2.7 mg/m ³ STEL: 1 ppm TWA: 1.3 mg/m ³ TWA: 0.5 ppm	TWA: 1.3 mg/m ³ 8 hodinách. Ceiling: 2.7 mg/m ³

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Chloroform	Nahk TWA: 2 ppm 8 tundides. TWA: 10 mg/m ³ 8 tundides.	Skin notation TWA: 2 ppm 8 hr TWA: 10 mg/m ³ 8 hr	TWA: 10 ppm TWA: 50 mg/m ³	TWA: 10 mg/m ³ 8 órában. AK	TWA: 2 ppm 8 klukkustundum. TWA: 10 mg/m ³ 8 klukkustundum. Skin notation Ceiling: 4 ppm Ceiling: 20 mg/m ³
Methanol	Nahk TWA: 200 ppm 8 tundides. TWA: 250 mg/m ³ 8 tundides. STEL: 250 ppm 15 minutites. STEL: 350 mg/m ³ 15 minutites.	Skin notation TWA: 200 ppm 8 hr TWA: 260 mg/m ³ 8 hr	skin - potential for cutaneous absorption STEL: 250 ppm STEL: 325 mg/m ³ TWA: 200 ppm TWA: 260 mg/m ³	TWA: 260 mg/m ³ 8 órában. AK TWA: 200 ppm 8 órában. AK lehetséges borón keresztül felszívódás	TWA: 200 ppm 8 klukkustundum. TWA: 260 mg/m ³ 8 klukkustundum. Skin notation Ceiling: 400 ppm Ceiling: 520 mg/m ³
Sulfur dioxide	TWA: 0.5 ppm 8 tundides. TWA: 1.3 mg/m ³ 8	TWA: 1.3 mg/m ³ 8 hr TWA: 0.5 ppm 8 hr STEL: 2.7 mg/m ³ 15 min	STEL: 1 ppm STEL: 2.7 mg/m ³ TWA: 0.5 ppm	STEL: 2.7 mg/m ³ 15 percekben. CK STEL: 1 ppm 15	STEL: 1 ppm STEL: 2.7 mg/m ³ TWA: 0.5 ppm 8

SAFETY DATA SHEET

Aqualine™ Solvent CM

Revision Date 08-Jul-2025

	tundides. STEL: 1 ppm 15 minutites. STEL: 2.7 mg/m ³ 15 minutites.	STEL: 1 ppm 15 min	TWA: 1.3 mg/m ³	percekben. CK TWA: 1.3 mg/m ³ 8 óraban. AK TWA: 0.5 ppm 8 óraban. AK	klukkustundum. TWA: 1.3 mg/m ³ 8 klukkustundum.
--	---	--------------------	----------------------------	---	--

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Chloroform	skin - potential for cutaneous exposure TWA: 2 ppm TWA: 10 mg/m ³	TWA: 10 mg/m ³ IPRD TWA: 2 ppm IPRD Oda	Possibility of significant uptake through the skin TWA: 2 ppm 8 Stunden TWA: 10 mg/m ³ 8 Stunden	possibility of significant uptake through the skin TWA: 2 ppm TWA: 10 mg/m ³	Skin notation TWA: 2 ppm 8 ore TWA: 10 mg/m ³ 8 ore
Methanol	skin - potential for cutaneous exposure TWA: 200 ppm TWA: 260 mg/m ³	TWA: 200 ppm IPRD TWA: 260 mg/m ³ IPRD Oda	Possibility of significant uptake through the skin TWA: 200 ppm 8 Stunden TWA: 260 mg/m ³ 8 Stunden	possibility of significant uptake through the skin TWA: 200 ppm TWA: 260 mg/m ³	Skin notation TWA: 200 ppm 8 ore TWA: 260 mg/m ³ 8 ore
Sulfur dioxide	STEL: 2.7 mg/m ³ STEL: 1 ppm TWA: 1.3 mg/m ³ TWA: 0.5 ppm	TWA: 1.3 mg/m ³ IPRD TWA: 0.5 ppm IPRD STEL: 2.7 mg/m ³ STEL: 1 ppm	TWA: 1.3 mg/m ³ 8 Stunden TWA: 0.5 ppm 8 Stunden STEL: 2.7 mg/m ³ 15 Minuten STEL: 1 ppm 15 Minuten	TWA: 0.5 ppm TWA: 1.3 mg/m ³ STEL: 1 ppm 15 minuti STEL: 2.7 mg/m ³ 15 minuti	TWA: 0.5 ppm 8 ore TWA: 1.3 mg/m ³ 8 ore STEL: 1 ppm 15 minute STEL: 2.7 mg/m ³ 15 minute

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Chloroform	TWA: 5 mg/m ³ 2019 Skin notation STEL: 10 mg/m ³ 2019	Potential for cutaneous absorption TWA: 2 ppm TWA: 10 mg/m ³	TWA: 2 ppm 8 urah TWA: 10 mg/m ³ 8 urah Koža	Indicative STLV: 5 ppm 15 minuter Indicative STLV: 25 mg/m ³ 15 minuter LLV: 2 ppm 8 timmar. LLV: 10 mg/m ³ 8 timmar. Hud	Deri TWA: 2 ppm 8 saat TWA: 10 mg/m ³ 8 saat
Methanol	TWA: 5 mg/m ³ 1250 Skin notation MAC: 15 mg/m ³	Potential for cutaneous absorption TWA: 200 ppm TWA: 260 mg/m ³	TWA: 200 ppm 8 urah TWA: 260 mg/m ³ 8 urah Koža STEL: 800 ppm 15 minutah STEL: 1040 mg/m ³ 15 minutah	Indicative STEL: 250 ppm 15 minuter Indicative STEL: 350 mg/m ³ 15 minuter TLV: 200 ppm 8 timmar. NGV TLV: 250 mg/m ³ 8 timmar. NGV Hud	Deri TWA: 200 ppm 8 saat TWA: 260 mg/m ³ 8 saat
Sulfur dioxide	Skin notation MAC: 10 mg/m ³	Ceiling: 2.7 mg/m ³ TWA: 0.5 ppm TWA: 1.3 mg/m ³	TWA: 0.5 ppm 8 urah TWA: 1.3 mg/m ³ 8 urah STEL: 1 ppm 15 minutah STEL: 2.7 mg/m ³ 15 minutah	Binding STEL: 1 ppm 15 minuter Binding STEL: 2.7 mg/m ³ 15 minuter TLV: 0.5 ppm 8 timmar. NGV TLV: 1.3 mg/m ³ 8 timmar. NGV	

Biological limit values

List source(s):

Component	European Union	United Kingdom	France	Spain	Germany
Methanol			Methanol: urine end of shift	Methanol: 15 mg/L urine end of shift	Methanol: 15 mg/L urine (end of shift) Methanol: 15 mg/L urine (for long-term exposures: at the end of the shift after several shifts)

Component	Italy	Finland	Denmark	Bulgaria	Romania
Methanol					Methanol: 6 mg/L urine

SAFETY DATA SHEET

Aqualine™ Solvent CM

Revision Date 08-Jul-2025

					end of shift
Component	Gibraltar	Latvia	Slovak Republic	Luxembourg	Turkey
Methanol			Methanol: 30 mg/L urine end of exposure or work shift Methanol: 30 mg/L urine after all work shifts for long-term exposure		

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Chloroform 67-66-3 (50 - 75)				DNEL = 0.94mg/kg bw/day
Methanol 67-56-1 (20 - 40)		DNEL = 20mg/kg bw/day		DNEL = 20mg/kg bw/day
1-Imidazole 288-32-4 (2.5 - 5)				DNEL = 1.5mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Chloroform 67-66-3 (50 - 75)		DNEL = 333mg/m³	DNEL = 2.5mg/m³	DNEL = 2.5mg/m³
Methanol 67-56-1 (20 - 40)	DNEL = 130mg/m³	DNEL = 130mg/m³	DNEL = 130mg/m³	DNEL = 130mg/m³
Sulfur dioxide 7446-09-5 (5 - 10)	DNEL = 2.7mg/m³		DNEL = 2.7mg/m³	
1-Imidazole 288-32-4 (2.5 - 5)				DNEL = 10.6mg/m³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Chloroform 67-66-3 (50 - 75)	PNEC = 0.146mg/L	PNEC = 0.45mg/kg sediment dw	PNEC = 0.133mg/L	PNEC = 0.048mg/L	PNEC = 0.56mg/kg soil dw
Methanol 67-56-1 (20 - 40)	PNEC = 20.8mg/L	PNEC = 77mg/kg sediment dw	PNEC = 1540mg/L	PNEC = 100mg/L	PNEC = 100mg/kg soil dw
1-Imidazole 288-32-4 (2.5 - 5)	PNEC = 0.13mg/L	PNEC = 0.336mg/kg sediment dw	PNEC = 1.3mg/L	PNEC = 10mg/L	PNEC = 0.0425mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
-----------	--------------	-----------------------	---------------------------	------------	-----

SAFETY DATA SHEET

Aqualine™ Solvent CM

Revision Date 08-Jul-2025

Chloroform 67-66-3 (50 - 75)	PNEC = 0.015mg/L	PNEC = 0.09mg/kg sediment dw			
Methanol 67-56-1 (20 - 40)	PNEC = 2.08mg/L	PNEC = 7.7mg/kg sediment dw			
1-Imidazole 288-32-4 (2.5 - 5)	PNEC = 0.013mg/L	PNEC = 0.0336mg/kg sediment dw			

8.2. Exposure controls

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles (European standard - EN 166)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Viton (R)	See manufacturers recommendations	-	EN 374	(minimum requirement)
Neoprene				
Butyl rubber				

Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Recommended Filter type: low boiling organic solvent Type AX Brown conforming to EN371

Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141
When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

Prevent product from entering drains.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State

Liquid

Appearance Odor

No information available
Alcohol-like

SAFETY DATA SHEET

Aqualine™ Solvent CM

Revision Date 08-Jul-2025

Odor Threshold	No data available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flammability (liquid)	Highly flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Flash Point	21 - 31 °C / 69.8 - 87.8 °F	Method - No information available
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
pH	No information available	
Viscosity	No data available	
Water Solubility	Partially soluble	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Chloroform	2	
Methanol	-0.74	
1-Imidazole	-0.02	
Vapor Pressure	No data available	
Density / Specific Gravity	1.14	
Bulk Density	Not applicable	Liquid
Vapor Density	No data available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

Explosive Properties Vapors may form explosive mixtures with air

Section 10: Stability and reactivity

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization Hazardous polymerization does not occur.
Hazardous Reactions None under normal processing.

10.4. Conditions to avoid

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents. Strong acids. Metals. Amines. Isocyanates. Peroxides. Oxidizing agent.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂). Nitrogen oxides (NO_x). Sulfur oxides. Hydrogen chloride gas.

Section 11: Toxicological information

SAFETY DATA SHEET

Aqualine™ Solvent CM

Revision Date 08-Jul-2025

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral	Category 3
Dermal	Category 3
Inhalation	Category 3

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Chloroform	LD50 = 908 mg/kg (rat) LD50 = 695 mg/kg (Rat) LD50 = 450 mg/kg (Rat)	LD50 > 20 g/kg (Rabbit)	LC50 = 10.5 mg/L (Rat) 4 h
Methanol	LD50 = 1187 – 2769 mg/kg (Rat)	LD50 = 17100 mg/kg (Rabbit)	LC50 = 128.2 mg/L (Rat) 4 h
Sulfur dioxide	-	-	Per CGA P-20: 2500 ppm/1hr (Rat)
1-Imidazole	970 mg/kg (Rat)	-	-

(b) skin corrosion/irritation; Category 1 B

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;

Respiratory	No data available
Skin	No data available

Component	Test method	Test species	Study result
Methanol 67-56-1 (20 - 40)	OECD Test Guideline 406 Guinea Pig Maximisation Test (GPMT)	guinea pig	non-sensitising

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; Category 2

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Chloroform				Group 2B

(g) reproductive toxicity; Category 1B

Component	Test method	Test species / Duration	Study result
Methanol 67-56-1 (20 - 40)	OECD Test Guideline 416	Rat / Inhalation 2 Generation	NOAEC = 1.3 mg/l (air)

Reproductive Effects
Developmental Effects

Possible risk of harm to the unborn child.
Component substance is listed on California Proposition 65 as a developmental hazard.

(h) STOT-single exposure; Category 3

Results / Target organs Optic nerve, Central nervous system (CNS).

(i) STOT-repeated exposure; Category 1

Target Organs Liver, Kidney.

SAFETY DATA SHEET

Aqualine™ Solvent CM

Revision Date 08-Jul-2025

(j) aspiration hazard; No data available

Symptoms / effects, both acute and delayed Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity effects Contains a substance which is: Harmful to aquatic organisms. The product contains following substances which are hazardous for the environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Chloroform	LC50: = 300 mg/L, 96h static (Poecilia reticulata) LC50: = 18 mg/L, 96h flow-through (Lepomis macrochirus) LC50: = 18 mg/L, 96h flow-through (Oncorhynchus mykiss) LC50: = 71 mg/L, 96h flow-through (Pimephales promelas)	EC50 = 28.9 mg/L/48h	EC50 = 560 mg/L/48h
Methanol	Pimephales promelas: LC50 > 10000 mg/L 96h	EC50 > 10000 mg/L 24h	
1-Imidazole		EC50: = 341.5 mg/L, 48h (Daphnia magna)	EC50: = 82 mg/L, 96h (Desmodesmus subspicatus) EC50: = 130 mg/L, 72h (Desmodesmus subspicatus)

Component	Microtox	M-Factor
Chloroform	Photobacterium phosphoreum: EC50 = 520 mg/L/5 min Photobacterium phosphoreum: EC50 = 670 mg/L/15 min Photobacterium phosphoreum: EC50 = 670 mg/L/30min	
Methanol	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	
1-Imidazole	= 1200 mg/L EC50 Pseudomonas putida 17 h = 231 mg/L EC50 Photobacterium phosphoreum 30 min	

12.2. Persistence and degradability

Component	Degradability
Methanol 67-56-1 (20 - 40)	DT50 ~ 17.2d >94% after 20d

Degradation in sewage treatment plant Contains no substances known to be hazardous to the environment or not degradable in waste water treatment plants. Contains substances known to be hazardous to the

SAFETY DATA SHEET

Aqualine™ Solvent CM

Revision Date 08-Jul-2025

environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential There is no data for this product

Component	log Pow	Bioconcentration factor (BCF)
Chloroform	2	1.4 - 13 dimensionless
Methanol	-0.74	<10 dimensionless
1-Imidazole	-0.02	No data available

12.4. Mobility in soil No information available .

12.5. Results of PBT and vPvB assessment No data available for assessment.

12.6. Endocrine disrupting properties
Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects
Persistent Organic Pollutant This product does not contain any known or suspected substance
Ozone Depletion Potential This product does not contain any known or suspected substance

Section 13: Disposal considerations

13.1. Waste treatment methods

Waste from Residues/Unused Products Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

European Waste Catalogue (EWC) According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms.

Switzerland - Waste Ordinance Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600
<https://www.fedlex.admin.ch/eli/cc/2015/891/en>

Section 14: Transport information

IMDG/IMO

14.1. UN number UN1992
14.2. UN proper shipping name FLAMMABLE LIQUID, TOXIC, N.O.S.
Technical Shipping Name (Contains Chloroform and Methyl alcohol)
14.3. Transport hazard class(es) 3
Subsidiary Hazard Class 6.1
14.4. Packing group II

SAFETY DATA SHEET

Aqualine™ Solvent CM

Revision Date 08-Jul-2025

ADR

14.1. UN number	UN1992
14.2. UN proper shipping name Technical Shipping Name	FLAMMABLE LIQUID, TOXIC, N.O.S. (Contains Chloroform and Methyl alcohol)
14.3. Transport hazard class(es)	3
Subsidiary Hazard Class	6.1
14.4. Packing group	II

IATA

14.1. UN number	UN1992
14.2. UN proper shipping name Technical Shipping Name	FLAMMABLE LIQUID, TOXIC, N.O.S. (Contains Chloroform and Methyl alcohol)
14.3. Transport hazard class(es)	3
Subsidiary Hazard Class	6.1
14.4. Packing group	II

14.5. Environmental hazards	No hazards identified
14.6. Special precautions for user	No special precautions required.
14.7. Maritime transport in bulk according to IMO instruments	Not applicable, packaged goods

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Chloroform	67-66-3	200-663-8	-	-	X	X	X	X	X
Methanol	67-56-1	200-659-6	-	-	X	X	KE-23193	X	X
Sulfur dioxide	7446-09-5	231-195-2	-	-	X	X	KE-32567	X	X
1-Imidazole	288-32-4	206-019-2	-	-	X	X	KE-20937	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Chloroform	67-66-3	X	ACTIVE	X	-	X	X	X
Methanol	67-56-1	X	ACTIVE	X	-	X	X	X
Sulfur dioxide	7446-09-5	X	ACTIVE	X	-	X	X	X
1-Imidazole	288-32-4	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Chloroform	67-66-3	-	Use restricted. See item 32.	-

SAFETY DATA SHEET

Aqualine™ Solvent CM

Revision Date 08-Jul-2025

			(see http://eur-lex.europa.eu/LexUriServ/LexUriServ.do?uri=CELEX:32006R1907:EN:NOT for restriction details)	
Methanol	67-56-1	-	Use restricted. See entry 69. (see link for restriction details) Use restricted. See entry 75. (see link for restriction details)	-
Sulfur dioxide	7446-09-5	-	Use restricted. See entry 75. (see link for restriction details)	-
1-Imidazole	288-32-4	-	Use restricted. See entry 30. (see link for restriction details) Use restricted. See entry 75. (see link for restriction details)	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Chloroform	67-66-3	Not applicable	Not applicable
Methanol	67-56-1	500 tonne	5000 tonne
Sulfur dioxide	7446-09-5	Not applicable	Not applicable
1-Imidazole	288-32-4	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Component	ANNEX I - PART 1 List of chemicals subject to export notification procedure (referred to in Article 8)	ANNEX I - PART 2 List of chemicals qualifying for PIC notification (referred to in Article 11)	ANNEX I - PART 3 List of chemicals subject to the PIC procedure (referred to in Articles 13 and 14)
Chloroform 67-66-3 (50 - 75)	b — ban (for the category or categories concerned) b — ban (for the category or categories concerned) i(2) — industrial chemical for public	-	-

<https://eur-lex.europa.eu/legal-content/EN/TXT/?uri=CELEX%3A32012R0649&qid=1604065742303>.

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

Take note of Directive 94/33/EC on the protection of young people at work

SAFETY DATA SHEET

Aqualine™ Solvent CM

Revision Date 08-Jul-2025

Take note of Dir 92/85/EC on the protection of pregnant and breastfeeding women at work

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification Water endangering class = 3 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Chloroform	WGK 3	Class I : 20 mg/m ³ (Massenkonzentration)
Methanol	WGK 2	Class I : 20 mg/m ³ (Massenkonzentration)
Sulfur dioxide	WGK1	
1-Imidazole	WGK2	

Component	France - INRS (Tables of occupational diseases)
Chloroform	Tableaux des maladies professionnelles (TMP) - RG 12
Methanol	Tableaux des maladies professionnelles (TMP) - RG 84

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Chloroform 67-66-3 (50 - 75)	Prohibited and Restricted Substances		Annex I - industrial chemical
Methanol 67-56-1 (20 - 40)	Prohibited and Restricted Substances	Group I	

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

Section 16: Other information

Full text of H-Statements referred to under sections 2 and 3

H301 - Toxic if swallowed
H311 - Toxic in contact with skin
H331 - Toxic if inhaled
H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage
H370 - Causes damage to organs
H336 - May cause drowsiness or dizziness
H351 - Suspected of causing cancer
H360D - May damage the unborn child
H361d - Suspected of damaging the unborn child
H372 - Causes damage to organs through prolonged or repeated exposure
H225 - Highly flammable liquid and vapor
H302 - Harmful if swallowed
H315 - Causes skin irritation
H319 - Causes serious eye irritation

Legend

CAS - Chemical Abstracts Service

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical

SAFETY DATA SHEET

Aqualine™ Solvent CM

Revision Date 08-Jul-2025

Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances
IECSC - Chinese Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances
AICS - Australian Inventory of Chemical Substances
NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadviser - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data

Health Hazards Calculation method

Environmental hazards Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Creation Date 06-Oct-2011

Revision Date 08-Jul-2025

Revision Summary SDS sections updated, 2, 3, 8.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006. COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No 1907/2006 .

For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2, Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and Preparations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet