

Australian statement of hazardous nature : Classified as hazardous according to criteria of Safe Work Australia

Section 1 - Identification

Product Name Methylmagnesium bromide, 3M in ether

Product Code	41252
Address	ThermoFisher Scientific Australia Pty Ltd 5 Caribbean Drive, Scoresby VICTORIA 3179, Australia
Emergency Tel.	CHEMTREC® 03 9757 4559 or +613 9757 4559
Telephone / Fax Numbers	Tel: 1300 735 292 Fax: 1800 067 639
E-mail address	ANZinfo@thermofisher.com

Recommended Use Laboratory chemicals.

Uses advised against Verify requirements related to using, handling and storing these substances. This product contains one or more substance(s) on the Illicit Drug Precursors/Reagents list. This product does not contain any substance(s) subject to Prohibition, Authorization or Restriction. This product does not contain any substance(s) listed on the voluntary National Code of Practice for Chemicals of Security Concern.

Section 2 - Hazard(s) Identification

Classification under Safe Work Australia

Classified as hazardous according to criteria of Safe Work Australia

Physical hazards

Flammable liquids	Category 1
Substances/mixtures which, in contact with water, emit flammable gases	Category 1

Health hazards

Acute Oral Toxicity	Category 4
Skin Corrosion/Irritation	Category 1 B
Serious Eye Damage/Eye Irritation	Category 1
Specific target organ toxicity - (single exposure)	Category 3

Environmental hazards

No hazards identified

Label Elements



Flame



Exclamation Mark



Corrosion

Signal Word**Danger****Hazard Statements**

H224 - Extremely flammable liquid and vapor
 H260 - In contact with water releases flammable gases which may ignite spontaneously
 H302 - Harmful if swallowed
 H314 - Causes severe skin burns and eye damage
 H336 - May cause drowsiness or dizziness
 AUH014 - Reacts violently with water
 AUH019 - May form explosive peroxides

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
 P231 + P232 - Handle and store contents under inert gas. Protect from moisture
 P233 - Keep container tightly closed
 P240 - Ground and bond container and receiving equipment
 P242 - Use non-sparking tools
 P243 - Take action to prevent static discharges
 P261 - Avoid breathing dust/fume/gas/mist/vapors/spray
 P264 - Wash face, hands and any exposed skin thoroughly after handling
 P270 - Do not eat, drink or smoke when using this product
 P271 - Use only outdoors or in a well-ventilated area
 P280 - Wear protective gloves/protective clothing/eye protection/face protection
 P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
 P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
 P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 P310 - Immediately call a POISON CENTER or doctor
 P330 - Rinse mouth
 P331 - Do NOT induce vomiting
 P363 - Wash contaminated clothing before reuse
 P372 - Explosion risk
 P374 - Fight fire with normal precautions from a reasonable distance
 P380 - Evacuate area
 P403 + P235 - Store in a well-ventilated place. Keep cool
 P402 + P404 - Store in a dry place. Store in a closed container
 P501 - Dispose of contents/ container to an approved waste disposal plant

Other information

Toxic to terrestrial vertebrates

Section 3 - Composition and Information on Ingredients

Component	CAS No	Weight %
Ethyl ether	60-29-7	65
Methyl magnesium bromide	75-16-1	35

Section 4 - First Aid Measures

Inhalation	Remove to fresh air. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required. If not breathing, give artificial respiration.
Ingestion	Do NOT induce vomiting. Call a physician or poison control center immediately.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.
General Advice	Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.
First Aid Facilities	Eyewash, safety shower and washroom.
Most important symptoms and effects	Causes burns by all exposure routes. Difficulty in breathing. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
Notes to Physician	Treat symptomatically. Symptoms may be delayed.

Section 5 - Fire Fighting Measures

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Water.

Hazardous Decomposition Products

Carbon monoxide (CO), Carbon dioxide (CO₂), Hydrogen halides, Magnesium oxides, Methane.

Specific Hazards Arising from the Chemical

Extremely flammable. Corrosive material. Reacts violently with water. Contact with water liberates extremely flammable gases. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition.

Special protective equipment and precautions for fire fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6 - Accidental Release Measures

Emergency procedures

Use personal protective equipment as required. Evacuate personnel to safe areas. Remove all sources of ignition. Take precautionary measures against static discharges. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing.

Environmental Precautions

Avoid release to the environment. See Section 12 for additional Ecological Information.

Methods for Containment and Clean Up**Clean-up methods - small spillage**

Do not expose spill to water. Remove all sources of ignition. Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Use spark-proof tools and explosion-proof equipment.

Clean-up methods - large spillage

Typically only supplied in small quantities as packaged goods.

If extremely toxic or used in larger quantities ensure a spillage action plan is in place. Evacuate area. Control the source and/or contain the spill if safe and able to do so. Use temporary diking, sand bags, dry sand, earth or proprietary booms/absorbent pads if available. Obtain advice on containment, neutralisation and clean-up from local emergency responders.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

Section 7 - Handling and Storage

Precautions for Safe Handling

Use only under a chemical fume hood. Wear personal protective equipment/face protection. Use spark-proof tools and explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not get in eyes, on skin, or on clothing. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Do not allow contact with water. If peroxide formation is suspected, do not open or move container. Use spark-proof tools and explosion-proof equipment. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Conditions for Safe Storage, Including any Incompatibilities

Store indoors. Keep away from heat, sparks and flame. Keep away from water or moist air. Store under an inert atmosphere. Flammables area. Containers should be dated when opened and tested periodically for the presence of peroxides. Should crystals form in a peroxidizable liquid, peroxidation may have occurred and the product should be considered extremely dangerous. In this instance, the container should only be opened remotely by professionals. Keep containers tightly closed in a dry, cool and well-ventilated place. Corrosives area.

AS/NZS 2243.10:2004, Safety in laboratories - Storage of chemicals

AS 1940-2004 - The storage and handling of flammable and combustible liquids

Section 8 - Exposure Controls and Personal Protection

Exposure limits

AUS - Exposure Standards for Atmospheric Contaminants in the Occupational Environment - Guidance Note on the Interpretation of Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:3008(1995)]

Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)]

updated in August, 2005. Safe Work Australia **ACGIH** - Threshold Limit Values - Ceiling (TLV-C) guidelines by the American Conference of Governmental Industrial Hygienists (ACGIH) for controlling worker exposure to airborne chemical concentrations in the workplace. **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **DE** - MAK and BAT values of Hazardous Chemical Compounds in the Work Area. Published by German Research Foundation on July 1, 2011

Component	Australia	New Zealand WEL	ACGIH TLV	The United Kingdom	Germany
Ethyl ether	STEL: 500 ppm STEL: 1520 mg/m ³ TWA: 400 ppm TWA: 1210 mg/m ³	TWA: 400 ppm TWA: 1210 mg/m ³ STEL: 500 ppm STEL: 1520 mg/m ³	TWA: 400 ppm STEL: 500 ppm	STEL: 200 ppm 15 min STEL: 620 mg/m ³ 15 min TWA: 100 ppm 8 hr TWA: 310 mg/m ³ 8 hr	TWA: 400 ppm (8 Stunden). AGW - exposure factor 1 TWA: 1200 mg/m ³ (8 Stunden). AGW - exposure factor 1 TWA: 400 ppm (8 Stunden). MAK TWA: 1200 mg/m ³ (8 Stunden). MAK Höhepunkt: 400 ppm

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Exposure Controls**Engineering Measures**

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment**Eye Protection**

Goggles (Australian/New Zealand Standard AS/NZS 1337 - Eye protectors for Industrial applications)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	AUS/NZ Standard	Glove comments
Nitrile rubber	See manufacturers	-	AS/NZS 2161	(minimum requirement)
Viton (R)	recommendations			

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatibility, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure

Respiratory Protection

Use an AS/NZS 1716 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained in line with AS/NZS 1715 on the use and maintenance of respiratory protective devices

Recommended Filter type:

low boiling organic solvent Type AX Brown conforming to EN371 or Organic gases and vapours filter Type A Brown conforming to EN14387 (or AUS/NZ equivalent)

Recommended half mask:-

Valve filtering: EN405 or Half mask: EN140 plus filter, EN 141 (or AUS/NZ equivalent)
When RPE is used a face piece Fit Test should be conducted

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

Environmental exposure controls

No information available.

Section 9 - Physical and Chemical Properties

Information on basic physical and chemical properties**Appearance**

Brown

Physical State

Liquid

Odor

No information available

Odor Threshold

No data available

pH

No information available

Melting Point/Range

No data available

Softening Point

No data available

Boiling Point/Range

No information available

Flash Point

-40 °C / -40 °F

Method - (based on components)

Evaporation Rate	No data available	
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Vapor Pressure	No data available	
Vapor Density	No data available	(Air = 1.0)
Specific Gravity / Density	1.035	
Bulk Density	Not applicable	Liquid
Water Solubility	vigorous reaction	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Ethyl ether	0.82	
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
Viscosity	No data available	
Explosive Properties		Vapors may form explosive mixtures with air
Oxidizing Properties	No information available	
Other information		
Molecular Formula	C H3 Br Mg	
Molecular Weight	119.26	

Section 10 - Stability and Reactivity

Reactivity	Yes
Stability	Reacts violently with water. Moisture sensitive. Air sensitive. May form explosive peroxides.
Conditions to Avoid	Keep away from open flames, hot surfaces and sources of ignition, Exposure to moist air or water, Exposure to air, Incompatible products.
Incompatible Materials	Acids, Bases, Water, Alcohols.
Hazardous Decomposition Products	Carbon monoxide (CO). Carbon dioxide (CO ₂). Hydrogen halides. Magnesium oxides. Methane.
Hazardous Polymerization	Hazardous polymerization does not occur.

Section 11 - Toxicological Information

Information on Toxicological Effects

Product Information

(a) acute toxicity;	
Oral	Category 4
Dermal	Based on available data, the classification criteria are not met
Inhalation	Based on available data, the classification criteria are not met

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethyl ether	1215 mg/kg (Rat)	20 mL/kg (Rabbit)	32000 ppm (Rat) 4 h

(b) skin corrosion/irritation; Category 1 B

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;

Respiratory	No data available
Skin	No data available

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; No data available
There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; No data available

(h) STOT-single exposure; Category 3
Results / Target organs Central nervous system (CNS)

(i) STOT-repeated exposure; No data available
Target Organs No information available.

(j) aspiration hazard; No data available

Other Adverse Effects The toxicological properties have not been fully investigated.

Symptoms / effects, both acute and delayed Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

Section 12 - Ecological Information

Ecotoxicity effects This product contains the following substance(s) which are hazardous for the environment. .

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Ethyl ether	LC50: > 10000 mg/L, 96h static (Lepomis macrochirus) LC50: = 2560 mg/L, 96h flow-through (Pimephales promelas)	EC50 = 165 mg/L/24h		EC50 = 5600 mg/L 15 min

Persistence and Degradability

Persistence Soluble in water, Persistence is unlikely, based on information available.
Bioaccumulative Potential Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Ethyl ether	0.82	No data available

Mobility The product is water soluble, and may spread in water systems. : Will likely be mobile in the environment due to its water solubility Highly mobile in soils

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors
Persistent Organic Pollutant This product does not contain any known or suspected substance
Ozone Depletion Potential This product does not contain any known or suspected substance

Section 13 - Disposal Considerations

Waste from Residues/Unused Do not allow into drains or watercourses or dispose of where ground or surface waters may

Products	be affected. Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with all federal, E.P.A., state and local regulations. Assure conformity with all applicable regulations.
Contaminated Packaging	Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.
Other Information	Chemical wastes should be disposed through a licensed commercial waste collection service. Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms.

Section 14 - Transport Information

IMDG/IMO

UN-No	UN1928
Proper Shipping Name	Methylmagnesium bromide in ethyl ether (Mixture)
Hazard Class	4.3
Subsidiary Hazard Class	3
Packing Group	I

ADG

UN-No	UN1928
Proper Shipping Name	Methylmagnesium bromide in ethyl ether (Mixture)
Hazard Class	4.3
Subsidiary Hazard Class	3
Packing Group	I

Component	Hazchem Code
Ethyl ether 60-29-7 (65)	3YE
Methyl magnesium bromide 75-16-1 (35)	4WE

IATA

UN-No	UN1928
Proper Shipping Name	Methyl magnesium bromide in ethyl ether (Mixture)
Hazard Class	4.3
Subsidiary Hazard Class	3
Packing Group	I

Environmental hazards	No hazards identified
Special Precautions	No special precautions required
Additional information	None known

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National Regulations **Australia**

See section 8 for national exposure control parameters.

Standard for the Uniform Scheduling of Medicines and Poisons

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons.

Component	Standard for the Uniform Scheduling of Medicines and Poisons
Ethyl ether - 60-29-7	Schedule 2 listed Schedule 4 listed - for use in anaesthesia Schedule 5 listed - in preparations for use in internal combustion engines Schedule 6 listed - except when included in Schedule 2, 4 or 5, or in preparations containing <=10% of Ether

Australian Industrial Chemicals Introduction Scheme (AICIS)

Component	Australian Industrial Chemicals Introduction Scheme (AICIS)	Additional information
Ethyl ether - 60-29-7	Present	-

Australian - Illicit Drug Precursors/Reagents Substance List

Verify requirements related to using, handling and storing these substances. This product contains one or more substance(s) on the Illicit Drug Precursors/Reagents list.

Chemicals of Security Concern

This product does not contain any substance(s) listed on the voluntary National Code of Practice for Chemicals of Security Concern

Component	Australian - Illicit Drug Precursors/Reagents Substance List	Chemicals of Security Concern
Ethyl ether - 60-29-7	Category 3	

Legend

Category 3 - Chemicals and apparatus that may be used in the illicit production of drugs. Purchases from this list should alert companies or organizations to seek further indicators of any suspicious orders or enquiries. No official reporting is required for items on this list unless considered warranted

National pollutant inventory Not applicable**Prohibition or notification/licensing requirements**

Shown below are details of specific prohibition/notifications or licensing requirements when they apply.

This product does not contain any substance(s) subject to Prohibition, Authorization or Restriction.

International Inventories

Component	AICS	NZIoC	EINECS	ELINCS	TSCA	DSL	NDSL	PICCS	ENCS	ISHL	IECSC	KECL
Ethyl ether	X	X	200-467-2	-	X	X	-	X	X	X	X	KE-27690
Methyl magnesium bromide	-	X	200-844-1	-	X	-	X	X	X	X	-	-

Legend: X - Listed, '-' - Not Listed. **KECL** - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)**International Regulations****Ozone Depletion Potential** This product does not contain any known or suspected substance**Persistent Organic Pollutant** This product does not contain any known or suspected substance

Rotterdam Convention (PIC) Not applicable

Basel convention on the control of transboundary movements of hazardous wastes and their disposal

Take note that wastes may be subject to export, import, or transit controls pursuant to the Basel convention and/or local regulations implementing the Basel convention.

Component	Basel Convention (Hazardous Waste)	Australian Hazardous Waste Act - Categories of Wastes to Be Controlled
Ethyl ether - 60-29-7	Annex I - Y40 Annex I - Y42	Y40 Y42 except Halogenated solvents

Component	CAS No	OECD HPV	Restriction of Hazardous Substances (RoHS)	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Ethyl ether	60-29-7	Listed	Not applicable	Not applicable	Not applicable
Methyl magnesium bromide	75-16-1	Not applicable	Not applicable	Not applicable	Not applicable

Authorisation/Restrictions according to EU REACH Not applicable

Section 16 - Other Information

Legend

AICS - Australian Inventory of Chemical Substances	NZIoC - New Zealand Inventory of Chemicals
TSCA - United States Toxic Substances Control Act Section 8(b) Inventory	EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List	ENCS - Japanese Existing and New Chemical Substances
IECSC - Chinese Inventory of Existing Chemical Substances	KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances	CAS - Chemical Abstracts Service
TWA - Time Weighted Average	ACGIH - American Conference of Governmental Industrial Hygienists
IARC - International Agency for Research on Cancer	PNEC - Predicted No Effect Concentration
ICAO/IATA - International Civil Aviation Organization/International Air Transport Association	IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code
MARPOL - International Convention for the Prevention of Pollution from Ships	ADG Australian Code for the Transport of Dangerous Goods by Road and Rail
NZS 5433:2012 - Transport of Dangerous Goods on Land	OECD - Organisation for Economic Co-operation and Development
LD50 - Lethal Dose 50%	LC50 - Lethal Concentration 50%
EC50 - Effective Concentration 50%	ATE - Acute Toxicity Estimate
WEL - Workplace Exposure Limit	RPE - Respiratory Protective Equipment
DNEL - Derived No Effect Level	NOEC - No Observed Effect Concentration
POW - Partition coefficient Octanol:Water	BCF - Bioconcentration factor
vPvB - very Persistent, very Bioaccumulative	PBT - Persistent, Bioaccumulative, Toxic
VOC - (Volatile Organic Compound)	

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>
Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health Hazards	Calculation method
Environmental hazards	Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Chemical incident response training.

Revision Date 20-Nov-2022
Revision Summary Not applicable.

This Safety Data Sheet (SDS) is prepared in accordance to and complies with the requirements of Safe Work Australia - Work Health and Safety Regulations (WHS Regulations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet