

ALFAA43119

## Aluminum oxide, Aerosol Refractory Brushable Paint

### SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

**产品说明:** 氧化铝, 气溶胶耐温涂料  
**Product Description:** Aluminum oxide, Aerosol Refractory Brushable Paint

**Cat No. :** 43119

**Supplier** Avocado Research Chemicals Ltd.  
(Part of Thermo Fisher Scientific)  
Shore Road, Heysham  
Lancashire, LA3 2XY,  
United Kingdom  
Office Tel: +44 (0) 1524 850506  
Office Fax: +44 (0) 1524 850608

**Emergency Telephone Number** For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11  
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99  
**CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

**E-mail address** begel.sdsdesk@thermofisher.com

**Recommended Use** Laboratory chemicals.  
**Uses advised against** Food, drug, pesticide or biocidal product use

### SECTION 2. HAZARD IDENTIFICATION

**Physical State**  
paste Liquid Solid

**Appearance**  
White

**Odor**  
No information available

#### Emergency Overview

Repeated exposure may cause skin dryness or cracking. Causes serious eye irritation. Highly flammable liquid and vapor.

#### Classification of the substance or mixture

|                                   |            |
|-----------------------------------|------------|
| Flammable liquids.                | Category 2 |
| Serious Eye Damage/Eye Irritation | Category 2 |

#### Label Elements



**Signal Word**

**Danger**

#### Hazard Statements

H225 - Highly flammable liquid and vapor  
H319 - Causes serious eye irritation

# SAFETY DATA SHEET

## Aluminum oxide, Aerosol Refractory Brushable Paint

### Precautionary Statements

#### Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P233 - Keep container tightly closed  
P240 - Ground and bond container and receiving equipment  
P241 - Use explosion-proof electrical/ ventilating/ lighting equipment  
P242 - Use non-sparking tools  
P243 - Take action to prevent static discharges  
P280 - Wear protective gloves/protective clothing/eye protection/face protection

#### Response

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower  
P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

#### Storage

P403 + P235 - Store in a well-ventilated place. Keep cool

#### Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

### Physical and Chemical Hazards

Vapors may cause flash fire or explosion. Highly flammable.

#### Health Hazards

Causes serious eye irritation.

#### Environmental hazards

Contains no substances known to be hazardous to the environment or not degradable in waste water treatment plants. Will likely be mobile in the environment due to its volatility. The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces.

This product does not contain any known or suspected endocrine disruptors.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

| Component      | CAS No     | Weight % |
|----------------|------------|----------|
| Aluminum oxide | 1344-28-1  | 47       |
| Ethyl alcohol  | 64-17-5    | 37       |
| Acetone        | 67-64-1    | 12       |
| Hectorite      | 12173-47-6 | 2        |
| Ethylcellulose | 9004-57-3  | 2        |

## SECTION 4. FIRST AID MEASURES

#### General Advice

If symptoms persist, call a physician.

#### Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

#### Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.

#### Inhalation

Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.

#### Ingestion

Clean mouth with water and drink afterwards plenty of water.

#### Most important symptoms and effects

None reasonably foreseeable. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: May cause pulmonary edema: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: May cause central nervous system depression

# SAFETY DATA SHEET

## Aluminum oxide, Aerosol Refractory Brushable Paint

**Self-Protection of the First Aider**

No special precautions required.

**Notes to Physician**

Treat symptomatically. Symptoms may be delayed.

**SECTION 5. FIRE-FIGHTING MEASURES****Suitable Extinguishing Media**

Water spray, carbon dioxide (CO<sub>2</sub>), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

**Extinguishing media which must not be used for safety reasons**

Do not use water jetstream.

**Specific Hazards Arising from the Chemical**

Flammable. Risk of ignition. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

**Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**SECTION 6. ACCIDENTAL RELEASE MEASURES****Personal Precautions**

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

**Environmental Precautions**

Do not flush into surface water or sanitary sewer system.

**Methods for Containment and Clean Up**

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Pressurized container: Do not pierce or burn, even after use

Refer to protective measures listed in Sections 8 and 13.

**SECTION 7. HANDLING AND STORAGE****Handling**

Wear personal protective equipment/face protection. Ensure adequate ventilation. Avoid ingestion and inhalation. Do not get in eyes, on skin, or on clothing. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

**Storage**

Flammables area. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Use only outdoors or in a well-ventilated area.

**Specific Use(s)**

Use in laboratories

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Control Parameters**

## Aluminum oxide, Aerosol Refractory Brushable Paint

| Component      | China                                                     | Taiwan                                       | Thailand                                              | Hong Kong                                                                                    |
|----------------|-----------------------------------------------------------|----------------------------------------------|-------------------------------------------------------|----------------------------------------------------------------------------------------------|
| Aluminum oxide | TWA: 4 mg/m <sup>3</sup>                                  | -                                            | TWA: 15 mg/m <sup>3</sup><br>TWA: 5 mg/m <sup>3</sup> | TWA: 10 mg/m <sup>3</sup>                                                                    |
| Ethyl alcohol  | -                                                         | TWA: 1000 ppm<br>TWA: 1880 mg/m <sup>3</sup> | TWA: 1000 ppm                                         | TWA: 1000 ppm<br>TWA: 1880 mg/m <sup>3</sup>                                                 |
| Acetone        | TWA: 300 mg/m <sup>3</sup><br>STEL: 450 mg/m <sup>3</sup> | TWA: 200 ppm<br>TWA: 475 mg/m <sup>3</sup>   | TWA: 1000 ppm                                         | TWA: 500 ppm<br>TWA: 1187 mg/m <sup>3</sup><br>STEL: 750 ppm<br>STEL: 1781 mg/m <sup>3</sup> |

| Component      | ACGIH TLV                     | OSHA PEL                                                                                                                                                                              | NIOSH                                                          | The United Kingdom                                                                                                                        | European Union                                        |
|----------------|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------|
| Aluminum oxide | TWA: 1 mg/m <sup>3</sup>      | (Vacated) TWA: 10 mg/m <sup>3</sup><br>(Vacated) TWA: 5 mg/m <sup>3</sup><br>TWA: 15 mg/m <sup>3</sup><br>TWA: 5 mg/m <sup>3</sup>                                                    |                                                                | STEL: 30 mg/m <sup>3</sup> 15 min<br>STEL: 12 mg/m <sup>3</sup> 15 min<br>TWA: 10 mg/m <sup>3</sup> 8 hr<br>TWA: 4 mg/m <sup>3</sup> 8 hr |                                                       |
| Ethyl alcohol  | STEL: 1000 ppm                | (Vacated) TWA: 1000 ppm<br>(Vacated) TWA: 1900 mg/m <sup>3</sup><br>TWA: 1000 ppm<br>TWA: 1900 mg/m <sup>3</sup>                                                                      | IDLH: 3300 ppm<br>TWA: 1000 ppm<br>TWA: 1900 mg/m <sup>3</sup> | TWA: 1000 ppm TWA;<br>1920 mg/m <sup>3</sup> TWA<br>WEL - STEL: 3000 ppm STEL; 5760 mg/m <sup>3</sup> STEL                                |                                                       |
| Acetone        | TWA: 250 ppm<br>STEL: 500 ppm | (Vacated) TWA: 750 ppm<br>(Vacated) TWA: 1800 mg/m <sup>3</sup><br>(Vacated) STEL: 2400 mg/m <sup>3</sup><br>(Vacated) STEL: 1000 ppm<br>TWA: 1000 ppm<br>TWA: 2400 mg/m <sup>3</sup> | IDLH: 2500 ppm<br>TWA: 250 ppm<br>TWA: 590 mg/m <sup>3</sup>   | TWA: 500 ppm<br>TWA: 1210 mg/m <sup>3</sup><br>STEL: 1500 ppm<br>STEL: 3620 mg/m <sup>3</sup>                                             | TWA: 500 ppm (8h)<br>TWA: 1210 mg/m <sup>3</sup> (8h) |

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

**Monitoring methods**

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust

**Exposure Controls****Engineering Measures**

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source.

**Personal protective equipment****Eye Protection**

Goggles (European standard - EN 166)

**Hand Protection**

Protective gloves

| Glove material  | Breakthrough time | Glove thickness | EU standard    | Glove comments                                                                 |
|-----------------|-------------------|-----------------|----------------|--------------------------------------------------------------------------------|
| Butyl rubber    | > 480 minutes     | 0.5 mm          | EN 374 Level 6 | As tested under EN374-3 Determination of Resistance to Permeation by Chemicals |
| Neoprene gloves | < 30 minutes      | 0.45 mm         |                |                                                                                |

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves.

## Aluminum oxide, Aerosol Refractory Brushable Paint

(Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

|                                        |                                                                                                                                                                                                                                                                                                                             |
|----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Skin and body protection</b>        | Long sleeved clothing                                                                                                                                                                                                                                                                                                       |
| <b>Respiratory Protection</b>          | When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.<br>To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly                                                                                     |
| <b>Large scale/emergency use</b>       | Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced<br><b>Recommended Filter type:</b> low boiling organic solvent Type AX Brown conforming to EN371                                                                        |
| <b>Small scale/Laboratory use</b>      | Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.<br><b>Recommended half mask:-</b> Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141<br>When RPE is used a face piece Fit Test should be conducted |
| <b>Hygiene Measures</b>                | Handle in accordance with good industrial hygiene and safety practice.                                                                                                                                                                                                                                                      |
| <b>Environmental exposure controls</b> | Do not allow material to contaminate ground water system. Prevent product from entering drains.                                                                                                                                                                                                                             |

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

|                                                |                                          |                                                                                       |
|------------------------------------------------|------------------------------------------|---------------------------------------------------------------------------------------|
| <b>Appearance</b>                              | White                                    |                                                                                       |
| <b>Physical State</b>                          | paste Liquid Solid                       |                                                                                       |
| <b>Odor</b>                                    | No information available                 |                                                                                       |
| <b>Odor Threshold</b>                          | No data available                        |                                                                                       |
| <b>pH</b>                                      | No information available                 |                                                                                       |
| <b>Melting Point/Range</b>                     | No data available                        |                                                                                       |
| <b>Softening Point</b>                         | No data available                        |                                                                                       |
| <b>Boiling Point/Range</b>                     | No information available                 |                                                                                       |
| <b>Flash Point</b>                             | No information available -4 °C / 24.8 °F | <b>Method -</b> No information available                                              |
| <b>Evaporation Rate</b>                        | Not applicable                           | Solid                                                                                 |
| <b>Flammability (solid,gas)</b>                | Not applicable                           | Liquid                                                                                |
| <b>Explosion Limits</b>                        | No data available                        |                                                                                       |
| <b>Vapor Pressure</b>                          | No data available                        |                                                                                       |
| <b>Vapor Density</b>                           | Not applicable                           | Solid                                                                                 |
| <b>Specific Gravity / Density</b>              | No data available                        |                                                                                       |
| <b>Bulk Density</b>                            | Not applicable                           | Liquid                                                                                |
| <b>Water Solubility</b>                        | Partially miscible                       |                                                                                       |
| <b>Solubility in other solvents</b>            | No information available                 |                                                                                       |
| <b>Partition Coefficient (n-octanol/water)</b> |                                          |                                                                                       |
| <b>Component</b>                               | <b>log Pow</b>                           |                                                                                       |
| Ethyl alcohol                                  | -0.32                                    |                                                                                       |
| Acetone                                        | -0.24                                    |                                                                                       |
| <b>Autoignition Temperature</b>                | No data available                        |                                                                                       |
| <b>Decomposition Temperature</b>               | No data available                        |                                                                                       |
| <b>Viscosity</b>                               | Not applicable                           | Solid                                                                                 |
| <b>Explosive Properties</b>                    | Not explosive                            | Vapors may form explosive mixtures with air<br>explosive air/vapour mixtures possible |
| <b>Oxidizing Properties</b>                    | Not oxidising                            |                                                                                       |

# SAFETY DATA SHEET

## Aluminum oxide, Aerosol Refractory Brushable Paint

VOC Content(%) 49

### SECTION 10. STABILITY AND REACTIVITY

**Stability** Stable under normal conditions.

**Hazardous Reactions** None under normal processing.

**Hazardous Polymerization** Hazardous polymerization does not occur.

**Conditions to Avoid** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep away from open flames, hot surfaces and sources of ignition.

**Materials to avoid** Strong oxidizing agents.

**Hazardous Decomposition Products** Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Product Information

(a) acute toxicity;  
Toxicology data for the components

| Component      | LD50 Oral                                                    | LD50 Dermal                                  | LC50 Inhalation                                                   |
|----------------|--------------------------------------------------------------|----------------------------------------------|-------------------------------------------------------------------|
| Aluminum oxide | > 5000 mg/kg ( Rat )<br>(OECD Guideline 401)                 |                                              | > 2.3 mg/l 4 h<br>(OECD Guideline 403)                            |
| Ethyl alcohol  | LD50 = 10470 mg/kg<br>OECD 401 (Rat)<br>3450 mg/kg ( Mouse ) |                                              | LC50 = 117-125 mg/l (4h)<br>OECD 403 (rat)<br>20000 ppm/10H (rat) |
| Acetone        | 5800 mg/kg ( Rat )                                           | > 15800 mg/kg (rabbit)<br>> 7400 mg/kg (rat) | 76 mg/l, 4 h, (rat)                                               |
| Hectorite      | LD50 > 5000 mg/kg ( Rat )                                    |                                              |                                                                   |
| Ethylcellulose | LD50 > 5 g/kg ( Rat )                                        |                                              |                                                                   |

(b) skin corrosion/irritation; No data available

(c) serious eye damage/irritation; No data available

(d) respiratory or skin sensitization;  
Respiratory No data available  
Skin No data available

| Component                       | Test method                                                | Test species | Study result    |
|---------------------------------|------------------------------------------------------------|--------------|-----------------|
| Ethyl alcohol<br>64-17-5 ( 37 ) | Mouse Ear Swelling Test (MEST)                             | mouse        | non-sensitising |
|                                 | -----<br>OECD Test Guideline 429<br>Local Lymph Node Assay | mouse        | non-sensitising |
| Acetone<br>67-64-1 ( 12 )       | Guinea Pig Maximisation Test<br>(GPMT)                     | guinea pig   | non-sensitising |

(e) germ cell mutagenicity; No data available

| Component     | Test method | Test species | Study result |
|---------------|-------------|--------------|--------------|
| Ethyl alcohol | AMES test   | in vitro     | negative     |

# SAFETY DATA SHEET

## Aluminum oxide, Aerosol Refractory Brushable Paint

|                           |                                                            |                       |          |
|---------------------------|------------------------------------------------------------|-----------------------|----------|
| 64-17-5 ( 37 )            | OECD Test Guideline 471                                    | Bacteria              |          |
|                           | Gene cell mutation<br>OECD Test Guideline 476              | in vitro<br>Mammalian | negative |
| Acetone<br>67-64-1 ( 12 ) | OECD Test Guideline 471<br>AMES test                       | in vivo               | negative |
|                           | OECD Test Guideline 476<br>Mammalian<br>Gene cell mutation | in vitro              | negative |

**(f) carcinogenicity;**

No data available

The table below indicates whether each agency has listed any ingredient as a carcinogen

| Component      | EU | UK | Germany             | IARC |
|----------------|----|----|---------------------|------|
| Aluminum oxide |    |    | Cat. 2 (Fibre dust) |      |

**(g) reproductive toxicity;**

No data available

| Component                       | Test method             | Test species / Duration   | Study result          |
|---------------------------------|-------------------------|---------------------------|-----------------------|
| Ethyl alcohol<br>64-17-5 ( 37 ) | OECD Test Guideline 416 | Oral / mouse 2 Generation | NOAEL = 13.8 g/kg/day |
|                                 | OECD Test Guideline 414 | Inhalation / Rat          | NOAEC = 16000 ppm     |

**(h) STOT-single exposure;**

No data available

**Results / Target organs**

Central nervous system (CNS)

**(i) STOT-repeated exposure;**

No data available

**Target Organs**

None known.

**(j) aspiration hazard;**Not applicable  
Solid**Symptoms / effects, both acute and delayed**

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: May cause pulmonary edema: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: May cause central nervous system depression

## SECTION 12. ECOLOGICAL INFORMATION

**Ecotoxicity effects**

Contains a substance which is: Toxic to aquatic organisms. The product contains following substances which are hazardous for the environment.

| Component     | Freshwater Fish                                                                                                                                                                     | Water Flea                                                             | Freshwater Algae                              | Microtox                                                                                                                |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------|-----------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| Ethyl alcohol | Fathead minnow<br>(Pimephales promelas)<br>LC50 = 14200 mg/l/96h                                                                                                                    | EC50 = 9268 mg/L/48h<br>EC50 = 10800 mg/L/24h                          | EC50 (72h) = 275 mg/l<br>(Chlorella vulgaris) | Photobacterium<br>phosphoreum: EC50 =<br>34634 mg/L/30 min<br>Photobacterium<br>phosphoreum: EC50 =<br>35470 mg/L/5 min |
| Acetone       | Oncorhynchus mykiss:<br>LC50 = 5540 mg/l 96h<br>Alburnus alburnus:<br>LC50 = 11000 mg/l 96h<br>Leuciscus idus: LC50 =<br>11300 mg/L/48h<br>Salmo gairdneri: LC50 =<br>6100 mg/L/24h | EC50 = 8800 mg/L/48h<br>EC50 = 12700 mg/L/48h<br>EC50 = 12600 mg/L/48h | NOEC = 430 mg/l<br>(algae; 96 h)              | EC50 = 14500 mg/L/15<br>min                                                                                             |

# SAFETY DATA SHEET

## Aluminum oxide, Aerosol Refractory Brushable Paint

**Persistence and Degradability**  
**Persistence**Readily biodegradable  
Persistence is unlikely, based on information available.

| Component                       | Degradability            |
|---------------------------------|--------------------------|
| Ethyl alcohol<br>64-17-5 ( 37 ) | OECD 301E = 94%          |
| Acetone<br>67-64-1 ( 12 )       | 91 % (28 d) (OECD 301 B) |

**Degradation in sewage treatment plant**

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

**Bioaccumulative Potential**

Bioaccumulation is unlikely

| Component     | log Pow | Bioconcentration factor (BCF) |
|---------------|---------|-------------------------------|
| Ethyl alcohol | -0.32   | No data available             |
| Acetone       | -0.24   | 0.69 dimensionless            |

**Mobility in soil**

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in air.

**Endocrine Disruptor Information**  
**Persistent Organic Pollutant**  
**Ozone Depletion Potential**This product does not contain any known or suspected endocrine disruptors  
This product does not contain any known or suspected substance  
This product does not contain any known or suspected substance**SECTION 13. DISPOSAL CONSIDERATIONS****Waste from Residues/Unused Products**

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

**Contaminated Packaging**

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

**Other Information**

Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations.

**SECTION 14. TRANSPORT INFORMATION****Road and Rail Transport**

|                      |        |
|----------------------|--------|
| UN-No                | UN1263 |
| Proper Shipping Name | PAINT  |
| Hazard Class         | 3      |
| Packing Group        | II     |

**IMDG/IMO**

|                      |        |
|----------------------|--------|
| UN-No                | UN1263 |
| Proper Shipping Name | PAINT  |
| Hazard Class         | 3      |
| Packing Group        | II     |

**IATA**

|                      |        |
|----------------------|--------|
| UN-No                | UN1263 |
| Proper Shipping Name | PAINT  |
| Hazard Class         | 3      |



# SAFETY DATA SHEET

## Aluminum oxide, Aerosol Refractory Brushable Paint

Packing Group II

Special Precautions for User No special precautions required

### SECTION 15. REGULATORY INFORMATION

#### International Inventories

China, X = listed, Australia, U.S.A. (TSCA), Canada (DSL/NDSL), Europe (EINECS/ELINCS/NLP), Australia (AICS), Korea (KECL), China (IECSC), Japan (ENCS), Philippines (PICCS).

| Component      | The Inventory of Hazardous Chemicals (2015 Edition) | List of dangerous goods GB 12268 - 2012 | TCSI | IECSC | EINECS    | TSCA | DSL | PICCS | ENCS | ISHL | AICS | KECL     |
|----------------|-----------------------------------------------------|-----------------------------------------|------|-------|-----------|------|-----|-------|------|------|------|----------|
| Aluminum oxide | -                                                   | -                                       | X    | X     | 215-691-6 | X    | X   | X     | X    | X    | X    | KE-01012 |
| Ethyl alcohol  | X                                                   | X                                       | X    | X     | 200-578-6 | X    | X   | X     | X    | X    | X    | KE-13217 |
| Acetone        | X                                                   | X                                       | X    | X     | 200-662-2 | X    | X   | X     | X    | X    | X    | KE-29367 |
| Hectorite      | -                                                   | -                                       | X    | X     | 235-340-0 | -    | X   | X     | -    |      | X    | KE-18198 |
| Ethylcellulose | -                                                   | -                                       | X    | X     | -         | X    | X   | X     | X    | X    | X    | KE-13689 |

#### National Regulations

### SECTION 16. OTHER INFORMATION

**Prepared By** Health, Safety and Environmental Department  
**Creation Date** 16-Mar-2018  
**Revision Date** 12-May-2024  
**Revision Summary** New emergency telephone response service provider.

#### Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

#### Legend

**CAS** - Chemical Abstracts Service

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**ENCS** - Japanese Existing and New Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**NZIoC** - New Zealand Inventory of Chemicals

**WEL** - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

**RPE** - Respiratory Protective Equipment

**LC50** - Lethal Concentration 50%

**NOEC** - No Observed Effect Concentration

**PBT** - Persistent, Bioaccumulative, Toxic

**TWA** - Time Weighted Average

**IARC** - International Agency for Research on Cancer

**PNEC** - Predicted No Effect Concentration

**LD50** - Lethal Dose 50%

**EC50** - Effective Concentration 50%

**POW** - Partition coefficient Octanol:Water

**vPvB** - very Persistent, very Bioaccumulative

**Aluminum oxide, Aerosol Refractory Brushable Paint**

---

**ICAO/IATA** - International Civil Aviation Organization/International Air Transport Association**ADR** - European Agreement Concerning the International Carriage of Dangerous Goods by Road**OECD** - Organisation for Economic Co-operation and Development**BCF** - Bioconcentration factor**IMO/IMDG** - International Maritime Organization/International Maritime Dangerous Goods Code**MARPOL** - International Convention for the Prevention of Pollution from Ships**ATE** - Acute Toxicity Estimate**VOC** - (Volatile Organic Compound)**Key literature references and sources for data**<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

**Physical hazards**

On basis of test data

**Health Hazards**

Calculation method

**Environmental hazards**

Calculation method

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**