

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**
**Product Identifier**

Perihalan Produk: **Aluminium oxide, Aerosol Refractory Paint**  
 Product Description: **Aluminium oxide, Aerosol Refractory Paint**  
 Cat No. : 40391

**Relevant identified uses of the substance or mixture and uses advised against**

Recommended Use Laboratory chemicals.  
 Uses advised against No Information available

**Company**

Thermo Fisher Scientific Fisher Scientific (M) Sdn Bhd  
 Hap Seng Business Park, Lot 01-03, 01-04 Aras 1 Unity Square,  
 No 12, Persiaran Perusahaan, Seksyen 23, 40300 Shah Alam,  
 Selangor Darul Ehsan, Malaysia.  
 Main line: +60 3-5525 7888

**Supplier**

E-mail address Enquiry.my@thermofisher.com

**Emergency Telephone Number**

Tel: +03-5525 7888  
 CHEMTREC Malaysia 1-800-815-308 (Malay)  
 CHEMTREC Malaysia (Kuala Lumpur) +(60)-327884561 (Malay)

**SECTION 2: HAZARDS IDENTIFICATION**
**Classification of the substance or mixture**

|                                                    |                   |
|----------------------------------------------------|-------------------|
| Flammable aerosols                                 | Category 1 (H222) |
| Serious Eye Damage/Eye Irritation                  | Category 2 (H319) |
| Specific target organ toxicity - (single exposure) | Category 3 (H336) |

**Label Elements**


Signal Word

Danger

**Hazard Statements**

H222 - Extremely flammable aerosol  
 H229 - Pressurised container: May burst if heated.

# SAFETY DATA SHEET

Aluminium oxide, Aerosol Refractory Paint

Revision Date 01-Apr-2025

H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness

## Precautionary Statements

### Prevention

P211 - Do not spray on an open flame or other ignition source  
P251 - Do not pierce or burn, even after use  
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray  
P264 - Wash face, hands and any exposed skin thoroughly after handling  
P271 - Use only outdoors or in a well-ventilated area  
P280 - Wear eye protection/ face protection

### Response

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P308 + P313 - IF exposed or concerned: Get medical advice/attention

### Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed  
P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

### Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

## Other Hazards

EUH066 - Repeated exposure may cause skin dryness or cracking

This product does not contain any known or suspected endocrine disruptors

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

| Component      | CAS No    | Weight % |
|----------------|-----------|----------|
| Acetone        | 67-64-1   | 35       |
| Ethyl alcohol  | 64-17-5   | 20       |
| Aluminum oxide | 1344-28-1 | 20       |
| Propane        | 74-98-6   | 12.5     |
| Butane         | 106-97-8  | 12.5     |

## SECTION 4: FIRST AID MEASURES

### Description of first aid measures

#### General Advice

If symptoms persist, call a physician. Do not breathe dust/fume/gas/mist/vapors/spray.

#### Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

#### Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.

#### Ingestion

Clean mouth with water and drink afterwards plenty of water.

#### Inhalation

Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.

#### Self-Protection of the First Aider

Remove all sources of ignition. Use personal protective equipment as required.

### Most important symptoms and effects, both acute and delayed

ALFAA40391

# SAFETY DATA SHEET

Aluminium oxide, Aerosol Refractory Paint

Revision Date 01-Apr-2025

. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. May cause pulmonary edema. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. May cause central nervous system depression.

## Indication of any immediate medical attention and special treatment needed

### **Notes to Physician**

Treat symptomatically. Symptoms may be delayed.

## **SECTION 5: FIREFIGHTING MEASURES**

### Extinguishing media

#### **Suitable Extinguishing Media**

Water spray, carbon dioxide (CO<sub>2</sub>), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

#### **Extinguishing media which must not be used for safety reasons**

Do not use water jetstream.

### Special hazards arising from the substance or mixture

Flammable. Risk of ignition. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

### **Hazardous Combustion Products**

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>).

### Advice for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Fight fire remotely due to the risk of explosion.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### Personal Precautions, Protective Equipment and Emergency Procedures

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

### Environmental precautions

Should not be released into the environment.

### Methods and Material for Containment and Cleaning Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Pressurized container: Do not pierce or burn, even after use.

### Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

## **SECTION 7: HANDLING AND STORAGE**

### Precautions for Safe Handling

Do not get in eyes, on skin, or on clothing. Wear personal protective equipment/face protection. Ensure adequate ventilation. Use

# SAFETY DATA SHEET

Aluminium oxide, Aerosol Refractory Paint

Revision Date 01-Apr-2025

only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid breathing vapors or mists.

## Conditions for Safe Storage, Including any Incompatibilities

Flammables area. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Pressurized container: Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

## Specific End Uses

Use in laboratories.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control Parameters

| Component      | Malaysia | ACGIH TLV                     | OSHA PEL                                                                                                                                                                              |
|----------------|----------|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Acetone        |          | TWA: 250 ppm<br>STEL: 500 ppm | (Vacated) TWA: 750 ppm<br>(Vacated) TWA: 1800 mg/m <sup>3</sup><br>(Vacated) STEL: 2400 mg/m <sup>3</sup><br>(Vacated) STEL: 1000 ppm<br>TWA: 1000 ppm<br>TWA: 2400 mg/m <sup>3</sup> |
| Ethyl alcohol  |          | STEL: 1000 ppm                | (Vacated) TWA: 1000 ppm<br>(Vacated) TWA: 1900 mg/m <sup>3</sup><br>TWA: 1000 ppm<br>TWA: 1900 mg/m <sup>3</sup>                                                                      |
| Aluminum oxide |          | TWA: 1 mg/m <sup>3</sup>      | (Vacated) TWA: 10 mg/m <sup>3</sup><br>(Vacated) TWA: 5 mg/m <sup>3</sup><br>TWA: 15 mg/m <sup>3</sup><br>TWA: 5 mg/m <sup>3</sup>                                                    |
| Propane        |          | :                             | (Vacated) TWA: 1000 ppm<br>(Vacated) TWA: 1800 mg/m <sup>3</sup><br>TWA: 1000 ppm<br>TWA: 1800 mg/m <sup>3</sup>                                                                      |
| Butane         |          | STEL: 1000 ppm                | (Vacated) TWA: 800 ppm<br>(Vacated) TWA: 1900 mg/m <sup>3</sup>                                                                                                                       |

| Component      | European Union                                        | The United Kingdom                                                                                                                        | Germany                                                                                                                                                                                                                                                                       |
|----------------|-------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Acetone        | TWA: 500 ppm (8h)<br>TWA: 1210 mg/m <sup>3</sup> (8h) | TWA: 500 ppm<br>TWA: 1210 mg/m <sup>3</sup><br>STEL: 1500 ppm<br>STEL: 3620 mg/m <sup>3</sup>                                             | TWA: 500 ppm<br>TWA: 1200 mg/m <sup>3</sup>                                                                                                                                                                                                                                   |
| Ethyl alcohol  |                                                       | TWA: 1000 ppm TWA; 1920 mg/m <sup>3</sup> TWA<br>WEL - STEL: 3000 ppm STEL;<br>5760 mg/m <sup>3</sup> STEL                                | 200 ppm TWA MAK; 380 mg/m <sup>3</sup> TWA MAK                                                                                                                                                                                                                                |
| Aluminum oxide |                                                       | STEL: 30 mg/m <sup>3</sup> 15 min<br>STEL: 12 mg/m <sup>3</sup> 15 min<br>TWA: 10 mg/m <sup>3</sup> 8 hr<br>TWA: 4 mg/m <sup>3</sup> 8 hr | TWA: 1.25 mg/m <sup>3</sup> (8 Stunden).<br>AGW - exposure factor 2<br>TWA: 10 mg/m <sup>3</sup> (8 Stunden). AGW -<br>exposure factor 2<br>TWA: 4 mg/m <sup>3</sup> (8 Stunden). MAK<br>TWA: 1.5 mg/m <sup>3</sup> (8 Stunden). MAK                                          |
| Propane        |                                                       |                                                                                                                                           | TWA: 1000 ppm (8 Stunden). AGW -<br>exposure factor 4<br>TWA: 1800 mg/m <sup>3</sup> (8 Stunden).<br>AGW - exposure factor 4<br>TWA: 1000 ppm (8 Stunden). MAK<br>TWA: 1800 mg/m <sup>3</sup> (8 Stunden).<br>MAK<br>Höhepunkt: 4000 ppm<br>Höhepunkt: 7200 mg/m <sup>3</sup> |
| Butane         |                                                       | STEL: 750 ppm 15 min                                                                                                                      | TWA: 1000 ppm (8 Stunden). AGW                                                                                                                                                                                                                                                |

# SAFETY DATA SHEET

Aluminium oxide, Aerosol Refractory Paint

Revision Date 01-Apr-2025

|  |  |                                                                                                                                          |                                                                                                                                                                                                                                             |
|--|--|------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  |  | STEL: 1810 mg/m <sup>3</sup> 15 min<br>TWA: 600 ppm 8 hr<br>TWA: 1450 mg/m <sup>3</sup> 8 hr<br>Carc. containing >0.1%<br>Buta-1,3-diene | - exposure factor 4<br>TWA: 2400 mg/m <sup>3</sup> (8 Stunden).<br>AGW - exposure factor 4<br>TWA: 1000 ppm (8 Stunden). MAK<br>TWA: 2400 mg/m <sup>3</sup> (8 Stunden).<br>MAK<br>Höhepunkt: 4000 ppm<br>Höhepunkt: 9600 mg/m <sup>3</sup> |
|--|--|------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

## Exposure Controls

### Engineering Measures

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

### Personal protective equipment

#### **Eye Protection**

Goggles

#### **Hand Protection**

Protective gloves

#### **Skin and body protection**

Long sleeved clothing

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

#### **Respiratory Protection**

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators

#### **Recommended Filter type:**

low boiling organic solvent Type AX Brown conforming to EN371

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

When RPE is used a face piece Fit Test should be conducted

### Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice

### Environmental exposure controls

Do not allow material to contaminate ground water system

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

|                |                          |
|----------------|--------------------------|
| Appearance     | White                    |
| Physical State | Liquid Aerosol           |
| Odor           | No information available |
| Odor Threshold | No data available        |
| pH             | No information available |

|                     |                     |
|---------------------|---------------------|
| Melting Point/Range | No data available   |
| Softening Point     | No data available   |
| Boiling Point/Range | -44 °C / -47.2 °F   |
| Flash Point         | -104 °C / -155.2 °F |

**Method** - No information available

# SAFETY DATA SHEET

Aluminium oxide, Aerosol Refractory Paint

Revision Date 01-Apr-2025

|                          |                                                                     |
|--------------------------|---------------------------------------------------------------------|
| Evaporation Rate         | No data available                                                   |
| Flammability (solid,gas) | No information available                                            |
| Explosion Limits         | No data available <b>Lower</b> 1.5 Vol %<br><b>Upper</b> 13.0 Vol % |

|                              |                          |             |
|------------------------------|--------------------------|-------------|
| Vapor Pressure               | No data available        |             |
| Vapor Density                | No data available        | (Air = 1.0) |
| Specific Gravity / Density   | No data available        |             |
| Bulk Density                 | No data available        |             |
| Water Solubility             | Partially miscible       |             |
| Solubility in other solvents | No information available |             |

## Partition Coefficient (n-octanol/water)

| Component     | log Pow |
|---------------|---------|
| Acetone       | -0.24   |
| Ethyl alcohol | -0.32   |
| Propane       | 1.09    |
| Butane        | 2.31    |

|                           |                          |
|---------------------------|--------------------------|
| Autoignition Temperature  | No data available        |
| Decomposition Temperature | No data available        |
| Viscosity                 | No data available        |
| Explosive Properties      | No information available |
| Oxidizing Properties      | No information available |

|                |    |
|----------------|----|
| VOC Content(%) | 80 |
|----------------|----|

## SECTION 10: STABILITY AND REACTIVITY

### Reactivity

None known, based on information available.

### Chemical Stability

Stable under normal conditions.

### Possibility of Hazardous Reactions

|                          |                                          |
|--------------------------|------------------------------------------|
| Hazardous Polymerization | Hazardous polymerization does not occur. |
| Hazardous Reactions      | None under normal processing.            |

### Conditions to Avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F.

### Incompatible Materials

Strong oxidizing agents.

### Hazardous Decomposition Products

# SAFETY DATA SHEET

Aluminium oxide, Aerosol Refractory Paint

Revision Date 01-Apr-2025

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

## SECTION 11: TOXICOLOGICAL INFORMATION

### Information on Toxicological Effects

#### Product Information

##### (a) acute toxicity;

Oral No data available  
Dermal No data available  
Inhalation No data available

| Component      | LD50 Oral                                                    | LD50 Dermal                                  | LC50 Inhalation                                                   |
|----------------|--------------------------------------------------------------|----------------------------------------------|-------------------------------------------------------------------|
| Acetone        | 5800 mg/kg ( Rat )                                           | > 15800 mg/kg (rabbit)<br>> 7400 mg/kg (rat) | 76 mg/l, 4 h, (rat)                                               |
| Ethyl alcohol  | LD50 = 10470 mg/kg<br>OECD 401 (Rat)<br>3450 mg/kg ( Mouse ) | -                                            | LC50 = 117-125 mg/l (4h)<br>OECD 403 (rat)<br>20000 ppm/10H (rat) |
| Aluminum oxide | > 5000 mg/kg ( Rat )<br>(OECD Guideline 401)                 | -                                            | > 2.3 mg/l 4 h<br>(OECD Guideline 403)                            |
| Propane        | -                                                            | -                                            | LC50 > 20000 ppm ( Rat ) 4h                                       |
| Butane         | -                                                            | -                                            | 658 mg/L ( Rat ) 4 h                                              |

(b) skin corrosion/irritation; No data available

(c) serious eye damage/irritation; No data available

##### (d) respiratory or skin sensitization;

Respiratory No data available  
Skin No data available

| Component                       | Test method                                       | Test species | Study result    |
|---------------------------------|---------------------------------------------------|--------------|-----------------|
| Acetone<br>67-64-1 ( 35 )       | Guinea Pig Maximisation Test<br>(GPMT)            | guinea pig   | non-sensitising |
| Ethyl alcohol<br>64-17-5 ( 20 ) | Mouse Ear Swelling Test (MEST)                    | mouse        | non-sensitising |
|                                 | OECD Test Guideline 429<br>Local Lymph Node Assay | mouse        | non-sensitising |

(e) germ cell mutagenicity; No data available

| Component                       | Test method                                                | Test species          | Study result |
|---------------------------------|------------------------------------------------------------|-----------------------|--------------|
| Acetone<br>67-64-1 ( 35 )       | OECD Test Guideline 471<br>AMES test                       | in vivo               | negative     |
|                                 | OECD Test Guideline 476<br>Mammalian<br>Gene cell mutation | in vitro              | negative     |
| Ethyl alcohol<br>64-17-5 ( 20 ) | AMES test<br>OECD Test Guideline 471                       | in vitro<br>Bacteria  | negative     |
|                                 | Gene cell mutation<br>OECD Test Guideline 476              | in vitro<br>Mammalian | negative     |

# SAFETY DATA SHEET

Aluminium oxide, Aerosol Refractory Paint

Revision Date 01-Apr-2025

**(f) carcinogenicity;** No data available  
There are no known carcinogenic chemicals in this product

| Component      | EU           | UK | Germany             | IARC |
|----------------|--------------|----|---------------------|------|
| Aluminum oxide |              |    | Cat. 2 (Fibre dust) |      |
| Butane         | Carc Cat. 1A |    |                     |      |

**(g) reproductive toxicity;** No data available

| Component                       | Test method             | Test species / Duration      | Study result          |
|---------------------------------|-------------------------|------------------------------|-----------------------|
| Ethyl alcohol<br>64-17-5 ( 20 ) | OECD Test Guideline 416 | Oral / mouse<br>2 Generation | NOAEL = 13.8 g/kg/day |
|                                 | OECD Test Guideline 414 | Inhalation / Rat             | NOAEC =<br>16000 ppm  |

**(h) STOT-single exposure;** Category 3  
**Results / Target organs** Central nervous system (CNS).

**(i) STOT-repeated exposure;** No data available  
**Target Organs** No information available.

**(j) aspiration hazard;** No data available

**Symptoms / effects,both acute and delayed** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. May cause pulmonary edema. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. May cause central nervous system depression.

**Endocrine Disrupting Properties** Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

## SECTION 12: ECOLOGICAL INFORMATION

### Ecotoxicity effects

| Component     | Freshwater Fish                                                                                                                                                                     | Water Flea                                                             | Freshwater Algae                              | Microtox                                                                                                              |
|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------|-----------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|
| Acetone       | Oncorhynchus mykiss:<br>LC50 = 5540 mg/l 96h<br>Alburnus alburnus:<br>LC50 = 11000 mg/l 96h<br>Leuciscus idus: LC50 =<br>11300 mg/L/48h<br>Salmo gairdneri: LC50 =<br>6100 mg/L/24h | EC50 = 8800 mg/L/48h<br>EC50 = 12700 mg/L/48h<br>EC50 = 12600 mg/L/48h | NOEC = 430 mg/l<br>(algae; 96 h)              | EC50 = 14500 mg/L/15<br>min                                                                                           |
| Ethyl alcohol | Fathead minnow<br>(Pimephales promelas)<br>LC50 = 14200 mg/l/96h                                                                                                                    | EC50 = 9268 mg/L/48h<br>EC50 = 10800 mg/L/24h                          | EC50 (72h) = 275 mg/l<br>(Chlorella vulgaris) | Photobacterium<br>phosphoreum:EC50 =<br>34634 mg/L/30 min<br>Photobacterium<br>phosphoreum:EC50 =<br>35470 mg/L/5 min |

**Persistence and degradability** Readily biodegradable  
**Persistence** Persistence is unlikely, based on information available.

| Component                 | Degradability            |
|---------------------------|--------------------------|
| Acetone<br>67-64-1 ( 35 ) | 91 % (28 d) (OECD 301 B) |



# SAFETY DATA SHEET

Aluminium oxide, Aerosol Refractory Paint

Revision Date 01-Apr-2025

|                                 |                 |
|---------------------------------|-----------------|
| Ethyl alcohol<br>64-17-5 ( 20 ) | OECD 301E = 94% |
|---------------------------------|-----------------|

**Bioaccumulative potential** Bioaccumulation is unlikely

| Component     | log Pow | Bioconcentration factor (BCF) |
|---------------|---------|-------------------------------|
| Acetone       | -0.24   | 0.69 dimensionless            |
| Ethyl alcohol | -0.32   | No data available             |
| Propane       | 1.09    | No data available             |
| Butane        | 2.31    | No data available             |

**Mobility in soil**

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in air.

**Endocrine Disruptor Information**

This product does not contain any known or suspected endocrine disruptors

**Other adverse effects**

No information available

## SECTION 13: DISPOSAL CONSIDERATIONS

**Waste treatment methods**

**Waste from Residues/Unused Products**

Waste is classified as hazardous Pressurized container: Do not pierce or burn, even after use Dispose of in accordance with the European Directives on waste and hazardous waste Dispose of in accordance with local regulations

**Contaminated Packaging**

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous Keep product and empty container away from heat and sources of ignition

**Other Information**

Waste codes should be assigned by the user based on the application for which the product was used Do not flush to sewer

## SECTION 14: TRANSPORT INFORMATION

**IMDG/IMO**

UN-No UN1950  
Hazard Class 2.1  
Proper Shipping Name AEROSOLS

**Road and Rail Transport**

UN-No UN1950  
Hazard Class 2.1  
Subsidiary Hazard Class 5F  
Proper Shipping Name Aerosols

**IATA**

UN-No UN1950  
Hazard Class 2.1  
Proper Shipping Name AEROSOLS, FLAMMABLE

**Special Precautions for User**

No special precautions required

# SAFETY DATA SHEET

Aluminium oxide, Aerosol Refractory Paint

Revision Date 01-Apr-2025

## SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories X = listed

| Component      | EINECS    | TSCA | DSL | PICCS | ENCS | ISHL | IECSC | AICS | KECL     |
|----------------|-----------|------|-----|-------|------|------|-------|------|----------|
| Acetone        | 200-662-2 | X    | X   | X     | X    | X    | X     | X    | KE-29367 |
| Ethyl alcohol  | 200-578-6 | X    | X   | X     | X    | X    | X     | X    | KE-13217 |
| Aluminum oxide | 215-691-6 | X    | X   | X     | X    | X    | X     | X    | KE-01012 |
| Propane        | 200-827-9 | X    | X   | X     | X    | X    | X     | X    | KE-29258 |
| Butane         | 203-448-7 | X    | X   | X     | X    | X    | X     | X    | KE-03751 |

| Component     | Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification | Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements | Rotterdam Convention (PIC) | Basel Convention (Hazardous Waste) |
|---------------|-------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|----------------------------|------------------------------------|
| Acetone       |                                                                                           |                                                                                          |                            | Annex I - Y42                      |
| Ethyl alcohol |                                                                                           |                                                                                          |                            | Annex I - Y42                      |

### National Regulations

**Persistent Organic Pollutant** This product does not contain any known or suspected substance  
**Ozone Depletion Potential** This product does not contain any known or suspected substance

## SECTION 16: OTHER INFORMATION

### Legend

**CAS** - Chemical Abstracts Service

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List

**ENCS** - Japanese Existing and New Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**NZIoC** - New Zealand Inventory of Chemicals

**WEL** - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**RPE** - Respiratory Protective Equipment

**LC50** - Lethal Concentration 50%

**POW** - Partition coefficient Octanol:Water

**TWA** - Time Weighted Average

**IARC** - International Agency for Research on Cancer

**LD50** - Lethal Dose 50%

**EC50** - Effective Concentration 50%

**ADR** - European Agreement Concerning the International Carriage of Dangerous Goods by Road

**IMO/IMDG** - International Maritime Organization/International Maritime Dangerous Goods Code

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

**ICAO/IATA** - International Civil Aviation Organization/International Air Transport Association

**MARPOL** - International Convention for the Prevention of Pollution from Ships

**ATE** - Acute Toxicity Estimate

**VOC** - (Volatile Organic Compound)

### **Key literature references and sources for data**

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

# SAFETY DATA SHEET

Aluminium oxide, Aerosol Refractory Paint

Revision Date 01-Apr-2025

---

|                  |                                             |
|------------------|---------------------------------------------|
| Prepared By      | Health, Safety and Environmental Department |
| Revision Date    | 01-Apr-2025                                 |
| Revision Summary | Not applicable.                             |

**In accordance with local and national regulations: Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013**

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**