

Creation Date 20-Aug-2009

Revision Date 25-Sep-2023

Revision Number 11

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: Hydrogen chloride, 5 to 6N solution in 2-propanol
Cat No. : 133700000; 133700010; 133700025
Synonyms Muriatic acid in Isopropanol

Unique Formula Identifier (UFI) TDNW-G27E-HX05-9HAQ

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

EU entity/business name
Thermo Fisher Scientific
Janssen Pharmaceuticaaan 3a, 2440 Geel, Belgium

UK entity/business name
Fisher Scientific UK
Bishop Meadow Road,
Loughborough, Leicestershire LE11 5RG, United Kingdom

Swiss distributor - Fisher Scientific AG
Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
e-mail - infoch@thermofisher.com

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

Poison Centre - Emergency information services

Ireland : National Poisons Information Centre (NPIC) -
01 809 2166 (8am-10pm, 7 days a week)
Malta : +356 2395 2000
Cyprus : +357 2240 5611

SECTION 2: HAZARDS IDENTIFICATION

SAFETY DATA SHEET

Hydrogen chloride, 5 to 6N solution in 2-propanol

Revision Date 25-Sep-2023

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Flammable liquids

Category 2 (H225)

Health hazards

Acute Inhalation Toxicity - Vapors

Category 4 (H332)

Skin Corrosion/Irritation

Category 1 A (H314)

Serious Eye Damage/Eye Irritation

Category 1 (H318)

Specific target organ toxicity - (single exposure)

Category 3 (H336)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H314 - Causes severe skin burns and eye damage

H332 - Harmful if inhaled

H336 - May cause drowsiness or dizziness

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/physician

2.3. Other hazards

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

SAFETY DATA SHEET

Hydrogen chloride, 5 to 6N solution in 2-propanol

Revision Date 25-Sep-2023

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Isopropyl alcohol	67-63-0	200-661-7	70-80	Flam. Liq. 2 (H225) Eye Irrit. 2 (H319) STOT SE 3 (H336)
Hydrochloric acid	7647-01-0	231-595-7	20-30	Skin Corr. 1A (H314) Eye Dam. 1 (H318) Acute Tox. 3 (H331) EUH071

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Hydrochloric acid	-	-	-

Components	Reach Registration Number
Propan-2-ol	01-2119457558-25
Hydrogen chloride	01-2119484862-27

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice	Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.
Ingestion	Do NOT induce vomiting. Call a physician or poison control center immediately.
Inhalation	If breathing is difficult, give oxygen. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Remove to fresh air. Immediate medical attention is required.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. . Causes burns by all exposure routes. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

SAFETY DATA SHEET

Hydrogen chloride, 5 to 6N solution in 2-propanol

Revision Date 25-Sep-2023

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

The product causes burns of eyes, skin and mucous membranes. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂), Hydrogen chloride gas.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Should not be released into the environment. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Use only under a chemical fume hood. Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges. Contents may develop pressure upon prolonged storage. Use caution when opening.

SAFETY DATA SHEET

Hydrogen chloride, 5 to 6N solution in 2-propanol

Revision Date 25-Sep-2023

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Corrosives area. Keep away from heat, sparks and flame. Do not store in metal containers.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Class 3

Switzerland - Storage of hazardous substances

Storage class - SC 3

<https://www.kvu.ch/de/themen/stoffe-und-produkte>

<https://www.kvu.ch/fr/themes/substances-et-produits>

<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Isopropyl alcohol		STEL: 500 ppm 15 min STEL: 1250 mg/m ³ 15 min TWA: 400 ppm 8 hr TWA: 999 mg/m ³ 8 hr	STEL / VLCT: 400 ppm. STEL / VLCT: 980 mg/m ³ .	TWA: 200 ppm 8 uren TWA: 500 mg/m ³ 8 uren STEL: 400 ppm 15 minuten STEL: 1000 mg/m ³ 15 minuten	STEL / VLA-EC: 400 ppm (15 minutos). STEL / VLA-EC: 1000 mg/m ³ (15 minutos). TWA / VLA-ED: 200 ppm (8 horas) TWA / VLA-ED: 500 mg/m ³ (8 horas)
Hydrochloric acid	TWA: 5 ppm (8h) TWA: 8 mg/m ³ (8h) STEL: 10 ppm (15min) STEL: 15 mg/m ³ (15min)	STEL: 5 ppm 15 min STEL: 8 mg/m ³ 15 min TWA: 1 ppm 8 hr TWA: 2 mg/m ³ 8 hr	STEL / VLCT: 5 ppm. restrictive limit STEL / VLCT: 7.6 mg/m ³ . restrictive limit	TWA: 5 ppm 8 uren TWA: 8 mg/m ³ 8 uren STEL: 10 ppm 15 minuten STEL: 15 mg/m ³ 15 minuten	STEL / VLA-EC: 10 ppm (15 minutos). STEL / VLA-EC: 15 mg/m ³ (15 minutos). TWA / VLA-ED: 5 ppm (8 horas) TWA / VLA-ED: 7.6 mg/m ³ (8 horas)

Component	Italy	Germany	Portugal	The Netherlands	Finland
Isopropyl alcohol		TWA: 200 ppm (8 Stunden). AGW - exposure factor 2 TWA: 500 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 200 ppm (8 Stunden). MAK TWA: 500 mg/m ³ (8 Stunden). MAK Höhepunkt: 400 ppm	STEL: 400 ppm 15 minutos TWA: 200 ppm 8 horas		TWA: 200 ppm 8 tunteina TWA: 500 mg/m ³ 8 tunteina STEL: 250 ppm 15 minuutteina STEL: 620 mg/m ³ 15 minuutteina

SAFETY DATA SHEET

Hydrogen chloride, 5 to 6N solution in 2-propanol

Revision Date 25-Sep-2023

		Höhepunkt: 1000 mg/m ³			
Hydrochloric acid	TWA: 5 ppm 8 ore. Time Weighted Average TWA: 8 mg/m ³ 8 ore. Time Weighted Average STEL: 10 ppm 15 minuti. Short-term STEL: 15 mg/m ³ 15 minuti. Short-term	TWA: 2 ppm (8 Stunden). AGW - exposure factor 2 TWA: 3 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 2 ppm (8 Stunden). MAK TWA: 3.0 mg/m ³ (8 Stunden). MAK Höhepunkt: 4 ppm Höhepunkt: 6 mg/m ³	STEL: 10 ppm 15 minutos STEL: 15 mg/m ³ 15 minutos Ceiling: 2 ppm TWA: 5 ppm 8 horas TWA: 8 mg/m ³ 8 horas	STEL: 15 mg/m ³ 15 minuten TWA: 8 mg/m ³ 8 uren	STEL: 5 ppm 15 minuutteina STEL: 7.6 mg/m ³ 15 minuutteina

Component	Austria	Denmark	Switzerland	Poland	Norway
Isopropyl alcohol	MAK-KZGW: 800 ppm 15 Minuten MAK-KZGW: 2000 mg/m ³ 15 Minuten MAK-TMW: 200 ppm 8 Stunden MAK-TMW: 500 mg/m ³ 8 Stunden	TWA: 200 ppm 8 timer TWA: 490 mg/m ³ 8 timer STEL: 400 ppm 15 minutter STEL: 980 mg/m ³ 15 minutter	STEL: 400 ppm 15 Minuten STEL: 1000 mg/m ³ 15 Minuten TWA: 200 ppm 8 Stunden TWA: 500 mg/m ³ 8 Stunden	STEL: 1200 mg/m ³ 15 minutach TWA: 900 mg/m ³ 8 godzinach	TWA: 100 ppm 8 timer TWA: 245 mg/m ³ 8 timer STEL: 150 ppm 15 minutter. value calculated STEL: 306.25 mg/m ³ 15 minutter. value calculated
Hydrochloric acid	MAK-KZGW: 10 ppm 15 Minuten MAK-KZGW: 15 mg/m ³ 15 Minuten MAK-TMW: 5 ppm 8 Stunden MAK-TMW: 8 mg/m ³ 8 Stunden	STEL: 5 ppm 15 minutter STEL: 8 mg/m ³ 15 minutter	STEL: 4 ppm 15 Minuten STEL: 6 mg/m ³ 15 Minuten TWA: 2 ppm 8 Stunden TWA: 3 mg/m ³ 8 Stunden	STEL: 10 mg/m ³ 15 minutach TWA: 5 mg/m ³ 8 godzinach	Ceiling: 5 ppm Ceiling: 7 mg/m ³

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Isopropyl alcohol	TWA: 980.0 mg/m ³ STEL : 1225.0 mg/m ³	TWA-GVI: 400 ppm 8 satima. TWA-GVI: 999 mg/m ³ 8 satima. STEL-KGVI: 500 ppm 15 minutama. STEL-KGVI: 1250 mg/m ³ 15 minutama.	TWA: 200 ppm 8 hr. STEL: 400 ppm 15 min Skin		TWA: 500 mg/m ³ 8 hodinách. Potential for cutaneous absorption Ceiling: 1000 mg/m ³
Hydrochloric acid	TWA: 5 ppm TWA: 8.0 mg/m ³ STEL : 10 ppm STEL : 15.0 mg/m ³	TWA-GVI: 5 ppm 8 satima. TWA-GVI: 8 mg/m ³ 8 satima. STEL-KGVI: 10 ppm 15 minutama. STEL-KGVI: 15 mg/m ³ 15 minutama.	TWA: 8 mg/m ³ 8 hr. F TWA: 5 ppm 8 hr. STEL: 10 ppm 15 min STEL: 15 mg/m ³ 15 min	STEL: 10 ppm STEL: 15 mg/m ³ TWA: 5 ppm TWA: 8 mg/m ³	TWA: 8 mg/m ³ 8 hodinách. Ceiling: 15 mg/m ³

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Isopropyl alcohol	TWA: 150 ppm 8 tundides. TWA: 350 mg/m ³ 8 tundides. STEL: 250 ppm 15 minutites. STEL: 600 mg/m ³ 15 minutites.		STEL: 500 ppm STEL: 1225 mg/m ³ TWA: 400 ppm TWA: 980 mg/m ³	STEL: 1000 mg/m ³ 15 percekben. CK TWA: 500 mg/m ³ 8 órában. AK lehetséges borön keresztüli felszívódás	TWA: 200 ppm 8 klukkustundum. TWA: 490 mg/m ³ 8 klukkustundum. Skin notation Ceiling: 400 ppm Ceiling: 980 mg/m ³
Hydrochloric acid	TWA: 5 ppm 8 tundides. TWA: 8 mg/m ³ 8 tundides. STEL: 10 ppm 15 minutites. STEL: 15 mg/m ³ 15 minutites.	TWA: 5 ppm 8 hr TWA: 8 mg/m ³ 8 hr STEL: 10 ppm 15 min STEL: 15 mg/m ³ 15 min	STEL: 5 ppm STEL: 7 mg/m ³ TWA: 5 ppm TWA: 7 mg/m ³	STEL: 16 mg/m ³ 15 percekben. CK TWA: 8 mg/m ³ 8 órában. AK	STEL: 5 ppm STEL: 8 mg/m ³

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
-----------	--------	-----------	------------	-------	---------

SAFETY DATA SHEET

Hydrogen chloride, 5 to 6N solution in 2-propanol

Revision Date 25-Sep-2023

Isopropyl alcohol	STEL: 600 mg/m ³ TWA: 350 mg/m ³	TWA: 150 ppm IPRD TWA: 350 mg/m ³ IPRD STEL: 250 ppm STEL: 600 mg/m ³			TWA: 81 ppm 8 ore TWA: 200 mg/m ³ 8 ore STEL: 203 ppm 15 minute STEL: 500 mg/m ³ 15 minute
Hydrochloric acid	STEL: 10 ppm STEL: 15 mg/m ³ TWA: 5 ppm TWA: 8 mg/m ³	TWA: 5 ppm IPRD TWA: 8 mg/m ³ IPRD STEL: 10 ppm STEL: 15 mg/m ³	TWA: 5 ppm 8 Stunden TWA: 8 mg/m ³ 8 Stunden STEL: 10 ppm 15 Minuten STEL: 15 mg/m ³ 15 Minuten	TWA: 5 ppm TWA: 8 mg/m ³ STEL: 10 ppm 15 minuti STEL: 15 mg/m ³ 15 minuti	TWA: 5 ppm 8 ore TWA: 8 mg/m ³ 8 ore STEL: 10 ppm 15 minute STEL: 15 mg/m ³ 15 minute

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Isopropyl alcohol	TWA: 10 mg/m ³ 1761 MAC: 50 mg/m ³	Ceiling: 1000 mg/m ³ TWA: 200 ppm TWA: 500 mg/m ³	TWA: 200 ppm 8 urah TWA: 500 mg/m ³ 8 urah STEL: 400 ppm 15 minutah STEL: 1000 mg/m ³ 15 minutah	Indicative STEL: 250 ppm 15 minuter Indicative STEL: 600 mg/m ³ 15 minuter TLV: 150 ppm 8 timmar. NGV TLV: 350 mg/m ³ 8 timmar. NGV	
Hydrochloric acid	MAC: 5 mg/m ³	Ceiling: 15 mg/m ³ TWA: 5 ppm TWA: 8.0 mg/m ³	TWA: 5 ppm 8 urah anhydrous TWA: 8 mg/m ³ 8 urah anhydrous STEL: 10 ppm 15 minutah anhydrous STEL: 15 mg/m ³ 15 minutah anhydrous	Binding STEL: 4 ppm 15 minuter Binding STEL: 6 mg/m ³ 15 minuter TLV: 2 ppm 8 timmar. NGV TLV: 3 mg/m ³ 8 timmar. NGV	TWA: 5 ppm 8 saat TWA: 8 mg/m ³ 8 saat STEL: 10 ppm 15 dakika STEL: 15 mg/m ³ 15 dakika

Biological limit values

List source(s):

Component	European Union	United Kingdom	France	Spain	Germany
Isopropyl alcohol				Acetone: 40 mg/L urine end of workweek	Acetone: 25 mg/L whole blood (end of shift) Acetone: 25 mg/L urine (end of shift)

Component	Italy	Finland	Denmark	Bulgaria	Romania
Isopropyl alcohol					Acetone: 50 mg/L urine end of shift

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Isopropyl alcohol 67-63-0 (70-80)				DNEL = 888mg/kg bw/day

SAFETY DATA SHEET

Hydrogen chloride, 5 to 6N solution in 2-propanol

Revision Date 25-Sep-2023

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Isopropyl alcohol 67-63-0 (70-80)				DNEL = 500mg/m ³
Hydrochloric acid 7647-01-0 (20-30)	DNEL = 15mg/m ³		DNEL = 8mg/m ³	

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Isopropyl alcohol 67-63-0 (70-80)	PNEC = 140.9mg/L	PNEC = 552mg/kg sediment dw	PNEC = 140.9mg/L	PNEC = 2251mg/L	PNEC = 28mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Isopropyl alcohol 67-63-0 (70-80)	PNEC = 140.9mg/L	PNEC = 552mg/kg sediment dw		PNEC = 160mg/kg food	

8.2. Exposure controls

Engineering Measures

Use only under a chemical fume hood. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles (European standard - EN 166)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Butyl rubber	> 480 minutes	0.5 mm	EN 374	As tested under EN374-3 Determination of Resistance to Permeation by Chemicals
Nitrile rubber	> 360 - 480 minutes	0.35 - 0.55 mm		
Viton (R)	> 480 minutes	0.4 mm		
Neoprene	< 40 minutes	0.7 mm		

Skin and body protection

Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced
Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to EN14387

Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN

SAFETY DATA SHEET

Hydrogen chloride, 5 to 6N solution in 2-propanol

Revision Date 25-Sep-2023

141

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls No information available.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance	Clear	
Odor	No information available	
Odor Threshold	No data available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	No data available	
Flammability (liquid)	Highly flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	Lower 2 Vol% Upper 12 Vol%	
Flash Point	11 °C / 51.8 °F	Method - No information available
Autoignition Temperature	399 °C / 750.2 °F	
Decomposition Temperature	No data available	
pH	Not applicable	
Viscosity	No data available	
Water Solubility	Miscible	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Isopropyl alcohol	0.05	
Vapor Pressure	No information available	
Density / Specific Gravity	0.909	
Bulk Density	Not applicable	Liquid
Vapor Density	No information available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

Molecular Weight	36.45
Explosive Properties	Vapors may form explosive mixtures with air
Evaporation Rate	No information available

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Hygroscopic.

10.3. Possibility of hazardous reactions

Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

10.4. Conditions to avoid

SAFETY DATA SHEET

Hydrogen chloride, 5 to 6N solution in 2-propanol

Revision Date 25-Sep-2023

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition. Exposure to moist air or water.

10.5. Incompatible materials

Strong oxidizing agents. Metals. Metals.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂). Hydrogen chloride gas.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral

Based on available data, the classification criteria are not met

Dermal

Based on available data, the classification criteria are not met

Inhalation

Category 4

ATE = 2600 ppm

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Isopropyl alcohol	5045 mg/kg (Rat) 3600 mg/kg (Mouse)	12800 mg/kg (Rat)	72.6 mg/L (Rat) 4 h
Hydrochloric acid	900 mg/kg (Rabbit)	> 5010 mg/kg (Rabbit)	LC50 = 4701 ppm (rat) 30 min (gas), LC50 = 588 ppm (4h) by extrapolation LC50 = 8.3 mg/L (rat) 30 min (aerosols) (MMAD < 5µm)

(b) skin corrosion/irritation;

Category 1 A

(c) serious eye damage/irritation;

Category 1

(d) respiratory or skin sensitization;

Respiratory

No data available

Skin

No data available

(e) germ cell mutagenicity;

No data available

(f) carcinogenicity;

No data available

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity;

No data available

(h) STOT-single exposure;

Category 3

Results / Target organs

Central nervous system (CNS).

(i) STOT-repeated exposure;

No data available

Target Organs

No information available.

SAFETY DATA SHEET

Hydrogen chloride, 5 to 6N solution in 2-propanol

Revision Date 25-Sep-2023

(j) aspiration hazard; No data available

Symptoms / effects, both acute and delayed Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects Large amounts will affect pH and harm aquatic organisms. Do not empty into drains.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Isopropyl alcohol	LC50: = 9640 mg/L, 96h flow-through (Pimephales promelas) LC50: > 1400000 µg/L, 96h (Lepomis macrochirus) LC50: = 11130 mg/L, 96h static (Pimephales promelas) LC50: = 10000000 µg/L, 96h (Daphnia)	13299 mg/L EC50 = 48 h 9714 mg/L EC50 = 24 h	EC50: > 1000 mg/L, 72h (Desmodesmus subspicatus) EC50: > 1000 mg/L, 96h (Desmodesmus subspicatus)

Component	Microtox	M-Factor
Isopropyl alcohol	= 35390 mg/L EC50 Photobacterium phosphoreum 5 min	

12.2. Persistence and degradability

Persistence Persistence is unlikely, based on information available, Miscible with water.

12.3. Bioaccumulative potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Isopropyl alcohol	0.05	No data available

12.4. Mobility in soil

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. The product is water soluble, and may spread in water systems. Will likely be mobile in the environment due to its volatility. Will likely be mobile in the environment due to its water solubility. Disperses rapidly in air: Highly mobile in soils

12.5. Results of PBT and vPvB assessment

No data available for assessment.

12.6. Endocrine disrupting properties

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

SAFETY DATA SHEET

Hydrogen chloride, 5 to 6N solution in 2-propanol

Revision Date 25-Sep-2023

12.7. Other adverse effects

Persistent Organic Pollutant
Ozone Depletion Potential

This product does not contain any known or suspected substance
This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

European Waste Catalogue (EWC)

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information

Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms.

Switzerland - Waste Ordinance

Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600
<https://www.fedlex.admin.ch/eli/cc/2015/891/en>

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number

UN2920

14.2. UN proper shipping name

Corrosive liquid, flammable, n.o.s.

Technical Shipping Name

Hydrogen chloride, solution in 2-propanol

14.3. Transport hazard class(es)

8

Subsidiary Hazard Class

3

14.4. Packing group

I

ADR

14.1. UN number

UN2920

14.2. UN proper shipping name

Corrosive liquid, flammable, n.o.s.

Technical Shipping Name

Hydrogen chloride, solution in 2-propanol

14.3. Transport hazard class(es)

8

Subsidiary Hazard Class

3

14.4. Packing group

I

IATA

14.1. UN number

UN2920

14.2. UN proper shipping name

Corrosive liquid, flammable, n.o.s.

Technical Shipping Name

Hydrogen chloride, solution in 2-propanol

14.3. Transport hazard class(es)

8

Subsidiary Hazard Class

3

14.4. Packing group

I

SAFETY DATA SHEET

Hydrogen chloride, 5 to 6N solution in 2-propanol

Revision Date 25-Sep-2023

- 14.5. Environmental hazards** No hazards identified
- 14.6. Special precautions for user** No special precautions required.
- 14.7. Maritime transport in bulk according to IMO instruments** Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Isopropyl alcohol	67-63-0	200-661-7	-	-	X	X	KE-29363	X	X
Hydrochloric acid	7647-01-0	231-595-7	-	-	X	X	KE-20189	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Isopropyl alcohol	67-63-0	X	ACTIVE	X	-	X	X	X
Hydrochloric acid	7647-01-0	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Isopropyl alcohol	67-63-0	-	Use restricted. See item 75. (see link for restriction details)	-
Hydrochloric acid	7647-01-0	-	Use restricted. See item 75. (see link for restriction details)	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Isopropyl alcohol	67-63-0	Not applicable	Not applicable
Hydrochloric acid	7647-01-0	25 tonne	250 tonne

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

SAFETY DATA SHEET

Hydrogen chloride, 5 to 6N solution in 2-propanol

Revision Date 25-Sep-2023

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification Water endangering class = 1 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Isopropyl alcohol	WGK1	
Hydrochloric acid	WGK1	

Component	France - INRS (Tables of occupational diseases)
Isopropyl alcohol	Tableaux des maladies professionnelles (TMP) - RG 84

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Isopropyl alcohol 67-63-0 (70-80)		Group I	
Hydrochloric acid 7647-01-0 (20-30)	Prohibited and Restricted Substances		

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H225 - Highly flammable liquid and vapor

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

H319 - Causes serious eye irritation

H331 - Toxic if inhaled

H336 - May cause drowsiness or dizziness

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

SAFETY DATA SHEET

Hydrogen chloride, 5 to 6N solution in 2-propanol

Revision Date 25-Sep-2023

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadviser - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data

Health Hazards Calculation method

Environmental hazards Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Creation Date 20-Aug-2009

Revision Date 25-Sep-2023

Revision Summary Not applicable.

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.
COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No
1907/2006 .**

**For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2,
Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and
Preparations).**

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet