

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
Product Identifier

Perihalan Produk: **Nickel on silica-alumina, catalyst**
 Product Description: **Nickel on silica-alumina, catalyst**
 Cat No. : 31276
 Molecular Formula 66+5% Ni

Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
 Uses advised against No Information available

Company

Thermo Fisher Scientific Fisher Scientific (M) Sdn Bhd
 Hap Seng Business Park, Lot 01-03, 01-04 Aras 1 Unity Square,
 No 12, Persiaran Perusahaan, Seksyen 23, 40300 Shah Alam,
 Selangor Darul Ehsan, Malaysia.
 Main line: +60 3-5525 7888

Supplier

E-mail address Enquiry.my@thermofisher.com

Emergency Telephone Number

Tel: +03-5525 7888
 CHEMTREC Malaysia **1-800-815-308** (Malay)
 CHEMTREC Malaysia (Kuala Lumpur) **+(60)-327884561** (Malay)

SECTION 2: HAZARDS IDENTIFICATION
Classification of the substance or mixture

Flammable solids	Category 2 (H228)
Skin Sensitization	Category 1 (H317)
Carcinogenicity	Category 1A (H350i)
Specific target organ toxicity - (repeated exposure)	Category 1 (H372)
Chronic aquatic toxicity	Category 4 (H413)

Label Elements


Signal Word

Danger

SAFETY DATA SHEET

Nickel on silica-alumina, catalyst

Revision Date 31-Mar-2025

Hazard Statements

H228 - Flammable solid
H317 - May cause an allergic skin reaction
H350i - May cause cancer by inhalation
H372 - Causes damage to organs through prolonged or repeated exposure
H413 - May cause long lasting harmful effects to aquatic life

Precautionary Statements

Prevention

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P240 - Ground and bond container and receiving equipment
P260 - Do not breathe dust/fume/gas/mist/vapors/spray
P264 - Wash face, hands and any exposed skin thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P272 - Contaminated work clothing should not be allowed out of the workplace
P280 - Wear protective gloves

Response

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water
P308 + P313 - IF exposed or concerned: Get medical advice/attention
P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish
P362 + P364 - Take off contaminated clothing and wash it before reuse

Storage

P403 - Store in a well-ventilated place

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Other Hazards

Toxicity to Soil Dwelling Organisms
This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No	Weight %
Nickel	7440-02-0	50.0
Nickel oxide	1313-99-1	25.0
Aluminum oxide	1344-28-1	13
Silica, amorphous	7631-86-9	12.0

SECTION 4: FIRST AID MEASURES

Description of first aid measures

General Advice

If symptoms persist, call a physician.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.

Ingestion

Clean mouth with water and drink afterwards plenty of water. Get medical attention if symptoms occur.

SAFETY DATA SHEET

Nickel on silica-alumina, catalyst

Revision Date 31-Mar-2025

Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.
<u>Most important symptoms and effects, both acute and delayed</u>	
May cause allergic skin reaction. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing.	
<u>Indication of any immediate medical attention and special treatment needed</u>	
Notes to Physician	Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing media

Suitable Extinguishing Media

approved class D extinguishers. Do not use water or foam.

Extinguishing media which must not be used for safety reasons

No information available.

Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors.

Hazardous Combustion Products

Silicon dioxide, Nickel oxides, Fumes of aluminum or aluminum oxide.

Advice for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Ensure adequate ventilation. Use personal protective equipment as required. Avoid dust formation.

Environmental precautions

Do not flush into surface water or sanitary sewer system. Should not be released into the environment. Do not allow material to contaminate ground water system.

Methods and Material for Containment and Cleaning Up

Sweep up and shovel into suitable containers for disposal. Keep in suitable, closed containers for disposal.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

SAFETY DATA SHEET

Nickel on silica-alumina, catalyst

Revision Date 31-Mar-2025

Precautions for Safe Handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Avoid dust formation.

Conditions for Safe Storage, Including any Incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Specific End Uses

Use in laboratories.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Component	Malaysia	ACGIH TLV	OSHA PEL
Nickel		TWA: 1.5 mg/m ³	(Vacated) TWA: 1 mg/m ³ TWA: 1 mg/m ³
Nickel oxide		TWA: 0.2 mg/m ³	(Vacated) TWA: 1 mg/m ³
Aluminum oxide		TWA: 1 mg/m ³	(Vacated) TWA: 10 mg/m ³ (Vacated) TWA: 5 mg/m ³ TWA: 15 mg/m ³ TWA: 5 mg/m ³
Silica, amorphous			(Vacated) TWA: 6 mg/m ³

Component	European Union	The United Kingdom	Germany
Nickel		STEL: 1.5 mg/m ³ 15 min TWA: 0.5 mg/m ³ 8 hr Skin	TWA: 0.03 mg/m ³ (8 Stunden). AGW - exposure factor 8 TWA: 0.006 mg/m ³ (8 Stunden). AGW - exposure factor 8
Nickel oxide		STEL: 1.5 mg/m ³ 15 min TWA: 0.5 mg/m ³ 8 hr Skin	TWA: 0.03 mg/m ³ (8 Stunden). AGW - exposure factor 8
Aluminum oxide		STEL: 30 mg/m ³ 15 min STEL: 12 mg/m ³ 15 min TWA: 10 mg/m ³ 8 hr TWA: 4 mg/m ³ 8 hr	TWA: 1.25 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 10 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 4 mg/m ³ (8 Stunden). MAK TWA: 1.5 mg/m ³ (8 Stunden). MAK
Silica, amorphous		STEL: 18 mg/m ³ 15 min STEL: 7.2 mg/m ³ 15 min TWA: 6 mg/m ³ 8 hr TWA: 2.4 mg/m ³ 8 hr	TWA: 4 mg/m ³ (8 Stunden). AGW - TWA: 0.02 mg/m ³ (8 Stunden). MAK Höhepunkt: 0.16 mg/m ³

Exposure Controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Wear safety glasses with side shields (or goggles)

Hand Protection

Protective gloves

Skin and body protection

Long sleeved clothing

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves.
(Refer to manufacturer/supplier for information)

SAFETY DATA SHEET

Nickel on silica-alumina, catalyst

Revision Date 31-Mar-2025

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators

Recommended Filter type:

Particulates filter conforming to EN 143

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

When RPE is used a face piece Fit Test should be conducted

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice

Environmental exposure controls

Prevent product from entering drains Do not allow material to contaminate ground water system Local authorities should be advised if significant spillages cannot be contained

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Grey
Physical State	Solid
Odor	Odorless
Odor Threshold	No data available
pH	No information available

Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flash Point	No information available	Method - No information available

Evaporation Rate	Not applicable	Solid
Flammability (solid,gas)	No information available	
Explosion Limits	No data available	

Vapor Pressure	No data available	
Vapor Density	Not applicable	Solid
Specific Gravity / Density	No data available	
Bulk Density	No data available	
Water Solubility	Insoluble in water	
Solubility in other solvents	No information available	

Partition Coefficient (n-octanol/water)

Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
Viscosity	Not applicable	Solid
Explosive Properties	No information available	
Oxidizing Properties	No information available	

Molecular Formula	66+5% Ni
-------------------	----------

SAFETY DATA SHEET

Nickel on silica-alumina, catalyst

Revision Date 31-Mar-2025

SECTION 10: STABILITY AND REACTIVITY

Reactivity

None known, based on information available.

Chemical Stability

Stable under normal conditions.

Possibility of Hazardous Reactions

Hazardous Polymerization Hazardous Reactions

No information available.
None under normal processing.

Conditions to Avoid

None known.

Incompatible Materials

Oxidizing agent.

Hazardous Decomposition Products

Silicon dioxide. Nickel oxides. Fumes of aluminum or aluminum oxide.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects

Product Information

(a) acute toxicity;

Oral

Based on available data, the classification criteria are not met

Dermal

Based on available data, the classification criteria are not met

Inhalation

Based on available data, the classification criteria are not met

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Nickel	LD50 > 9000 mg/kg (Rat)	-	LC50 > 10.2 mg/L (Rat) 1 h
Nickel oxide	LD50 > 5000 mg/kg (Rat)	-	LC50 > 5.08 mg/L (Rat) 4 h
Aluminum oxide	> 5000 mg/kg (Rat) (OECD Guideline 401)	-	> 2.3 mg/l 4 h (OECD Guideline 403)
Silica, amorphous	>5000 mg/kg (Rat)	>2000 mg/kg (Rabbit)	-

(b) skin corrosion/irritation;

No data available

(c) serious eye damage/irritation;

No data available

SAFETY DATA SHEET

Nickel on silica-alumina, catalyst

Revision Date 31-Mar-2025

(d) respiratory or skin sensitization;

Respiratory
Skin

No data available
Category 1

May cause sensitization by skin contact

(e) germ cell mutagenicity;

No data available

(f) carcinogenicity;

Category 1A

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Nickel			Cat. 1	Group 2B
Nickel oxide	Carc Cat. 1A		Cat. 1	Group 1
Aluminum oxide			Cat. 2 (Fibre dust)	

(g) reproductive toxicity;

No data available

(h) STOT-single exposure;

No data available

(i) STOT-repeated exposure;

Category 1

Route of exposure
Target Organs

Inhalation
Lungs.

(j) aspiration hazard;

Not applicable
Solid

Symptoms / effects, both acute and delayed

Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing.

Endocrine Disrupting Properties

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity effects

The product contains following substances which are hazardous for the environment. Contains a substance which is: Very toxic to aquatic organisms. May cause long-term adverse effects in the environment. Do not allow material to contaminate ground water system.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Nickel	LC50: > 100 mg/L, 96h (Brachydanio rerio) LC50: = 1.3 mg/L, 96h semi-static (Cyprinus carpio) LC50: = 10.4 mg/L, 96h static (Cyprinus carpio)	EC50: = 1 mg/L, 48h Static (Daphnia magna) EC50: > 100 mg/L, 48h (Daphnia magna)	EC50: 0.174 - 0.311 mg/L, 96h static (Pseudokirchneriella subcapitata) EC50: = 0.18 mg/L, 72h (Pseudokirchneriella subcapitata)	
Nickel oxide	LC50: > 100 mg/L, 96h static (Brachydanio rerio)	EC50: > 100 mg/L, 48h (Daphnia magna)	EC50: > 127.3 mg/L, 72h (Pseudokirchneriella subcapitata)	

SAFETY DATA SHEET

Nickel on silica-alumina, catalyst

Revision Date 31-Mar-2025

Silica, amorphous	LC50: 5000 mg/L/96 h	EC50: 7600 mg/L/48h	EC50: 440 mg/L/72h	
-------------------	----------------------	---------------------	--------------------	--

Persistence and degradability

Persistence
Degradability
Degradation in sewage treatment plant

Product contains heavy metals. Discharge into the environment must be avoided. Special pre-treatment is necessary
Insoluble in water, May persist.
Not relevant for inorganic substances.
Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

Bioaccumulative potential

May have some potential to bioaccumulate; Product has a high potential to bioconcentrate

Mobility in soil

Spillage unlikely to penetrate soil. Is not likely mobile in the environment due its low water solubility.

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

Other adverse effects

No information available

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous Dispose of in accordance with the European Directives on waste and hazardous waste Dispose of in accordance with local regulations

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous Keep product and empty container away from heat and sources of ignition

Other Information

Do not flush to sewer Waste codes should be assigned by the user based on the application for which the product was used Can be landfilled or incinerated, when in compliance with local regulations

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

UN-No UN3178
Hazard Class 4.1
Packing Group II
Proper Shipping Name Flammable solid, inorganic, n.o.s. (Nickel powder)

Road and Rail Transport

UN-No UN3178
Hazard Class 4.1
Packing Group II
Proper Shipping Name Flammable solid, inorganic, n.o.s. (Nickel powder)

IATA

UN-No UN3178
Hazard Class 4.1
Packing Group II
Proper Shipping Name Flammable solid, inorganic, n.o.s. (Nickel powder)

SAFETY DATA SHEET

Nickel on silica-alumina, catalyst

Revision Date 31-Mar-2025

Special Precautions for User No special precautions required

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories X = listed

Component	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	IECSC	AICS	KECL
Nickel	231-111-4	X	X	X	X		X	X	KE-25818
Nickel oxide	215-215-7	X	X	X	X	X	X	X	KE-25858
Aluminum oxide	215-691-6	X	X	X	X	X	X	X	KE-01012
Silica, amorphous	231-545-4	X	X	X	X	X	X	X	KE-31032

Component	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Nickel oxide		1 tonne		

National Regulations

Persistent Organic Pollutant This product does not contain any known or suspected substance
Ozone Depletion Potential This product does not contain any known or suspected substance

SECTION 16: OTHER INFORMATION

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

POW - Partition coefficient Octanol:Water

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

SAFETY DATA SHEET

Nickel on silica-alumina, catalyst

Revision Date 31-Mar-2025

Prepared By	Health, Safety and Environmental Department
Revision Date	31-Mar-2025
Revision Summary	Not applicable.

In accordance with local and national regulations: Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet