

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: Copper Beryllium foil, alloy C17200
Cat No. : 41913
Molecular Formula Cu:Be; 98.1:1.9 wt%

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

Thermo Fisher (Kandel) GmbH
 Erlenbachweg 2, 76870 Kandel, Germany
 Tel: +49 (0) 721 84007 280
 Fax: +49 (0) 721 84007 300

Swiss distributor - Fisher Scientific AG
 Neuhofstrasse 11, CH 4153 Reinach
 Tel: +41 (0) 56 618 41 11
<https://www.fishersci.ch/ch/en/customer-help-support/forms/email-us.html>

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:
 Tox Info Suisse Emergency Number: **145 (24hr)**
 Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
 Chemtrec (24h) Toll-Free: 0800 564 402
 Chemtrec Local: +41-43 508 20 11 (Zurich)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

SAFETY DATA SHEET

Copper Beryllium foil, alloy C17200

Revision Date 20-Feb-2024

Based on available data, the classification criteria are not met

Health hazards

Acute Inhalation Toxicity - Dusts and Mists
Skin Sensitization
Specific target organ toxicity - (repeated exposure)

Category 4 (H332)
Category 1 (H317)
Category 2 (H373)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H332 - Harmful if inhaled
H317 - May cause an allergic skin reaction
H350i - May cause cancer by inhalation
H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary Statements

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P312 - Call a POISON CENTER or doctor if you feel unwell
P302 + P352 - IF ON SKIN: Wash with plenty of soap and water
P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention
P280 - Wear protective gloves/protective clothing/eye protection/face protection

2.3. Other hazards

In accordance with Annex XIII of the REACH Regulation, inorganic substances do not require assessment

Toxicity to Soil Dwelling Organisms
Toxic to terrestrial vertebrates
This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Copper	7440-50-8	EEC No. 231-159-6	98.1	-
Beryllium	7440-41-7	EEC No. 231-150-7	1.9	Acute Tox. 3 (H301) Acute Tox. 2 (H330) Skin Irrit. 2 (H315)

SAFETY DATA SHEET

Copper Beryllium foil, alloy C17200

Revision Date 20-Feb-2024

				Eye Irrit. 2 (H319) Skin Sens. 1 (H317) Carc. 1B (H350i) STOT SE 3 (H335) STOT RE 1 (H372)
--	--	--	--	--

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice	If symptoms persist, call a physician.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Get medical attention if symptoms occur.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

May cause allergic skin reaction. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically.
---------------------------	------------------------

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Not combustible. approved class D extinguishers.

Extinguishing media which must not be used for safety reasons

Water may be ineffective.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors.

Hazardous Combustion Products

Heavy metal oxides, Metal oxides.

5.3. Advice for firefighters

SAFETY DATA SHEET

Copper Beryllium foil, alloy C17200

Revision Date 20-Feb-2024

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Avoid dust formation. No special precautions required.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system. Should not be released into the environment. Do not allow material to contaminate ground water system.

6.3. Methods and material for containment and cleaning up

Sweep up and shovel into suitable containers for disposal. Keep in suitable, closed containers for disposal. Pick up and transfer to properly labelled containers.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Avoid dust formation.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep in a dry place. Keep away from acids.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Storage Class/LGK 13

Switzerland - Storage of hazardous substances

Storage class - SC 11/13
<https://www.kvu.ch/de/themen/stoffe-und-produkte>
<https://www.kvu.ch/fr/themes/substances-et-produits>
<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority.

- The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is

CH

SAFETY DATA SHEET

Copper Beryllium foil, alloy C17200

Revision Date 20-Feb-2024

based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund). **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC

Component	European Union	The United Kingdom	France	Belgium	Spain
Copper		STEL: 0.6 mg/m ³ 15 min STEL: 2 mg/m ³ 15 min TWA: 1 mg/m ³ 8 hr TWA: 0.2 mg/m ³ 8 hr	TWA / VME: 0.2 mg/m ³ (8 heures). TWA / VME: 1 mg/m ³ (8 heures). STEL / VLCT: 2 mg/m ³ .	TWA: 0.2 mg/m ³ 8 uren TWA: 1 mg/m ³ 8 uren	TWA / VLA-ED: 0.01 mg/m ³ (8 horas)
Beryllium	TWA: 0.0002 mg/m ³ (8h) Skin	STEL: 0.006 mg/m ³ 15 min TWA: 0.002 mg/m ³ 8 hr Carc.	TWA / VME: 0.0006 mg/m ³ (8 heures). restrictive limit	TWA: 0.00005 mg/m ³ 8 uren STEL: 0.01 mg/m ³ 15 minuten Huid	TWA / VLA-ED: 0.0002 mg/m ³ (8 horas)

Component	Italy	Germany	Portugal	The Netherlands	Finland
Copper		TWA: 0.01 mg/m ³ (8 Stunden). MAK Höhepunkt: 0.02 mg/m ³	TWA: 0.2 mg/m ³ 8 horas TWA: 1 mg/m ³ 8 horas	TWA: 0.1 mg/m ³ 8 uren	TWA: 0.02 mg/m ³ 8 tunteina
Beryllium	TWA: 0.0002 mg/m ³ 8 ore. Time Weighted Average TWA: 0.0006 mg/m ³ 8 ore. Time Weighted Average until July 11, 2026 Pelle	TWA: 0.00006 mg/m ³ (8 Stunden). AGW - exposure factor 1 TWA: 0.00014 mg/m ³ (8 Stunden). AGW - exposure factor 1	STEL: 0.01 mg/m ³ 15 minutos TWA: 0.0002 mg/m ³ 8 horas TWA: 0.0006 mg/m ³ 8 horas Pele	huid TWA: 0.0006 mg/m ³ 8 uren	TWA: 0.0001 mg/m ³ 8 tunteina STEL: 0.0004 mg/m ³ 15 minuutteina Iho

Component	Austria	Denmark	Switzerland	Poland	Norway
Copper	MAK-KZGW: 4 mg/m ³ 15 Minuten MAK-KZGW: 0.4 mg/m ³ 15 Minuten MAK-TMW: 1 mg/m ³ 8 Stunden MAK-TMW: 0.1 mg/m ³ 8 Stunden	TWA: 1.0 mg/m ³ 8 timer TWA: 0.1 mg/m ³ 8 timer STEL: 2 mg/m ³ 15 minutter STEL: 0.2 mg/m ³ 15 minutter	STEL: 0.2 mg/m ³ 15 Minuten TWA: 0.1 mg/m ³ 8 Stunden	TWA: 0.2 mg/m ³ 8 godzinach	TWA: 0.1 mg/m ³ 8 timer TWA: 1 mg/m ³ 8 timer STEL: 3 mg/m ³ 15 minutter. value calculated STEL: 0.3 mg/m ³ 15 minutter. value calculated fume
Beryllium	TRK-KZGW: 0.0024 mg/m ³ 15 Minuten TRK-TMW: 0.0006 mg/m ³ MAK-KZGW: 0.0002 mg/m ³ 15 Minuten MAK-TMW: 0.00002 mg/m ³ 8 Stunden	TWA: 0.00002 mg/m ³ 8 timer STEL: 0.00004 mg/m ³ 15 minutter	TWA: 0.002 mg/m ³ 8 Stunden	TWA: 0.0002 mg/m ³ 8 godzinach	TWA: 0.0002 mg/m ³ 8 timer STEL: 0.0006 mg/m ³ 15 minutter. value calculated; valid until July 11, 2026 inhalable fraction

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Copper	TWA: 0.1 mg/m ³	TWA-GVI: 0.2 mg/m ³ 8 satima. Cu fume TWA-GVI: 1 mg/m ³ 8 satima. Cu dust STEL-KGVI: 2 mg/m ³ 15 minutama. dust Cu	TWA: 0.2 mg/m ³ 8 hr. Cu fume TWA: 1 mg/m ³ 8 hr. Cu dusts and mists STEL: 2 mg/m ³ 15 min STEL: 0.6 mg/m ³ 15 min		TWA: 1 mg/m ³ 8 hodinách. dust TWA: 0.1 mg/m ³ 8 hodinách. fume Ceiling: 2 mg/m ³ dust Ceiling: 0.2 mg/m ³ fume
Beryllium	TWA: 0.0006 mg/m ³	kože TWA-GVI: 0.002 mg/m ³ 8 satima.	TWA: 0.0002 mg/m ³ 8 hr. STEL: 0.0006 mg/m ³ 15 min Skin	TWA: 0.0002 mg/m ³	TWA: 0.0006 mg/m ³ 8 hodinách. Ceiling: 0.002 mg/m ³

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Copper	TWA: 1 mg/m ³ 8 tundides. total dust TWA: 0.2 mg/m ³ 8 tundides. respirable dust		STEL: 2 mg/m ³ TWA: 0.2 mg/m ³ TWA: 1 mg/m ³	STEL: 0.2 mg/m ³ 15 percekben. CK TWA: 0.1 mg/m ³ 8 órában. AK TWA: 0.01 mg/m ³ 8 órában. AK	TWA: 1.0 mg/m ³ 8 klukkustundum. total dust and powder TWA: 0.1 mg/m ³ 8 klukkustundum. Cu respirable fraction, fume Ceiling: 2 mg/m ³ total dust dust and powder

SAFETY DATA SHEET

Copper Beryllium foil, alloy C17200

Revision Date 20-Feb-2024

					Ceiling: 0.2 mg/m ³ Cu respirable dust, fume
Beryllium	TWA: 0.0006 mg/m ³ 8 tundides. valid until July 10, 2026		TWA: 0.0002 mg/m ³	TWA: 0.0006 mg/m ³ 8 órában. AK lehetséges bőrön keresztüli felszívódás	TWA: 0.0002 mg/m ³ 8 klukkustundum. irritates respiratory system inhalable fraction TWA: 0.0006 mg/m ³ 8 klukkustundum. valid until July 11, 2026;irritates respiratory system inhalable fraction Skin notation Ceiling: 0.0004 mg/m ³ irritates respiratory system inhalable fraction Ceiling: 0.0012 mg/m ³ valid until July 11, 2026;irritates respiratory system inhalable fraction

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Copper	STEL: 1 mg/m ³ TWA: 0.5 mg/m ³	TWA: 1 mg/m ³ inhalable fraction IPRD TWA: 0.2 mg/m ³ respirable fraction IPRD			TWA: 0.5 mg/m ³ 8 ore STEL: 0.2 mg/m ³ 15 minute STEL: 1.5 mg/m ³ 15 minute
Beryllium	TWA: 0.001 mg/m ³ TWA: 0.0002 mg/m ³	TWA: 0.0006 mg/m ³ inhalable fraction IPRD substance may affect skin and respiratory tract			TWA: 0.002 mg/m ³ 8 ore

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Copper	TWA: 0.5 mg/m ³ 1234 MAC: 1 mg/m ³	TWA: 1 mg/m ³ inhalable fraction TWA: 0.2 mg/m ³ respirable fraction		TLV: 0.01 mg/m ³ 8 timmar. NGV	
Beryllium	TWA: 0.001 mg/m ³ 0300 MAC: 0.003 mg/m ³	TWA: 0.005 mg/m ³ 8 hodinách treated metal and alloy TWA: 0.002 mg/m ³ 8 hodinách others STEL: 0.025 mg/m ³ 15 minútach treated metal and alloy STEL: 0.01 mg/m ³ 15 minútach	TWA: 0.0006 mg/m ³ 8 urah applies until July 11, 2026 inhalable fraction	TLV: 0.0002 mg/m ³ 8 timmar. NGV TLV: 0.0006 mg/m ³ 8 timmar. NGV	

Biological limit values

List source(s):

Component	Italy	Finland	Denmark	Bulgaria	Romania
Beryllium					Beryllium: 2 µg/L urine end of shift

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust

MDHS 91 Metals and metalloids in workplace air by X-ray fluorescence spectrometry

MDHS 99 Metals in air by ICP-AES

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

SAFETY DATA SHEET

Copper Beryllium foil, alloy C17200

Revision Date 20-Feb-2024

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Copper 7440-50-8 (98.1)		DNEL = 273mg/kg bw/day		DNEL = 137mg/kg bw/day

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Copper 7440-50-8 (98.1)	PNEC = 7.8µg/L	PNEC = 87mg/kg sediment dw		PNEC = 230µg/L	PNEC = 65mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Copper 7440-50-8 (98.1)	PNEC = 5.2µg/L	PNEC = 676mg/kg sediment dw			

8.2. Exposure controls

Engineering Measures

None under normal use conditions. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protective equipment

Eye Protection

Goggles (European standard - EN 166)

Hand Protection

No special protective equipment required

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Natural rubber Nitrile rubber Neoprene PVC	See manufacturers recommendations	-	EN 374	(minimum requirement)

Skin and body protection

Long sleeved clothing.

Respiratory Protection

No special protective equipment required.

Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: Particulates filter conforming to EN 143

Small scale/Laboratory use

No personal respiratory protective equipment normally required Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Particle filtering: EN149:2001

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

Prevent product from entering drains. Do not allow material to contaminate ground water system. Local authorities should be advised if significant spillages cannot be contained.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

SAFETY DATA SHEET

Copper Beryllium foil, alloy C17200

Revision Date 20-Feb-2024

Physical State	Solid	
Appearance	Bronze	
Odor	Odorless	
Odor Threshold	No data available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flammability (liquid)	Not applicable	Solid
Flammability (solid,gas)	No information available	
Explosion Limits	No data available	
Flash Point	No information available	Method - No information available
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
pH	No information available	
Viscosity	Not applicable	Solid
Water Solubility	Insoluble in water	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Vapor Pressure	<=1100 hPa @ 50 °C	
Density / Specific Gravity	8.36 g/cm3	@ 20 °C
Bulk Density	No data available	
Vapor Density	Not applicable	Solid
Particle characteristics	No data available	

9.2. Other information

Molecular Formula	Cu:Be; 98.1:1.9 wt%
Evaporation Rate	Not applicable - Solid

SECTION 10: STABILITY AND REACTIVITY

<u>10.1. Reactivity</u>	None known, based on information available
-------------------------	--

<u>10.2. Chemical stability</u>	Stable under normal conditions.
---------------------------------	---------------------------------

10.3. Possibility of hazardous reactions

Hazardous Polymerization	No information available.
Hazardous Reactions	None under normal processing.

<u>10.4. Conditions to avoid</u>	Incompatible products. Excess heat.
----------------------------------	-------------------------------------

<u>10.5. Incompatible materials</u>	None known.
-------------------------------------	-------------

<u>10.6. Hazardous decomposition products</u>	Heavy metal oxides. Metal oxides.
---	-----------------------------------

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

SAFETY DATA SHEET

Copper Beryllium foil, alloy C17200

Revision Date 20-Feb-2024

(a) acute toxicity;

Oral No data available
Dermal No data available
Inhalation Category 4

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Copper	-	-	LC50 > 5.11 mg/L (Rat) 4 h

(b) skin corrosion/irritation; No data available

(c) serious eye damage/irritation; No data available

(d) respiratory or skin sensitization;

Respiratory No data available
Skin Category 1

No information available

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; No data available

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Beryllium	Carc Cat. 1B		Cat. 1	Group 1

(g) reproductive toxicity; No data available

(h) STOT-single exposure; No data available

(i) STOT-repeated exposure; Category 2

Route of exposure Inhalation
Target Organs Lungs.

(j) aspiration hazard; Not applicable
Solid

Symptoms / effects, both acute and delayed Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

Contains a substance which is: Very toxic to aquatic organisms. The product contains following substances which are hazardous for the environment. May cause long-term adverse effects in the environment. Do not allow material to contaminate ground water

SAFETY DATA SHEET

Copper Beryllium foil, alloy C17200

Revision Date 20-Feb-2024

system.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Copper	LC50: = 1.25 mg/L, 96h static (Lepomis macrochirus) LC50: = 0.3 mg/L, 96h semi-static (Cyprinus carpio) LC50: = 0.8 mg/L, 96h static (Cyprinus carpio) LC50: = 0.112 mg/L, 96h flow-through (Poecilia reticulata) LC50: = 0.052 mg/L, 96h flow-through (Oncorhynchus mykiss) LC50: 0.0068 - 0.0156 mg/L, 96h (Pimephales promelas) LC50: < 0.3 mg/L, 96h static (Pimephales promelas) LC50: = 0.2 mg/L, 96h flow-through (Pimephales promelas)	EC50: = 0.03 mg/L, 48h Static (Daphnia magna)	EC50: 0.031 - 0.054 mg/L, 96h static (Pseudokirchneriella subcapitata) EC50: 0.0426 - 0.0535 mg/L, 72h static (Pseudokirchneriella subcapitata)

12.2. Persistence and degradability Product contains heavy metals. Discharge into the environment must be avoided. Special pre-treatment is necessary
Persistence Insoluble in water, May persist.
Degradability Not relevant for inorganic substances.
Degradation in sewage treatment plant Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential May have some potential to bioaccumulate; Product has a high potential to bioconcentrate

12.4. Mobility in soil Spillage unlikely to penetrate soil Is not likely mobile in the environment due its low water solubility.

12.5. Results of PBT and vPvB assessment In accordance with Annex XIII of the REACH Regulation, inorganic substances do not require assessment.

12.6. Endocrine disrupting properties
Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects
Persistent Organic Pollutant This product does not contain any known or suspected substance
Ozone Depletion Potential This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

European Waste Catalogue (EWC) According to the European Waste Catalog, Waste Codes are not product specific, but

SAFETY DATA SHEET

Copper Beryllium foil, alloy C17200

Revision Date 20-Feb-2024

application specific.

Other Information

Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Do not empty into drains.

Switzerland - Waste Ordinance

Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600
<https://www.fedlex.admin.ch/eli/cc/2015/891/en>

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

Not regulated

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

ADR

Not regulated

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

IATA

Not regulated

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

14.5. Environmental hazards

No hazards identified

14.6. Special precautions for user

No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Copper	7440-50-8	231-159-6	-	-	X	X	KE-08896	X	-
Beryllium	7440-41-7	231-150-7	-	-	X	X	KE-02829	X	-

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Copper	7440-50-8	X	ACTIVE	X	-	X	X	X
Beryllium	7440-41-7	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

SAFETY DATA SHEET

Copper Beryllium foil, alloy C17200

Revision Date 20-Feb-2024

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Copper	7440-50-8	-	Use restricted. See item 75. (see link for restriction details)	-
Beryllium	7440-41-7	-	Use restricted. See item 28. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Copper	7440-50-8	Not applicable	Not applicable
Beryllium	7440-41-7	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification Water endangering class = non-hazardous to waters (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Copper	WGK2	Class III : 1 mg/m ³ (Massenkonzentration)
Beryllium		Krebserzeugende Stoffe - Class I : 0.05 mg/m ³ (Massenkonzentration)

Component	France - INRS (Tables of occupational diseases)
Beryllium	Tableaux des maladies professionnelles (TMP) - RG 33

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from	Switzerland - Ordinance on Incentive Taxes on Volatile	Switzerland - Ordinance of the Rotterdam Convention on the
-----------	---	--	--

SAFETY DATA SHEET

Copper Beryllium foil, alloy C17200

Revision Date 20-Feb-2024

	handling of hazardous substances preparation (SR 814.81)	Organic Compounds (OVOC)	Prior Informed Consent Procedure
Copper 7440-50-8 (98.1)	Prohibited and Restricted Substances		

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H332 - Harmful if inhaled
H317 - May cause an allergic skin reaction
H350 - May cause cancer
H350i - May cause cancer by inhalation
H373 - May cause damage to organs through prolonged or repeated exposure
H301 - Toxic if swallowed
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H330 - Fatal if inhaled
H335 - May cause respiratory irritation
H372 - Causes damage to organs through prolonged or repeated exposure

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadviser - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data

Health Hazards Calculation method

Environmental hazards Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

SAFETY DATA SHEET

Copper Beryllium foil, alloy C17200

Revision Date 20-Feb-2024

Prepared By	Health, Safety and Environmental Department
Revision Date	20-Feb-2024
Revision Summary	New emergency telephone response service provider.

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.
COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No
1907/2006 .**

**For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2,
Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and
Preparations).**

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet