

ALFAA41775

Graphite, colloidal, lubricant, aerosol spray

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

产品说明: 石墨
Product Description: Graphite, colloidal, lubricant, aerosol spray

Cat No. : 41775

Supplier Avocado Research Chemicals Ltd.
 (Part of Thermo Fisher Scientific)
 Shore Road, Heysham
 Lancashire, LA3 2XY,
 United Kingdom
 Office Tel: +44 (0) 1524 850506
 Office Fax: +44 (0) 1524 850608

Emergency Telephone Number For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

E-mail address begel.sdsdesk@thermofisher.com

Recommended Use Laboratory chemicals.
Uses advised against No Information available

SECTION 2. HAZARD IDENTIFICATION

Physical State
 Liquid Aerosol

Appearance
 Black

Odor
 No information available

Emergency Overview

Extremely flammable aerosol. Pressurized container: May burst if heated. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness and dizziness. Very toxic to aquatic life with long lasting effects.

Classification of the substance or mixture

Extremely flammable aerosol.	Category 1
Aspiration Toxicity	Category 1
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Reproductive Toxicity	Category 2
Specific target organ toxicity - (single exposure)	Category 3
Acute aquatic toxicity	Category 1
Chronic aquatic toxicity	Category 1

Label Elements

SAFETY DATA SHEET

Graphite, colloidal, lubricant, aerosol spray

**Signal Word****Danger****Hazard Statements**

H222 - Extremely flammable aerosol
H229 - Pressurised container: May burst if heated
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H361 - Suspected of damaging fertility or the unborn child
H410 - Very toxic to aquatic life with long lasting effects

Precautionary Statements**Prevention**

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P211 - Do not spray on an open flame or other ignition source
P251 - Do not pierce or burn, even after use
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray
P264 - Wash face, hands and any exposed skin thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear eye protection/ face protection

Response

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor
P302 + P352 - IF ON SKIN: Wash with plenty of soap and water
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308 + P313 - IF exposed or concerned: Get medical advice/attention
P331 - Do NOT induce vomiting
P332 + P313 - If skin irritation occurs: Get medical advice/attention
P362 + P364 - Take off contaminated clothing and wash it before reuse

Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed
P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Physical and Chemical Hazards

Extremely flammable aerosol. Pressurized container: May burst if heated.

Health Hazards

Aspiration hazard if swallowed - can enter lungs and cause damage. Causes skin irritation. Causes serious eye irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness.

Environmental hazards

Very toxic to aquatic life with long lasting effects. Will likely be mobile in the environment due to its volatility. The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces.

This product does not contain any known or suspected endocrine disruptors.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No	Weight %
n-Heptane	142-82-5	45

SAFETY DATA SHEET

Graphite, colloidal, lubricant, aerosol spray

Propane	74-98-6	15
Isopropyl alcohol	67-63-0	15
Butane	106-97-8	15
Toluene	108-88-3	5
Graphite	7782-42-5	5

SECTION 4. FIRST AID MEASURES

General Advice

If symptoms persist, call a physician.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.

Inhalation

Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.

Ingestion

Clean mouth with water and drink afterwards plenty of water.

Most important symptoms and effects

None reasonably foreseeable. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: May cause pulmonary edema: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: May cause central nervous system depression

Self-Protection of the First Aider

Remove all sources of ignition. Use personal protective equipment as required.

Notes to Physician

Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Do not use water jetstream.

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Do not allow run-off from fire-fighting to enter drains or water courses.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

Use personal protective equipment as required. Ensure adequate ventilation.

Environmental Precautions

Should not be released into the environment. See Section 12 for additional Ecological Information. Avoid release to the

SAFETY DATA SHEET

Graphite, colloidal, lubricant, aerosol spray

environment. Collect spillage.

Methods for Containment and Clean Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal.
 Pressurized container: Do not pierce or burn, even after use

Refer to protective measures listed in Sections 8 and 13.

SECTION 7. HANDLING AND STORAGE

Handling

Do not get in eyes, on skin, or on clothing. Wear personal protective equipment/face protection. Ensure adequate ventilation. Avoid ingestion and inhalation.

Storage

Flammables area. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame.
 Pressurized container: Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Protect from sunlight.
 Do not expose to temperatures exceeding 50 °C/122 °F.

Specific Use(s)

Use in laboratories

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Component	China	Taiwan	Thailand	Hong Kong
n-Heptane	TWA: 500 mg/m ³ STEL: 1000 mg/m ³	TWA: 400 ppm TWA: 1640 mg/m ³	TWA: 500 ppm	TWA: 400 ppm TWA: 1640 mg/m ³ STEL: 500 ppm STEL: 2050 mg/m ³
Propane	-	TWA: 1000 ppm TWA: 1800 mg/m ³		TWA: 2500 ppm TWA: 4508 mg/m ³
Isopropyl alcohol	TWA: 350 mg/m ³ STEL: 700 mg/m ³	TWA: 400 ppm TWA: 983 mg/m ³	TWA: 400 ppm	TWA: 400 ppm TWA: 983 mg/m ³ STEL: 500 ppm STEL: 1230 mg/m ³
Butane	-	TWA: 800 ppm TWA: 1900 mg/m ³		TWA: 800 ppm TWA: 1900 mg/m ³
Toluene	TWA: 50 mg/m ³ STEL: 100 mg/m ³ Skin	TWA: 100 ppm TWA: 376 mg/m ³	Ceiling: 300 ppm STEL: 500 ppm TWA: 200 ppm	TWA: 50 ppm TWA: 188 mg/m ³
Graphite	TWA: 4 mg/m ³ TWA: 2 mg/m ³	-		-

Component	ACGIH TLV	OSHA PEL	NIOSH	The United Kingdom	European Union
n-Heptane	TWA: 400 ppm STEL: 500 ppm	(Vacated) TWA: 400 ppm (Vacated) TWA: 1600 mg/m ³ (Vacated) STEL: 500 ppm (Vacated) STEL: 2000 mg/m ³ TWA: 500 ppm TWA: 2000 mg/m ³	IDLH: 750 ppm TWA: 85 ppm TWA: 350 mg/m ³ Ceiling: 440 ppm Ceiling: 1800 mg/m ³	STEL: 1500 ppm 15 min STEL: 6255 mg/m ³ 15 min TWA: 500 ppm 8 hr TWA: 2085 mg/m ³ 8 hr	TWA: 500 ppm (8h) TWA: 2085 mg/m ³ (8h)
Propane	:	(Vacated) TWA: 1000 ppm (Vacated) TWA: 1800 mg/m ³ TWA: 1000 ppm TWA: 1800 mg/m ³	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³	-	
Isopropyl alcohol	TWA: 200 ppm STEL: 400 ppm	(Vacated) TWA: 400 ppm	IDLH: 2000 ppm TWA: 400 ppm	STEL: 500 ppm 15 min STEL: 1250 mg/m ³ 15 min	

SAFETY DATA SHEET**Graphite, colloidal, lubricant, aerosol spray**

		(Vacated) TWA: 980 mg/m ³ (Vacated) STEL: 500 ppm (Vacated) STEL: 1225 mg/m ³ TWA: 400 ppm TWA: 980 mg/m ³	TWA: 980 mg/m ³ STEL: 500 ppm STEL: 1225 mg/m ³	min TWA: 400 ppm 8 hr TWA: 999 mg/m ³ 8 hr	
Butane	STEL: 1000 ppm	(Vacated) TWA: 800 ppm (Vacated) TWA: 1900 mg/m ³	IDLH: 1600 ppm TWA: 800 ppm TWA: 1900 mg/m ³	STEL: 750 ppm 15 min STEL: 1810 mg/m ³ 15 min TWA: 600 ppm 8 hr TWA: 1450 mg/m ³ 8 hr Carc. containing >0.1% Buta-1,3-diene	
Toluene	TWA: 20 ppm	(Vacated) TWA: 100 ppm (Vacated) TWA: 375 mg/m ³ Ceiling: 300 ppm (Vacated) STEL: 150 ppm (Vacated) STEL: 560 mg/m ³ TWA: 200 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³	STEL: 100 ppm 15 min STEL: 384 mg/m ³ 15 min TWA: 50 ppm 8 hr TWA: 191 mg/m ³ 8 hr Skin	TWA: 50 ppm (8hr) TWA: 192 mg/m ³ (8hr) STEL: 100 ppm (15min) STEL: 384 mg/m ³ (15min) Skin
Graphite	TWA: 2 mg/m ³	(Vacated) TWA: 2.5 mg/m ³ (Vacated) TWA: 10 mg/m ³ (Vacated) TWA: 5 mg/m ³ TWA: 15 mg/m ³ TWA: 5 mg/m ³	IDLH: 1250 mg/m ³ TWA: 2.5 mg/m ³	STEL: 30 mg/m ³ 15 min STEL: 12 mg/m ³ 15 min TWA: 10 mg/m ³ 8 hr TWA: 4 mg/m ³ 8 hr	

Legend

ACGIH - American Conference of Governmental Industrial Hygienists
 OSHA - Occupational Safety and Health Administration
 NIOSH: NIOSH - National Institute for Occupational Safety and Health

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents. MDHS70 General methods for sampling airborne gases and vapours MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Exposure Controls**Engineering Measures**

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source.

Personal protective equipment

Eye Protection Goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Butyl rubber	> 480 minutes	0.5 mm	EN 374 Level 6	As tested under EN374-3 Determination of Resistance to Permeation by Chemicals
Neoprene gloves	< 30 minutes	0.45 mm		

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves.

SAFETY DATA SHEET

Graphite, colloidal, lubricant, aerosol spray

(Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Skin and body protection	Long sleeved clothing
Respiratory Protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly
Large scale/emergency use	Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced Recommended Filter type: low boiling organic solvent Type AX Brown conforming to EN371
Small scale/Laboratory use	Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141 When RPE is used a face piece Fit Test should be conducted
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice.
Environmental exposure controls	Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Black	
Physical State	Liquid Aerosol	
Odor	No information available	
Odor Threshold	No data available	
pH	No information available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flash Point	-97 °C / -142.6 °F	Method - No information available
Evaporation Rate	No data available	
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Vapor Pressure	No data available	
Vapor Density	No data available	(Air = 1.0)
Specific Gravity / Density	No data available	
Bulk Density	Not applicable	Liquid
Water Solubility	Partially miscible	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
n-Heptane	4.66	
Propane	1.09	
Isopropyl alcohol	0.05	
Butane	2.31	
Toluene	2.73	
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
Viscosity	No data available	
Explosive Properties		Vapors may form explosive mixtures with air

SAFETY DATA SHEET

Graphite, colloidal, lubricant, aerosol spray

Oxidizing Properties No information available

VOC Content(%) 95

SECTION 10. STABILITY AND REACTIVITY

Stability Stable under normal conditions.

Hazardous Reactions None under normal processing.
Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F. Keep away from open flames, hot surfaces and sources of ignition.

Materials to avoid Strong oxidizing agents.

Hazardous Decomposition Products Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11. TOXICOLOGICAL INFORMATION

Product Information

(a) acute toxicity;
Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
n-Heptane	>2000 mg/kg (rat)	LD50 = 3000 mg/kg (Rabbit)	LC50 > 73.5 mg/L (Rat) 4 h
Propane			LC50 > 20000 ppm (Rat) 4h
Isopropyl alcohol	5045 mg/kg (Rat) 3600 mg/kg (Mouse)	12800 mg/kg (Rat)	72.6 mg/L (Rat) 4 h
Butane			658 mg/L (Rat) 4 h
Toluene	> 5000 mg/kg (Rat)	LD50 = 12000 mg/kg (Rabbit)	26700 ppm (Rat) 1 h
Graphite			LC50 > 2000 mg/m ³ (Rat) 4 h

(b) skin corrosion/irritation; No data available

(c) serious eye damage/irritation; No data available

(d) respiratory or skin sensitization;
Respiratory No data available
Skin No data available

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; No data available

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Butane	Carc Cat. 1A			

(g) reproductive toxicity; No data available

SAFETY DATA SHEET

Graphite, colloidal, lubricant, aerosol spray

(h) STOT-single exposure; No data available

Results / Target organs Central nervous system (CNS)
Respiratory system

(i) STOT-repeated exposure; No data available

Target Organs No information available.

(j) aspiration hazard; Category 1

Symptoms / effects, both acute and delayed Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: May cause pulmonary edema: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: May cause central nervous system depression

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity effects The product contains following substances which are hazardous for the environment. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
n-Heptane	LC50: = 375.0 mg/L, 96h (Cichlid fish)	EC50: >10 mg/L/24h		
Isopropyl alcohol	LC50: = 9640 mg/L, 96h flow-through (Pimephales promelas) LC50: > 1400000 µg/L, 96h (Lepomis macrochirus) LC50: = 11130 mg/L, 96h static (Pimephales promelas) LC50: = 10000000 µg/L, 96h (Daphnia)	13299 mg/L EC50 = 48 h 9714 mg/L EC50 = 24 h	EC50: > 1000 mg/L, 72h (Desmodesmus subspicatus) EC50: > 1000 mg/L, 96h (Desmodesmus subspicatus)	= 35390 mg/L EC50 Photobacterium phosphoreum 5 min
Toluene	50-70 mg/L LC50 96 h 5-7 mg/L LC50 96 h 15-19 mg/L LC50 96 h 28 mg/L LC50 96 h 12 mg/L LC50 96 h	EC50: = 11.5 mg/L, 48h (Daphnia magna) EC50: 5.46 - 9.83 mg/L, 48h Static (Daphnia magna)	EC50: = 12.5 mg/L, 72h static (Pseudokirchneriella subcapitata) EC50: > 433 mg/L, 96h (Pseudokirchneriella subcapitata)	EC50 = 19.7 mg/L 30 min
Graphite	LC50: > 100 mg/L, 96h semi-static (Danio rerio)			

Persistence and Degradability Readily biodegradable
Persistence Persistence is unlikely, based on information available.

Component	Degradability
Toluene 108-88-3 (5)	86% (20d)

Degradation in sewage treatment plant Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

Bioaccumulative Potential Bioaccumulation is unlikely

SAFETY DATA SHEET

Graphite, colloidal, lubricant, aerosol spray

Component	log Pow	Bioconcentration factor (BCF)
n-Heptane	4.66	No data available
Propane	1.09	No data available
Isopropyl alcohol	0.05	No data available
Butane	2.31	No data available
Toluene	2.73	90

Mobility in soil The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in air.

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors.
Persistent Organic Pollutant This product does not contain any known or suspected substance.
Ozone Depletion Potential This product does not contain any known or suspected substance.

SECTION 13. DISPOSAL CONSIDERATIONS

Waste from Residues/Unused Products Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

Other Information Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not let this chemical enter the environment. Do not empty into drains.

SECTION 14. TRANSPORT INFORMATION

Road and Rail Transport

UN-No UN1950
 Proper Shipping Name Aerosols
 Hazard Class 2.1
 Subsidiary Hazard Class 5F

IMDG/IMO

UN-No UN1950
 Proper Shipping Name AEROSOLS
 Hazard Class 2.1

IATA

UN-No UN1950
 Proper Shipping Name AEROSOLS, FLAMMABLE
 Hazard Class 2.1

Special Precautions for User No special precautions required

SECTION 15. REGULATORY INFORMATION

International Inventories

X = listed, China (IECSC), Europe (EINECS/ELINCS/NLP), U.S.A. (TSCA), Canada (DSL/NDSL), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), Korea (KECL).

Component	The	List of	TCSI	IECSC	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	AICS	KECL
-----------	-----	---------	------	-------	--------	------	-----	-------	------	------	------	------

SAFETY DATA SHEET

Graphite, colloidal, lubricant, aerosol spray

	Inventory of Hazardous Chemicals (2015 Edition)	dangerous goods GB 12268 - 2012										
n-Heptane	X	X	X	X	205-563-8	X	X	X	X	X	X	KE-18271
Propane	X	X	X	X	200-827-9	X	X	X	X	X	X	KE-29258
Isopropyl alcohol	X	X	X	X	200-661-7	X	X	X	X	X	X	KE-29363
Butane	X	X	X	X	203-448-7	X	X	X	X	X	X	KE-03751
Toluene	X	X	X	X	203-625-9	X	X	X	X	X	X	KE-33936
Graphite	-	-	X	X	231-955-3	X	X	X	-		X	KE-18101

National Regulations

SECTION 16. OTHER INFORMATION

Prepared By Health, Safety and Environmental Department
Creation Date 16-Mar-2018
Revision Date 12-May-2024
Revision Summary New emergency telephone response service provider.

Training Advice
 Chemical incident response training.

Legend

CAS - Chemical Abstracts Service EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances PICCS - Philippines Inventory of Chemicals and Chemical Substances IECSC - Chinese Inventory of Existing Chemical Substances KECL - Korean Existing and Evaluated Chemical Substances WEL - Workplace Exposure Limit ACGIH - American Conference of Governmental Industrial Hygienists DNEL - Derived No Effect Level RPE - Respiratory Protective Equipment LC50 - Lethal Concentration 50% NOEC - No Observed Effect Concentration PBT - Persistent, Bioaccumulative, Toxic ICAO/IATA - International Civil Aviation Organization/International Air Transport Association ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road OECD - Organisation for Economic Co-operation and Development BCF - Bioconcentration factor	TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List ENCS - Japanese Existing and New Chemical Substances AICS - Australian Inventory of Chemical Substances NZIoC - New Zealand Inventory of Chemicals TWA - Time Weighted Average IARC - International Agency for Research on Cancer PNEC - Predicted No Effect Concentration LD50 - Lethal Dose 50% EC50 - Effective Concentration 50% POW - Partition coefficient Octanol:Water vPvB - very Persistent, very Bioaccumulative IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code MARPOL - International Convention for the Prevention of Pollution from Ships ATE - Acute Toxicity Estimate VOC - (Volatile Organic Compound)
---	--

Key literature references and sources for data
<https://echa.europa.eu/information-on-chemicals>
 Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Physical hazards On basis of test data
Health Hazards Calculation method
Environmental hazards Calculation method

SAFETY DATA SHEET

Graphite, colloidal, lubricant, aerosol spray

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet