

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: **Potassium tert-butoxide, 1.0M in THF**
Cat No. : **H30530**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use: Laboratory chemicals.
Uses advised against: No Information available

1.3. Details of the supplier of the safety data sheet

Company

Thermo Fisher (Kandel) GmbH
Erlenbachweg 2, 76870 Kandel, Germany
Tel: +49 (0) 721 84007 280
Fax: +49 (0) 721 84007 300

Swiss distributor - Fisher Scientific AG
Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
<https://www.fishersci.ch/ch/en/customer-help-support/forms/email-us.html>

E-mail address: begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Flammable liquids

Category 2 (H225)

SAFETY DATA SHEET

Potassium tert-butoxide, 1.0M in THF

Revision Date 07-Dec-2024

Self-heating substances/mixtures	Category 2 (H252)
Health hazards	
Acute oral toxicity	Category 4 (H302)
Skin Corrosion/Irritation	Category 1 A (H314)
Serious Eye Damage/Eye Irritation	Category 1 (H318)
Carcinogenicity	Category 2 (H351)
Specific target organ toxicity - (single exposure)	Category 3 (H335) (H336)
Environmental hazards	
Based on available data, the classification criteria are not met	

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor
H252 - Self-heating in large quantities; may catch fire
H302 - Harmful if swallowed
H314 - Causes severe skin burns and eye damage
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H351 - Suspected of causing cancer
EUH014 - Reacts violently with water
EUH019 - May form explosive peroxides

Precautionary Statements

P235 + P410 - Keep cool. Protect from sunlight
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a POISON CENTER or doctor/physician
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

2.3. Other hazards

Toxic to terrestrial vertebrates
This product does not contain any known or suspected endocrine disruptors

Section 3: Composition/information on ingredients

SAFETY DATA SHEET

Potassium tert-butoxide, 1.0M in THF

Revision Date 07-Dec-2024

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Tetrahydrofuran	109-99-9	203-726-8	80-90	Flam. Liq. 2 (H225) Acute Tox. 4 (H302) Eye Irrit. 2 (H319) STOT SE 3 (H335) STOT SE 3 (H336) Carc. 2 (H351) (EUH019)
2-Propanol, 2-methyl-, potassium salt	865-47-4	EEC No. 212-740-3	10-15	Flam. Sol. 1 (H228) Self-heat. 2 (H252) Skin Corr. 1A (H314) Eye Dam. 1 (H318) (EUH014)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Tetrahydrofuran	Acute Tox. 4 :: C>82.5% Eye Irrit. 2 :: C>=25% STOT SE 3 :: C>=25%	-	-

Full text of Hazard Statements: see section 16

Section 4: First aid measures

4.1. Description of first aid measures

General Advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Call a physician immediately.
Ingestion	Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately.
Inhalation	If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation

SAFETY DATA SHEET

Potassium tert-butoxide, 1.0M in THF

Revision Date 07-Dec-2024

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically.

Section 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Water.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Reacts violently with water. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂), Potassium oxides.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Should not be released into the environment.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Do not expose spill to water. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

Section 7: Handling and storage

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Do not allow contact with water. If peroxide formation is suspected, do not open or move container. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the

SAFETY DATA SHEET

Potassium tert-butoxide, 1.0M in THF

Revision Date 07-Dec-2024

equipment must be grounded. Take precautionary measures against static discharges.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep under nitrogen. Corrosives area. Keep away from water or moist air. Keep containers tightly closed in a dry, cool and well-ventilated place. Containers should be dated when opened and tested periodically for the presence of peroxides. Should crystals form in a peroxidizable liquid, peroxidation may have occurred and the product should be considered extremely dangerous. In this instance, the container should only be opened remotely by professionals. Keep away from heat, sparks and flame.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Storage Class/LGK 4.2

Switzerland - Storage of hazardous substances

Storage class - SC 4.2

<https://www.kvu.ch/de/themen/stoffe-und-produkte>

<https://www.kvu.ch/fr/themes/substances-et-produits>

<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

Section 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Tetrahydrofuran	TWA: 50 ppm (8h) TWA: 150 mg/m ³ (8h) STEL: 100 ppm (15min) STEL: 300 mg/m ³ (15min) Skin	STEL: 100 ppm 15 min STEL: 300 mg/m ³ 15 min TWA: 50 ppm 8 hr TWA: 150 mg/m ³ 8 hr Skin	TWA / VME: 50 ppm (8 heures). restrictive limit TWA / VME: 150 mg/m ³ (8 heures). restrictive limit STEL / VLCT: 100 ppm. restrictive limit STEL / VLCT: 300 mg/m ³ . restrictive limit Peau	TWA: 50 ppm 8 uren TWA: 150 mg/m ³ 8 uren STEL: 100 ppm 15 minuten STEL: 300 mg/m ³ 15 minuten Huid	STEL / VLA-EC: 100 ppm (15 minutos). STEL / VLA-EC: 300 mg/m ³ (15 minutos). TWA / VLA-ED: 50 ppm (8 horas) TWA / VLA-ED: 150 mg/m ³ (8 horas) Piel

Component	Italy	Germany	Portugal	The Netherlands	Finland
Tetrahydrofuran	TWA: 50 ppm 8 ore. Time Weighted Average TWA: 150 mg/m ³ 8 ore. Time Weighted Average STEL: 100 ppm 15 minuti. Short-term STEL: 300 mg/m ³ 15 minuti. Short-term Pelle	TWA: 50 ppm (8 Stunden). AGW - exposure factor 2 TWA: 150 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 20 ppm (8 Stunden). MAK TWA: 60 mg/m ³ (8 Stunden). MAK Höhepunkt: 40 ppm	STEL: 100 ppm 15 minutos STEL: 300 mg/m ³ 15 minutos TWA: 50 ppm 8 horas TWA: 150 mg/m ³ 8 horas Pele	huid STEL: 200 ppm 15 minuten STEL: 600 mg/m ³ 15 minuten TWA: 100 ppm 8 uren TWA: 300 mg/m ³ 8 uren	TWA: 50 ppm 8 tunteina TWA: 150 mg/m ³ 8 tunteina STEL: 100 ppm 15 minuutteina STEL: 300 mg/m ³ 15 minuutteina Iho

SAFETY DATA SHEET

Potassium tert-butoxide, 1.0M in THF

Revision Date 07-Dec-2024

		Höhepunkt: 120 mg/m ³ Haut			
--	--	--	--	--	--

Component	Austria	Denmark	Switzerland	Poland	Norway
Tetrahydrofuran	Haut MAK-KZGW: 100 ppm 15 Minuten MAK-KZGW: 300 mg/m ³ 15 Minuten MAK-TMW: 50 ppm 8 Stunden MAK-TMW: 150 mg/m ³ 8 Stunden	TWA: 50 ppm 8 timer TWA: 150 mg/m ³ 8 timer STEL: 300 mg/m ³ 15 minutter STEL: 100 ppm 15 minutter Hud	Haut/Peau STEL: 100 ppm 15 Minuten STEL: 300 mg/m ³ 15 Minuten TWA: 50 ppm 8 Stunden TWA: 150 mg/m ³ 8 Stunden	STEL: 300 mg/m ³ 15 minutach TWA: 150 mg/m ³ 8 godzinach	TWA: 50 ppm 8 timer TWA: 150 mg/m ³ 8 timer STEL: 75 ppm 15 minutter. value calculated STEL: 187.5 mg/m ³ 15 minutter. value calculated Hud

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Tetrahydrofuran	TWA: 50.0 ppm TWA: 150.0 mg/m ³ STEL : 100 ppm STEL : 300.0 mg/m ³ Skin notation	kože TWA-GVI: 50 ppm 8 satima. TWA-GVI: 150 mg/m ³ 8 satima. STEL-KGVI: 100 ppm 15 minutama. STEL-KGVI: 300 mg/m ³ 15 minutama.	TWA: 50 ppm 8 hr. TWA: 150 mg/m ³ 8 hr. STEL: 100 ppm 15 min STEL: 300 mg/m ³ 15 min Skin	Skin-potential for cutaneous absorption STEL: 100 ppm STEL: 300 mg/m ³ TWA: 50 ppm TWA: 150 mg/m ³	TWA: 150 mg/m ³ 8 hodinách. Potential for cutaneous absorption Ceiling: 300 mg/m ³

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Tetrahydrofuran	Nahk TWA: 50 ppm 8 tundides. TWA: 150 mg/m ³ 8 tundides. STEL: 100 ppm 15 minutites. STEL: 300 mg/m ³ 15 minutites.	Skin notation TWA: 50 ppm 8 hr TWA: 150 mg/m ³ 8 hr STEL: 100 ppm 15 min STEL: 300 mg/m ³ 15 min	STEL: 250 ppm STEL: 735 mg/m ³ TWA: 200 ppm TWA: 590 mg/m ³	STEL: 300 mg/m ³ 15 percekben. CK STEL: 100 ppm 15 percekben. CK TWA: 150 mg/m ³ 8 óraban. AK TWA: 50 ppm 8 óraban. AK lehetséges borön keresztüli felszívódás	STEL: 100 ppm STEL: 300 mg/m ³ TWA: 50 ppm 8 klukkustundum. TWA: 150 mg/m ³ 8 klukkustundum. Skin notation

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Tetrahydrofuran	skin - potential for cutaneous exposure STEL: 100 ppm STEL: 300 mg/m ³ TWA: 50 ppm TWA: 150 mg/m ³	TWA: 50 ppm IPRD TWA: 150 mg/m ³ IPRD Oda STEL: 100 ppm STEL: 300 mg/m ³	Possibility of significant uptake through the skin TWA: 50 ppm 8 Stunden TWA: 150 mg/m ³ 8 Stunden STEL: 100 ppm 15 Minuten STEL: 300 mg/m ³ 15 Minuten	possibility of significant uptake through the skin TWA: 50 ppm TWA: 150 mg/m ³ STEL: 100 ppm 15 minuti STEL: 300 mg/m ³ 15 minuti	Skin notation TWA: 50 ppm 8 ore TWA: 150 mg/m ³ 8 ore STEL: 100 ppm 15 minute STEL: 300 mg/m ³ 15 minute

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Tetrahydrofuran	MAC: 100 mg/m ³	Ceiling: 300 mg/m ³ Potential for cutaneous absorption TWA: 50 ppm TWA: 150 mg/m ³	TWA: 50 ppm 8 urah TWA: 150 mg/m ³ 8 urah Koža STEL: 100 ppm 15 minutah STEL: 300 mg/m ³ 15 minutah	Binding STEL: 100 ppm 15 minuter Binding STEL: 300 mg/m ³ 15 minuter TLV: 50 ppm 8 timmar. NGV TLV: 150 mg/m ³ 8 timmar. NGV	Deri TWA: 50 ppm 8 saat TWA: 150 mg/m ³ 8 saat STEL: 100 ppm 15 dakika STEL: 300 mg/m ³ 15 dakika

Biological limit values

List source(s):

Component	European Union	United Kingdom	France	Spain	Germany
Tetrahydrofuran				Tetrahydrofuran: 2 mg/L urine end of shift	Tetrahydrofuran: 2 mg/L urine (end of shift)

SAFETY DATA SHEET

Potassium tert-butoxide, 1.0M in THF

Revision Date 07-Dec-2024

Component	Gibraltar	Latvia	Slovak Republic	Luxembourg	Turkey
Tetrahydrofuran			Tetrahydrofuran: 2 mg/L urine end of exposure or work shift		

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Tetrahydrofuran 109-99-9 (80-90)				DNEL = 12.6mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Tetrahydrofuran 109-99-9 (80-90)	DNEL = 300mg/m ³	DNEL = 96mg/m ³	DNEL = 150mg/m ³	DNEL = 72.4mg/m ³
2-Propanol, 2-methyl-, potassium salt 865-47-4 (10-15)	DNEL = 1mg/m ³	DNEL = 1mg/m ³	DNEL = 1mg/m ³	DNEL = 1mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Tetrahydrofuran 109-99-9 (80-90)	PNEC = 4.32mg/L	PNEC = 23.3mg/kg sediment dw	PNEC = 21.6mg/L	PNEC = 4.6mg/L	PNEC = 2.13mg/kg soil dw
2-Propanol, 2-methyl-, potassium salt 865-47-4 (10-15)	PNEC = 0.11mg/L	PNEC = 0.419mg/kg sediment dw	PNEC = 1.1mg/L	PNEC = 10mg/L	PNEC = 0.0192mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Tetrahydrofuran 109-99-9 (80-90)	PNEC = 0.432mg/L	PNEC = 2.33mg/kg sediment dw		PNEC = 67mg/kg food	
2-Propanol, 2-methyl-, potassium salt 865-47-4 (10-15)	PNEC = 0.011mg/L	PNEC = 0.0419mg/kg sediment dw			

8.2. Exposure controls

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to

SAFETY DATA SHEET

Potassium tert-butoxide, 1.0M in THF

Revision Date 07-Dec-2024

control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles (European standard - EN 166)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Nitrile rubber	See manufacturers	-	EN 374	(minimum requirement)
Neoprene	recommendations			
Natural rubber				
PVC				
Butyl rubber				
Neoprene gloves				

Skin and body protection

Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced
Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to EN14387

Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141
When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

No information available.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State

Liquid

Appearance

Odor

No information available

Odor Threshold

No data available

Melting Point/Range

No data available

Softening Point

No data available

Boiling Point/Range

No information available

Flammability (liquid)

Highly flammable

On basis of test data

Flammability (solid,gas)

Not applicable

Liquid

Explosion Limits

No data available

Flash Point

-19 °C / -2.2 °F

Method - No information available

Autoignition Temperature

No data available

Decomposition Temperature

No data available

pH

Not applicable

Viscosity

No data available

Water Solubility

No information available

ALFAAH30530

SAFETY DATA SHEET

Potassium tert-butoxide, 1.0M in THF

Revision Date 07-Dec-2024

Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Tetrahydrofuran	0.45	
Vapor Pressure	No data available	
Density / Specific Gravity	0.903	
Bulk Density	Not applicable	Liquid
Vapor Density	No data available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

Explosive Properties Vapors may form explosive mixtures with air

Section 10: Stability and reactivity

10.1. Reactivity Yes

10.2. Chemical stability Moisture sensitive. Air sensitive.

10.3. Possibility of hazardous reactions

Hazardous Polymerization No information available.
Hazardous Reactions None under normal processing. Reacts violently with water.

10.4. Conditions to avoid Exposure to moist air or water. Exposure to moisture. Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials Strong oxidizing agents.

10.6. Hazardous decomposition products Carbon monoxide (CO). Carbon dioxide (CO₂). Potassium oxides.

Section 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;
Oral Category 4
Dermal Based on available data, the classification criteria are not met
Inhalation Based on available data, the classification criteria are not met

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Tetrahydrofuran	1650 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	180 mg/L (Rat) 1 h 53.9 mg/L (Rat) 4 h

(b) skin corrosion/irritation; Category 1 A

SAFETY DATA SHEET

Potassium tert-butoxide, 1.0M in THF

Revision Date 07-Dec-2024

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;

Respiratory No data available
Skin No data available

Component	Test method	Test species	Study result
Tetrahydrofuran 109-99-9 (80-90)	Local Lymph Node Assay OECD Test Guideline 429	mouse	non-sensitising

(e) germ cell mutagenicity; No data available

Component	Test method	Test species	Study result
Tetrahydrofuran 109-99-9 (80-90)	OECD Test Guideline 476 Gene cell mutation	in vivo Mammalian	negative
	OECD Test Guideline 473 Chromosomal aberration assay	in vitro Mammalian	negative

(f) carcinogenicity; Category 2

The table below indicates whether each agency has listed any ingredient as a carcinogen
Limited evidence of a carcinogenic effect

Component	EU	UK	Germany	IARC
Tetrahydrofuran				Group 2B

(g) reproductive toxicity; No data available

Component	Test method	Test species / Duration	Study result
Tetrahydrofuran 109-99-9 (80-90)	OECD Test Guideline 416	Rat 2 Generation	NOAEL = 3,000 ppm

(h) STOT-single exposure; Category 3

Results / Target organs Respiratory system, Central nervous system (CNS).

(i) STOT-repeated exposure; No data available

Target Organs No information available.

(j) aspiration hazard; No data available

Symptoms / effects, both acute and delayed Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

Section 12: Ecological information

SAFETY DATA SHEET

Potassium tert-butoxide, 1.0M in THF

Revision Date 07-Dec-2024

12.1. Toxicity

Ecotoxicity effects

Component	Freshwater Fish	Water Flea	Freshwater Algae
Tetrahydrofuran	2160 mg/l LC50 = 96 h Pimephales promelas Leuciscus idus: LC50: 2820 mg/L/48h	EC50 48 h 3485 mg/l EC50: >10000 mg/L/24h	

12.2. Persistence and degradability

Persistence

No information available
Persistence is unlikely.

12.3. Bioaccumulative potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Tetrahydrofuran	0.45	No data available

12.4. Mobility in soil

No information available

12.5. Results of PBT and vPvB assessment

No data available for assessment.

12.6. Endocrine disrupting properties

Endocrine Disruptor Information

Component	EU - Endocrine Disruptors Candidate List	EU - Endocrine Disruptors - Evaluated Substances
Tetrahydrofuran	Group III Chemical	

12.7. Other adverse effects

Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance
This product does not contain any known or suspected substance

Section 13: Disposal considerations

13.1. Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

European Waste Catalogue (EWC)

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information

Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms.

Switzerland - Waste Ordinance

Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance,

SAFETY DATA SHEET

Potassium tert-butoxide, 1.0M in THF

Revision Date 07-Dec-2024

ADWO) SR 814.600
<https://www.fedlex.admin.ch/eli/cc/2015/891/en>

Section 14: Transport information

IMDG/IMO

14.1. UN number UN2924
14.2. UN proper shipping name Flammable liquid, corrosive, n.o.s.
Technical Shipping Name Potassium tert-butoxide/THF
14.3. Transport hazard class(es) 3
Subsidiary Hazard Class 8
14.4. Packing group II

ADR

14.1. UN number UN2924
14.2. UN proper shipping name Flammable liquid, corrosive, n.o.s.
Technical Shipping Name Potassium tert-butoxide/THF
14.3. Transport hazard class(es) 3
Subsidiary Hazard Class 8
14.4. Packing group II

IATA

14.1. UN number UN2924
14.2. UN proper shipping name Flammable liquid, corrosive, n.o.s.
Technical Shipping Name Potassium tert-butoxide/THF
14.3. Transport hazard class(es) 3
Subsidiary Hazard Class 8
14.4. Packing group II

14.5. Environmental hazards No hazards identified

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments Not applicable, packaged goods

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Tetrahydrofuran	109-99-9	203-726-8	-	-	X	X	KE-33454	X	X
2-Propanol, 2-methyl-, potassium salt	865-47-4	212-740-3	-	-	X	X	KE-24897	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Tetrahydrofuran	109-99-9	X	ACTIVE	X	-	X	X	X
2-Propanol, 2-methyl-, potassium salt	865-47-4	X	ACTIVE	X	-	X	X	X

ALFAAH30530

SAFETY DATA SHEET

Potassium tert-butoxide, 1.0M in THF

Revision Date 07-Dec-2024

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Tetrahydrofuran	109-99-9	-	Use restricted. See entry 75. (see link for restriction details)	-
2-Propanol, 2-methyl-, potassium salt	865-47-4	-	-	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Tetrahydrofuran	109-99-9	Not applicable	Not applicable
2-Propanol, 2-methyl-, potassium salt	865-47-4	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 1 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Tetrahydrofuran	WGK1	
2-Propanol, 2-methyl-, potassium salt	WGK1	

Component	France - INRS (Tables of occupational diseases)
Tetrahydrofuran	Tableaux des maladies professionnelles (TMP) - RG 84

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

SAFETY DATA SHEET

Potassium tert-butoxide, 1.0M in THF

Revision Date 07-Dec-2024

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Tetrahydrofuran 109-99-9 (80-90)		Group I	

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

Section 16: Other information

Full text of H-Statements referred to under sections 2 and 3

H252 - Self-heating in large quantities; may catch fire
H302 - Harmful if swallowed
H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H351 - Suspected of causing cancer
EUH014 - Reacts violently with water
EUH019 - May form explosive peroxides
H225 - Highly flammable liquid and vapor
H228 - Flammable solid
H319 - Causes serious eye irritation

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data

Health Hazards Calculation method

Environmental hazards Calculation method

SAFETY DATA SHEET

Potassium tert-butoxide, 1.0M in THF

Revision Date 07-Dec-2024

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Prepared By

Health, Safety and Environmental Department

Revision Date

07-Dec-2024

Revision Summary

Not applicable.

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.
COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No
1907/2006 .**

**For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2,
Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and
Preparations).**

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet