

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
Product Identifier

Perihal Produk: (Trimethylsilyl)methyl lithium, 0.7M (10wt%) solution in hexanes
 Product Description: (Trimethylsilyl)methyl lithium, 0.7M (10wt%) solution in hexanes
 Cat No. : 377450000; 377451000; 377458000
 Molecular Formula: C₄ H₁₁ Li Si

Relevant identified uses of the substance or mixture and uses advised against

Recommended Use: Laboratory chemicals.
 Uses advised against: No Information available

Company

Thermo Fisher Scientific Fisher Scientific (M) Sdn Bhd
 Hap Seng Business Park, Lot 01-03, 01-04 Aras 1 Unity Square,
 No 12, Persiaran Perusahaan, Seksyen 23, 40300 Shah Alam,
 Selangor Darul Ehsan, Malaysia.
 Main line: +60 3-5525 7888

E-mail address

Enquiry.my@thermofisher.com

Emergency Telephone Number

Tel: +03-5525 7888
 CHEMTREC Malaysia **1-800-815-308** (Malay)
 CHEMTREC Malaysia (Kuala Lumpur) **+(60)-327884561** (Malay)

SECTION 2: HAZARDS IDENTIFICATION
Classification of the substance or mixture

Flammable liquids	Category 2 (H225)
Aspiration Toxicity	Category 1 (H304)
Skin Corrosion/Irritation	Category 1 B (H314)
Reproductive Toxicity	Category 2 (H361f)
Specific target organ toxicity - (single exposure)	Category 3 (H336)
Specific target organ toxicity - (repeated exposure)	Category 2 (H373)
Chronic aquatic toxicity	Category 2 (H411)

Label Elements


Signal Word

Danger

SAFETY DATA SHEET

(Trimethylsilyl)methyl lithium, 0.7M (10wt%) solution in hexanes

Revision Date 22-Mar-2025

Hazard Statements

H225 - Highly flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H314 - Causes severe skin burns and eye damage
H336 - May cause drowsiness or dizziness
H361f - Suspected of damaging fertility
H373 - May cause damage to organs through prolonged or repeated exposure
H411 - Toxic to aquatic life with long lasting effects

Precautionary Statements

Prevention

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P240 - Ground and bond container and receiving equipment
P242 - Use non-sparking tools
P243 - Take action to prevent static discharges
P260 - Do not breathe dust/fume/gas/mist/vapors/spray
P264 - Wash face, hands and any exposed skin thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves/protective clothing/eye protection/face protection

Response

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a POISON CENTER or doctor
P330 - Rinse mouth
P331 - Do NOT induce vomiting
P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish
P362 + P364 - Take off contaminated clothing and wash it before reuse

Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Other Hazards

EUH014 - Reacts violently with water

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No	Weight %
Hexane, branched and linear	92112-69-1	90
Trimethylsilylmethyl lithium	1822-00-0	10

SECTION 4: FIRST AID MEASURES

Description of first aid measures

General Advice

Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

SAFETY DATA SHEET

(Trimethylsilyl)methylolithium, 0.7M (10wt%) solution in hexanes

Revision Date 22-Mar-2025

Immediate medical attention is required.

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Call a physician immediately.

Ingestion

Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.

Inhalation

If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately. Risk of serious damage to the lungs (by aspiration).

Self-Protection of the First Aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing media

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Water.

Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Reacts violently with water. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂), Silicon dioxide.

Advice for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away

SAFETY DATA SHEET

(Trimethylsilyl)methylolithium, 0.7M (10wt%) solution in hexanes

Revision Date 22-Mar-2025

from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental precautions

Do not flush into surface water or sanitary sewer system.

Methods and Material for Containment and Cleaning Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Do not expose spill to water. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Do not allow contact with water. Handle under an inert atmosphere. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Conditions for Safe Storage, Including any Incompatibilities

Flammables area. Corrosives area. Keep under nitrogen. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Keep away from water or moist air. Store under an inert atmosphere. Protect from moisture.

Specific End Uses

Use in laboratories.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Component	Malaysia	ACGIH TLV	OSHA PEL
Hexane, branched and linear			(Vacated) TWA: 500 ppm (Vacated) TWA: 1800 mg/m ³ (Vacated) STEL: 1000 ppm (Vacated) STEL: 3600 mg/m ³

Component	European Union	The United Kingdom	Germany
Hexane, branched and linear			TWA: 500 ppm (8 Stunden). AGW - exposure factor 2 TWA: 1800 mg/m ³ (8 Stunden). AGW - exposure factor 2 Höhepunkt: 1000 ppm Höhepunkt: 3600 mg/m ³

Exposure Controls

Engineering Measures

Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

SAFETY DATA SHEET

(Trimethylsilyl)methylolithium, 0.7M (10wt%) solution in hexanes

Revision Date 22-Mar-2025

Personal protective equipment

Eye Protection	Goggles
Hand Protection	Protective gloves
Skin and body protection	Wear appropriate protective gloves and clothing to prevent skin exposure

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves.
(Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators
Recommended Filter type:	low boiling organic solvent Type AX Brown conforming to EN371 or Organic gases and vapours filter Type A Brown conforming to EN14387 To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly When RPE is used a face piece Fit Test should be conducted

<u>Hygiene Measures</u>	Handle in accordance with good industrial hygiene and safety practice
--------------------------------	---

<u>Environmental exposure controls</u>	Prevent product from entering drains Do not allow material to contaminate ground water system
---	---

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance		
Physical State	Liquid	
Odor	No information available	
Odor Threshold	No data available	
pH	No information available	>7
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	65 - 70 °C / 149 - 158 °F	
Flash Point	-40 °C / -40 °F	Method - No information available
Evaporation Rate	No data available	
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Vapor Pressure	No data available	
Vapor Density	No data available	(Air = 1.0)
Specific Gravity / Density	0.7	
Bulk Density	Not applicable	Liquid
Water Solubility	Reacts violently with water	
Solubility in other solvents	No information available	

SAFETY DATA SHEET

(Trimethylsilyl)methyl lithium, 0.7M (10wt%) solution in hexanes

Revision Date 22-Mar-2025

Partition Coefficient (n-octanol/water)

Component	log Pow
Hexane, branched and linear	4.11

Autoignition Temperature No data available

Decomposition Temperature No data available

Viscosity No data available

Explosive Properties Vapors may form explosive mixtures with air

Oxidizing Properties No information available

Molecular Formula C₄ H₁₁ Li Si

Molecular Weight 94.16

SECTION 10: STABILITY AND REACTIVITY

Reactivity

Yes.

Chemical Stability

Reacts violently with water. Moisture sensitive.

Possibility of Hazardous Reactions

Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	Reacts violently with water.

Conditions to Avoid

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition. Exposure to moist air or water. Exposure to moisture.

Incompatible Materials

Strong oxidizing agents. Water. Acids. Alcohols.

Hazardous Decomposition Products

Carbon monoxide (CO). Carbon dioxide (CO₂). Silicon dioxide.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects

Product Information

(a) acute toxicity;

Oral	Based on available data, the classification criteria are not met
Dermal	Based on available data, the classification criteria are not met
Inhalation	Based on available data, the classification criteria are not met

SAFETY DATA SHEET

(Trimethylsilyl)methyl lithium, 0.7M (10wt%) solution in hexanes

Revision Date 22-Mar-2025

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Hexane, branched and linear	LD50 = 15000 mg/kg (Rat)	LD50 = 3350 mg/kg (Rabbit)	LC50 = 259354 mg/m ³ (Rat) 4h

(b) skin corrosion/irritation; Category 1 B

(c) serious eye damage/irritation; No data available

(d) respiratory or skin sensitization;

Respiratory

No data available

Skin

No data available

No information available

(e) germ cell mutagenicity; No data available

(f) carcinogenicity;

No data available

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; Category 2

(h) STOT-single exposure; Category 3

Results / Target organs

Central nervous system (CNS).

(i) STOT-repeated exposure; Category 2

Target Organs

Skin, Respiratory system, Eyes, Gastrointestinal tract (GI).

(j) aspiration hazard; Category 1

Other Adverse Effects

The toxicological properties have not been fully investigated.

Symptoms / effects, both acute and delayed

Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated.

Endocrine Disrupting Properties

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity effects

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment. Reacts with water so no ecotoxicity data for the substance is available.

Persistence and degradability

Persistence

Persistence is unlikely, based on information available.

SAFETY DATA SHEET

(Trimethylsilyl)methyl lithium, 0.7M (10wt%) solution in hexanes

Revision Date 22-Mar-2025

Degradability
Degradation in sewage treatment plant

Reacts with water.
Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants. Reacts violently with water.

Bioaccumulative potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Hexane, branched and linear	4.11	No data available

Mobility in soil

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in air.

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

Other adverse effects

No information available

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous Dispose of in accordance with the European Directives on waste and hazardous waste Dispose of in accordance with local regulations

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous Keep product and empty container away from heat and sources of ignition

Other Information

Do not flush to sewer Waste codes should be assigned by the user based on the application for which the product was used Can be landfilled or incinerated, when in compliance with local regulations Do not empty into drains Large amounts will affect pH and harm aquatic organisms Do not let this chemical enter the environment

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

UN-No UN2924
Hazard Class 3
Subsidiary Hazard Class 8
Packing Group II
Proper Shipping Name FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Trimethylsilyl)methyl lithium, 0.7M (10 wt%) solution in hexanes

Road and Rail Transport

UN-No UN2924
Hazard Class 3
Subsidiary Hazard Class 8
Packing Group II
Proper Shipping Name FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Trimethylsilyl)methyl lithium, 0.7M (10 wt%) solution in hexanes

IATA

UN-No UN2924
Hazard Class 3

SAFETY DATA SHEET

(Trimethylsilyl)methyl lithium, 0.7M (10wt%) solution in hexanes

Revision Date 22-Mar-2025

Subsidiary Hazard Class 8
Packing Group II
Proper Shipping Name FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Trimethylsilyl)methyl lithium, 0.7M (10 wt%) solution in hexanes

Special Precautions for User No special precautions required

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories X = listed

Component	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	IECSC	AICS	KECL
Hexane, branched and linear	295-570-2	-	-	-	X	X	-	X	-
Trimethylsilylmethyl lithium	-	-	-	-	-	-	-	-	KE-34681

National Regulations

Persistent Organic Pollutant This product does not contain any known or suspected substance
Ozone Depletion Potential This product does not contain any known or suspected substance

SECTION 16: OTHER INFORMATION

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

POW - Partition coefficient Octanol:Water

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Revision Date 22-Mar-2025

ACR37745

SAFETY DATA SHEET

(Trimethylsilyl)methylolithium, 0.7M (10wt%) solution in hexanes

Revision Date 22-Mar-2025

Revision Summary

Not applicable.

In accordance with local and national regulations: Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet