

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
Product Identifier

Perihal Produk:

Product Description:

Cat No. :

Lithium bis(trimethylsilyl)amide, 25% solution in THF

Lithium bis(trimethylsilyl)amide, 25% solution in THF

Z15012

Relevant identified uses of the substance or mixture and uses advised against

Recommended Use

Laboratory chemicals.

Uses advised against

No Information available

Company

 Thermo Fisher Scientific Fisher Scientific (M) Sdn Bhd
 Hap Seng Business Park, Lot 01-03, 01-04 Aras 1 Unity Square,
 No 12, Persiaran Perusahaan, Seksyen 23, 40300 Shah Alam,
 Selangor Darul Ehsan, Malaysia.
 Main line: +60 3-5525 7888

Supplier

E-mail address

Enquiry.my@thermofisher.com

Emergency Telephone Number

Tel: +03-5525 7888

CHEMTREC Malaysia 1-800-815-308 (Malay)

CHEMTREC Malaysia (Kuala Lumpur) +(60)-327884561 (Malay)

SECTION 2: HAZARDS IDENTIFICATION
Classification of the substance or mixture

Flammable liquids	Category 2 (H225)
Acute oral toxicity	Category 4 (H302)
Skin Corrosion/Irritation	Category 1 B (H314)
Serious Eye Damage/Eye Irritation	Category 1 (H318)
Carcinogenicity	Category 2 (H351)
Specific target organ toxicity - (single exposure)	Category 3 (H335) (H336)

Label Elements


Signal Word

Danger

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 25% solution in THF

Revision Date 31-Mar-2025

Hazard Statements

H225 - Highly flammable liquid and vapor
H302 - Harmful if swallowed
H314 - Causes severe skin burns and eye damage
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H351 - Suspected of causing cancer

Precautionary Statements

Prevention

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P240 - Ground and bond container and receiving equipment
P242 - Use non-sparking tools
P243 - Take action to prevent static discharges
P260 - Do not breathe dust/fume/gas/mist/vapors/spray
P264 - Wash face, hands and any exposed skin thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves/protective clothing/eye protection/face protection

Response

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a POISON CENTER or doctor
P330 - Rinse mouth
P331 - Do NOT induce vomiting
P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish
P362 + P364 - Take off contaminated clothing and wash it before reuse

Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Other Hazards

EUH014 - Reacts violently with water
EUH019 - May form explosive peroxides

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No	Weight %
Tetrahydrofuran	109-99-9	75
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, lithium salt	4039-32-1	25

SECTION 4: FIRST AID MEASURES

Description of first aid measures

General Advice

Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 25% solution in THF

Revision Date 31-Mar-2025

Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Call a physician immediately.
Ingestion	Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately.
Inhalation	If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing media

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Water.

Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Reacts violently with water. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon oxides, Nitrogen oxides (NO_x), Lithium oxide, Silicon dioxide.

Advice for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 25% solution in THF

Revision Date 31-Mar-2025

Environmental precautions

Should not be released into the environment. Do not allow material to contaminate ground water system. Do not flush into surface water or sanitary sewer system.

Methods and Material for Containment and Cleaning Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Do not expose spill to water. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Do not allow contact with water. If peroxide formation is suspected, do not open or move container. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Conditions for Safe Storage, Including any Incompatibilities

Keep under nitrogen. Corrosives area. Keep away from water or moist air. Keep containers tightly closed in a dry, cool and well-ventilated place. Containers should be dated when opened and tested periodically for the presence of peroxides. Should crystals form in a peroxidizable liquid, peroxidation may have occurred and the product should be considered extremely dangerous. In this instance, the container should only be opened remotely by professionals. Keep away from heat, sparks and flame.

Specific End Uses

Use in laboratories.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Component	Malaysia	ACGIH TLV	OSHA PEL
Tetrahydrofuran		TWA: 50 ppm STEL: 100 ppm Skin	(Vacated) TWA: 200 ppm (Vacated) TWA: 590 mg/m ³ (Vacated) STEL: 250 ppm (Vacated) STEL: 735 mg/m ³ TWA: 200 ppm TWA: 590 mg/m ³

Component	European Union	The United Kingdom	Germany
Tetrahydrofuran	TWA: 50 ppm (8h) TWA: 150 mg/m ³ (8h) STEL: 100 ppm (15min) STEL: 300 mg/m ³ (15min) Skin	STEL: 100 ppm 15 min STEL: 300 mg/m ³ 15 min TWA: 50 ppm 8 hr TWA: 150 mg/m ³ 8 hr Skin	TWA: 50 ppm (8 Stunden). AGW - exposure factor 2 TWA: 150 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 20 ppm (8 Stunden). MAK TWA: 60 mg/m ³ (8 Stunden). MAK Höhepunkt: 40 ppm Höhepunkt: 120 mg/m ³ Haut
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, lithium salt			TWA: 0.2 mg/m ³ (8 Stunden). MAK inorganic compounds, except Lithium and strong irritant Lithium compounds such as Lithium amide,

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 25% solution in THF

Revision Date 31-Mar-2025

			Lithium hydride, Lithium hydroxide, Lithium nitride, Lithium oxide, Lithium tetrahydro aluminate, Lithium tetrahydroborate
--	--	--	---

Exposure Controls

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles

Hand Protection

Protective gloves

Skin and body protection

Long sleeved clothing

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators

Recommended Filter type:

Organic gases and vapours filter Type A Brown conforming to EN14387

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

When RPE is used a face piece Fit Test should be conducted

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice

Environmental exposure controls

No information available

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance

Colorless to yellow

Physical State

Liquid

Odor

No information available

Odor Threshold

No data available

pH

Not applicable

Melting Point/Range

No data available

Softening Point

No data available

Boiling Point/Range

No information available

Flash Point

-17 °C / 1.4 °F

Method - No information available

Evaporation Rate

No data available

Flammability (solid,gas)

Not applicable

Liquid

Explosion Limits

No data available

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 25% solution in THF

Revision Date 31-Mar-2025

Vapor Pressure	No data available	
Vapor Density	No data available	(Air = 1.0)
Specific Gravity / Density	0.891	
Bulk Density	Not applicable	Liquid
Water Solubility	No information available	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Tetrahydrofuran	0.45	
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
Viscosity	No data available	
Explosive Properties	No information available	Vapors may form explosive mixtures with air
Oxidizing Properties	No information available	

SECTION 10: STABILITY AND REACTIVITY

Reactivity

Yes.

Chemical Stability

Moisture sensitive. Air sensitive.

Possibility of Hazardous Reactions

Hazardous Polymerization	No information available.
Hazardous Reactions	None under normal processing. Reacts violently with water.

Conditions to Avoid

Exposure to moist air or water. Exposure to moisture. Keep away from open flames, hot surfaces and sources of ignition.

Incompatible Materials

None known.

Hazardous Decomposition Products

Carbon oxides. Nitrogen oxides (NOx). Lithium oxide. Silicon dioxide.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 25% solution in THF

Revision Date 31-Mar-2025

Product Information

(a) acute toxicity;

Oral

Category 4

Dermal

Based on available data, the classification criteria are not met

Inhalation

Based on available data, the classification criteria are not met

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Tetrahydrofuran	1650 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	180 mg/L (Rat) 1 h 53.9 mg/L (Rat) 4 h

(b) skin corrosion/irritation;

Category 1 B

(c) serious eye damage/irritation;

Category 1

(d) respiratory or skin sensitization;

Respiratory

No data available

Skin

No data available

Component	Test method	Test species	Study result
Tetrahydrofuran 109-99-9 (75)	Local Lymph Node Assay OECD Test Guideline 429	mouse	non-sensitising

(e) germ cell mutagenicity;

No data available

Component	Test method	Test species	Study result
Tetrahydrofuran 109-99-9 (75)	OECD Test Guideline 476 Gene cell mutation	in vivo Mammalian	negative
	OECD Test Guideline 473 Chromosomal aberration assay	in vitro Mammalian	negative

(f) carcinogenicity;

Category 2

The table below indicates whether each agency has listed any ingredient as a carcinogen
Limited evidence of a carcinogenic effect

Component	EU	UK	Germany	IARC
Tetrahydrofuran				Group 2B

(g) reproductive toxicity;

No data available

Component	Test method	Test species / Duration	Study result
Tetrahydrofuran 109-99-9 (75)	OECD Test Guideline 416	Rat 2 Generation	NOAEL = 3,000 ppm

(h) STOT-single exposure;

Category 3

Results / Target organs

Respiratory system, Central nervous system (CNS).

(i) STOT-repeated exposure;

No data available

Target Organs

None known.

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 25% solution in THF

Revision Date 31-Mar-2025

(j) aspiration hazard; No data available

Symptoms / effects, both acute and delayed Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity effects May cause long-term adverse effects in the environment. Do not allow material to contaminate ground water system.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Tetrahydrofuran	2160 mg/l LC50 = 96 h Pimephales promelas Leuciscus idus: LC50: 2820 mg/L/48h	EC50 48 h 3485 mg/l EC50: >10000 mg/L/24h		

Persistence and degradability Product contains heavy metals. Discharge into the environment must be avoided. Special pre-treatment is necessary.
Persistence May persist.
Degradation in sewage treatment plant Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

Bioaccumulative potential Product has a high potential to bioconcentrate

Component	log Pow	Bioconcentration factor (BCF)
Tetrahydrofuran	0.45	No data available

Mobility in soil No information available.

Endocrine Disruptor Information

Component	EU - Endocrine Disrupters Candidate List	EU - Endocrine Disruptors - Evaluated Substances
Tetrahydrofuran	Group III Chemical	

Other adverse effects No information available

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from Residues/Unused Products Waste is classified as hazardous Dispose of in accordance with the European Directives on waste and hazardous waste Dispose of in accordance with local regulations

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous Keep product and empty container away from heat and sources of ignition

Other Information Waste codes should be assigned by the user based on the application for which the product was used Do not flush to sewer Can be landfilled or incinerated, when in compliance with

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 25% solution in THF

Revision Date 31-Mar-2025

local regulations Do not empty into drains Large amounts will affect pH and harm aquatic organisms

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

UN-No UN2924
Hazard Class 3
Subsidiary Hazard Class 8
Packing Group II
Proper Shipping Name FLAMMABLE LIQUID, CORROSIVE, N.O.S. Tetrahydrofuran/Lithium bis(trimethylsilyl)amide

Road and Rail Transport

UN-No UN2924
Hazard Class 3
Subsidiary Hazard Class 8
Packing Group II
Proper Shipping Name FLAMMABLE LIQUID, CORROSIVE, N.O.S. Tetrahydrofuran/Lithium bis(trimethylsilyl)amide

IATA

UN-No UN2924
Hazard Class 3
Subsidiary Hazard Class 8
Packing Group II
Proper Shipping Name FLAMMABLE LIQUID, CORROSIVE, N.O.S. Tetrahydrofuran/Lithium bis(trimethylsilyl)amide

Special Precautions for User No special precautions required

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

X = listed U.S.A. (TSCA) Canada (DSL/NDSL) Europe (EINECS/ELINCS/NLP) Australia (AICS) Korea (KECL) China (IECSC) Japan (ENCS) Philippines (PICCS)

Component	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	IECSC	AICS	KECL
Tetrahydrofuran	203-726-8	X	X	X	X	X	X	X	KE-33454
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, lithium salt	223-725-6	X	-	X	X	X	-	-	-

National Regulations

Persistent Organic Pollutant
Ozone Depletion Potential

This product does not contain any known or suspected substance
This product does not contain any known or suspected substance

SECTION 16: OTHER INFORMATION

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 25% solution in THF

Revision Date 31-Mar-2025

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

POW - Partition coefficient Octanol:Water

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Prepared By

Revision Date

Revision Summary

Health, Safety and Environmental Department

31-Mar-2025

SDS sections updated.

In accordance with local and national regulations: Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet