

Creation Date 30-Apr-2020

Revision Date 04-Jan-2021

Revision Number 2

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: **DOSINACO Mobile Phase B**
Cat No. : **227-40503-58; 227-40503-55; 227-40503-91**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company **EU entity/business name**
Acros Organics BVBA
Janssen Pharmaceuticaaan 3a
2440 Geel, Belgium
General Info; Tel: +32-14-57 52 11
(info@acros.com)
Technical Support; Tel +32-14-56 56 00
(acros.techsupport@thermofisher.com)

UK entity/business name
Fisher Scientific UK
Bishop Meadow Road, Loughborough,
Leicestershire LE11 5RG, United Kingdom
General info; Tel: +44 (0)1509 231166

Swiss distributor - Fisher Scientific AG
Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
e-mail - infoch@thermofisher.com

E-mail address **begel.sdsdesk@thermofisher.com**

1.4. Emergency telephone number

Tel: 01509 231166
Chemtrec US: (800) 424-9300
Chemtrec EU: 001-703-527-3887

For customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

SECTION 2: HAZARDS IDENTIFICATION

SAFETY DATA SHEET

DOSINACO Mobile Phase B

Revision Date 04-Jan-2021

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Flammable liquids

Category 2 (H225)

Health hazards

Acute oral toxicity

Category 3 (H301)

Acute dermal toxicity

Category 3 (H311)

Acute Inhalation Toxicity - Vapors

Category 3 (H331)

Specific target organ toxicity - (single exposure)

Category 1 (H370)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements

Contains METHANOL



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H370 - Causes damage to organs

H301 + H311 + H331 - Toxic if swallowed, in contact with skin or if inhaled

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P280 - Wear protective gloves/protective clothing

P301 + P330 + P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P311 - Call a POISON CENTER or doctor/physician

2.3. Other hazards

Toxic to terrestrial vertebrates

SAFETY DATA SHEET

DOSINACO Mobile Phase B

Revision Date 04-Jan-2021

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Methanol	67-56-1	200-659-6	87.6	Flam. Liq. 2 (H225) Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370)
Water	7732-18-5	231-791-2	12.21	-
Formic acid	64-18-6	200-579-1	0.15	Flam. Liq. 3 (H226) Acute Tox. 4 (H302) Skin Corr. 1A (H314) Eye Dam. 1 (H318) Acute Tox. 3 (H331) EUH071
Ammonium formate	540-69-2	EEC No. 208-753-9	0.04	Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) STOT SE 3 (H335)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Methanol	STOT SE 1 (H370) :: C>=10% STOT SE 2 (H371) :: 3%<=C<10%	-	-
Formic acid	Skin Corr. 1A :: C>=90% Skin Corr. 1B :: 10%<=C<90% Skin Irrit. 2 :: 2%<=C<10% Eye Irrit. 2 :: 2%<=C<10%	-	-

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.
Ingestion	Do NOT induce vomiting. Call a physician or poison control center immediately.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

SAFETY DATA SHEET

DOSINACO Mobile Phase B

Revision Date 04-Jan-2021

4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

None under normal use conditions.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Should not be released into the environment.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

SAFETY DATA SHEET

DOSINACO Mobile Phase B

Revision Date 04-Jan-2021

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and flame. Flammables area. Keep container tightly closed in a dry and well-ventilated place.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Class 3

Switzerland - Storage of hazardous substances

Storage class - SC 3

<https://www.kvu.ch/de/themen/stoffe-und-produkte>

<https://www.kvu.ch/fr/themes/substances-et-produits>

<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Third edition. Published 2018. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Methanol	TWA: 200 ppm 8 hr TWA: 260 mg/m ³ 8 hr Skin	WEL - TWA: 200 ppm TWA: 266 mg/m ³ TWA WEL - STEL: 250 ppm STEL: 333 mg/m ³ STEL	TWA / VME: 200 ppm (8 heures). restrictive limit TWA / VME: 260 mg/m ³ (8 heures). restrictive limit STEL / VLCT: 1000 ppm. STEL / VLCT: 1300 mg/m ³ . Peau	TWA: 200 ppm 8 uren TWA: 266 mg/m ³ 8 uren STEL: 250 ppm 15 minuten STEL: 333 mg/m ³ 15 minuten Huid	TWA / VLA-ED: 200 ppm (8 horas) TWA / VLA-ED: 266 mg/m ³ (8 horas) Piel
Formic acid	TWA: 5 ppm 8 hr TWA: 9 mg/m ³ 8 hr	STEL: 15 ppm 15 min STEL: 28.8 mg/m ³ 15 min TWA: 5 ppm 8 hr TWA: 9.6 mg/m ³ 8 hr	TWA / VME: 5 ppm (8 heures). indicative limit TWA / VME: 9 mg/m ³ (8 heures). indicative limit	TWA: 5 ppm 8 uren TWA: 9.5 mg/m ³ 8 uren STEL: 10 ppm 15 minuten STEL: 19 mg/m ³ 15 minuten	TWA / VLA-ED: 5 ppm (8 horas) TWA / VLA-ED: 9 mg/m ³ (8 horas)

Component	Italy	Germany	Portugal	The Netherlands	Finland
Methanol	TWA: 200 ppm 8 ore. Media Ponderata nel Tempo TWA: 260 mg/m ³ 8 ore.	100 ppm TWA MAK; 130 mg/m ³ TWA MAKSkin absorber	STEL: 250 ppm 15 minutos TWA: 200 ppm 8 horas TWA: 260 mg/m ³ 8	huid TWA: 133 mg/m ³ 8 uren	TWA: 200 ppm 8 tunteina TWA: 270 mg/m ³ 8 tunteina

SAFETY DATA SHEET

DOSINACO Mobile Phase B

Revision Date 04-Jan-2021

	Media Ponderata nel Tempo Pelle		horas Pele		STEL: 250 ppm 15 minuutteina STEL: 330 mg/m ³ 15 minuutteina lho
Formic acid	TWA: 5 ppm 8 ore. TWA: 9 mg/m ³ 8 ore.	TWA: 5 ppm (8 Stunden). AGW - exposure factor 2 TWA: 9.5 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 5 ppm (8 Stunden). MAK TWA: 9.5 mg/m ³ (8 Stunden). MAK Höhepunkt: 10 ppm Höhepunkt: 19 mg/m ³	STEL: 10 ppm 15 minutos TWA: 5 ppm 8 horas TWA: 9 mg/m ³ 8 horas	STEL: 5 mg/m ³ 15 minuten	TWA: 3 ppm 8 tunteina TWA: 5 mg/m ³ 8 tunteina STEL: 10 ppm 15 minuutteina STEL: 19 mg/m ³ 15 minuutteina

Component	Austria	Denmark	Switzerland	Poland	Norway
Methanol	Haut MAK-KZGW: 800 ppm 15 Minuten MAK-KZGW: 1040 mg/m ³ 15 Minuten MAK-TMW: 200 ppm 8 Stunden MAK-TMW: 260 mg/m ³ 8 Stunden	TWA: 200 ppm 8 timer TWA: 260 mg/m ³ 8 timer Hud	Haut/Peau STEL: 400 ppm 15 Minuten STEL: 520 mg/m ³ 15 Minuten TWA: 200 ppm 8 Stunden TWA: 260 mg/m ³ 8 Stunden	STEL: 300 mg/m ³ 15 minutach TWA: 100 mg/m ³ 8 godzinach	TWA: 100 ppm 8 timer TWA: 130 mg/m ³ 8 timer STEL: 150 ppm 15 minutter. value calculated STEL: 162.5 mg/m ³ 15 minutter. value calculated Hud
Formic acid	MAK-KZW: 5 ppm 15 Minuten MAK-KZW: 9 mg/m ³ 15 Minuten MAK-TMW: 5 ppm 8 Stunden MAK-TMW: 9 mg/m ³ 8 Stunden Ceiling: 5 ppm Ceiling: 9 mg/m ³	TWA: 5 ppm 8 timer TWA: 9 mg/m ³ 8 timer	STEL: 10 ppm 15 Minuten STEL: 19 mg/m ³ 15 Minuten TWA: 5 ppm 8 Stunden TWA: 9.5 mg/m ³ 8 Stunden	STEL: 15 mg/m ³ 15 minutach TWA: 5 mg/m ³ 8 godzinach	TWA: 5 ppm 8 timer TWA: 9 mg/m ³ 8 timer STEL: 10 ppm 15 minutter. STEL: 18 mg/m ³ 15 minutter.

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Methanol	TWA: 200 ppm TWA: 260.0 mg/m ³ Skin notation	kože TWA-GVI: 200 ppm 8 satima. TWA-GVI: 260 mg/m ³ 8 satima.	TWA: 200 ppm 8 hr. TWA: 260 mg/m ³ 8 hr. STEL: 600 ppm 15 min STEL: 780 mg/m ³ 15 min Skin	Skin-potential for cutaneous absorption TWA: 200 ppm TWA: 260 mg/m ³	TWA: 250 mg/m ³ 8 hodinách. Potential for cutaneous absorption Ceiling: 1000 mg/m ³
Formic acid	TWA: 5 ppm TWA: 9.0 mg/m ³	TWA-GVI: 5 ppm 8 satima. >90% TWA-GVI: 9 mg/m ³ 8 satima. >90%	TWA: 5 ppm 8 hr. TWA: 9 mg/m ³ 8 hr. STEL: 15 ppm 15 min STEL: 27 mg/m ³ 15 min	TWA: 5 ppm TWA: 9 mg/m ³	TWA: 9 mg/m ³ 8 hodinách. Ceiling: 18 mg/m ³

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Methanol	Nahk TWA: 200 ppm 8 tundides. TWA: 250 mg/m ³ 8 tundides. STEL: 250 ppm 15 minutites. STEL: 350 mg/m ³ 15 minutites.	Skin notation TWA: 200 ppm 8 hr TWA: 260 mg/m ³ 8 hr	skin - potential for cutaneous absorption STEL: 250 ppm STEL: 325 mg/m ³ TWA: 200 ppm TWA: 260 mg/m ³	TWA: 260 mg/m ³ 8 órában. AK lehetséges borón keresztül felszívódás	TWA: 200 ppm 8 klukkustundum. TWA: 260 mg/m ³ 8 klukkustundum. Skin notation Ceiling: 400 ppm Ceiling: 520 mg/m ³
Formic acid	TWA: 5 ppm 8 tundides. TWA: 9 mg/m ³ 8 tundides.	TWA: 5 ppm 8 hr TWA: 9 mg/m ³ 8 hr	TWA: 5 ppm TWA: 9 mg/m ³	TWA: 9 mg/m ³ 8 órában. AK	TWA: 5 ppm 8 klukkustundum. TWA: 9 mg/m ³ 8 klukkustundum. Skin notation Ceiling: 10 ppm Ceiling: 18 mg/m ³

SAFETY DATA SHEET

DOSINACO Mobile Phase B

Revision Date 04-Jan-2021

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Methanol	skin - potential for cutaneous exposure TWA: 200 ppm TWA: 260 mg/m ³	TWA: 200 ppm IPRD TWA: 260 mg/m ³ IPRD Oda	Possibility of significant uptake through the skin TWA: 200 ppm 8 Stunden TWA: 260 mg/m ³ 8 Stunden	possibility of significant uptake through the skin TWA: 200 ppm TWA: 260 mg/m ³	Skin notation TWA: 200 ppm 8 ore TWA: 260 mg/m ³ 8 ore
Formic acid	TWA: 5 ppm TWA: 9 mg/m ³	TWA: 5 ppm IPRD TWA: 9 mg/m ³ IPRD	TWA: 5 ppm 8 Stunden TWA: 9 mg/m ³ 8 Stunden	TWA: 5 ppm TWA: 9 mg/m ³	TWA: 5 ppm 8 ore TWA: 9 mg/m ³ 8 ore

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Methanol	TWA: 5 mg/m ³ 1250 Skin notation MAC: 15 mg/m ³	Potential for cutaneous absorption TWA: 200 ppm TWA: 260 mg/m ³	TWA: 200 ppm 8 urah TWA: 260 mg/m ³ 8 urah Koža STEL: 800 ppm 15 minutah STEL: 1040 mg/m ³ 15 minutah	Indicative STEL: 250 ppm 15 minuter Indicative STEL: 350 mg/m ³ 15 minuter TLV: 200 ppm 8 timmar. NGV TLV: 250 mg/m ³ 8 timmar. Hud	Deri TWA: 200 ppm 8 saat TWA: 260 mg/m ³ 8 saat
Formic acid	Skin notation MAC: 1 mg/m ³	TWA: 5 ppm TWA: 9.0 mg/m ³	TWA: 5 ppm 8 urah TWA: 9 mg/m ³ 8 urah	STV: 5 ppm 15 minuter STV: 9 mg/m ³ 15 minuter LLV: 3 ppm 8 timmar. LLV: 5 mg/m ³ 8 timmar.	TWA: 5 ppm 8 saat TWA: 9 mg/m ³ 8 saat
Ammonium formate	MAC: 10 mg/m ³				

Biological limit values

List source(s):

Component	European Union	United Kingdom	France	Spain	Germany
Methanol			Methanol: 15 mg/L urine end of shift	Methanol: 15 mg/L urine end of shift	Methanol: 15 mg/L urine (end of shift) Methanol: 15 mg/L urine (for long-term exposures: at the end of the shift after several shifts)

Component	Italy	Finland	Denmark	Bulgaria	Romania
Methanol					Methanol: 6 mg/L urine end of shift

Component	Gibraltar	Latvia	Slovak Republic	Luxembourg	Turkey
Methanol			Methanol: 30 mg/L urine end of exposure or work shift Methanol: 30 mg/L urine after all work shifts for long-term exposure		

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

SAFETY DATA SHEET

DOSINACO Mobile Phase B

Revision Date 04-Jan-2021

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Methanol 67-56-1 (87.6)		DNEL = 20mg/kg bw/day		DNEL = 20mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Methanol 67-56-1 (87.6)	DNEL = 130mg/m ³	DNEL = 130mg/m ³	DNEL = 130mg/m ³	DNEL = 130mg/m ³
Formic acid 64-18-6 (0.15)			DNEL = 9.5mg/m ³	

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Methanol 67-56-1 (87.6)	PNEC = 20.8mg/L	PNEC = 77mg/kg sediment dw	PNEC = 1540mg/L	PNEC = 100mg/L	PNEC = 100mg/kg soil dw
Formic acid 64-18-6 (0.15)	PNEC = 2mg/L	PNEC = 13.4mg/kg sediment dw	PNEC = 1mg/L	PNEC = 7.2mg/L	PNEC = 1.5mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Methanol 67-56-1 (87.6)	PNEC = 2.08mg/L	PNEC = 7.7mg/kg sediment dw			
Formic acid 64-18-6 (0.15)	PNEC = 0.2mg/L	PNEC = 1.34mg/kg sediment dw			

8.2. Exposure controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Wear safety glasses with side shields (or goggles) (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Nitrile rubber	See manufacturers	-	EN 374	(minimum requirement)
Viton (R)	recommendations			

Skin and body protection Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

SAFETY DATA SHEET

DOSINACO Mobile Phase B

Revision Date 04-Jan-2021

Large scale/emergency use	Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced Recommended Filter type: low boiling organic solvent Type AX Brown conforming to EN371 or Organic gases and vapours filter Type A Brown conforming to EN14387
Small scale/Laboratory use	Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141 When RPE is used a face piece Fit Test should be conducted
Environmental exposure controls	No information available.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance	No information available	
Odor	No information available	
Odor Threshold	No data available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flammability (liquid)	Highly flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Flash Point	12 °C / 53.6 °F	Method - Estimated
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
pH	No information available	
Viscosity	No data available	
Water Solubility	Miscible	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Methanol	-0.74	
Formic acid	-0.54	
Vapor Pressure	No data available	
Density / Specific Gravity	0.83	
Bulk Density	Not applicable	Liquid
Vapor Density	No data available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

VOC Content(%)	87.75
Explosive Properties	Vapors may form explosive mixtures with air

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None known, based on information available

SAFETY DATA SHEET

DOSINACO Mobile Phase B

Revision Date 04-Jan-2021

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization Hazardous Reactions

No information available.
None under normal processing.

10.4. Conditions to avoid

Heat, flames and sparks. Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

None under normal use conditions.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral	Category 3
Dermal	Category 3
Inhalation	Category 3

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methanol	LD50 = 1187 – 2769 mg/kg (Rat)	LD50 = 17100 mg/kg (Rabbit)	LC50 = 128.2 mg/L (Rat) 4 h
Water	-	-	-
Formic acid	730 mg/kg (Rat)	-	15 g/m ³ (Rat) 15 min

(b) skin corrosion/irritation; No data available

(c) serious eye damage/irritation; No data available

(d) respiratory or skin sensitization;

Respiratory	No data available
Skin	No data available

Component	Test method	Test species	Study result
Methanol 67-56-1 (87.6)	OECD Test Guideline 406 Guinea Pig Maximisation Test (GPMT)	guinea pig	non-sensitising

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; No data available

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; No data available

SAFETY DATA SHEET

DOSINACO Mobile Phase B

Revision Date 04-Jan-2021

Component	Test method	Test species / Duration	Study result
Methanol 67-56-1 (87.6)	OECD Test Guideline 416	Rat / Inhalation 2 Generation	NOAEC = 1.3 mg/l (air)

(h) STOT-single exposure; Category 1
Results / Target organs Optic nerve, Central nervous system (CNS).

(i) STOT-repeated exposure; No data available
Target Organs None known.

(j) aspiration hazard; No data available

Symptoms / effects, both acute and delayed Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity Ecotoxicity effects

Component	Freshwater Fish	Water Flea	Freshwater Algae
Methanol	Pimephales promelas: LC50 > 10000 mg/L 96h	EC50 > 10000 mg/L 24h	
Formic acid	Leuciscus idus: LC50 = 46-100 mg/L/96h	EC50 = 34 mg/L/48h	EC50 = 25 mg/L/96h

Component	Microtox	M-Factor
Methanol	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	
Formic acid	EC50 = 46.7 mg/L/17h	

12.2. Persistence and degradability

Persistence Persistence is unlikely.

Component	Degradability
Methanol 67-56-1 (87.6)	DT50 ~ 17.2d >94% after 20d

12.3. Bioaccumulative potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Methanol	-0.74	<10
Formic acid	-0.54	0.22

12.4. Mobility in soil

No information available

12.5. Results of PBT and vPvB assessment

No data available for assessment.

SAFETY DATA SHEET

DOSINACO Mobile Phase B

Revision Date 04-Jan-2021

12.6. Endocrine disrupting properties

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

Component	EU - Endocrine Disruptors Candidate List	EU - Endocrine Disruptors - Evaluated Substances
Formic acid	Applicable	

12.7. Other adverse effects

Persistent Organic Pollutant

This product does not contain any known or suspected substance

Ozone Depletion Potential

This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

European Waste Catalogue (EWC)

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information

Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with local regulations.

Switzerland - Waste Ordinance

Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600
<https://www.fedlex.admin.ch/eli/cc/2015/891/en>

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number

UN1230

14.2. UN proper shipping name

METHANOL SOLUTION

14.3. Transport hazard class(es)

3

Subsidiary Hazard Class

6.1

14.4. Packing group

II

ADR

14.1. UN number

UN1230

14.2. UN proper shipping name

METHANOL SOLUTION

14.3. Transport hazard class(es)

3

Subsidiary Hazard Class

6.1

14.4. Packing group

II

IATA

14.1. UN number

UN1230

14.2. UN proper shipping name

METHANOL SOLUTION

FSU22740503

SAFETY DATA SHEET

DOSINACO Mobile Phase B

Revision Date 04-Jan-2021

14.3. Transport hazard class(es) 3
Subsidiary Hazard Class 6.1
14.4. Packing group II

14.5. Environmental hazards No hazards identified

14.6. Special precautions for user No special precautions required

14.7. Maritime transport in bulk according to IMO instruments Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

X = listed, Europe (EINECS/ELINCS/NLP), U.S.A. (TSCA), Canada (DSL/NDSL), Philippines (PICCS), China (IECSC), Japan (ENCS), Japan (ISHL), Australia (AICS), Korea (KECL).

Component	EINECS	ELINCS	NLP	TSCA	DSL	NDSL	PICCS	IECSC	ENCS	ISHL	AICS	KECL
Methanol	200-659-6	-		X	X	-	X	X	X	X	X	KE-23193
Water	231-791-2	-		X	X	-	X	X	X		X	KE-35400
Formic acid	200-579-1	-		X	X	-	X	X	X	X	X	X
Ammonium formate	208-753-9	-		X	X	-	X	X	X	X	X	KE-17235

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Methanol		Use restricted. See item 69. (see link for restriction details)	
Formic acid		Use restricted. See item 75. (see link for restriction details)	

<https://echa.europa.eu/substances-restricted-under-reach>

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Methanol	67-56-1	500 tonne	5000 tonne
Water	7732-18-5	Not applicable	Not applicable
Formic acid	64-18-6	Not applicable	Not applicable
Ammonium formate	540-69-2	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals
 Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .
 Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification Water endangering class = 2 (self classification)

Component	Germany - Water Classification (VwVwS)	Germany - TA-Luft Class
Methanol	WGK 2	

SAFETY DATA SHEET

DOSINACO Mobile Phase B

Revision Date 04-Jan-2021

Formic acid	WGK 1	Class I : 20 mg/m ³ (Massenkonzentration)
Ammonium formate	WGK1	

Component	France - INRS (Tables of occupational diseases)
Methanol	Tableaux des maladies professionnelles (TMP) - RG 84

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Methanol 67-56-1 (87.6)	Prohibited and Restricted Substances	Group I	
Formic acid 64-18-6 (0.15)	Prohibited and Restricted Substances		

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H301 - Toxic if swallowed
H311 - Toxic in contact with skin
H331 - Toxic if inhaled
H370 - Causes damage to organs
H225 - Highly flammable liquid and vapor
H226 - Flammable liquid and vapor
H302 - Harmful if swallowed
H314 - Causes severe skin burns and eye damage
H315 - Causes skin irritation
H318 - Causes serious eye damage
H319 - Causes serious eye irritation
H335 - May cause respiratory irritation
EUH071 - Corrosive to the respiratory tract

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

SAFETY DATA SHEET

DOSINACO Mobile Phase B

Revision Date 04-Jan-2021

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data

Health Hazards Calculation method

Environmental hazards Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Chemical incident response training.

Creation Date 30-Apr-2020

Revision Date 04-Jan-2021

Revision Summary Not applicable.

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.
COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No
1907/2006 .**

**For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2,
Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and
Preparations).**

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet