

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
Product Identifier

Perihal Produk:

Product Description:

Cat No. :

Synonyms

CAS No

Molecular Formula

ETIL AKRILAT
Ethyl acrylate, stabilized

117980000; 117980010; 117980025; 117980250; 117980100

2-Propenoic acid, ethyl ester.

140-88-5

C5 H8 O2

Relevant identified uses of the substance or mixture and uses advised against

Recommended Use

Laboratory chemicals.

Uses advised against

No Information available

Company

 Thermo Fisher Scientific Fisher Scientific (M) Sdn Bhd
 Hap Seng Business Park, Lot 01-03, 01-04 Aras 1 Unity Square,
 No 12, Persiaran Perusahaan, Seksyen 23, 40300 Shah Alam,
 Selangor Darul Ehsan, Malaysia.
 Main line: +60 3-5525 7888

E-mail address

Enquiry.my@thermofisher.com

Emergency Telephone Number

Tel: +03-5525 7888

 CHEMTREC Malaysia **1-800-815-308** (Malay)

 CHEMTREC Malaysia (Kuala Lumpur) **+(60)-327884561** (Malay)

SECTION 2: HAZARDS IDENTIFICATION
Classification of the substance or mixture

Flammable liquids	Category 2 (H225)
Acute oral toxicity	Category 4 (H302)
Acute dermal toxicity	Category 4 (H312)
Acute Inhalation Toxicity - Vapors	Category 3 (H331)
Skin Corrosion/Irritation	Category 2 (H315)
Serious Eye Damage/Eye Irritation	Category 2 (H319)
Skin Sensitization	Category 1 (H317)
Specific target organ toxicity - (single exposure)	Category 3 (H335)
Chronic aquatic toxicity	Category 3 (H412)

Label Elements


SAFETY DATA SHEET

Ethyl acrylate, stabilized

Revision Date 21-Mar-2025

Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor
H302 + H312 - Harmful if swallowed or in contact with skin
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H331 - Toxic if inhaled
H335 - May cause respiratory irritation
H412 - Harmful to aquatic life with long lasting effects

Precautionary Statements

Prevention

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P240 - Ground and bond container and receiving equipment
P241 - Use explosion-proof electrical/ ventilating/ lighting equipment
P242 - Use non-sparking tools
P243 - Take action to prevent static discharges
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray
P264 - Wash face, hands and any exposed skin thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P271 - Use only outdoors or in a well-ventilated area
P272 - Contaminated work clothing should not be allowed out of the workplace
P280 - Wear protective gloves/protective clothing/eye protection/face protection

Response

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P311 - Call a POISON CENTER or doctor
P330 - Rinse mouth
P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish
P362 + P364 - Take off contaminated clothing and wash it before reuse

Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed
P405 - Store locked up

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Other Hazards

Lachrymator (substance which increases the flow of tears)
Stench
Toxicity to Soil Dwelling Organisms
Toxic to terrestrial vertebrates
This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No	Weight %
Ethyl acrylate	140-88-5	>95

SAFETY DATA SHEET

Ethyl acrylate, stabilized

Revision Date 21-Mar-2025

SECTION 4: FIRST AID MEASURES

Description of first aid measures

General Advice

Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.

Ingestion

Do NOT induce vomiting. Call a physician or poison control center immediately.

Inhalation

Remove to fresh air. If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required.

Self-Protection of the First Aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

Difficulty in breathing. May cause allergic skin reaction. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing media

Suitable Extinguishing Media

Water spray. Carbon dioxide (CO₂). Dry chemical. Alcohol resistant foam. Chemical foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

No information available.

Special hazards arising from the substance or mixture

Flammable. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Vapors may form explosive mixtures with air.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂).

Advice for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SAFETY DATA SHEET

Ethyl acrylate, stabilized

Revision Date 21-Mar-2025

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Use personal protective equipment as required. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas.

Environmental precautions

Should not be released into the environment. See Section 12 for additional Ecological Information. Avoid release to the environment. Collect spillage.

Methods and Material for Containment and Cleaning Up

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance.

Conditions for Safe Storage, Including any Incompatibilities

Refrigerator/flammables. Keep container tightly closed. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Specific End Uses

Use in laboratories.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Component	Malaysia	ACGIH TLV	OSHA PEL
Ethyl acrylate		TWA: 5 ppm STEL: 15 ppm	(Vacated) TWA: 5 ppm (Vacated) TWA: 20 mg/m ³ (Vacated) STEL: 25 ppm (Vacated) STEL: 100 mg/m ³ Skin TWA: 25 ppm TWA: 100 mg/m ³

Component	European Union	The United Kingdom	Germany
Ethyl acrylate	TWA: 5 ppm (8h) TWA: 21 mg/m ³ (8h) STEL: 10 ppm (15min) STEL: 42 mg/m ³ (15min)	STEL: 10 ppm 15 min STEL: 42 mg/m ³ 15 min TWA: 5 ppm 8 hr TWA: 21 mg/m ³ 8 hr	TWA: 2 ppm (8 Stunden). AGW - exposure factor 2 TWA: 8.3 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 2 ppm (8 Stunden). MAK even if the MAK value is adhered to, "odor-associated" symptoms cannot be ruled out in individual cases TWA: 8.3 mg/m ³ (8 Stunden). MAK even if the MAK value is adhered to, "odor-associated" symptoms cannot be ruled out in individual cases Höhepunkt: 4 ppm

SAFETY DATA SHEET

Ethyl acrylate, stabilized

Revision Date 21-Mar-2025

			Höhepunkt: 16.6 mg/m ³ Haut
--	--	--	---

Exposure Controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles

Hand Protection

Protective gloves

Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators

Recommended Filter type:

Organic gases and vapours filter Type A Brown conforming to EN14387

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

When RPE is used a face piece Fit Test should be conducted

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice

Environmental exposure controls

Prevent product from entering drains Do not allow material to contaminate ground water system

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance

Colorless

Physical State

Liquid

Odor

Stench

Odor Threshold

No data available

pH

No information available

Melting Point/Range

-71 °C / -95.8 °F

Softening Point

No data available

Boiling Point/Range

99 °C / 210.2 °F

Flash Point

16 °C / 60.8 °F

@ 760 mmHg

Method - No information available

Evaporation Rate

No data available

Flammability (solid,gas)

Not applicable

Liquid

Explosion Limits

Lower 1.8

Upper 13

SAFETY DATA SHEET

Ethyl acrylate, stabilized

Revision Date 21-Mar-2025

Vapor Pressure	29.5 mmHg @ 20 °C	
Vapor Density	3.45	(Air = 1.0)
Specific Gravity / Density	0.920	
Bulk Density	Not applicable	Liquid
Water Solubility	1.5% (25°C)	
Solubility in other solvents	No information available	

Partition Coefficient (n-octanol/water)

Component	log Pow
Ethyl acrylate	1.18

Autoignition Temperature	399 °C / 750.2 °F	
Decomposition Temperature	No data available	
Viscosity	0.58 cP at 20 °C	
Explosive Properties		Vapors may form explosive mixtures with air
Oxidizing Properties	No information available	

Molecular Formula	C5 H8 O2
Molecular Weight	100.12

SECTION 10: STABILITY AND REACTIVITY

Reactivity

Yes.

Chemical Stability

Light sensitive.

Possibility of Hazardous Reactions

Hazardous Polymerization	Polymerization can occur.
Hazardous Reactions	None under normal processing.

Conditions to Avoid

Keep away from open flames, hot surfaces and sources of ignition. Excess heat. Exposure to light. Incompatible products.

Incompatible Materials

Acids. Bases. Peroxides.

Hazardous Decomposition Products

Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: TOXICOLOGICAL INFORMATION

SAFETY DATA SHEET

Ethyl acrylate, stabilized

Revision Date 21-Mar-2025

Information on Toxicological Effects

Product Information

(a) acute toxicity;

Oral Category 4
Dermal Category 4
Inhalation Category 3

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethyl acrylate	1120 mg/kg (Rat)	3049-5000 mg/kg (Rat)	<9.14 mg/L/4h (Rat) (vapour) 25.8 mg/L/1h (Rat) (vapour)

(b) skin corrosion/irritation; Category 2

(c) serious eye damage/irritation; Category 2

(d) respiratory or skin sensitization;

Respiratory Based on available data, the classification criteria are not met
Skin Category 1
May cause sensitization by skin contact

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

(f) carcinogenicity; Based on available data, the classification criteria are not met
The table below indicates whether each agency has listed any ingredient as a carcinogen
Limited evidence of a carcinogenic effect

Component	EU	UK	Germany	IARC
Ethyl acrylate				Group 2B

(g) reproductive toxicity; Based on available data, the classification criteria are not met

(h) STOT-single exposure; Category 3

Results / Target organs Respiratory system.

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met

Target Organs None known.

(j) aspiration hazard; Based on available data, the classification criteria are not met

Symptoms / effects, both acute and delayed Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing.

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

SAFETY DATA SHEET

Ethyl acrylate, stabilized

Revision Date 21-Mar-2025

Ecotoxicity effects

The product contains following substances which are hazardous for the environment.
Contains a substance which is: Toxic to aquatic organisms.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Ethyl acrylate	LC50: 2.31 - 2.7 mg/L, 96h flow-through (Pimephales promelas) LC50: = 4.6 mg/L, 96h (Oncorhynchus mykiss)	EC50: = 7.9 mg/L, 48h (Daphnia magna)	EC50: = 48 mg/L, 72h (Desmodesmus subspicatus)	EC50 = 1536 mg/L 17 h EC50 = 46.8 mg/L 24 h

Persistence and degradability

Persistence

Readily biodegradable

Degradation in sewage treatment plant

Persistence is unlikely.

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

Bioaccumulative potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Ethyl acrylate	1.18	No data available

Mobility in soil

The product is water soluble, and may spread in water systems. . Will likely be mobile in the environment due to its water solubility. Highly mobile in soils.

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

Other adverse effects

No information available

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous Dispose of in accordance with the European Directives on waste and hazardous waste Dispose of in accordance with local regulations

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous Keep product and empty container away from heat and sources of ignition

Other Information

Do not flush to sewer Waste codes should be assigned by the user based on the application for which the product was used Can be landfilled or incinerated, when in compliance with local regulations Do not let this chemical enter the environment Do not empty into drains

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

UN-No	UN1917
Hazard Class	3
Packing Group	II
Proper Shipping Name	ETHYL ACRYLATE, STABILIZED

Road and Rail Transport

UN-No	UN1917
-------	--------

SAFETY DATA SHEET

Ethyl acrylate, stabilized

Revision Date 21-Mar-2025

Hazard Class 3
Packing Group II
Proper Shipping Name ETHYL ACRYLATE, STABILIZED

IATA

UN-No UN1917
Hazard Class 3
Packing Group II
Proper Shipping Name ETHYL ACRYLATE, STABILIZED

Special Precautions for User Inhibitors have been added to stabilize this product Inhibitor levels should be maintained
Hazardous polymerization may occur upon depletion of inhibitor

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories X = listed

Component	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	IECSC	AICS	KECL
Ethyl acrylate	205-438-8	X	X	X	X	X	X	X	KE-29507

National Regulations

Persistent Organic Pollutant This product does not contain any known or suspected substance
Ozone Depletion Potential This product does not contain any known or suspected substance

SECTION 16: OTHER INFORMATION

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

POW - Partition coefficient Octanol:Water

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

SAFETY DATA SHEET

Ethyl acrylate, stabilized

Revision Date 21-Mar-2025

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Revision Date

21-Mar-2025

Revision Summary

SDS sections updated, 7, 9, 14.

**In accordance with local and national regulations: Occupational Safety and Health
(Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013**

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet