

## Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

**Product Description:** Sulfur in Diesel Fuel standard solution, Specpure®, 500 µg/g (0.040%)  
**Cat No. :** 38769

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended Use** Laboratory chemicals.  
**Uses advised against** No Information available

### 1.3. Details of the supplier of the safety data sheet

#### Company

Thermo Fisher (Kandel) GmbH  
Erlenbachweg 2, 76870 Kandel, Germany  
Tel: +49 (0) 721 84007 280  
Fax: +49 (0) 721 84007 300

**Swiss distributor** - Fisher Scientific AG  
Neuhofstrasse 11, CH 4153 Reinach  
Tel: +41 (0) 56 618 41 11  
<https://www.fishersci.ch/ch/en/customer-help-support/forms/email-us.html>

**E-mail address** [begel.sdsdesk@thermofisher.com](mailto:begel.sdsdesk@thermofisher.com)

### 1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11  
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99  
**CHEMTREC** Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:  
Tox Info Suisse Emergency Number: **145 (24hr)**  
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)  
Chemtrec (24h) Toll-Free: 0800 564 402  
Chemtrec Local: +41-43 508 20 11 (Zurich)

#### Poison Centre - Emergency information services

**Ireland** : National Poisons Information Centre (NPIC) -  
**01 809 2166** (8am-10pm, 7 days a week)  
**Malta** : +356 2395 2000  
**Cyprus** : +357 2240 5611

## Section 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

# SAFETY DATA SHEET

Sulfur in Diesel Fuel standard solution, Specpure®, 500 µg/g (0.040%)

Revision Date 30-Nov-2024

## Physical hazards

Based on available data, the classification criteria are not met

## Health hazards

Carcinogenicity

Category 2 (H351)

## Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

## 2.2. Label elements



Signal Word

Warning

## Hazard Statements

H351 - Suspected of causing cancer  
Combustible liquid

## Precautionary Statements

P201 - Obtain special instructions before use  
P280 - Wear protective gloves/protective clothing/eye protection/face protection  
P308 + P313 - IF exposed or concerned: Get medical advice/attention

## 2.3. Other hazards

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)

This product does not contain any known or suspected endocrine disruptors

## **Section 3: Composition/information on ingredients**

### 3.2. Mixtures

| Component            | CAS No     | EC No             | Weight % | CLP Classification - Regulation (EC) No 1272/2008               |
|----------------------|------------|-------------------|----------|-----------------------------------------------------------------|
| Fuels, diesel, no. 2 | 68476-34-6 | EEC No. 270-676-1 | 99.76    | Carc. 2 (H351)                                                  |
| Butane, 1,1-thiobis- | 544-40-1   | EEC No. 208-870-5 | 0.24     | Skin Irrit. 2 (H315)<br>Eye Irrit. 2 (H319)<br>STOT SE 3 (H335) |

# SAFETY DATA SHEET

Sulfur in Diesel Fuel standard solution, Specpure®, 500 µg/g (0.040%)

Revision Date 30-Nov-2024

Full text of Hazard Statements: see section 16

## Section 4: First aid measures

### 4.1. Description of first aid measures

|                                           |                                                                                                                                                  |
|-------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>General Advice</b>                     | If symptoms persist, call a physician.                                                                                                           |
| <b>Eye Contact</b>                        | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.                                  |
| <b>Skin Contact</b>                       | Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.                                |
| <b>Ingestion</b>                          | Clean mouth with water and drink afterwards plenty of water.                                                                                     |
| <b>Inhalation</b>                         | Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.                                     |
| <b>Self-Protection of the First Aider</b> | Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. |

### 4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

### 4.3. Indication of any immediate medical attention and special treatment needed

**Notes to Physician** Treat symptomatically.

## Section 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable Extinguishing Media

Water mist may be used to cool closed containers.

#### Extinguishing media which must not be used for safety reasons

No information available.

### 5.2. Special hazards arising from the substance or mixture

Combustible material. Containers may explode when heated.

#### Hazardous Combustion Products

None under normal use conditions.

### 5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## Section 6: ACCIDENTAL RELEASE MEASURES

# SAFETY DATA SHEET

Sulfur in Diesel Fuel standard solution, Specpure®, 500 µg/g (0.040%)

Revision Date 30-Nov-2024

## 6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges.

## 6.2. Environmental precautions

Should not be released into the environment. See Section 12 for additional Ecological Information. Do not flush into surface water or sanitary sewer system.

## 6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition.

## 6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition.

#### Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

### 7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame.

#### Technical Rules for Hazardous Substances (TRGS) 510

Storage Class/LGK 10

#### Storage Class (LGK) (Germany)

#### Switzerland - Storage of hazardous substances

Storage class - SC 10/12

<https://www.kvu.ch/de/themen/stoffe-und-produkte>

<https://www.kvu.ch/fr/themes/substances-et-produits>

<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

### 7.3. Specific end use(s)

Use in laboratories

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits

List source(s):

| Component            | European Union | The United Kingdom | France | Belgium                                   | Spain |
|----------------------|----------------|--------------------|--------|-------------------------------------------|-------|
| Fuels, diesel, no. 2 |                |                    |        | TWA: 100 mg/m <sup>3</sup> 8 uren<br>Huid |       |

| Component            | Italy | Germany | Portugal                     | The Netherlands | Finland |
|----------------------|-------|---------|------------------------------|-----------------|---------|
| Fuels, diesel, no. 2 |       |         | TWA: 100 mg/m <sup>3</sup> 8 |                 |         |

# SAFETY DATA SHEET

Sulfur in Diesel Fuel standard solution, Specpure®, 500 µg/g (0.040%)

Revision Date 30-Nov-2024

|  |  |  |               |  |  |
|--|--|--|---------------|--|--|
|  |  |  | horas<br>Pele |  |  |
|--|--|--|---------------|--|--|

## Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

## Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

## Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

| Component                                    | Acute effects local<br>(Dermal) | Acute effects<br>systemic (Dermal) | Chronic effects local<br>(Dermal) | Chronic effects<br>systemic (Dermal) |
|----------------------------------------------|---------------------------------|------------------------------------|-----------------------------------|--------------------------------------|
| Fuels, diesel, no. 2<br>68476-34-6 ( 99.76 ) |                                 |                                    |                                   | DNEL = 2.91mg/kg<br>bw/day           |

| Component                                    | Acute effects local<br>(Inhalation) | Acute effects<br>systemic (Inhalation) | Chronic effects local<br>(Inhalation) | Chronic effects<br>systemic (Inhalation) |
|----------------------------------------------|-------------------------------------|----------------------------------------|---------------------------------------|------------------------------------------|
| Fuels, diesel, no. 2<br>68476-34-6 ( 99.76 ) |                                     | DNEL = 4288mg/m <sup>3</sup>           |                                       | DNEL = 68.34mg/m <sup>3</sup>            |

## Predicted No Effect Concentration (PNEC)

No information available.

## 8.2. Exposure controls

### Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

### Personal protective equipment

#### Eye Protection

Goggles (European standard - EN 166)

#### Hand Protection

Protective gloves

| Glove material                                      | Breakthrough time                    | Glove thickness | EU standard | Glove comments        |
|-----------------------------------------------------|--------------------------------------|-----------------|-------------|-----------------------|
| Natural rubber<br>Nitrile rubber<br>Neoprene<br>PVC | See manufacturers<br>recommendations | -               | EN 374      | (minimum requirement) |

# SAFETY DATA SHEET

Sulfur in Diesel Fuel standard solution, Specpure®, 500 µg/g (0.040%)

Revision Date 30-Nov-2024

**Skin and body protection** Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

**Respiratory Protection** When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.  
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

**Large scale/emergency use** Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced  
**Recommended Filter type:** Particulates filter conforming to EN 143

**Small scale/Laboratory use** Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.  
**Recommended half mask:-** Particle filtering: EN149:2001  
When RPE is used a face piece Fit Test should be conducted

**Environmental exposure controls** Prevent product from entering drains.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|                                                |                               |                                          |
|------------------------------------------------|-------------------------------|------------------------------------------|
| <b>Physical State</b>                          | Liquid                        |                                          |
| <b>Appearance</b>                              | Light brown                   |                                          |
| <b>Odor</b>                                    | Petroleum distillates         |                                          |
| <b>Odor Threshold</b>                          | No data available             |                                          |
| <b>Melting Point/Range</b>                     | No data available             |                                          |
| <b>Softening Point</b>                         | No data available             |                                          |
| <b>Boiling Point/Range</b>                     | 171 - 315 °C / 339.8 - 599 °F |                                          |
| <b>Flammability (liquid)</b>                   | Combustible liquid            | On basis of test data                    |
| <b>Flammability (solid,gas)</b>                | Not applicable                | Liquid                                   |
| <b>Explosion Limits</b>                        | No data available             |                                          |
| <b>Flash Point</b>                             | 69 °C / 156.2 °F              | <b>Method -</b> No information available |
| <b>Autoignition Temperature</b>                | 500 °C / 932 °F               |                                          |
| <b>Decomposition Temperature</b>               | No data available             |                                          |
| <b>pH</b>                                      | No information available      |                                          |
| <b>Viscosity</b>                               | No data available             |                                          |
| <b>Water Solubility</b>                        | No information available      |                                          |
| <b>Solubility in other solvents</b>            | No information available      |                                          |
| <b>Partition Coefficient (n-octanol/water)</b> |                               |                                          |
| <b>Vapor Pressure</b>                          | No data available             |                                          |
| <b>Density / Specific Gravity</b>              | 0.75 g/cm3                    | @ 20 °C                                  |
| <b>Bulk Density</b>                            | Not applicable                | Liquid                                   |
| <b>Vapor Density</b>                           | No data available             | (Air = 1.0)                              |
| <b>Particle characteristics</b>                | Not applicable (liquid)       |                                          |

### 9.2. Other information

**Explosive Properties** explosive air/vapour mixtures possible

## Section 10: Stability and reactivity

# SAFETY DATA SHEET

Sulfur in Diesel Fuel standard solution, Specpure®, 500 µg/g (0.040%)

Revision Date 30-Nov-2024

## 10.1. Reactivity

None known, based on information available

## 10.2. Chemical stability

Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

### **Hazardous Polymerization**

No information available.

### **Hazardous Reactions**

None under normal processing.

## 10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

## 10.5. Incompatible materials

None known.

## 10.6. Hazardous decomposition products

None under normal use conditions.

## **Section 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Product Information**

#### **(a) acute toxicity;**

**Oral**

Based on available data, the classification criteria are not met

**Dermal**

Based on available data, the classification criteria are not met

**Inhalation**

Based on available data, the classification criteria are not met

#### **Toxicology data for the components**

| Component            | LD50 Oral                 | LD50 Dermal                  | LC50 Inhalation                                            |
|----------------------|---------------------------|------------------------------|------------------------------------------------------------|
| Fuels, diesel, no. 2 | -                         | LD50 > 2000 mg/kg ( Rabbit ) | LC50 = 5.4 mg/L ( Rat ) 4 h<br>LC50 = 3.6 mg/L ( Rat ) 4 h |
| Butane, 1,1-thiobis- | LD50 = 2220 mg/kg ( Rat ) | -                            | -                                                          |

#### **(b) skin corrosion/irritation;**

No data available

#### **(c) serious eye damage/irritation;**

No data available

#### **(d) respiratory or skin sensitization;**

**Respiratory**

No data available

**Skin**

No data available

#### **(e) germ cell mutagenicity;**

No data available

#### **(f) carcinogenicity;**

Category 2

There are no known carcinogenic chemicals in this product

# SAFETY DATA SHEET

Sulfur in Diesel Fuel standard solution, Specpure®, 500 µg/g (0.040%)

Revision Date 30-Nov-2024

(g) reproductive toxicity; No data available

(h) STOT-single exposure; No data available

(i) STOT-repeated exposure; No data available

Target Organs No information available.

(j) aspiration hazard; No data available

Symptoms / effects, both acute and delayed Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

## 11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

## Section 12: Ecological information

### 12.1. Toxicity

#### Ecotoxicity effects

Contains a substance which is: Harmful to aquatic organisms. The product contains following substances which are hazardous for the environment.

| Component            | Freshwater Fish                                           | Water Flea | Freshwater Algae |
|----------------------|-----------------------------------------------------------|------------|------------------|
| Fuels, diesel, no. 2 | LC50: = 35 mg/L, 96h flow-through (Pimephales promelas)   |            |                  |
| Butane, 1,1-thiobis- | LC50: = 3.58 mg/L, 96h flow-through (Pimephales promelas) |            |                  |

### 12.2. Persistence and degradability

#### Degradation in sewage treatment plant

No information available

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

### 12.3. Bioaccumulative potential

No information available

### 12.4. Mobility in soil

No information available

### 12.5. Results of PBT and vPvB assessment

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB).

### 12.6. Endocrine disrupting properties

#### Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors



# SAFETY DATA SHEET

Sulfur in Diesel Fuel standard solution, Specpure®, 500 µg/g (0.040%)

Revision Date 30-Nov-2024

## 12.7. Other adverse effects

Persistent Organic Pollutant  
Ozone Depletion Potential

This product does not contain any known or suspected substance  
This product does not contain any known or suspected substance

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point.

European Waste Catalogue (EWC)

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information

Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Do not empty into drains.

Switzerland - Waste Ordinance

Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600  
<https://www.fedlex.admin.ch/eli/cc/2015/891/en>

## Section 14: Transport information

IMDG/IMO

Not regulated

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

ADR

Not regulated

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

IATA

Not regulated

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

14.5. Environmental hazards

No hazards identified

14.6. Special precautions for user

No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable, packaged goods

## Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# SAFETY DATA SHEET

Sulfur in Diesel Fuel standard solution, Specpure®, 500 µg/g (0.040%)

Revision Date 30-Nov-2024

## International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

| Component            | CAS No     | EINECS    | ELINCS | NLP | IECSC | TCSI | KECL     | ENCS | ISHL |
|----------------------|------------|-----------|--------|-----|-------|------|----------|------|------|
| Fuels, diesel, no. 2 | 68476-34-6 | 270-676-1 | -      | -   | X     | X    | KE-17287 | -    | -    |
| Butane, 1,1-thiobis- | 544-40-1   | 208-870-5 | -      | -   | X     | X    | -        | X    | X    |

| Component            | CAS No     | TSCA | TSCA Inventory notification - Active-Inactive | DSL | NDSL | AICS | NZIoC | PICCS |
|----------------------|------------|------|-----------------------------------------------|-----|------|------|-------|-------|
| Fuels, diesel, no. 2 | 68476-34-6 | X    | ACTIVE                                        | X   | -    | X    | X     | X     |
| Butane, 1,1-thiobis- | 544-40-1   | X    | ACTIVE                                        | X   | -    | X    | X     | X     |

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

## Authorisation/Restrictions according to EU REACH

| Component            | CAS No     | REACH (1907/2006) - Annex XIV - Substances Subject to Authorization | REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances | REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC) |
|----------------------|------------|---------------------------------------------------------------------|-------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------|
| Fuels, diesel, no. 2 | 68476-34-6 | -                                                                   | Use restricted. See entry 75. (see link for restriction details)              | -                                                                                                     |
| Butane, 1,1-thiobis- | 544-40-1   | -                                                                   | -                                                                             | -                                                                                                     |

## REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

## Seveso III Directive (2012/18/EC)

| Component            | CAS No     | Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification | Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements |
|----------------------|------------|-------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|
| Fuels, diesel, no. 2 | 68476-34-6 | Not applicable                                                                            | Not applicable                                                                           |
| Butane, 1,1-thiobis- | 544-40-1   | Not applicable                                                                            | Not applicable                                                                           |

## Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

## Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

## National Regulations

**UK** - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

## WGK Classification

Water endangering class = 2 (self classification)

| Component | Germany - Water Classification (AwSV) | Germany - TA-Luft Class |
|-----------|---------------------------------------|-------------------------|
|-----------|---------------------------------------|-------------------------|

ALFAA38769

# SAFETY DATA SHEET

Sulfur in Diesel Fuel standard solution, Specpure®, 500 µg/g (0.040%)

Revision Date 30-Nov-2024

|                      |      |  |
|----------------------|------|--|
| Fuels, diesel, no. 2 | WGK2 |  |
| Butane, 1,1-thiobis- | WGK2 |  |

## Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

## 15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

## Section 16: Other information

### Full text of H-Statements referred to under sections 2 and 3

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H335 - May cause respiratory irritation

H351 - Suspected of causing cancer

### Legend

**CAS** - Chemical Abstracts Service

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List

**ENCS** - Japanese Existing and New Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**NZIoC** - New Zealand Inventory of Chemicals

**WEL** - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

**RPE** - Respiratory Protective Equipment

**LC50** - Lethal Concentration 50%

**NOEC** - No Observed Effect Concentration

**PBT** - Persistent, Bioaccumulative, Toxic

**TWA** - Time Weighted Average

**IARC** - International Agency for Research on Cancer Predicted No Effect Concentration (PNEC)

**LD50** - Lethal Dose 50%

**EC50** - Effective Concentration 50%

**POW** - Partition coefficient Octanol:Water

**vPvB** - very Persistent, very Bioaccumulative

**ADR** - European Agreement Concerning the International Carriage of Dangerous Goods by Road

**IMO/IMDG** - International Maritime Organization/International Maritime Dangerous Goods Code

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

**ICAO/IATA** - International Civil Aviation Organization/International Air Transport Association

**MARPOL** - International Convention for the Prevention of Pollution from Ships

**ATE** - Acute Toxicity Estimate

**VOC** - (volatile organic compound)

### Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

### Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

**Physical hazards** On basis of test data

**Health Hazards** Calculation method

**Environmental hazards** Calculation method

### Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

# SAFETY DATA SHEET

Sulfur in Diesel Fuel standard solution, Specpure®, 500 µg/g (0.040%)

Revision Date 30-Nov-2024

---

First aid for chemical exposure, including the use of eye wash and safety showers.

|                  |                                             |
|------------------|---------------------------------------------|
| Prepared By      | Health, Safety and Environmental Department |
| Revision Date    | 30-Nov-2024                                 |
| Revision Summary | Not applicable.                             |

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.  
COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No  
1907/2006 .**

**For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2,  
Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and  
Preparations).**

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**