

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: Multi-element ICP Standard, Specpure
Cat No. : 98119

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

Thermo Fisher (Kandel) GmbH
Erlenbachweg 2, 76870 Kandel, Germany
Tel: +49 (0) 721 84007 280
Fax: +49 (0) 721 84007 300

Swiss distributor - Fisher Scientific AG
Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
<https://www.fishersci.ch/ch/en/customer-help-support/forms/email-us.html>

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

SAFETY DATA SHEET

Multi-element ICP Standard, Specpure

Revision Date 15-Feb-2024

Substances/mixtures corrosive to metal

Category 1 (H290)

Health hazards

Acute Inhalation Toxicity - Vapors
Skin Corrosion/Irritation
Serious Eye Damage/Eye Irritation
Carcinogenicity

Category 4 (H332)
Category 1 (H314) B
Category 1 (H318)
Category 1B (H350)

Environmental hazards

Chronic aquatic toxicity

Category 3 (H412)

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H290 - May be corrosive to metals
H332 - Harmful if inhaled
H314 - Causes severe skin burns and eye damage
H350 - May cause cancer
H412 - Harmful to aquatic life with long lasting effects
EUH208 - Contains Chromium. May produce an allergic reaction

Precautionary Statements

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a POISON CENTER or doctor/physician

Additional EU labelling

Restricted to professional users

2.3. Other hazards

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
-----------	--------	-------	----------	---

SAFETY DATA SHEET

Multi-element ICP Standard, Specpure

Revision Date 15-Feb-2024

Water	7732-18-5	231-791-2	93.4	-
Nitric acid	7697-37-2	231-714-2	5	Ox. Liq. 3 (H272) Met. Corr. 1 (H290) Acute Tox. 3 (H331) Skin Corr. 1A (H314) Eye Dam. 1 (H318) (EUH071)
Selenium	7782-49-2	EEC No. 231-957-4	0.5	Acute Tox. 3 (H331) Acute Tox. 3 (H301) STOT RE 2 (H373) Aquatic Chronic 4 (H413)
Arsenic	7440-38-2	EEC No. 231-148-6	0.5	Acute Tox. 3 (H301) Acute Tox. 3 (H331) Carc. 1A (H350) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)
Silver	7440-22-4	EEC No. 231-131-3	0.1	-
Nickel	7440-02-0	EEC No. 231-111-4	0.1	Skin Sens. 1 (H317) Carc. 2 (H351) STOT RE 1 (H372)
Lead	7439-92-1	EEC No. 231-100-4	0.1	Acute Tox. 4 (H332) Acute Tox. 4 (H302) Repr. 1A (H360Df) STOT RE 2 (H373) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)
Chromium	7440-47-3	EEC No. 231-157-5	0.1	-
Cadmium	7440-43-9	EEC No. 231-152-8	0.1	Acute Tox. 2 (H330) Muta. 2 (H341) Carc. 1B (H350) Repr. 2 (H361fd) STOT RE 1 (H372) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)
Barium	7440-39-3	EEC No. 231-149-1	0.1	Flam. Sol. 2 (H228) Water-react. 1 (H260) Acute Tox. 3 (H301) Skin Corr. 1B (H314) Eye Dam. 1 (H318)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Nitric acid	Ox. Liq. 2 :: C>=99% Ox. Liq. 3 :: 65%<=C<99% Acute Tox. 1 (inhal) :: C>=70% Acute Tox. 3 (inhal) :: 70%>C>=26.5% Acute Tox. 4 (inhal) :: 26.5%>C>=13.25% Skin Corr. 1A :: C>=20% Skin Corr. 1B :: 5%<=C<20% Met. Corr. 1 :: C>=2% EUH071 :: C>=20%	-	-
Arsenic	-	1	-
Lead	Repr. 1A : C ≥ 0.03 % STOT RE 1 : C ≥ 0.5 %	1 (acute) 10 (Chronic)	-
Cadmium	-	10	-

Component	ECHA (RAC) ATE (Oral)	ECHA (RAC) ATE (Dermal)	ECHA (RAC) ATE (Inhalation)
Nitric acid	-	-	ATE = 2.65 mg/L (vapours)

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

SAFETY DATA SHEET

Multi-element ICP Standard, Specpure

Revision Date 15-Feb-2024

General Advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Call a physician immediately.
Ingestion	Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately.
Inhalation	If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes.

Hazardous Combustion Products

Nitrogen oxides (NO_x), Metal oxides.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

SAFETY DATA SHEET

Multi-element ICP Standard, Specpure

Revision Date 15-Feb-2024

6.2. Environmental precautions

Should not be released into the environment. Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Corrosives area. Keep containers tightly closed in a dry, cool and well-ventilated place.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Storage Class/LGK 6.1D

Switzerland - Storage of hazardous substances

Storage class - SC 6.1
<https://www.kvu.ch/de/themen/stoffe-und-produkte>
<https://www.kvu.ch/fr/themes/substances-et-produits>
<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Nitric acid	STEL: 1 ppm (15min) STEL: 2.6 mg/m ³ (15min)	STEL: 1 ppm 15 min STEL: 2.6 mg/m ³ 15 min	STEL / VLCT: 1 ppm. indicative limit STEL / VLCT: 2.6 mg/m ³ . indicative limit	STEL: 1 ppm 15 minuten STEL: 2.6 mg/m ³ 15 minuten	STEL / VLA-EC: 1 ppm (15 minutos). STEL / VLA-EC: 2.6 mg/m ³ (15 minutos).
Selenium		STEL: 0.3 mg/m ³ 15 min TWA: 0.1 mg/m ³ 8 hr		TWA: 0.2 mg/m ³ 8 uren	TWA / VLA-ED: 0.1 mg/m ³ (8 horas)

SAFETY DATA SHEET

Multi-element ICP Standard, Specpure

Revision Date 15-Feb-2024

Arsenic		STEL: 0.3 mg/m ³ 15 min TWA: 0.1 mg/m ³ 8 hr Carc.		TWA: 0.01 mg/m ³ 8 uren	TWA / VLA-ED: 0.01 mg/m ³ (8 horas)
Silver	TWA: 0.1 mg/m ³ (8h)	STEL: 0.3 mg/m ³ 15 min TWA: 0.1 mg/m ³ 8 hr	TWA / VME: 0.1 mg/m ³ (8 heures). indicative limit	TWA: 0.1 mg/m ³ 8 uren	TWA / VLA-ED: 0.1 mg/m ³ (8 horas)
Nickel		STEL: 1.5 mg/m ³ 15 min TWA: 0.5 mg/m ³ 8 hr Skin	TWA / VME: 1 mg/m ³ (8 heures). TWA / VME: 1 mg/m ³ (8 heures). metal gratings	TWA: 1 mg/m ³ 8 uren	TWA / VLA-ED: 1 mg/m ³ (8 horas)
Lead	TWA: 0.15 mg/m ³ (8h)	STEL: 0.45 mg/m ³ 15 min TWA: 0.15 mg/m ³ 8 hr	TWA / VME: 0.1 mg/m ³ (8 heures). restrictive limit		TWA / VLA-ED: 0.15 mg/m ³ (8 horas)
Chromium	TWA: 2 mg/m ³ (8hr)	STEL: 1.5 mg/m ³ 15 min TWA: 0.5 mg/m ³ 8 hr	TWA / VME: 2 mg/m ³ (8 heures). indicative limit	TWA: 0.5 mg/m ³ 8 uren	TWA / VLA-ED: 2 mg/m ³ (8 horas)
Cadmium	TWA: 0.001 mg/m ³ (8h)	STEL: 0.075 mg/m ³ 15 min TWA: 0.025 mg/m ³ 8 hr Carc. metal	TWA / VME: 0.004 mg/m ³ (8 heures). restrictive limit	TWA: 0.01 mg/m ³ 8 uren TWA: 0.004 mg/m ³ 8 uren	TWA / VLA-ED: 0.01 mg/m ³ (8 horas) TWA / VLA-ED: 0.002 mg/m ³ (8 horas)
Barium				TWA: 0.5 mg/m ³ 8 uren	TWA / VLA-ED: 0.5 mg/m ³ (8 horas)

Component	Italy	Germany	Portugal	The Netherlands	Finland
Nitric acid	STEL: 1 ppm 15 minuti. Short-term STEL: 2.6 mg/m ³ 15 minuti. Short-term	TWA: 1 ppm (8 Stunden). AGW - TWA: 2.6 mg/m ³ (8 Stunden). AGW -	STEL: 1 ppm 15 minutos STEL: 2.6 mg/m ³ 15 minutos TWA: 2 ppm 8 horas	STEL: 1.3 mg/m ³ 15 minuten	TWA: 0.5 ppm 8 tunteina TWA: 1.3 mg/m ³ 8 tunteina STEL: 1 ppm 15 minuutteina STEL: 2.6 mg/m ³ 15 minuutteina
Selenium		TWA: 0.05 mg/m ³ (8 Stunden). AGW - exposure factor 1 TWA: 0.02 mg/m ³ (8 Stunden). MAK Höhepunkt: 0.16 mg/m ³ Haut	TWA: 0.2 mg/m ³ 8 horas		TWA: 0.1 mg/m ³ 8 tunteina STEL: 0.3 mg/m ³ 15 minuutteina
Arsenic			TWA: 0.01 mg/m ³ 8 horas	TWA: 0.0028 mg/m ³ 8 uren	TWA: 0.01 mg/m ³ 8 tunteina
Silver	TWA: 0.1 mg/m ³ 8 ore. Time Weighted Average	TWA: 0.1 mg/m ³ (8 Stunden). AGW - exposure factor 8 TWA: 0.1 mg/m ³ (8 Stunden). MAK Höhepunkt: 0.8 mg/m ³	TWA: 0.01 mg/m ³ 8 horas	TWA: 0.1 mg/m ³ 8 uren	TWA: 0.1 mg/m ³ 8 tunteina
Nickel		TWA: 0.03 mg/m ³ (8 Stunden). AGW - exposure factor 8 TWA: 0.006 mg/m ³ (8 Stunden). AGW - exposure factor 8	TWA: 1.5 mg/m ³ 8 horas		TWA: 0.01 mg/m ³ 8 tunteina
Lead	TWA: 0.15 mg/m ³ 8 ore. Time Weighted Average	TWA: 0.004 mg/m ³ (8 Stunden). MAK Höhepunkt: 0.032 mg/m ³	TWA: 0.05 mg/m ³ 8 horas	TWA: 0.15 mg/m ³ 8 uren	TWA: 0.1 mg/m ³ 8 tunteina
Chromium	TWA: 0.5 mg/m ³ 8 ore. Time Weighted Average	TWA: 2 mg/m ³ (8 Stunden). AGW - exposure factor 1	TWA: 0.5 mg/m ³ 8 horas	TWA: 0.5 mg/m ³ 8 uren	TWA: 0.5 mg/m ³ 8 tunteina
Cadmium	TWA: 0.001 mg/m ³ 8 ore. Time Weighted Average TWA: 0.004 mg/m ³ 8 ore. Time Weighted Average until July 11, 2027	TWA: 0.002 mg/m ³ (8 Stunden). AGW - exposure factor 8 TWA: 0.002 mg/m ³ (8 Stunden). AGW - Haut	TWA: 0.001 mg/m ³ 8 horas TWA: 0.004 mg/m ³ 8 horas	TWA: 0.004 mg/m ³ 8 uren	TWA: 0.004 mg/m ³ 8 tunteina
Barium			TWA: 0.5 mg/m ³ 8 horas		

Component	Austria	Denmark	Switzerland	Poland	Norway
Nitric acid	MAK-KZGW: 1 ppm 15 Minuten MAK-KZGW: 2.6 mg/m ³	STEL: 1 ppm 15 minutter STEL: 2.6 mg/m ³ 15	STEL: 2 ppm 15 Minuten STEL: 5 mg/m ³ 15	STEL: 2.6 mg/m ³ 15 minutach TWA: 1.4 mg/m ³ 8	TWA: 2 ppm 8 timer TWA: 5 mg/m ³ 8 timer STEL: 4 ppm 15

SAFETY DATA SHEET

Multi-element ICP Standard, Specpure

Revision Date 15-Feb-2024

	15 Minuten	minutter	Minuten TWA: 2 ppm 8 Stunden TWA: 5 mg/m ³ 8 Stunden	godzinach	minutter. value calculated STEL: 10 mg/m ³ 15 minutter. value calculated
Selenium	MAK-KZGW: 0.3 mg/m ³ 15 Minuten MAK-TMW: 0.1 mg/m ³ 8 Stunden	TWA: 0.1 mg/m ³ 8 timer STEL: 0.2 mg/m ³ 15 minutter	Haut/Peau STEL: 0.16 mg/m ³ 15 Minuten TWA: 0.02 mg/m ³ 8 Stunden	STEL: 0.3 mg/m ³ 15 minutach TWA: 0.1 mg/m ³ 8 godzinach	TWA: 0.05 mg/m ³ 8 timer STEL: 0.15 mg/m ³ 15 minutter. value calculated
Arsenic		TWA: 0.0028 mg/m ³ 8 timer STEL: 0.0056 mg/m ³ 15 minutter	Haut/Peau TWA: 0.01 mg/m ³ 8 Stunden	TWA: 0.01 mg/m ³ 8 godzinach	TWA: 0.005 mg/m ³ 8 timer STEL: 0.015 mg/m ³ 15 minutter. value calculated inhalable fraction Hud
Silver	MAK-KZGW: 0.1 mg/m ³ 15 Minuten MAK-TMW: 0.1 mg/m ³ 8 Stunden Ceiling: 0.1 mg/m ³	TWA: 0.01 mg/m ³ 8 timer STEL: 0.02 mg/m ³ 15 minutter	STEL: 0.8 mg/m ³ 15 Minuten TWA: 0.1 mg/m ³ 8 Stunden	TWA: 0.05 mg/m ³ 8 godzinach	TWA: 0.1 mg/m ³ 8 timer STEL: 0.3 mg/m ³ 15 minutter. value calculated metal dust and fume
Nickel	TRK-KZGW: 2 mg/m ³ 15 Minuten TRK-TMW: 0.5 mg/m ³	TWA: 0.05 mg/m ³ 8 timer STEL: 0.1 mg/m ³ 15 minutter	TWA: 0.5 mg/m ³ 8 Stunden	TWA: 0.25 mg/m ³ 8 godzinach	TWA: 0.05 mg/m ³ 8 timer STEL: 0.15 mg/m ³ 15 minutter. value calculated
Lead	MAK-KZGW: 0.4 mg/m ³ 15 Minuten MAK-TMW: 0.1 mg/m ³ 8 Stunden	TWA: 0.05 mg/m ³ 8 timer STEL: 0.1 mg/m ³ 15 minutter	STEL: 0.8 mg/m ³ 15 Minuten TWA: 0.1 mg/m ³ 8 Stunden	TWA: 0.05 mg/m ³ 8 godzinach	TWA: 0.05 mg/m ³ 8 timer STEL: 0.15 mg/m ³ 15 minutter. value calculated dust and fume
Chromium	MAK-TMW: 2 mg/m ³ 8 Stunden	TWA: 0.5 mg/m ³ 8 timer STEL: 1 mg/m ³ 15 minutter	TWA: 0.5 mg/m ³ 8 Stunden	TWA: 0.5 mg/m ³ 8 godzinach	TWA: 0.5 mg/m ³ 8 timer STEL: 1.5 mg/m ³ 15 minutter. value calculated
Cadmium	TRK-KZGW: 0.016 mg/m ³ 15 Minuten TRK-KZGW: 0.004 mg/m ³ 15 Minuten TRK-TMW: 0.004 mg/m ³ TRK-TMW: 0.001 mg/m ³	TWA: 0.001 mg/m ³ 8 timer STEL: 0.002 mg/m ³ 15 minutter	Haut/Peau TWA: 0.001 mg/m ³ 8 Stunden	TWA: 0.004 mg/m ³ 8 godzinach	TWA: 0.001 mg/m ³ 8 timer STEL: 0.003 mg/m ³ 15 minutter. value calculated inhalable fraction
Barium				TWA: 0.5 mg/m ³ 8 godzinach	TWA: 0.5 mg/m ³ 8 timer STEL: 1.5 mg/m ³ 15 minutter. value calculated

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Nitric acid	STEL : 1 ppm STEL : 2.6 mg/m ³	STEL-KGVI: 1 ppm 15 minutama. STEL-KGVI: 2.6 mg/m ³ 15 minutama.	STEL: 1 ppm 15 min STEL: 2.6 mg/m ³ 15 min	STEL: 1 ppm STEL: 2.6 mg/m ³	TWA: 1 mg/m ³ 8 hodinách. Ceiling: 2.5 mg/m ³
Selenium	TWA: 0.2 mg/m ³	TWA-GVI: 0.1 mg/m ³ 8 satima.	TWA: 0.1 mg/m ³ 8 hr. Se STEL: 0.3 mg/m ³ 15 min		TWA: 0.1 mg/m ³ 8 hodinách. Ceiling: 0.2 mg/m ³
Arsenic		TWA-GVI: 0.1 mg/m ³ 8 satima. except Arsine	TWA: 0.01 mg/m ³ 8 hr. STEL: 0.03 mg/m ³ 15 min		TWA: 0.1 mg/m ³ 8 hodinách. Ceiling: 0.4 mg/m ³ biological test
Silver	TWA: 0.1 mg/m ³	TWA-GVI: 0.1 mg/m ³ 8 satima.	TWA: 0.1 mg/m ³ 8 hr. Ag metallic STEL: 0.3 mg/m ³ 15 min	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³ 8 hodinách. respirable fraction of aerosol Ceiling: 0.3 mg/m ³
Nickel	TWA: 0.05 mg/m ³	TWA-GVI: 0.5 mg/m ³ 8 satima.	TWA: 0.5 mg/m ³ 8 hr. STEL: 1.5 mg/m ³ 15 min		TWA: 0.5 mg/m ³ 8 hodinách. respirable fraction of aerosol Ceiling: 1 mg/m ³
Lead	TWA: 0.05 mg/m ³	TWA-GVI: 0.15 mg/m ³ 8 satima.	TWA: 0.15 mg/m ³ 8 hr. STEL: 0.45 mg/m ³ 15 min	TWA: 0.15 mg/m ³	TWA: 0.05 mg/m ³ 8 hodinách. Ceiling: 0.2 mg/m ³ biological test, toxic for

SAFETY DATA SHEET

Multi-element ICP Standard, Specpure

Revision Date 15-Feb-2024

					reproduction
Chromium	TWA: 2.0 mg/m ³	TWA-GVI: 2 mg/m ³ 8 satima. Cr	TWA: 2 mg/m ³ 8 hr. STEL: 6 mg/m ³ 15 min	TWA: 2 mg/m ³	TWA: 0.5 mg/m ³ 8 hodinách. dust Ceiling: 1.5 mg/m ³
Cadmium	TWA: 0.004 mg/m ³	TWA-GVI: 0.004 mg/m ³ 8 satima. applies during the transition period until July 11, 2027 inhalable fraction	TWA: 0.001 mg/m ³ 8 hr. inhalable fraction TWA: 0.004 mg/m ³ 8 hr. limit value 0.004 mg/m ³ until 11 July 2027 inhalable fraction STEL: 0.003 mg/m ³ 15 min STEL: 0.012 mg/m ³ 15 min	TWA: 0.001 mg/m ³	TWA: 0.004 mg/m ³ 8 hodinách. 0.002 mg Cd/g Creatinine in urine inhalable fraction of aerosol Potential for cutaneous absorption Ceiling: 0.008 mg/m ³
Barium		TWA-GVI: 0.5 mg/m ³ 8 satima.			

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Nitric acid	STEL: 1 ppm 15 minutites. STEL: 2.6 mg/m ³ 15 minutites.	STEL: 1 ppm 15 min STEL: 2.6 mg/m ³ 15 min	STEL: 1 ppm STEL: 2.6 mg/m ³	STEL: 2.6 mg/m ³ 15 percekben. CK	STEL: 1 ppm STEL: 2.6 mg/m ³
Selenium			TWA: 0.2 mg/m ³		TWA: 0.1 mg/m ³ 8 klukkustundum. Ceiling: 0.2 mg/m ³
Arsenic	TWA: 0.03 mg/m ³ 8 tundides.		TWA: 0.1 mg/m ³	TWA: 0.01 mg/m ³ 8 órában. AK lehetséges borön keresztüli felszívódás	TWA: 0.01 mg/m ³ 8 klukkustundum. Ceiling: 0.02 mg/m ³
Silver	TWA: 0.1 mg/m ³ 8 tundides.		TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³ 8 órában. AK	TWA: 0.01 mg/m ³ 8 klukkustundum. dust and powder Ceiling: 0.02 mg/m ³ dust and powder
Nickel	TWA: 0.5 mg/m ³ 8 tundides.		TWA: 1 mg/m ³	TWA: 0.01 mg/m ³ 8 órában. AK	TWA: 0.05 mg/m ³ 8 klukkustundum. Ni dust and powder Ceiling: 0.1 mg/m ³ Ni dust and powder
Lead	TWA: 0.1 mg/m ³ 8 tundides. total dust TWA: 0.05 mg/m ³ 8 tundides. respirable dust	TWA: 0.15 mg/m ³ 8 hr	TWA: 0.15 mg/m ³	TWA: 0.1 mg/m ³ 8 órában. AK TWA: 0.05 mg/m ³ 8 órában. AK	TWA: 0.05 mg/m ³ 8 klukkustundum. dust, fume, and powder Ceiling: 0.1 mg/m ³ dust, fume, and powder
Chromium	TWA: 2 mg/m ³ 8 tundides.	TWA: 2 mg/m ³ 8 hr	TWA: 1 mg/m ³	TWA: 2 mg/m ³ 8 órában. AK	TWA: 0.5 mg/m ³ 8 klukkustundum. powder Ceiling: 1 mg/m ³ powder
Cadmium	TWA: 0.004 mg/m ³ 8 tundides. valid until July 10, 2027		TWA: 0.001 mg/m ³	TWA: 0.004 mg/m ³ 8 órában. AK	TWA: 0.001 mg/m ³ 8 klukkustundum. inhalable fraction TWA: 0.004 mg/m ³ 8 klukkustundum. valid until July 11, 2027 inhalable fraction Ceiling: 0.002 mg/m ³ inhalable fraction Ceiling: 0.008 mg/m ³ valid until July 11, 2027 inhalable fraction

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Nitric acid	STEL: 1 ppm STEL: 2.6 mg/m ³ TWA: 0.78 ppm TWA: 2 mg/m ³	STEL: 1 ppm STEL: 2.6 mg/m ³	STEL: 1 ppm 15 Minuten STEL: 2.6 mg/m ³ 15 Minuten	STEL: 1 ppm 15 minuti STEL: 2.6 mg/m ³ 15 minuti	STEL: 1 ppm 15 minute STEL: 2.6 mg/m ³ 15 minute
Selenium		TWA: 0.1 mg/m ³ IPRD			TWA: 0.1 mg/m ³ 8 ore STEL: 0.2 mg/m ³ 15 minute
Arsenic					TWA: 0.01 mg/m ³ 8 ore STEL: 0.1 mg/m ³ 15

SAFETY DATA SHEET

Multi-element ICP Standard, Specpure

Revision Date 15-Feb-2024

					minute
Silver	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³ IPRD Ag	TWA: 0.1 mg/m ³ 8 Stunden	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³ 8 ore
Nickel	TWA: 0.05 mg/m ³	TWA: 0.5 mg/m ³ IPRD			TWA: 0.1 mg/m ³ 8 ore STEL: 0.5 mg/m ³ 15 minute
Lead	STEL: 0.1 mg/m ³ TWA: 0.05 mg/m ³	TWA: 0.15 mg/m ³ inhalable fraction IPRD TWA: 0.07 mg/m ³ respirable fraction IPRD	TWA: 0.15 mg/m ³ 8 Stunden		TWA: 0.15 mg/m ³ 8 ore
Chromium	TWA: 2 mg/m ³	TWA: 2 mg/m ³ IPRD	TWA: 2 mg/m ³ 8 Stunden	TWA: 2 mg/m ³	TWA: 2 mg/m ³ 8 ore
Cadmium	TWA: 0.001 mg/m ³	TWA: 0.004 mg/m ³ inhalable fraction IPRD			TWA: 0.05 mg/m ³ 8 ore
Barium				TWA: 0.5 mg/m ³	TWA: 0.5 mg/m ³ 8 ore

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Nitric acid	Skin notation MAC: 2 mg/m ³	Ceiling: 2.6 mg/m ³	TWA: 1 ppm 8 urah TWA: 2.6 mg/m ³ 8 urah STEL: 1 ppm 15 minutah STEL: 2.6 mg/m ³ 15 minutah	Binding STEL: 1 ppm 15 minuter Binding STEL: 2.6 mg/m ³ 15 minuter TLV: 0.5 ppm 8 timmar. NGV TLV: 1.3 mg/m ³ 8 timmar. NGV	STEL: 1 ppm 15 dakika STEL: 2.6 mg/m ³ 15 dakika
Selenium	TWA: 2 mg/m ³ 1830	TWA: 0.05 mg/m ³	TWA: 0.05 mg/m ³ 8 urah inhalable fraction STEL: 0.05 mg/m ³ 15 minutah inhalable fraction	TLV: 0.1 mg/m ³ 8 timmar. NGV	
Arsenic				TLV: 0.01 mg/m ³ 8 timmar. NGV	
Silver	MAC: 1 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.01 mg/m ³ 8 urah inhalable fraction STEL: 0.02 mg/m ³ 15 minutah inhalable fraction	TLV: 0.1 mg/m ³ 8 timmar. NGV	TWA: 0.1 mg/m ³ 8 saat TWA: 0.01 mg/m ³ 8 saat
Nickel	MAC: 0.05 mg/m ³	TWA: 0.5 mg/m ³ 8 hodínach STEL: 0.05 mg/m ³ 15 minútach	TWA: 0.006 mg/m ³ 8 urah respirable fraction STEL: 0.048 mg/m ³ 15 minutah respirable fraction	TLV: 0.5 mg/m ³ 8 timmar. NGV	
Lead	TWA: 0.05 mg/m ³ 1826	TWA: 0.15 mg/m ³ inhalable fraction TWA: 0.5 mg/m ³ respirable fraction	TWA: 0.1 mg/m ³ 8 urah inhalable fraction STEL: 0.4 mg/m ³ 15 minutah inhalable fraction	TLV: 0.1 mg/m ³ 8 timmar. NGV TLV: 0.05 mg/m ³ 8 timmar. NGV	TWA: 0.15 mg/m ³ 8 saat
Chromium			TWA: 2 mg/m ³ 8 urah inhalable fraction STEL: 2 mg/m ³ 15 minutah inhalable fraction	TLV: 0.5 mg/m ³ 8 timmar. NGV	TWA: 2 mg/m ³ 8 saat
Cadmium	TWA: 0.01 mg/m ³ 1051 MAC: 0.05 mg/m ³	TWA: 0.03 mg/m ³ 8 hodínach manufactured TWA: 0.15 mg/m ³ 8 hodínach others STEL: 0.15 mg/m ³ 15 minútach manufactured STEL: 0.75 mg/m ³ 15 minútach others	TWA: 0.004 mg/m ³ 8 urah applies until July 11, 2027 inhalable fraction	TLV: 0.001 mg/m ³ 8 timmar. NGV TLV: 0.004 mg/m ³ 8 timmar. NGV	
Barium		TWA: 0.5 mg/m ³ respirable fraction TWA: 0.5 mg/m ³	TWA: 0.5 mg/m ³ 8 urah inhalable fraction STEL: 0.5 mg/m ³ 15 minutah inhalable fraction		TWA: 0.5 mg/m ³ 8 saat

Biological limit values

List source(s):

Component	European Union	United Kingdom	France	Spain	Germany
Selenium					Selenium: 150 µg/L

SAFETY DATA SHEET

Multi-element ICP Standard, Specpure

Revision Date 15-Feb-2024

					serum (no restriction)
Arsenic			Metabolites of inorganic Arsenic: 0.05 mg/g creatinine urine end of workweek	Inorganic arsenic plus Methylated metabolites: 35 µg As/L urine end of workweek	
Lead			Lead: 400 µg/L blood Lead: 180 µg/L blood indifferent sampling time Lead: 300 µg/L blood Lead: 200 µg/L blood Lead: 100 µg/L blood	Lead: 70 µg/dL blood not critical	Lead: 150 µg/L whole blood (no restriction)
Chromium			Total Chromium: 0.01 mg/g creatinine urine augmented during shift Total Chromium: 0.03 mg/g creatinine urine end of shift at end of workweek		
Cadmium			Cadmium: 0.005 mg/g creatinine urine not critical Cadmium: 0.004 mg/L blood not critical	Cadmium: 2 µg/g Creatinine urine not critical Cadmium: 5 µg/L blood not critical	

Component	Italy	Finland	Denmark	Bulgaria	Romania
Arsenic		Arsenic, inorganic: 70 nmol/L urine after the work phase or shift after a working week or exposure period. Does not apply to the exposure of gallium arsenide			Arsenic: 50 µg/g Creatinine urine end of work week Arsenic: 0.5 mg/100g hair end of work week
Nickel		Nickel: 0.1 µmol/L urine after the shift after a working week or exposure period.		Nickel: 45 µg/L urine after several work shifts	Nickel: 3 µg/L urine end of shift
Lead	60 Pb µg/100 mL blood end of workweek	Lead: 1.4 µmol/L blood time of day does not matter.	Lead: 20 µg/100 mL blood	Lead: 300 µg/L blood not fixed for women under 45 years old Lead: 400 µg/L blood not fixed	Lead: 150 µg/L urine end of shift Lead: 70 µg/100 mL blood end of shift Lead: 3 mg/cm hair end of shift .delta.-Aminolevulinic acid: 10 mg/L urine end of shift Coproporphyrin: 300 µg/L urine end of shift free erythrocytes protoporphyrin: 100 µg/100 mL erythrocyte blood end of shift
Chromium					Chromium: 10 µg/g Creatinine urine during working hours Chromium: 30 µg/g Creatinine urine end of work week
Cadmium		Cadmium: 20 nmol/L urine at the end of a working week; time of day does not matter.			Cadmium: 2 µg/g Creatinine urine end of shift Cadmium: 5 µg/L blood end of shift Protein: 2 mg/L urine end of shift

Component	Gibraltar	Latvia	Slovak Republic	Luxembourg	Turkey
Nickel		Nickel: 3 µg/L urine	Nickel: 0.03 mg/L blood end of exposure or work shift		
Lead	70 µg/100 mL blood Lead binding biological	Lead: 30 µg/100 mL blood	Lead: 400 µg/L blood not critical	Lead: 70 µg/100 mL blood.	Lead: 70 µg/100 mL blood

SAFETY DATA SHEET

Multi-element ICP Standard, Specpure

Revision Date 15-Feb-2024

	limit value;biological monitoring must include measuring the blood-lead level using absorption spectrometry or a method giving equivalent results 0.075 mg/m ³ air 40 hours per week Lead medical surveillance must be carried out;threshold measured in individual employees 40 µg/100 mL blood Lead medical surveillance must be carried out;threshold measured in individual employees	Coproporphyrin: 100 µg/g Creatinine urine Aminolevulinic acid: 5 mg/g Creatinine urine	Lead: 100 µg/L blood not critical women younger than 45 years of age .delta.-Aminolevulinic acid: 15 mg/L urine not critical .delta.-Aminolevulinic acid: 6 mg/L urine not critical women younger than 45 years of age Coproporphyrins: 0.30 mg/L urine not critical	Lead: 0.072 mg/m ³ blood. medical surveillance threshold in air measured as a time weighted average over 40 hours per week Lead: 40 µg/100 mL blood. medical surveillance threshold measured in individual workers	
Chromium		Chromium: 10 µg/g Creatinine urine end of shift; end of work week			
Cadmium		Cadmium: 2 µg/L urine	Cadmium: 3.1 µg/L urine not critical carcinogen, category 2		

Monitoring methods

MDHS 91 Metals and metalloids in workplace air by X-ray fluorescence spectrometry

MDHS 99 Metals in air by ICP-AES

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Selenium 7782-49-2 (0.5)				DNEL = 7mg/kg bw/day
Arsenic 7440-38-2 (0.5)				DNEL = 85µg/kg bw/day
Nickel 7440-02-0 (0.1)			DNEL = 0.035mg/cm2	
Barium 7440-39-3 (0.1)				DNEL = 28.5mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Selenium 7782-49-2 (0.5)				DNEL = 0.05mg/m ³
Arsenic 7440-38-2 (0.5)				DNEL = 4µg/m ³
Silver 7440-22-4 (0.1)				DNEL = 0.1mg/m ³
Nickel 7440-02-0 (0.1)	DNEL = 11.9mg/m ³		DNEL = 0.05mg/m ³	DNEL = 0.05mg/m ³
Chromium 7440-47-3 (0.1)			DNEL = 0.5mg/m ³	
Cadmium 7440-43-9 (0.1)			DNEL = 4µg/m ³	
Barium 7440-39-3 (0.1)				DNEL = 5.8mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

SAFETY DATA SHEET

Multi-element ICP Standard, Specpure

Revision Date 15-Feb-2024

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Arsenic 7440-38-2 (0.5)	PNEC = 13µg/L	PNEC = 130mg/kg sediment dw	PNEC = 13µg/L	PNEC = 61µg/L	PNEC = 0.5mg/kg soil dw
Silver 7440-22-4 (0.1)	PNEC = 0.04µg/L	PNEC = 438.13mg/kg sediment dw		PNEC = 0.025mg/L	PNEC = 1.41mg/kg soil dw
Nickel 7440-02-0 (0.1)	PNEC = 7.1µg/L	PNEC = 109mg/kg sediment dw		PNEC = 0.33mg/L	PNEC = 29.9mg/kg soil dw
Lead 7439-92-1 (0.1)	PNEC = 2.4µg/L	PNEC = 186mg/kg sediment dw		PNEC = 100µg/L	PNEC = 212mg/kg soil dw
Chromium 7440-47-3 (0.1)	PNEC = 6.5µg/L	PNEC = 205.7mg/kg sediment dw			PNEC = 21.1mg/kg soil dw
Cadmium 7440-43-9 (0.1)	PNEC = 0.19µg/L	PNEC = 1.8mg/kg sediment dw		PNEC = 20µg/L	PNEC = 0.9mg/kg soil dw
Barium 7440-39-3 (0.1)	PNEC = 114.7µg/L	PNEC = 598.9mg/kg sediment dw		PNEC = 62.2mg/L	PNEC = 207.7mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Arsenic 7440-38-2 (0.5)	PNEC = 0.8µg/L	PNEC = 8mg/kg sediment dw	PNEC = 0.9µg/L	PNEC = 1mg/kg food	
Silver 7440-22-4 (0.1)	PNEC = 0.86µg/L	PNEC = 438.13mg/kg sediment dw			
Nickel 7440-02-0 (0.1)	PNEC = 8.6µg/L	PNEC = 109mg/kg sediment dw		PNEC = 0.12mg/kg food	
Lead 7439-92-1 (0.1)	PNEC = 3.3µg/L	PNEC = 168mg/kg sediment dw		PNEC = 10.9mg/kg food	
Cadmium 7440-43-9 (0.1)	PNEC = 1.14µg/L	PNEC = 0.64mg/kg sediment dw		PNEC = 0.16mg/kg food	

8.2. Exposure controls

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles (European standard - EN 166)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Natural rubber	See manufacturers	-	EN 374	(minimum requirement)
Nitrile rubber	recommendations			
Neoprene				
PVC				

Skin and body protection

Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used

SAFETY DATA SHEET

Multi-element ICP Standard, Specpure

Revision Date 15-Feb-2024

and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced
Recommended Filter type: Particulates filter conforming to EN 143

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Recommended half mask:- Particle filtering: EN149:2001
When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls Prevent product from entering drains.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance		
Odor	No information available	
Odor Threshold	No data available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flammability (liquid)	No data available	
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Flash Point	No information available	Method - No information available
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
pH	2	
Viscosity	No data available	
Water Solubility	No information available	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Nitric acid	-2.3	
Vapor Pressure	No data available	
Density / Specific Gravity	No data available	
Bulk Density	Not applicable	Liquid
Vapor Density	No data available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity
None known, based on information available

10.2. Chemical stability
Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization No information available.
Hazardous Reactions None under normal processing.

SAFETY DATA SHEET

Multi-element ICP Standard, Specpure

Revision Date 15-Feb-2024

10.4. Conditions to avoid

Incompatible products. Excess heat.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Nitrogen oxides (NOx). Metal oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral

Based on available data, the classification criteria are not met

Dermal

Based on available data, the classification criteria are not met

Inhalation

Category 4

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Water	-	-	-
Nitric acid	-	-	LC50 = 2500 ppm. (Rat) 1h
Selenium	LD50 = 6700 mg/kg (Rat)	-	>5.67 mg/l (Rat) 4hr
Arsenic	LD50 = 15 mg/kg (Rat)	-	-
Silver	> 2000 mg/kg (Rat)	LD50 > 2000 mg/kg (rat)	LC50 > 5.16 mg/L (Rat) 4 h
Nickel	LD50 > 9000 mg/kg (Rat)	-	LC50 > 10.2 mg/L (Rat) 1 h
Cadmium	LD50 = 2330 mg/kg (Rat)	-	LC50 = 25 mg/m ³ (Rat) 30 min
Barium	LD50 = 132 mg/kg (Rat)	-	-

Component	ECHA (RAC) ATE (Oral)	ECHA (RAC) ATE (Dermal)	ECHA (RAC) ATE (Inhalation)
Nitric acid	-	-	ATE = 2.65 mg/L (vapours)

(b) skin corrosion/irritation;

Category 1 B

(c) serious eye damage/irritation;

Category 1

(d) respiratory or skin sensitization;

Respiratory

No data available

Skin

No data available

(e) germ cell mutagenicity;

No data available

(f) carcinogenicity;

Category 1B

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Arsenic			Cat. 1	Group 1
Nickel			Cat. 1	Group 2B
Lead				Group 2A
Cadmium	Carc Cat. 1B		Cat. 1	Group 1

SAFETY DATA SHEET

Multi-element ICP Standard, Specpure

Revision Date 15-Feb-2024

(g) reproductive toxicity; No data available

(h) STOT-single exposure; No data available

(i) STOT-repeated exposure; No data available

Target Organs No information available.

(j) aspiration hazard; No data available

Symptoms / effects, both acute and delayed Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment. May cause long-term adverse effects in the environment. Do not allow material to contaminate ground water system.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Selenium	LC50: > 100 mg/L, 96h semi-static (Oncorhynchus mykiss)		
Silver	LC50: = 0.064 mg/L, 96h static (Lepomis macrochirus) LC50: = 0.0062 mg/L, 96h flow-through (Oncorhynchus mykiss) LC50: 0.00155 - 0.00293 mg/L, 96h static (Pimephales promelas)	EC50: = 0.00024 mg/L, 48h Static (Daphnia magna)	
Nickel	LC50: > 100 mg/L, 96h (Brachydanio rerio) LC50: = 1.3 mg/L, 96h semi-static (Cyprinus carpio) LC50: = 10.4 mg/L, 96h static (Cyprinus carpio)	EC50 = 510 µg/L 96h	EC50 = 0.1 mg/L 72h EC50 = 0.18 mg/L 72h
Lead	LC50: = 1.32 mg/L, 96h static (Oncorhynchus mykiss) LC50: = 1.17 mg/L, 96h flow-through (Oncorhynchus mykiss) LC50: = 0.44 mg/L, 96h semi-static (Cyprinus carpio)	EC50: = 600 µg/L, 48h (water flea)	
Cadmium	LC50: 0.0004 - 0.003 mg/L, 96h (Pimephales promelas) LC50: = 0.016 mg/L, 96h (Oryzias latipes) LC50: = 21.1 mg/L, 96h flow-through (Lepomis	EC50: = 0.0244 mg/L, 48h Static (Daphnia magna)	

SAFETY DATA SHEET

Multi-element ICP Standard, Specpure

Revision Date 15-Feb-2024

	macrochirus) LC50: = 0.24 mg/L, 96h static (Cyprinus carpio) LC50: = 4.26 mg/L, 96h semi-static (Cyprinus carpio) LC50: = 0.002 mg/L, 96h (Cyprinus carpio) LC50: = 0.006 mg/L, 96h static (Oncorhynchus mykiss) LC50: = 0.003 mg/L, 96h flow-through (Oncorhynchus mykiss)		
Barium	LC50: > 500 mg/L/96h (Cyprinodon variegatus)		

Component	Microtox	M-Factor
Arsenic		1
Lead		1 (acute) 10 (Chronic)
Cadmium		10

12.2. Persistence and degradability Product contains heavy metals. Discharge into the environment must be avoided. Special pre-treatment is necessary

Persistence May persist.

Degradation in sewage treatment plant Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential Product has a high potential to bioconcentrate

Component	log Pow	Bioconcentration factor (BCF)
Nitric acid	-2.3	No data available
Chromium		1.03 - 1.22

12.4. Mobility in soil No information available

12.5. Results of PBT and vPvB assessment No data available for assessment.

12.6. Endocrine disrupting properties

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant This product does not contain any known or suspected substance

Ozone Depletion Potential This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point.

European Waste Catalogue (EWC) According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information Do not flush to sewer. Waste codes should be assigned by the user based on the

SAFETY DATA SHEET

Multi-element ICP Standard, Specpure

Revision Date 15-Feb-2024

application for which the product was used. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms. Solutions with low pH-value must be neutralized before discharge. Do not let this chemical enter the environment.

Switzerland - Waste Ordinance

Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600

<https://www.fedlex.admin.ch/eli/cc/2015/891/en>

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number	UN3264
14.2. UN proper shipping name	Corrosive liquid, acidic, inorganic, n.o.s.
Technical Shipping Name	Nitric acid solution
14.3. Transport hazard class(es)	8
14.4. Packing group	III

ADR

14.1. UN number	UN3264
14.2. UN proper shipping name	Corrosive liquid, acidic, inorganic, n.o.s.
Technical Shipping Name	Nitric acid solution
14.3. Transport hazard class(es)	8
14.4. Packing group	III

IATA

14.1. UN number	UN3264
14.2. UN proper shipping name	Corrosive liquid, acidic, inorganic, n.o.s.
Technical Shipping Name	Nitric acid solution
14.3. Transport hazard class(es)	8
14.4. Packing group	III

14.5. Environmental hazards	No hazards identified
14.6. Special precautions for user	No special precautions required.
14.7. Maritime transport in bulk according to IMO instruments	Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

China, X = listed, Australia, U.S.A. (TSCA), Canada (DSL/NDL), Europe (EINECS/ELINCS/NLP), Australia (AICS), Korea (KECL), China (IECSC), Japan (ENCS), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Water	7732-18-5	231-791-2	-	-	X	X	KE-35400	X	-
Nitric acid	7697-37-2	231-714-2	-	-	X	X	KE-25911	X	X
Selenium	7782-49-2	231-957-4	-	-	X	X	KE-30924	X	-
Arsenic	7440-38-2	231-148-6	-	-	X	X	KE-01933	X	-
Silver	7440-22-4	231-131-3	-	-	X	X	KE-31261	X	-
Nickel	7440-02-0	231-111-4	-	-	X	X	KE-25818	X	-
Lead	7439-92-1	231-100-4	-	-	X	X	KE-21887	X	-
Chromium	7440-47-3	231-157-5	-	-	X	X	KE-05970	X	-
Cadmium	7440-43-9	231-152-8	-	-	X	X	KE-04397	X	-

SAFETY DATA SHEET

Multi-element ICP Standard, Specpure

Revision Date 15-Feb-2024

Barium	7440-39-3	231-149-1	-	-	X	X	KE-02022	X	-
Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS	
Water	7732-18-5	X	ACTIVE	X	-	X	X	X	
Nitric acid	7697-37-2	X	ACTIVE	X	-	X	X	X	
Selenium	7782-49-2	X	ACTIVE	X	-	X	X	X	
Arsenic	7440-38-2	X	ACTIVE	X	-	X	X	X	
Silver	7440-22-4	X	ACTIVE	X	-	X	X	X	
Nickel	7440-02-0	X	ACTIVE	X	-	X	X	X	
Lead	7439-92-1	X	ACTIVE	X	-	X	X	X	
Chromium	7440-47-3	X	ACTIVE	X	-	X	X	X	
Cadmium	7440-43-9	X	ACTIVE	X	-	X	X	X	
Barium	7440-39-3	X	ACTIVE	X	-	X	X	X	

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Water	7732-18-5	-	-	-
Nitric acid	7697-37-2	-	Use restricted. See item 75. (see link for restriction details)	-
Selenium	7782-49-2	-	Use restricted. See item 75. (see link for restriction details)	-
Arsenic	7440-38-2	-	Use restricted. See item 75. (see link for restriction details)	-
Silver	7440-22-4	-	Use restricted. See item 75. (see link for restriction details)	-
Nickel	7440-02-0	-	Use restricted. See item 27. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-
Lead	7439-92-1	-	Use restricted. See item 72. (see link for restriction details) Use restricted. See item 30. (see link for restriction details) Use restricted. See item 63. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	SVHC Candidate list - 231-100-4 - Toxic for reproduction (Article 57c)
Chromium	7440-47-3	-	Use restricted. See item 75. (see link for restriction details)	-

SAFETY DATA SHEET

Multi-element ICP Standard, Specpure

Revision Date 15-Feb-2024

Cadmium	7440-43-9	-	Use restricted. See item 72. (see link for restriction details) Use restricted. See item 23. (see link for restriction details) Use restricted. See item 28. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	SVHC Candidate list - 231-152-8 - Carcinogenic, Article 57a; Specific target organ toxicity after repeated exposure, Article 57(f) - human health
Barium	7440-39-3	-	Use restricted. See item 75. (see link for restriction details)	-

After the sunset date the use of this substance requires either an authorization or can only be used for exempted uses, e.g. use in scientific research and development which includes routine analytics or use as intermediate.

REACH links

<https://echa.europa.eu/authorisation-list>

<https://echa.europa.eu/substances-restricted-under-reach>

<https://echa.europa.eu/candidate-list-table>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Water	7732-18-5	Not applicable	Not applicable
Nitric acid	7697-37-2	Not applicable	Not applicable
Selenium	7782-49-2	Not applicable	Not applicable
Arsenic	7440-38-2	Not applicable	Not applicable
Silver	7440-22-4	Not applicable	Not applicable
Nickel	7440-02-0	Not applicable	Not applicable
Lead	7439-92-1	Not applicable	Not applicable
Chromium	7440-47-3	Not applicable	Not applicable
Cadmium	7440-43-9	Not applicable	Not applicable
Barium	7440-39-3	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Component	ANNEX I - PART 1 List of chemicals subject to export notification procedure (referred to in Article 8)	ANNEX I - PART 2 List of chemicals qualifying for PIC notification (referred to in Article 11)	ANNEX I - PART 3 List of chemicals subject to the PIC procedure (referred to in Articles 13 and 14)
Lead 7439-92-1 (0.1)	sr — severe restriction i(2) — industrial chemical for public	-	-
Cadmium 7440-43-9 (0.1)	i(1) — industrial chemical for professional use sr — severe restriction i(2) — industrial chemical for public sr — severe restriction	i — industrial chemical sr — severe restriction	-

<https://eur-lex.europa.eu/legal-content/EN/TXT/?uri=CELEX%3A32012R0649&qid=1604065742303>

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

SAFETY DATA SHEET

Multi-element ICP Standard, Specpure

Revision Date 15-Feb-2024

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

Take note of Dir 76/769/EEC relating to restrictions on the marketing and use of certain dangerous substances and preparations

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 3 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Nitric acid	WGK1	
Selenium	WGK2	Class II : 0.5 mg/m ³ (Massenkonzentration)
Arsenic	WGK3	Krebserzeugende Stoffe - Class I : 0.05 mg/m ³ (Massenkonzentration)
Silver	nwg	
Nickel	WGK 2	Class II : 0.5 mg/m ³ (Massenkonzentration) Krebserzeugende Stoffe - Class II : 0.5 mg/m ³ (Massenkonzentration)
Lead	nwg	Class II : 0.5 mg/m ³ (Massenkonzentration)
Chromium	nwg	Class III : 1 mg/m ³ (Massenkonzentration)
Cadmium	WGK3	Krebserzeugende Stoffe - Class I : 0.05 mg/m ³ (Massenkonzentration)
Barium	WGK1	

Component	France - INRS (Tables of occupational diseases)
Selenium	Tableaux des maladies professionnelles (TMP) - RG 75
Arsenic	Tableaux des maladies professionnelles (TMP) - RG 20,RG 20bis
Lead	Tableaux des maladies professionnelles (TMP) - RG 1
Chromium	Tableaux des maladies professionnelles (TMP) - RG 10
Cadmium	Tableaux des maladies professionnelles (TMP) - RG 61,RG 61bis

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Nitric acid 7697-37-2 (5)	Prohibited and Restricted Substances		
Arsenic 7440-38-2 (0.5)	Prohibited and Restricted Substances		Annex I - pesticide
Nickel 7440-02-0 (0.1)	Prohibited and Restricted Substances		
Lead 7439-92-1 (0.1)	Prohibited and Restricted Substances		
Chromium 7440-47-3 (0.1)	Prohibited and Restricted Substances		
Cadmium 7440-43-9 (0.1)	Prohibited and Restricted Substances		Annex I - industrial chemical

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

SAFETY DATA SHEET

Multi-element ICP Standard, Specpure

Revision Date 15-Feb-2024

Full text of H-Statements referred to under sections 2 and 3

H290 - May be corrosive to metals
H332 - Harmful if inhaled
H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage
H350 - May cause cancer
H412 - Harmful to aquatic life with long lasting effects
H260 - In contact with water releases flammable gases which may ignite spontaneously
H272 - May intensify fire; oxidizer
H301 - Toxic if swallowed
H302 - Harmful if swallowed
H317 - May cause an allergic skin reaction
H330 - Fatal if inhaled
H331 - Toxic if inhaled
H341 - Suspected of causing genetic defects
H351 - Suspected of causing cancer
H360Df - May damage the unborn child. Suspected of damaging fertility
H361fd - Suspected of damaging fertility. Suspected of damaging the unborn child
H372 - Causes damage to organs through prolonged or repeated exposure
H400 - Very toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects
EUH071 - Corrosive to the respiratory tract

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadviser - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data

Health Hazards Calculation method

Environmental hazards Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Prepared By

Revision Date

Revision Summary

Health, Safety and Environmental Department

15-Feb-2024

New emergency telephone response service provider.

SAFETY DATA SHEET

Multi-element ICP Standard, Specpure

Revision Date 15-Feb-2024

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.
COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No
1907/2006 .**

**For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2,
Number 3, Chemo (SR 813.11 - Ordinance on Protection against Dangerous Substances and
Preparations).**

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet