

Classified as hazardous in accordance with the criteria of EPA New Zealand

Section 1 - Identification

Product Identifier

Product Name Potassium hydroxide, 0.1N Standardized Solution in methanol

Synonyms Potassium hydroxide solution 0.1M (0.1N); Methyl hydroxide; Carbinol; Methanol; Monohydroxymethane; Pyroxylic spirit; Wood alcohol; Wood naphtha; Wood spirit; Methyl hydrate

Recommended Use Laboratory chemicals.
Uses advised against No Information available

Product Code	42734
Address	Thermo Fisher Scientific New Zealand Ltd 244 Bush Road, Albany, Auckland, New Zealand
Emergency Tel.	CHEMTREC® 09 980 6780 or +64 9 980 6780
Telephone / Fax Numbers	Tel: 09 980 6700 Fax: 09 980 6788
E-mail address	ANZinfo@thermofisher.com

Section 2 - Hazard(s) Identification

Classification under Work Safe New Zealand

Classified as hazardous in accordance with the criteria of EPA New Zealand

GHS Classification

Physical hazards

Flammable liquids

Category 2

Health hazards

Acute Oral Toxicity	Category 3
Acute Dermal Toxicity	Category 3
Acute Inhalation Toxicity - Vapors	Category 3
Serious Eye Damage/Eye Irritation	Category 2
Reproductive Toxicity	Category 2
Specific target organ toxicity - (single exposure)	Category 1

Environmental hazards

Based on available data, the classification criteria are not met

Label Elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor
H370 - Causes damage to organs
H319 - Causes serious eye irritation
H361 - Suspected of damaging fertility or the unborn child
H301 + H311 + H331 - Toxic if swallowed, in contact with skin or if inhaled

Precautionary Statements

Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P233 - Keep container tightly closed
P270 - Do not eat, drink or smoke when using this product
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P240 - Ground and bond container and receiving equipment
P242 - Use non-sparking tools
P243 - Take action to prevent static discharges
P264 - Wash face, hands and any exposed skin thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area

Response

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish
P311 - Call a POISON CENTER or doctor
P330 - Rinse mouth
P362 + P364 - Take off contaminated clothing and wash it before reuse

Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed
P405 - Store locked up

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Other hazards which do not result in classification

Toxic to terrestrial vertebrates

Section 3 - Composition and Information on Ingredients

Component	CAS No	Weight %
Methyl alcohol	67-56-1	> 99
Potassium hydroxide	1310-58-3	< 1

Section 4 - First Aid Measures

Description of first aid measures

General Advice

Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

New Zealand Emergency Tel.	CHEMTREC® 09 980 6780 or +64 9 980 6780
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.
Ingestion	Do NOT induce vomiting. Call a physician or poison control center immediately.
Self-Protection of the First Aider	Use personal protective equipment as required.
First Aid Facilities	Eyewash, safety shower and washroom.
Most important symptoms and effects	Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
Notes to Physician	Treat symptomatically. Symptoms may be delayed.

Section 5 - Fire Fighting Measures

Suitable Extinguishing Media

Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

No information available.

Specific Hazards Arising from the Chemical

Flammable. Thermal decomposition can lead to release of irritating gases and vapors. Vapors may form explosive mixtures with air. Flammable/toxic gases may accumulate in confined areas (basements, tanks, hopper/tank cars etc.). Vapors may travel to source of ignition and flash back. Vapors from liquefied gas are initially heavier than air and spread along ground. Will be easily ignited by heat, sparks or flames. Containers may explode when heated. Vapors may form explosive mixtures with air.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂), Formaldehyde, Thermal decomposition can lead to release of irritating gases and vapors.

Special protective equipment and precautions for fire fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

Section 6 - Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures

Emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions

Should not be released into the environment.

Methods for Containment and Clean Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use

spark-proof tools and explosion-proof equipment.

Precautions to prevent secondary hazards

Clean contaminated objects and areas thoroughly observing environmental regulations

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

Section 7 - Handling and Storage

Precautions for Safe Handling

Advice on safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

Conditions for Safe Storage, Including any Incompatibilities

Storage Conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat, sparks and flame.

Incompatible Materials

Acids. Acid anhydrides. Acid chlorides. halocarbons. Isocyanates. Oxidizing agent.

AS/NZS 2243.10:2004, Safety in laboratories - Storage of chemicals

AS 1940-2004 - The storage and handling of flammable and combustible liquids

Section 8 - Exposure Controls and Personal Protection

Control parameters

Exposure limits

NZ - Workplace Exposure Standards and Biological Exposure Indices (6th edition). New Zealand Department of Labor

UK - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020.

ACGIH - Threshold Limit Values - Ceiling (TLV-C) guidelines by the American Conference of Governmental Industrial Hygienists (ACGIH) for controlling worker exposure to airborne chemical concentrations in the workplace.

AUS - Exposure Standards for Atmospheric Contaminants in the Occupational Environment - Guidance Note on the Interpretation of Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:3008(1995)]

Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)] updated in August, 2005. Safe Work Australia

Component	New Zealand WEL	Australia	ACGIH TLV	The United Kingdom
Methyl alcohol	TWA: 200 ppm TWA: 262 mg/m ³ STEL: 250 ppm STEL: 328 mg/m ³ Skin	STEL: 250 ppm STEL: 328 mg/m ³ TWA: 200 ppm TWA: 262 mg/m ³	TWA: 200 ppm STEL: 250 ppm Skin	WEL - TWA: 200 ppm TWA; 266 mg/m ³ TWA WEL - STEL: 250 ppm STEL; 333 mg/m ³ STEL
Potassium hydroxide	Ceiling: 2 mg/m ³	Ceiling: 2 mg/m ³	Ceiling: 2 mg/m ³	WEL - 2 mg/m ³ STEL

Biological limit values

NZ - Substances assigned Biological Exposure Indices in the New Zealand Workplace Exposure Standards and Biological Exposure Indices (6th edition). New Zealand Department of Labor

ACGIH - American Conference of Governmental Industrial Hygienists (ACGIH) TLVs® and BEIs®- Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices. 2022 Edition

Component	New Zealand	Australia	ACGIH - Biological Exposure Indices	United Kingdom
-----------	-------------	-----------	-------------------------------------	----------------

Methyl alcohol	15 mg/L (urine) end of shift (Methyl alcohol)		15 mg/L Medium: urine Time: end of shift Determinant: Methanol	
----------------	--	--	---	--

Appropriate engineering controls

Engineering Measures

Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Individual protection measures, such as personal protective equipment

Eye Protection Goggles Tight sealing safety goggles (Australian/New Zealand Standard AS/NZS 1337 - Eye protectors for Industrial applications)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	AUS/NZ Standard	Glove comments
Viton (R), Butyl rubber.	> 480 minutes	0.35 mm	AS/NZS 2161	As tested under EN374-3 Determination of Resistance to Permeation by Chemicals
	> 480 minutes	0.70 mm		
Neoprene gloves	< 60 minutes	0.45 mm		
Nitrile rubber	< 30 minutes	0.38 mm		

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Skin and body protection Long sleeved clothing

Respiratory Protection Use an AS/NZS 1716 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained in line with AS/NZS 1715 on the use and maintenance of respiratory protective devices

Recommended Filter type: low boiling organic solvent Type AX Brown conforming to EN371 (or AUS/NZ equivalent)
Recommended half mask:- Valve filtering: EN405 or Half mask: EN140 plus filter, EN 141 (or AUS/NZ equivalent)
When RPE is used a face piece Fit Test should be conducted

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

Environmental exposure controls No information available.

Section 9 - Physical and Chemical Properties

Information on basic physical and chemical properties

Physical State	Liquid	
Appearance	Clear, Colorless	
Odor	Alcohol-like	
Odor Threshold	No data available	
pH	> 13	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	64.7 °C / 148.5 °F	
Flammability (liquid)	Highly flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid

Explosion Limits	No data available	
Flash Point	12 °C / 53.6 °F	Method - No information available
Autoignition Temperature	455 °C / 851 °F	
Decomposition Temperature	No data available	
Viscosity	No data available	
Water Solubility	Miscible	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Methyl alcohol	-0.74	
Potassium hydroxide	0.83	
Vapor Pressure	No data available	
Density / Specific Gravity	0.8	
Bulk Density	Not applicable	Liquid
Vapor Density	No data available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	
<u>Other information</u>		
Explosive Properties	Vapors may form explosive mixtures with air	

Section 10 - Stability and Reactivity

Reactivity	None known, based on information available
Stability	Stable under normal conditions.
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.
Conditions to Avoid	Incompatible products, Excess heat, Keep away from open flames, hot surfaces and sources of ignition.
Incompatible Materials	Acids, Acid anhydrides, Acid chlorides, halocarbons, Isocyanates, Oxidizing agent.
Hazardous Decomposition Products	Carbon monoxide (CO). Carbon dioxide (CO ₂). Formaldehyde. Thermal decomposition can lead to release of irritating gases and vapors.

Section 11 - Toxicological Information

Acute Effects

Information on likely routes of exposure

Product Information

Inhalation	Toxic by inhalation. May cause irritation of respiratory tract.
Eyes	May cause irritation. Irritating to eyes. Contact with eyes may cause irritation.
Skin	Toxic in contact with skin. May cause irritation. Irritating to skin. May cause eye/skin irritation.
Ingestion	Toxic if swallowed. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Ingestion may cause irritation to mucous membranes.

Numerical measures of toxicity

(a) acute toxicity;	
Oral	Category 3
Dermal	Category 3
Inhalation	Category 3

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methyl alcohol	LD50 = 1187 – 2769 mg/kg (Rat)	LD50 = 17100 mg/kg (Rabbit)	LC50 = 128.2 mg/L (Rat) 4 h
Potassium hydroxide	LD50 = 333-384 mg/kg (Rat)		

(b) skin corrosion/irritation; Based on available data, the classification criteria are not met

(c) serious eye damage/irritation; Based on available data, the classification criteria are not met

(d) respiratory or skin sensitization;
 Respiratory Based on available data, the classification criteria are not met
 Skin Based on available data, the classification criteria are not met

Component	Test method	Test species	Study result
Methyl alcohol 67-56-1 (> 99)	OECD Test Guideline 406 Guinea Pig Maximisation Test (GPMT)	guinea pig	non-sensitising

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

(f) carcinogenicity; Based on available data, the classification criteria are not met
There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; Based on available data, the classification criteria are not met

Component	Test method	Test species / Duration	Study result
Methyl alcohol 67-56-1 (> 99)	OECD Test Guideline 416	Rat / Inhalation 2 Generation	NOAEC = 1.3 mg/l (air)

(h) STOT-single exposure; Category 1
Results / Target organs Optic nerve
Central nervous system (CNS)

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met
Target Organs None known.

(j) aspiration hazard; Based on available data, the classification criteria are not met

Symptoms / effects, both acute and delayed
Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Section 12 - Ecological Information

Ecotoxicity

Aquatic ecotoxicity .

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Methyl alcohol	Pimephales promelas: LC50 > 10000 mg/L 96h	EC50 > 10000 mg/L 24h		EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min

Terrestrial ecotoxicity

Component	Earthworm	Avian	Honeybees
Methyl alcohol	Acute toxicity: LC50 > 1 mg/cm2 (Eisenia foetida, 48 h, filter paper)		

Persistence and Degradability

Persistence Persistence is unlikely, based on information available.

Component	Degradability
Methyl alcohol 67-56-1 (> 99)	DT50 ~ 17.2d >94% after 20d

Bioaccumulative Potential Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Methyl alcohol	-0.74	<10 dimensionless
Potassium hydroxide	0.83	No data available

Mobility The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in air

Other adverse effects

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors
Persistent Organic Pollutant This product does not contain any known or suspected substance
Ozone Depletion Potential This product does not contain any known or suspected substance

Section 13 - Disposal Considerations

Waste treatment methods

Waste from Residues/Unused Products Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with all federal, E.P.A., state and local regulations. Assure conformity with all applicable regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

Other Information Disposal agencies or waste contractors must comply with the New Zealand Hazardous Substances (Disposal) Regulations . Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with local regulations. Solutions with high pH-value must be neutralized before discharge.

Section 14 - Transport Information

Component	Hazchem Code
Methyl alcohol 67-56-1 (> 99)	2WE
Potassium hydroxide 1310-58-3 (< 1)	2W 2R

NZS 5433:2020

UN-No UN1230
Proper Shipping Name METHANOL
Hazard Class 3
Subsidiary Hazard Class 6.1
Packing Group II

IATA

UN-No UN1230
Proper Shipping Name METHANOL
Hazard Class 3
Subsidiary Hazard Class 6.1
Packing Group II

IMDG/IMO

UN-No UN1230
Proper Shipping Name METHANOL
Hazard Class 3
Subsidiary Hazard Class 6.1
Packing Group II

Environmental hazards No hazards identified

Transport in bulk according to
Annex II of MARPOL 73/78 and the
IBC Code Not applicable, packaged goods

Special Precautions No special precautions required. Please refer to the applicable dangerous goods regulations for additional information.

Additional information None known

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National Regulations

There are no applicable tolerable exposure limits or environmental exposure limits according to the EPA Controls for Hazardous Substances

Certified handlers, tracking and controlled substance license requirements

Certified handlers are required for some substances. This includes substances requiring a controlled substance license, and most explosives, vertebrates toxic agents, and certain fumigants. Acutely toxic substances which are a Category 1 or 2, such as pesticides also require Certified handlers. Please check the Health and Safety at Work Act 2015 for further information. Tracking is required for some highly hazardous substances. These substances need to be under the control of an appropriately trained person or appropriately secured. Please check the Health and Safety at Work Act 2015 for further information.

Prohibition or notification/licensing requirements

Shown below are details of specific prohibition/notifications or licencing requirements when they apply.

International Regulations

Ozone Depletion Potential This product does not contain any known or suspected substance

Persistent Organic Pollutant This product does not contain any known or suspected substance

Rotterdam Convention (PIC) Not applicable

Component	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	IMDG Marine Pollutant
Methyl alcohol	500 tonne	5000 tonne	

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Methyl alcohol	-	Use restricted. See item 69. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-
Potassium hydroxide	-	Use restricted. See item 75. (see link for restriction details)	-

<https://echa.europa.eu/substances-restricted-under-reach>

International Inventories

New Zealand (NZIoC), Australia (AICS), Europe (EINECS/ELINCS/NLP), Korea (KECL), China (IECSC), Taiwan (TCSI), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	NZIoC	AICS	EINECS	ELINCS	NLP	KECL	IECSC	TCSI
Methyl alcohol	67-56-1	X	X	-	-	-	KE-23193	X	X
Potassium hydroxide	1310-58-3	X	X	215-181-3	-	-	KE-29139	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	PICCS	ISHL	ENCS
Methyl alcohol	67-56-1	X	ACTIVE	X	-	X	X	X
Potassium hydroxide	1310-58-3	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Section 16 - Other Information

This safety data sheet complies with the requirements of the EPA Hazardous Substances (Hazard Classification) Notice 2020 and WorkSafe New Zealand Regulations

Legend

NZIoC - New Zealand Inventory of Chemicals

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

IECSC - Chinese Inventory of Existing Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japanese Existing and New Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

CAS - Chemical Abstracts Service

TWA - Time Weighted Average IARC - International Agency for Research on Cancer NZS 5433:2020 - Transport of Dangerous Goods on Land ICAO/IATA - International Civil Aviation Organization/International Air Transport Association MARPOL - International Convention for the Prevention of Pollution from Ships LD50 - Lethal Dose 50% EC50 - Effective Concentration 50% WEL - Workplace Exposure Limit DNEL - Derived No Effect Level POW - Partition coefficient Octanol:Water vPvB - very Persistent, very Bioaccumulative VOC - (Volatile Organic Compound)	ACGIH - American Conference of Governmental Industrial Hygienists PNEC - Predicted No Effect Concentration OECD - Organisation for Economic Co-operation and Development IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code ADG - Australian Code for the Transport of Dangerous Goods by Road and Rail LC50 - Lethal Concentration 50% ATE - Acute Toxicity Estimate RPE - Respiratory Protective Equipment NOEC - No Observed Effect Concentration BCF - Bioconcentration factor PBT - Persistent, Bioaccumulative, Toxic
--	--

Key literature references and sources for data

HSNO classifications provided in the New Zealand Chemical Classification Information Database (CCID).

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

EPA Guide to classifying hazardous substances in New Zealand

EPA - Assigning a product to an existing HSNO approval guide

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health Hazards	Calculation method
Environmental hazards	Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Revision Date	20-Mar-2023
Revision Summary	Not applicable

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet