

SAFETY DATA SHEET

Creation Date 11-June-2009

Revision Date 25-December-2021

Revision Number 6

1. Identification

Product Name Xylenes

Cat No. : AC390790000; AC390790010; AC390790025; AC390790100

CAS-No 1330-20-7
Synonyms Dimethylbenzene

Recommended Use Laboratory chemicals.
Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Importer/Distributor

Fisher Scientific
112 Colonnade Road,
Ottawa, ON K2E 7L6,
Canada
Tel: 1-800-234-7437

Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410

Manufacturer

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Emergency Telephone Number For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

WHMIS 2015 Classification Classified as hazardous under the Hazardous Products Regulations (SOR/2015-17)

Flammable liquids	Category 3
Acute dermal toxicity	Category 4
Acute Inhalation Toxicity	Category 4
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Target Organs - Respiratory system, Central nervous system (CNS).	
Specific target organ toxicity - (repeated exposure)	Category 2
Target Organs - Heart, Liver, Kidney, Ears.	
Aspiration Toxicity	Category 1

Label Elements

Signal Word

Danger

Hazard Statements

Flammable liquid and vapor
Harmful in contact with skin or if inhaled
May be fatal if swallowed and enters airways
Causes skin irritation
Causes serious eye irritation
May cause respiratory irritation
Suspected of causing cancer
May cause damage to organs through prolonged or repeated exposure

**Precautionary Statements****Prevention**

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ventilating/lighting/equipment
Use only non-sparking tools
Take precautionary measures against static discharges
Use only outdoors or in a well-ventilated area
Do not breathe dust/fumes/gas/mist/vapours/spray
Wash face, hands and any exposed skin thoroughly after handling
Wear protective gloves/protective clothing/eye protection/face protection

Response

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
IF exposed or concerned: Get medical advice/attention
Call a POISON CENTER/ doctor if you feel unwell
IF SWALLOWED: Immediately call a POISON CENTER/doctor
IF INHALED: Remove person to fresh air and keep comfortable for breathing
Do NOT induce vomiting
Wash contaminated clothing before reuse
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Other Hazards

Harmful to aquatic life with long lasting effects

3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Xylenes (o-, m-, p- isomers)	1330-20-7	>75

Ethylbenzene	100-41-4	<25
--------------	----------	-----

4. First-aid measures

Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Get medical attention.
Inhalation	Remove to fresh air. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention. Risk of serious damage to the lungs (by aspiration). If not breathing, give artificial respiration.
Ingestion	Aspiration hazard. Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
Most important symptoms/effects	Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media	Water spray, carbon dioxide (CO ₂), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.
Unsuitable Extinguishing Media	No information available
Flash Point	23 - 30 °C / 73.4 - 86 °F
Method -	No information available
Autoignition Temperature	460 °C / 860 °F
Explosion Limits	
Upper	No data available
Lower	No data available
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO₂). Hydrocarbons. Aldehydes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health
3

Flammability
2

Instability
0

Physical hazards
N/A

6. Accidental release measures

Personal Precautions	Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges. Avoid contact with skin, eyes or clothing.
-----------------------------	--

Environmental Precautions Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Do not flush into surface water or sanitary sewer system. See Section 12 for additional Ecological Information. Avoid release to the environment. Collect spillage.

Methods for Containment and Clean Up Remove all sources of ignition. Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. Soak up with inert absorbent material. Keep in suitable, closed containers for disposal.

7. Handling and storage

Handling Wear personal protective equipment/face protection. Ensure adequate ventilation. Use spark-proof tools and explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not get in eyes, on skin, or on clothing. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Use only non-sparking tools.

Storage. Keep container tightly closed in a dry and well-ventilated place. Keep away from heat, sparks and flame. Flammables area. Incompatible Materials. Strong oxidizing agents. Strong acids.

8. Exposure controls / personal protection

Exposure Guidelines

Component	Alberta	British Columbia	Ontario TWA/EV	Quebec	ACGIH TLV	OSHA PEL	NIOSH IDLH
Xylenes (o-, m-, p-isomers)	TWA: 100 ppm TWA: 434 mg/m ³ STEL: 150 ppm STEL: 651 mg/m ³	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 434 mg/m ³ STEL: 150 ppm STEL: 651 mg/m ³	TWA: 100 ppm STEL: 150 ppm	(Vacated) TWA: 100 ppm (Vacated) TWA: 435 mg/m ³ (Vacated) STEL: 150 ppm (Vacated) STEL: 655 mg/m ³ TWA: 100 ppm TWA: 435 mg/m ³	
Ethylbenzene	TWA: 100 ppm TWA: 434 mg/m ³ STEL: 125 ppm STEL: 543 mg/m ³	TWA: 20 ppm	TWA: 20 ppm	TWA: 20 ppm	TWA: 20 ppm	(Vacated) TWA: 100 ppm (Vacated) TWA: 435 mg/m ³ (Vacated) STEL: 125 ppm (Vacated) STEL: 545 mg/m ³ TWA: 100 ppm TWA: 435 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection
Hand ProtectionGoggles
Wear appropriate protective gloves and clothing to prevent skin exposure.

Glove material	Breakthrough time	Glove thickness	Glove comments
Viton (R)	See manufacturers recommendations	-	Splash protection only

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to EN14387

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

Prevent product from entering drains. Do not allow material to contaminate ground water system.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State	Liquid
Appearance	Colorless
Odor	aromatic
Odor Threshold	No information available
pH	No information available
Melting Point/Range	-34 °C / -29.2 °F
Boiling Point/Range	136 - 140 °C / 276.8 - 284 °F @ 760 mmHg
Flash Point	23 - 30 °C / 73.4 - 86 °F
Evaporation Rate	No information available
Flammability (solid,gas)	Not applicable
Flammability or explosive limits	
Upper	No data available
Lower	No data available
Vapor Pressure	8 mbar @ 20 °C
Vapor Density	No information available
Specific Gravity	0.865
Solubility	practically insoluble
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	460 °C / 860 °F
Decomposition Temperature	No information available
Viscosity	0.6 mPa s @ 20 °C
Molecular Formula	C8 H10
Molecular Weight	106.17

10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Stable under normal conditions.
Conditions to Avoid	Incompatible products. Excess heat. Keep away from open flames, hot surfaces and

sources of ignition.

Incompatible Materials Strong oxidizing agents, Strong acids**Hazardous Decomposition Products** Carbon monoxide (CO), Carbon dioxide (CO₂), Hydrocarbons, Aldehydes**Hazardous Polymerization** Hazardous polymerization does not occur.**Hazardous Reactions** None under normal processing.

11. Toxicological information

Acute Toxicity**Product Information****Oral LD50** Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.**Dermal LD50** Category 4. ATE = 1000 - 2000 mg/kg.**Vapor LC50** Category 4. ATE = 10 - 20 mg/l.**Component Information**

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Xylenes (o-, m-, p- isomers)	LD50 = 3500 mg/kg (Rat)	LD50 > 4350 mg/kg (Rabbit)	29.08 mg/L [MOE Risk Assessment Vol.1, 2002]
Ethylbenzene	3500 mg/kg (Rat)	15400 mg/kg (Rabbit)	17.2 mg/L (Rat) 4 h

Toxicologically Synergistic Products No information available**Delayed and immediate effects as well as chronic effects from short and long-term exposure****Irritation** Irritating to eyes, respiratory system and skin**Sensitization** No information available**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Xylenes (o-, m-, p- isomers)	1330-20-7	Not listed	Not listed	Not listed	Not listed	Not listed
Ethylbenzene	100-41-4	Group 2B	Not listed	A3	X	A3

*IARC (International Agency for Research on Cancer)**IARC (International Agency for Research on Cancer)**Group 1 - Carcinogenic to Humans**Group 2A - Probably Carcinogenic to Humans**Group 2B - Possibly Carcinogenic to Humans**A1 - Known Human Carcinogen**A2 - Suspected Human Carcinogen**A3 - Animal Carcinogen**ACGIH: (American Conference of Governmental Industrial Hygienists)**ACGIH: (American Conference of Governmental Industrial Hygienists)***Mutagenic Effects** No information available**Reproductive Effects** No information available.**Developmental Effects** No information available.**Teratogenicity** No information available.**STOT - single exposure** Respiratory system Central nervous system (CNS)**STOT - repeated exposure** Heart Liver Kidney Ears**Aspiration hazard** Aspiration hazard Category 1**Symptoms / effects, both acute and delayed** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting**Endocrine Disruptor Information** No information available

Other Adverse Effects

The toxicological properties have not been fully investigated.

12. Ecological information**Ecotoxicity**

Contains a substance which is: Toxic to aquatic organisms. The product contains following substances which are hazardous for the environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Xylenes (o-, m-, p- isomers)	Not listed	LC50: 30.26 - 40.75 mg/L, 96h static (Poecilia reticulata) LC50: = 780 mg/L, 96h semi-static (Cyprinus carpio) LC50: 23.53 - 29.97 mg/L, 96h static (Pimephales promelas) LC50: > 780 mg/L, 96h (Cyprinus carpio) LC50: 7.711 - 9.591 mg/L, 96h static (Lepomis macrochirus) LC50: = 19 mg/L, 96h (Lepomis macrochirus) LC50: 13.1 - 16.5 mg/L, 96h flow-through (Lepomis macrochirus) LC50: 13.5 - 17.3 mg/L, 96h (Oncorhynchus mykiss) LC50: 2.661 - 4.093 mg/L, 96h static (Oncorhynchus mykiss) LC50: = 13.4 mg/L, 96h flow-through (Pimephales promelas)	EC50 = 0.0084 mg/L 24 h	LC50: = 0.6 mg/L, 48h (Gammarus lacustris) EC50: = 3.82 mg/L, 48h (water flea)
Ethylbenzene	EC50: 2.6 - 11.3 mg/L, 72h static (Pseudokirchneriella subcapitata) EC50: 1.7 - 7.6 mg/L, 96h static (Pseudokirchneriella subcapitata) EC50: > 438 mg/L, 96h (Pseudokirchneriella subcapitata) EC50: = 4.6 mg/L, 72h (Pseudokirchneriella subcapitata)	LC50: 7.55 - 11 mg/L, 96h flow-through (Pimephales promelas) LC50: 11.0 - 18.0 mg/L, 96h static (Oncorhynchus mykiss) LC50: = 4.2 mg/L, 96h semi-static (Oncorhynchus mykiss) LC50: = 32 mg/L, 96h static (Lepomis macrochirus) LC50: 9.1 - 15.6 mg/L, 96h static (Pimephales promelas) LC50: = 9.6 mg/L, 96h static (Poecilia reticulata)	EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	EC50: 1.8 - 2.4 mg/L, 48h (Daphnia magna)

Persistence and Degradability

Persistence is unlikely

Bioaccumulation/ Accumulation

No information available.

Mobility

. Is not likely mobile in the environment due its low water solubility. Will likely be mobile in the environment due to its volatility.

Component	log Pow
Xylenes (o-, m-, p- isomers)	3.15
Ethylbenzene	3.2

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Xylenes (o-, m-, p- isomers) - 1330-20-7	U239	-

14. Transport information

DOT

UN-No UN1307
 Proper Shipping Name XYLENES
 Hazard Class 3
 Packing Group III

TDG

UN-No UN1307
 Proper Shipping Name XYLENES
 Hazard Class 3
 Packing Group III

IATA

UN-No UN1307
 Proper Shipping Name XYLENES
 Hazard Class 3
 Packing Group III

IMDG/IMO

UN-No UN1307
 Proper Shipping Name XYLENES
 Hazard Class 3
 Packing Group III

15. Regulatory information

International Inventories

Component	CAS-No	DSL	NDSL	TSCA	TSCA Inventory notification - Active-Inactive	EINECS	ELINCS	NLP
Xylenes (o-, m-, p- isomers)	1330-20-7	X	-	X	ACTIVE	215-535-7	-	-
Ethylbenzene	100-41-4	X	-	X	ACTIVE	202-849-4	-	-

Component	CAS-No	IECSC	KECL	ENCS	ISHL	TCSI	AICS	NZIoC	PICCS
Xylenes (o-, m-, p- isomers)	1330-20-7	X	KE-35427	X	X	X	X	X	X
Ethylbenzene	100-41-4	X	KE-13532	X	X	X	X	X	X

Legend:

X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

Canada

SDS in compliance with provisions of information as set out in Canadian Standard - Part 4, Schedule 1 and 2 of the Hazardous Products Regulations (HPR) and meets the requirements of the HPR (Paragraph 13(1)(a) of the Hazardous Products Act (HPA)).

Component	Canada - National Pollutant Release Inventory (NPRI)	Canadian Environmental Protection Agency (CEPA)	Canada's Chemicals Management Plan (CEPA)
-----------	--	---	---

		- List of Toxic Substances	
Xylenes (o-, m-, p- isomers)	Part 1, Group A Substance Part 5, Isomer Groups Part 4 Substance		
Ethylbenzene	Part 1, Group A Substance Part 4 Substance		

Legend

NPRI - National Pollutant Release Inventory

Other International Regulations**Authorisation/Restrictions according to EU REACH**

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Xylenes (o-, m-, p- isomers)	-	Use restricted. See item 75. (see link for restriction details)	-

<https://echa.europa.eu/substances-restricted-under-reach>

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS-No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Xylenes (o-, m-, p- isomers)	1330-20-7	Listed	Not applicable	Not applicable	Not applicable
Ethylbenzene	100-41-4	Listed	Not applicable	Not applicable	Not applicable

Component	CAS-No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Xylenes (o-, m-, p- isomers)	1330-20-7	Not applicable	Not applicable	Not applicable	Annex I - Y42
Ethylbenzene	100-41-4	Not applicable	Not applicable	Not applicable	Not applicable

16. Other information

Prepared By

Regulatory Affairs
Thermo Fisher Scientific
Email: EMSDS.RA@thermofisher.com

Creation Date

11-June-2009

Revision Date

25-December-2021

Print Date

25-December-2021

Revision Summary

This document has been updated to comply with the requirements of WHMIS 2015 to align with the Globally Harmonised System (GHS) for the Classification and Labelling of Chemicals.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS