

Creation Date 31-May-2018

Revision Date 04-Oct-2023

Revision Number 11

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description:	<u>Xylenes, mixture of isomers</u>
Cat No. :	383930000; 383930010; 383930050; 383930250
CAS No	1330-20-7
EC No	215-535-7
Molecular Formula	C8 H10
REACH registration number	01-2119488216-32

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use	Laboratory chemicals.
Sector of use	SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites
Product category	PC21 - Laboratory chemicals
Process categories	PROC15 - Use as a laboratory reagent
Environmental release category	ERC6a - Industrial use resulting in manufacture of another substance (use of intermediates)
Uses advised against	No Information available

1.3. Details of the supplier of the safety data sheet

Company

EU entity/business name
Thermo Fisher Scientific
Janssen Pharmaceuticaaan 3a, 2440 Geel, Belgium

UK entity/business name
Fisher Scientific UK
Bishop Meadow Road,
Loughborough, Leicestershire LE11 5RG, United Kingdom

Swiss distributor - Fisher Scientific AG
Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
e-mail - infoch@thermofisher.com

E-mail address

begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

SAFETY DATA SHEET

Xylenes, mixture of isomers

Revision Date 04-Oct-2023

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Flammable liquids

Category 3 (H226)

Health hazards

Aspiration Toxicity

Category 1 (H304)

Acute dermal toxicity

Category 4 (H312)

Acute Inhalation Toxicity - Vapors

Category 4 (H332)

Skin Corrosion/Irritation

Category 2 (H315)

Serious Eye Damage/Eye Irritation

Category 2 (H319)

Specific target organ toxicity - (single exposure)

Category 3 (H335)

Specific target organ toxicity - (repeated exposure)

Category 2 (H373)

Environmental hazards

Chronic aquatic toxicity

Category 3 (H412)

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H226 - Flammable liquid and vapor

H304 - May be fatal if swallowed and enters airways

H312 + H332 - Harmful in contact with skin or if inhaled

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H335 - May cause respiratory irritation

H373 - May cause damage to organs through prolonged or repeated exposure

H412 - Harmful to aquatic life with long lasting effects

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301 + P330 + P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

SAFETY DATA SHEET

Xylenes, mixture of isomers

Revision Date 04-Oct-2023

P310 - Immediately call a POISON CENTER or doctor/physician

2.3. Other hazards

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Xylenes (o-, m-, p- isomers)	1330-20-7	EEC No. 215-535-7	>95	Flam. Liq. 3 (H226) Asp. Tox. 1 (H304) Acute Tox. 4 (H312) Acute Tox. 4 (H332) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) STOT SE 3 (H335) STOT RE 2 (H373) Aquatic Chronic 3 (H412)

REACH registration number	01-2119488216-32
---------------------------	------------------

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice	If symptoms persist, call a physician.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur. Risk of serious damage to the lungs (by aspiration).
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

SAFETY DATA SHEET

Xylenes, mixture of isomers

Revision Date 04-Oct-2023

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Water spray. Alcohol resistant foam. Dry chemical. Carbon dioxide (CO₂). Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

None under normal use conditions.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges.

SAFETY DATA SHEET

Xylenes, mixture of isomers

Revision Date 04-Oct-2023

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and flame. Flammables area. Keep container tightly closed in a dry and well-ventilated place.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Class 3

Switzerland - Storage of hazardous substances

Storage class - SC 3
<https://www.kvu.ch/de/themen/stoffe-und-produkte>
<https://www.kvu.ch/fr/themes/substances-et-produits>
<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Xylenes (o-, m-, p-isomers)	TWA: 50 ppm (8h) TWA: 221 mg/m ³ (8h) STEL: 100 ppm (15min) STEL: 442 mg/m ³ (15min) Skin	STEL: 100 ppm 15 min STEL: 441 mg/m ³ 15 min TWA: 50 ppm 8 hr TWA: 220 mg/m ³ 8 hr Skin	TWA / VME: 50 ppm (8 heures). restrictive limit TWA / VME: 221 mg/m ³ (8 heures). restrictive limit TWA / VME: 1000 mg/m ³ (8 heures). STEL / VLCT: 100 ppm. restrictive limit STEL / VLCT: 442 mg/m ³ . restrictive limit STEL / VLCT: 1500 mg/m ³ . Peau	TWA: 50 ppm 8 uren TWA: 221 mg/m ³ 8 uren STEL: 100 ppm 15 minuten STEL: 442 mg/m ³ 15 minuten Huid	STEL / VLA-EC: 100 ppm (15 minutos). STEL / VLA-EC: 442 mg/m ³ (15 minutos). TWA / VLA-ED: 50 ppm (8 horas) TWA / VLA-ED: 221 mg/m ³ (8 horas) Piel

Component	Italy	Germany	Portugal	The Netherlands	Finland
Xylenes (o-, m-, p-isomers)	TWA: 50 ppm 8 ore. Time Weighted Average pure TWA: 221 mg/m ³ 8 ore. Time Weighted Average pure STEL: 100 ppm 15 minuti. Short-term pure STEL: 442 mg/m ³ 15 minuti. Short-term pure Pelle	TWA: 50 ppm (8 Stunden). AGW - exposure factor 2 TWA: 220 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 50 ppm (8 Stunden). MAK all isomers TWA: 220 mg/m ³ (8 Stunden). MAK all isomers Höhepunkt: 100 ppm Höhepunkt: 440 mg/m ³	STEL: 100 ppm 15 minutos STEL: 442 mg/m ³ 15 minutos TWA: 50 ppm 8 horas TWA: 221 mg/m ³ 8 horas Pele	huid STEL: 442 mg/m ³ 15 minuten TWA: 210 mg/m ³ 8 uren	TWA: 50 ppm 8 tunteina TWA: 220 mg/m ³ 8 tunteina STEL: 100 ppm 15 minuutteina STEL: 440 mg/m ³ 15 minuutteina Iho

SAFETY DATA SHEET

Xylenes, mixture of isomers

Revision Date 04-Oct-2023

		Haut Haut all isomers			
--	--	--------------------------	--	--	--

Component	Austria	Denmark	Switzerland	Poland	Norway
Xylenes (o-, m-, p-isomers)	MAK-KZGW: 100 ppm 15 Minuten MAK-KZGW: 442 mg/m ³ 15 Minuten MAK-TMW: 50 ppm 8 Stunden MAK-TMW: 221 mg/m ³ 8 Stunden	TWA: 25 ppm 8 timer TWA: 109 mg/m ³ 8 timer STEL: 442 mg/m ³ 15 minutter STEL: 100 ppm 15 minutter Hud	Haut/Peau STEL: 100 ppm 15 Minuten STEL: 440 mg/m ³ 15 Minuten TWA: 50 ppm 8 Stunden TWA: 220 mg/m ³ 8 Stunden	STEL: 200 mg/m ³ 15 minutach TWA: 100 mg/m ³ 8 godzinach	TWA: 25 ppm 8 timer TWA: 108 mg/m ³ 8 timer STEL: 37.5 ppm 15 minutter. value calculated STEL: 135 mg/m ³ 15 minutter. value calculated Hud

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Xylenes (o-, m-, p-isomers)	TWA: 50 ppm TWA: 221.0 mg/m ³ STEL : 100 ppm STEL : 442 mg/m ³ Skin notation	kože TWA-GVI: 50 ppm 8 satima. TWA-GVI: 221 mg/m ³ 8 satima. STEL-KGVI: 100 ppm 15 minutama. STEL-KGVI: 442 mg/m ³ 15 minutama.	TWA: 50 ppm 8 hr. TWA: 221 mg/m ³ 8 hr. STEL: 100 ppm 15 min STEL: 442 mg/m ³ 15 min Skin	Skin-potential for cutaneous absorption STEL: 100 ppm STEL: 442 mg/m ³ TWA: 50 ppm TWA: 221 mg/m ³	TWA: 200 mg/m ³ 8 hodinách. Potential for cutaneous absorption Ceiling: 400 mg/m ³

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Xylenes (o-, m-, p-isomers)	Nahk TWA: 50 ppm 8 tundides. TWA: 200 mg/m ³ 8 tundides. STEL: 100 ppm 15 minutites. STEL: 450 mg/m ³ 15 minutites.	Skin notation TWA: 50 ppm 8 hr pure TWA: 221 mg/m ³ 8 hr pure STEL: 100 ppm 15 min pure STEL: 442 mg/m ³ 15 min pure	skin - potential for cutaneous absorption STEL: 150 ppm STEL: 650 mg/m ³ TWA: 100 ppm TWA: 435 mg/m ³	STEL: 442 mg/m ³ 15 percekben. CK TWA: 221 mg/m ³ 8 óraban. AK lehetséges borón keresztüli felszívódás	STEL: 100 ppm STEL: 442 mg/m ³ TWA: 25 ppm 8 klukkustundum. TWA: 109 mg/m ³ 8 klukkustundum. Skin notation

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Xylenes (o-, m-, p-isomers)	skin - potential for cutaneous exposure STEL: 100 ppm STEL: 442 mg/m ³ TWA: 50 ppm TWA: 221 mg/m ³	TWA: 221 mg/m ³ IPRD mixed isomers, pure TWA: 50 ppm IPRD mixed isomers, pure Oda STEL: 442 mg/m ³ STEL: 100 ppm	Possibility of significant uptake through the skin TWA: 50 ppm 8 Stunden TWA: 221 mg/m ³ 8 Stunden STEL: 100 ppm 15 Minuten STEL: 442 mg/m ³ 15 Minuten	possibility of significant uptake through the skin TWA: 50 ppm TWA: 221 mg/m ³ STEL: 100 ppm 15 minuti STEL: 442 mg/m ³ 15 minuti	Skin notation TWA: 50 ppm 8 ore TWA: 221 mg/m ³ 8 ore STEL: 100 ppm 15 minute STEL: 442 mg/m ³ 15 minute

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Xylenes (o-, m-, p-isomers)	TWA: 50 mg/m ³ 0741 mixture of 2-, 3-, 4- isomers MAC: 150 mg/m ³	Ceiling: 442 mg/m ³ Potential for cutaneous absorption TWA: 50 ppm TWA: 221 mg/m ³	TWA: 50 ppm 8 urah TWA: 221 mg/m ³ 8 urah Koža STEL: 100 ppm 15 minutah STEL: 442 mg/m ³ 15 minutah	Binding STEL: 100 ppm 15 minuter Binding STEL: 442 mg/m ³ 15 minuter TLV: 50 ppm 8 timmar. NGV TLV: 221 mg/m ³ 8 timmar. NGV Hud	Deri TWA: 50 ppm 8 saat TWA: 221 mg/m ³ 8 saat STEL: 100 ppm 15 dakika STEL: 442 mg/m ³ 15 dakika

Biological limit values

List source(s): **UK** - Biological Monitoring Guidance Values provided by the UK's Health and Safety Executive (HSE) Control of Substances Hazardous to Health Regulations (COSHH) 2002 (as amended) and EH40/2005.

Component	European Union	United Kingdom	France	Spain	Germany
Xylenes (o-, m-, p-isomers)		Methyl hippuric acid: 650 mmol/mol creatinine urine post shift	Methylhippuric acid: 1500 mg/g creatinine urine end of shift	Methylhippuric acids: 1 g/g Creatinine urine end of shift	Methylhippuric(tolur-)aci d (all isomers): 2000 mg/L urine (end of shift)

SAFETY DATA SHEET

Xylenes, mixture of isomers

Revision Date 04-Oct-2023

					all isomers)
Component	Italy	Finland	Denmark	Bulgaria	Romania
Xylenes (o-, m-, p- isomers)		Methylhippuric acid: 5.0 mmol/L urine after the shift.			Methylhippuric acid: 3 g/L urine end of shift
Component	Gibraltar	Latvia	Slovak Republic	Luxembourg	Turkey
Xylenes (o-, m-, p- isomers)			Xylene: 1.5 mg/L blood end of exposure or work shift all isomers Methylhippuric acid: 2000 mg/L urine end of exposure or work shift		

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Xylenes (o-, m-, p- isomers) 1330-20-7 (>95)				DNEL = 212mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Xylenes (o-, m-, p- isomers) 1330-20-7 (>95)	DNEL = 442mg/m ³	DNEL = 442mg/m ³	DNEL = 221mg/m ³	DNEL = 221mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Xylenes (o-, m-, p- isomers) 1330-20-7 (>95)	PNEC = 0.327mg/L	PNEC = 12.46mg/kg sediment dw	PNEC = 0.327mg/L	PNEC = 6.58mg/L	PNEC = 2.31mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Xylenes (o-, m-, p- isomers) 1330-20-7 (>95)	PNEC = 0.327mg/L	PNEC = 12.46mg/kg sediment dw			

8.2. Exposure controls

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment.

SAFETY DATA SHEET

Xylenes, mixture of isomers

Revision Date 04-Oct-2023

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Viton (R)	> 480 minutes	0.7 mm	Level 6	As tested under EN374-3 Determination of Resistance to Permeation by Chemicals
PVA	> 360 minutes	0.38 mm	Level 5 EN 374	
Nitrile rubber	> 96 minutes	0.38 mm		

Skin and body protection Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced
Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to EN14387

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141
When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls Prevent product from entering drains. Do not allow material to contaminate ground water system. Local authorities should be advised if significant spillages cannot be contained.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State	Liquid		
Appearance	Colourless		
Odor	aromatic		
Odor Threshold	No data available		
Melting Point/Range	-34 °C / -29.2 °F		
Softening Point	No data available		
Boiling Point/Range	136 - 140 °C / 276.8 - 284 °F	@ 760 mmHg	
Flammability (liquid)	Flammable	On basis of test data	
Flammability (solid,gas)	Not applicable	Liquid	
Explosion Limits	Lower 1% (V) Upper 7% (V)		
Flash Point	23 °C / 73.4 °F	Method - No information available	
Autoignition Temperature	463 °C		
Decomposition Temperature	No data available		

SAFETY DATA SHEET

Xylenes, mixture of isomers

Revision Date 04-Oct-2023

pH	No information available	
Viscosity	No data available	
Water Solubility	Insoluble	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Xylenes (o-, m-, p- isomers)	3.15	
Vapor Pressure	8 mbar @ 20°C	
Density / Specific Gravity	0.865	
Bulk Density	Not applicable	Liquid
Vapor Density	No data available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

Molecular Formula	C8 H10
Molecular Weight	106.17
Explosive Properties	explosive air/vapour mixtures possible

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization	No information available.
Hazardous Reactions	None under normal processing.

10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

None under normal use conditions.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral	Based on available data, the classification criteria are not met
Dermal	
Inhalation	

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Xylenes (o-, m-, p- isomers)	LD50 = 3500 mg/kg (Rat)	LD50 > 4350 mg/kg (Rabbit)	29.08 mg/L [MOE Risk Assessment Vol.1, 2002]

SAFETY DATA SHEET

Xylenes, mixture of isomers

Revision Date 04-Oct-2023

(b) skin corrosion/irritation;	Category 2
(c) serious eye damage/irritation;	Category 2
(d) respiratory or skin sensitization; Respiratory Skin	Based on available data, the classification criteria are not met Based on available data, the classification criteria are not met
(e) germ cell mutagenicity;	Based on available data, the classification criteria are not met
(f) carcinogenicity;	Based on available data, the classification criteria are not met There are no known carcinogenic chemicals in this product
(g) reproductive toxicity;	Based on available data, the classification criteria are not met
(h) STOT-single exposure; Results / Target organs	Category 3 Respiratory system.
(i) STOT-repeated exposure; Target Organs	Category 2 No information available.
(j) aspiration hazard;	Category 1
Symptoms / effects, both acute and delayed	Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

11.2. Information on other hazards

Endocrine Disrupting Properties	Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.
---------------------------------	---

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

The product contains following substances which are hazardous for the environment.
Contains a substance which is: Harmful to aquatic organisms.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Xylenes (o-, m-, p- isomers)	LC50: 30.26 - 40.75 mg/L, 96h static (Poecilia reticulata) LC50: = 780 mg/L, 96h semi-static (Cyprinus carpio) LC50: 23.53 - 29.97 mg/L, 96h static (Pimephales promelas) LC50: > 780 mg/L, 96h (Cyprinus carpio) LC50: 7.711 - 9.591 mg/L, 96h static (Lepomis macrochirus) LC50: = 19 mg/L, 96h (Lepomis macrochirus) LC50: 13.1 - 16.5 mg/L, 96h	LC50: = 0.6 mg/L, 48h (Gammarus lacustris) EC50: = 3.82 mg/L, 48h (water flea)	

SAFETY DATA SHEET

Xylenes, mixture of isomers

Revision Date 04-Oct-2023

	flow-through (Lepomis macrochirus) LC50: 13.5 - 17.3 mg/L, 96h (Oncorhynchus mykiss) LC50: 2.661 - 4.093 mg/L, 96h static (Oncorhynchus mykiss) LC50: = 13.4 mg/L, 96h flow-through (Pimephales promelas)		
--	---	--	--

Component	Microtox	M-Factor
Xylenes (o-, m-, p- isomers)	EC50 = 0.0084 mg/L 24 h	

12.2. Persistence and degradability

Persistence

Persistence is unlikely.

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Xylenes (o-, m-, p- isomers)	3.15	0.6 - 15 dimensionless

12.4. Mobility in soil

Spillage unlikely to penetrate soil. The product is insoluble and floats on water. Is not likely mobile in the environment due its low water solubility.

12.5. Results of PBT and vPvB assessment

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB).

12.6. Endocrine disrupting properties

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance
This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

European Waste Catalogue (EWC)

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information

Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not let this chemical enter the environment. Do not empty into drains.

SAFETY DATA SHEET

Xylenes, mixture of isomers

Revision Date 04-Oct-2023

Switzerland - Waste Ordinance

Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600
<https://www.fedlex.admin.ch/eli/cc/2015/891/en>

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number UN1307
14.2. UN proper shipping name XYLENES
14.3. Transport hazard class(es) 3
14.4. Packing group III

ADR

14.1. UN number UN1307
14.2. UN proper shipping name XYLENES
14.3. Transport hazard class(es) 3
14.4. Packing group III

IATA

14.1. UN number UN1307
14.2. UN proper shipping name XYLENES
14.3. Transport hazard class(es) 3
14.4. Packing group III

14.5. Environmental hazards No hazards identified
14.6. Special precautions for user No special precautions required.
14.7. Maritime transport in bulk according to IMO instruments Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Xylenes (o-, m-, p- isomers)	1330-20-7	215-535-7	-	-	X	X	KE-35427	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Xylenes (o-, m-, p- isomers)	1330-20-7	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) -	REACH (1907/2006) -	REACH Regulation (EC)
-----------	--------	---------------------	---------------------	-----------------------

ACR38393

SAFETY DATA SHEET

Xylenes, mixture of isomers

Revision Date 04-Oct-2023

		Annex XIV - Substances Subject to Authorization	Annex XVII - Restrictions on Certain Dangerous Substances	1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Xylenes (o-, m-, p- isomers)	1330-20-7	-	Use restricted. See item 75. (see link for restriction details)	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Xylenes (o-, m-, p- isomers)	1330-20-7	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

See table for values

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Xylenes (o-, m-, p- isomers)	WGK2	

Component	France - INRS (Tables of occupational diseases)
Xylenes (o-, m-, p- isomers)	Tableaux des maladies professionnelles (TMP) - RG 4bis, RG 84

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Xylenes (o-, m-, p- isomers) 1330-20-7 (>95)	Prohibited and Restricted Substances	Group II	

15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has not been conducted

SAFETY DATA SHEET

Xylenes, mixture of isomers

Revision Date 04-Oct-2023

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H226 - Flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H312 - Harmful in contact with skin
H332 - Harmful if inhaled
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H335 - May cause respiratory irritation
H373 - May cause damage to organs through prolonged or repeated exposure
H412 - Harmful to aquatic life with long lasting effects

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Creation Date 31-May-2018

Revision Date 04-Oct-2023

Revision Summary Not applicable.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006. COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No 1907/2006 .

For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2, Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and

SAFETY DATA SHEET

Xylenes, mixture of isomers

Revision Date 04-Oct-2023

Preparations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet