

Creation Date 22-Oct-2009

Revision Date 11-Oct-2023

Revision Number 7

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: Benzyl chloroformate, 50 wt% solution in toluene
Cat No. : 428900000; 428901000
Synonyms Carbobenzoxy chloride; Carbonochloride acid benzylester
Molecular Formula C8 H7 Cl O2

Unique Formula Identifier (UFI) 3P78-X3NF-RX0K-TXPE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

EU entity/business name
 Thermo Fisher Scientific
 Janssen Pharmaceuticaaan 3a, 2440 Geel, Belgium

UK entity/business name
 Fisher Scientific UK
 Bishop Meadow Road,
 Loughborough, Leicestershire LE11 5RG, United Kingdom

Swiss distributor - Fisher Scientific AG
 Neuhofstrasse 11, CH 4153 Reinach
 Tel: +41 (0) 56 618 41 11
 e-mail - infoch@thermofisher.com

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
 Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:
 Tox Info Suisse Emergency Number: **145 (24hr)**
 Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
 Chemtrec (24h) Toll-Free: 0800 564 402
 Chemtrec Local: +41-43 508 20 11 (Zurich)

Poison Centre - Emergency information services

Ireland : National Poisons Information Centre (NPIC) -
01 809 2166 (8am-10pm, 7 days a week)
Malta : +356 2395 2000
Cyprus : +357 2240 5611

SAFETY DATA SHEET

Benzyl chloroformate, 50 wt% solution in toluene

Revision Date 11-Oct-2023

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Flammable liquids
Substances/mixtures corrosive to metal

Category 2 (H225)
(H290)

Health hazards

Aspiration Toxicity
Acute Inhalation Toxicity - Vapors
Skin Corrosion/Irritation
Serious Eye Damage/Eye Irritation
Skin Sensitization
Carcinogenicity
Reproductive Toxicity
Specific target organ toxicity - (single exposure)
Specific target organ toxicity - (repeated exposure)

Category 1 (H304)
Category 4 (H332)
Category 1 (H314) B
Category 1 (H318)
Category 1 (H317)
Category 1B (H350)
Category 2 (H361d)
Category 3 (H335) (H336)
Category 2 (H373)

Environmental hazards

Acute aquatic toxicity
Chronic aquatic toxicity

Category 1 (H400)
Category 1 (H410)

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor
H290 - May be corrosive to metals
H304 - May be fatal if swallowed and enters airways
H314 - Causes severe skin burns and eye damage
H317 - May cause an allergic skin reaction
H332 - Harmful if inhaled
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H350 - May cause cancer
H361d - Suspected of damaging the unborn child
H373 - May cause damage to organs through prolonged or repeated exposure
H410 - Very toxic to aquatic life with long lasting effects
May produce an allergic reaction

SAFETY DATA SHEET

Benzyl chloroformate, 50 wt% solution in toluene

Revision Date 11-Oct-2023

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a POISON CENTER or doctor/physician

Additional EU labelling

Restricted to professional users

2.3. Other hazards

Decomposes in contact with water
Lachrymator (substance which increases the flow of tears)
Toxic to terrestrial vertebrates
This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Toluene	108-88-3	203-625-9	50	Flam. Liq. 2 (H225) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) STOT SE 3 (H336) Repr. 2 (H361d) STOT RE 2 (H373)
Benzyl chloride	100-44-7	EEC No. 202-853-6	>0.1	Met. Corr. 1 (H290) Acute Tox. 4 (H302) Acute Tox. 3 (H331) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) STOT SE 3 (H335) Carc. 1B (H350) STOT RE 2 (H373) Skin Sens. 1 (H317)
Benzyl chloroformate	501-53-1	EEC No. 207-925-0	50	Skin Corr. 1B (H314) Eye Dam. 1 (H318) STOT SE 3 (H335) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Benzyl chloroformate	STOT SE 3 >= 5%	1	-

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

SAFETY DATA SHEET

Benzyl chloroformate, 50 wt% solution in toluene

Revision Date 11-Oct-2023

General Advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.
Ingestion	Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
Inhalation	If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Remove to fresh air. Immediate medical attention is required. Risk of serious damage to the lungs (by aspiration).
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. May cause allergic skin reaction. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting; Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Water.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Do not allow run-off from fire-fighting to enter drains or water courses.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂), Hydrogen chloride gas.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SAFETY DATA SHEET

Benzyl chloroformate, 50 wt% solution in toluene

Revision Date 11-Oct-2023

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Flammables area. Keep away from heat, sparks and flame. Keep refrigerated. Corrosives area. Keep container tightly closed in a dry and well-ventilated place.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Class 3

Switzerland - Storage of hazardous substances

Storage class - SC 3
<https://www.kvu.ch/de/themen/stoffe-und-produkte>
<https://www.kvu.ch/fr/themes/substances-et-produits>
<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

SAFETY DATA SHEET

Benzyl chloroformate, 50 wt% solution in toluene

Revision Date 11-Oct-2023

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Toluene	TWA: 50 ppm (8hr) TWA: 192 mg/m ³ (8hr) STEL: 100 ppm (15min) STEL: 384 mg/m ³ (15min) Skin	STEL: 100 ppm 15 min STEL: 384 mg/m ³ 15 min TWA: 50 ppm 8 hr TWA: 191 mg/m ³ 8 hr Skin	TWA / VME: 20 ppm (8 heures). restrictive limit TWA / VME: 76.8 mg/m ³ (8 heures). restrictive limit TWA / VME: 1000 mg/m ³ (8 heures). STEL / VLCT: 100 ppm. restrictive limit STEL / VLCT: 384 mg/m ³ . restrictive limit STEL / VLCT: 1500 mg/m ³ . Peau	TWA: 20 ppm 8 uren TWA: 77 mg/m ³ 8 uren STEL: 100 ppm 15 minuten STEL: 384 mg/m ³ 15 minuten Huid	STEL / VLA-EC: 100 ppm (15 minutos). STEL / VLA-EC: 384 mg/m ³ (15 minutos). TWA / VLA-ED: 50 ppm (8 horas) TWA / VLA-ED: 192 mg/m ³ (8 horas) Piel
Benzyl chloride		STEL: 1.5 ppm 15 min STEL: 7.9 mg/m ³ 15 min TWA: 0.5 ppm 8 hr TWA: 2.6 mg/m ³ 8 hr Carc.	TWA / VME: 1 ppm (8 heures). TWA / VME: 5 mg/m ³ (8 heures). STEL / VLCT: 2 ppm. STEL / VLCT: 11 mg/m ³ .	TWA: 1 ppm 8 uren TWA: 5.3 mg/m ³ 8 uren	TWA / VLA-ED: 1 ppm (8 horas) TWA / VLA-ED: 5.3 mg/m ³ (8 horas)

Component	Italy	Germany	Portugal	The Netherlands	Finland
Toluene	TWA: 50 ppm 8 ore. Time Weighted Average TWA: 192 mg/m ³ 8 ore. Time Weighted Average Pelle	TWA: 50 ppm (8 Stunden). AGW - exposure factor 2 TWA: 190 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 50 ppm (8 Stunden). MAK TWA: 190 mg/m ³ (8 Stunden). MAK Höhepunkt: 100 ppm Höhepunkt: 380 mg/m ³ Haut	STEL: 100 ppm 15 minutos STEL: 384 mg/m ³ 15 minutos TWA: 50 ppm 8 horas TWA: 192 mg/m ³ 8 horas Pele	STEL: 384 mg/m ³ 15 minuten TWA: 150 mg/m ³ 8 uren	TWA: 25 ppm 8 tunteina TWA: 81 mg/m ³ 8 tunteina STEL: 100 ppm 15 minuutteina STEL: 380 mg/m ³ 15 minuutteina Iho
Benzyl chloride		Haut	TWA: 1 ppm 8 horas		TWA: 0.5 ppm 8 tunteina TWA: 2.6 mg/m ³ 8 tunteina Ceiling: 1.5 ppm Ceiling: 7.9 mg/m ³

Component	Austria	Denmark	Switzerland	Poland	Norway
Toluene	Haut MAK-KZGW: 100 ppm 15 Minuten MAK-KZGW: 380 mg/m ³ 15 Minuten MAK-TMW: 50 ppm 8 Stunden MAK-TMW: 190 mg/m ³ 8 Stunden	TWA: 25 ppm 8 timer TWA: 94 mg/m ³ 8 timer STEL: 384 mg/m ³ 15 minutter STEL: 100 ppm 15 minutter Hud	Haut/Peau STEL: 200 ppm 15 Minuten STEL: 760 mg/m ³ 15 Minuten TWA: 50 ppm 8 Stunden TWA: 190 mg/m ³ 8 Stunden	STEL: 200 mg/m ³ 15 minutach TWA: 100 mg/m ³ 8 godzinach	TWA: 25 ppm 8 timer TWA: 94 mg/m ³ 8 timer STEL: 37.5 ppm 15 minutter. value calculated STEL: 141 mg/m ³ 15 minutter. value calculated Hud
Benzyl chloride	TRK-KZGW: 0.8 mg/m ³ 15 Minuten Haut TRK-TMW: 0.2 mg/m ³	Ceiling: 1 ppm Ceiling: 5 mg/m ³	Haut/Peau TWA: 0.2 mg/m ³ 8 Stunden	STEL: 9 mg/m ³ 15 minutach TWA: 3 mg/m ³ 8 godzinach	Ceiling: 1 ppm Ceiling: 5 mg/m ³

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Toluene	TWA: 50 ppm	kože	TWA: 192 mg/m ³ 8 hr.	Skin-potential for	TWA: 200 mg/m ³ 8

SAFETY DATA SHEET

Benzyl chloroformate, 50 wt% solution in toluene

Revision Date 11-Oct-2023

	TWA: 192.0 mg/m ³ STEL : 100 ppm STEL : 384.0 mg/m ³ Skin notation	TWA-GVI: 50 ppm 8 satima. TWA-GVI: 192 mg/m ³ 8 satima. STEL-KGVI: 100 ppm 15 minutama. STEL-KGVI: 384 mg/m ³ 15 minutama.	TWA: 50 ppm 8 hr. STEL: 384 mg/m ³ 15 min STEL: 100 ppm 15 min Skin	cutaneous absorption STEL: 100 ppm STEL: 384 mg/m ³ TWA: 50 ppm TWA: 192 mg/m ³	hodinách. Potential for cutaneous absorption Ceiling: 500 mg/m ³
Benzyl chloride	TWA: 3.0 mg/m ³ STEL : 5.0 mg/m ³	kože TWA-GVI: 0.5 ppm 8 satima. TWA-GVI: 2.6 mg/m ³ 8 satima. STEL-KGVI: 1.5 ppm 15 minutama. STEL-KGVI: 7.9 mg/m ³ 15 minutama.	TWA: 1 ppm 8 hr. STEL: 0.5 ppm 15 min		TWA: 5 mg/m ³ 8 hodinách. Ceiling: 10 mg/m ³

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Toluene	Nahk TWA: 50 ppm 8 tundides. TWA: 192 mg/m ³ 8 tundides. STEL: 100 ppm 15 minutites. STEL: 384 mg/m ³ 15 minutites.	Skin notation TWA: 50 ppm 8 hr TWA: 192 mg/m ³ 8 hr STEL: 100 ppm 15 min STEL: 384 mg/m ³ 15 min	skin - potential for cutaneous absorption STEL: 100 ppm STEL: 384 mg/m ³ TWA: 50 ppm TWA: 192 mg/m ³	STEL: 380 mg/m ³ 15 percekben. CK TWA: 190 mg/m ³ 8 órában. AK lehetséges borön keresztüli felszívódás	STEL: 50 ppm STEL: 188 mg/m ³ TWA: 25 ppm 8 klukkustundum. TWA: 94 mg/m ³ 8 klukkustundum. Skin notation
Benzyl chloride	TWA: 1 ppm 8 tundides. TWA: 5 mg/m ³ 8 tundides. STEL: 2 ppm 15 minutites. STEL: 11 mg/m ³ 15 minutites.		TWA: 1 ppm TWA: 5 mg/m ³	STEL: 5 mg/m ³ 15 percekben. CK TWA: 2.6 mg/m ³ 8 órában. AK lehetséges borön keresztüli felszívódás	STEL: 1 ppm STEL: 5 mg/m ³

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Toluene	skin - potential for cutaneous exposure STEL: 40 ppm STEL: 150 mg/m ³ TWA: 14 ppm TWA: 50 mg/m ³	TWA: 50 ppm IPRD TWA: 192 mg/m ³ IPRD Oda STEL: 100 ppm STEL: 384 mg/m ³	Possibility of significant uptake through the skin TWA: 50 ppm 8 Stunden TWA: 192 mg/m ³ 8 Stunden STEL: 100 ppm 15 Minuten STEL: 384 mg/m ³ 15 Minuten	possibility of significant uptake through the skin TWA: 50 ppm TWA: 192 mg/m ³ STEL: 100 ppm 15 minuti STEL: 384 mg/m ³ 15 minuti	Skin notation TWA: 50 ppm 8 ore TWA: 192 mg/m ³ 8 ore STEL: 100 ppm 15 minute STEL: 384 mg/m ³ 15 minute
Benzyl chloride	TWA: 5 mg/m ³	TWA: 1 ppm IPRD TWA: 5 mg/m ³ IPRD STEL: 2 ppm STEL: 11 mg/m ³			TWA: 1 ppm 8 ore TWA: 5 mg/m ³ 8 ore STEL: 1.5 ppm 15 minute STEL: 8 mg/m ³ 15 minute

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Toluene	TWA: 50 mg/m ³ 1264 MAC: 150 mg/m ³	Ceiling: 384 mg/m ³ Potential for cutaneous absorption TWA: 50 ppm TWA: 192 mg/m ³	TWA: 50 ppm 8 urah TWA: 192 mg/m ³ 8 urah Koža STEL: 100 ppm 15 minutah STEL: 384 mg/m ³ 15 minutah	Binding STEL: 100 ppm 15 minuter Binding STEL: 384 mg/m ³ 15 minuter TLV: 50 ppm 8 timmar. NGV TLV: 192 mg/m ³ 8 timmar. NGV Hud	Deri TWA: 50 ppm 8 saat TWA: 192 mg/m ³ 8 saat STEL: 100 ppm 15 dakika STEL: 384 mg/m ³ 15 dakika
Benzyl chloride	MAC: 0.5 mg/m ³		TWA: 0.2 mg/m ³ 8 urah STEL: 0.8 mg/m ³ 15 minutah	Indicative STEL: 2 ppm 15 minuter Indicative STEL: 11 mg/m ³ 15 minuter TLV: 1 ppm 8 timmar.	

SAFETY DATA SHEET

Benzyl chloroformate, 50 wt% solution in toluene

Revision Date 11-Oct-2023

				NGV TLV: 5 mg/m ³ 8 timmar. NGV	
Benzyl chloroformate	Skin notation MAC: 0.5 mg/m ³				

Biological limit values

List source(s):

Component	European Union	United Kingdom	France	Spain	Germany
Toluene			Toluene: 1 mg/L venous blood end of shift Hippuric acid: 2500 mg/g creatinine urine end of shift	o-Cresol: 0.6 mg/L urine end of shift Toluene: 0.05 mg/L blood start of last shift of workweek Toluene: 0.08 mg/L urine end of shift	Toluene: 600 µg/L whole blood (immediately after exposure) Toluene: 75 µg/L urine (end of shift) o-Cresol (after hydrolysis): 1.5 mg/L urine (for long-term exposures: at the end of the shift after several shifts) o-Cresol (after hydrolysis): 1.5 mg/L urine (end of shift)

Component	Italy	Finland	Denmark	Bulgaria	Romania
Toluene		Toluene: 500 nmol/L blood in the morning after a working day.		Hippuric acid: 1.6 mmol/mmol Creatinine urine at the end of exposure or end of work shift	Hippuric acid: 2 g/L urine end of shift o-Cresol: 3 mg/L urine end of shift

Component	Gibraltar	Latvia	Slovak Republic	Luxembourg	Turkey
Toluene		Hippuric acid: 1.6 g/g Creatinine urine end of shift Toluene: 0.05 mg/L blood end of shift	Toluene: 600 µg/L blood end of exposure or work shift o-Cresol: 1.5 mg/L urine after all work shifts for long-term exposure o-Cresol: 1.5 mg/L urine end of exposure or work shift Hippuric acid: 1600 mg/g creatinine end of exposure or work shift		

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Toluene 108-88-3 (50)				DNEL = 384mg/kg bw/day

SAFETY DATA SHEET

Benzyl chloroformate, 50 wt% solution in toluene

Revision Date 11-Oct-2023

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Toluene 108-88-3 (50)	DNEL = 384mg/m ³	DNEL = 384mg/m ³	DNEL = 192mg/m ³	DNEL = 192mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Toluene 108-88-3 (50)	PNEC = 0.68mg/L	PNEC = 16.39mg/kg sediment dw	PNEC = 0.68mg/L	PNEC = 13.61mg/L	PNEC = 2.89mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Toluene 108-88-3 (50)	PNEC = 0.68mg/L	PNEC = 16.39mg/kg sediment dw			

8.2. Exposure controls

Engineering Measures

Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles (European standard - EN 166)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Natural rubber Butyl rubber Nitrile rubber Neoprene PVC	See manufacturers recommendations	-	EN 374	(minimum requirement)

Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: Particulates filter conforming to EN 143 or Acid gases filter Type E Yellow conforming to EN14387

Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure

SAFETY DATA SHEET

Benzyl chloroformate, 50 wt% solution in toluene

Revision Date 11-Oct-2023

limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls Prevent product from entering drains. Do not allow material to contaminate ground water system. Local authorities should be advised if significant spillages cannot be contained.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance	Light yellow - Light pink	
Odor	Characteristic	
Odor Threshold	No data available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flammability (liquid)	Highly flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Flash Point	7 °C / 44.6 °F	Method - No information available
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
pH	No information available	
Viscosity	No data available	
Water Solubility	Decomposes	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Toluene	2.73	
Benzyl chloride	2.3	
Vapor Pressure	2 mmHg @ 78 °C	
Density / Specific Gravity	1.010	
Bulk Density	Not applicable	Liquid
Vapor Density	No information available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

Molecular Formula	C8 H7 Cl O2
Molecular Weight	170.6
Explosive Properties	Vapors may form explosive mixtures with air

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Moisture sensitive.

10.3. Possibility of hazardous reactions

SAFETY DATA SHEET

Benzyl chloroformate, 50 wt% solution in toluene

Revision Date 11-Oct-2023

Hazardous Polymerization Hazardous Reactions

Hazardous polymerization does not occur.
None under normal processing.

10.4. Conditions to avoid

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition. Exposure to moist air or water.

10.5. Incompatible materials

Strong oxidizing agents. Acids. Bases. Alcohols. Amines.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂). Hydrogen chloride gas.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral

Based on available data, the classification criteria are not met

Dermal

Based on available data, the classification criteria are not met

Inhalation

Category 4

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Toluene	> 5000 mg/kg (Rat)	LD50 = 12000 mg/kg (Rabbit)	26700 ppm (Rat) 1 h
Benzyl chloride	LD50 = 625 mg/kg (Rat)	-	LC50 = 0.74 mg/L (Rat) 2 h
Benzyl chloroformate	LD50 = 3 g/kg (Rat)	-	LC50 = 590 mg/m ³ (Rat) 4 h

(b) skin corrosion/irritation;

Category 1 B

(c) serious eye damage/irritation;

Category 1

(d) respiratory or skin sensitization;

Respiratory

No data available

Skin

Category 1

No information available

(e) germ cell mutagenicity;

No data available

(f) carcinogenicity;

Category 1B

Possible cancer hazard. May cause cancer based on animal data The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Benzyl chloride	Carc Cat. 1B		Cat. 2	Group 2A

(g) reproductive toxicity; Reproductive Effects

Category 2

May cause harm to the unborn child.

SAFETY DATA SHEET

Benzyl chloroformate, 50 wt% solution in toluene

Revision Date 11-Oct-2023

(h) STOT-single exposure;	Category 3
Results / Target organs	Central nervous system (CNS), Respiratory system.
(i) STOT-repeated exposure;	Category 2
Target Organs	None known, Eyes, Skin, Respiratory system, Gastrointestinal tract (GI), Central nervous system (CNS), Neuropsychological effects, Ears.
(j) aspiration hazard;	Category 1
Symptoms / effects, both acute and delayed	Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

The product contains following substances which are hazardous for the environment. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Reacts with water so no ecotoxicity data for the substance is available.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Toluene	50-70 mg/L LC50 96 h 5-7 mg/L LC50 96 h 15-19 mg/L LC50 96 h 28 mg/L LC50 96 h 12 mg/L LC50 96 h	EC50: = 11.5 mg/L, 48h (Daphnia magna) EC50: 5.46 - 9.83 mg/L, 48h Static (Daphnia magna)	EC50: = 12.5 mg/L, 72h static (Pseudokirchneriella subcapitata) EC50: > 433 mg/L, 96h (Pseudokirchneriella subcapitata)
Benzyl chloride	LC50: = 4 mg/L, 96h static (Brachydanio rerio) LC50: 4.4 - 5.6 mg/L, 96h static (Pimephales promelas)		

Component	Microtox	M-Factor
Toluene	EC50 = 19.7 mg/L 30 min	
Benzyl chloride	EC50 = 1.92 mg/L 5 min EC50 = 2.25 mg/L 15 min EC50 = 2.97 mg/L 30 min	
Benzyl chloroformate		1

12.2. Persistence and degradability

Persistence

Soluble in water, Persistence is unlikely, based on information available.

Degradability

Decomposes in contact with water.

Component	Degradability
Toluene 108-88-3 (50)	86% (20d)

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants. Decomposes in contact with water.

SAFETY DATA SHEET

Benzyl chloroformate, 50 wt% solution in toluene

Revision Date 11-Oct-2023

12.3. Bioaccumulative potential

Bioaccumulation is unlikely; Product does not bioaccumulate due to reaction with water

Component	log Pow	Bioconcentration factor (BCF)
Toluene	2.73	90
Benzyl chloride	2.3	No data available

12.4. Mobility in soil

The product is water soluble, and may spread in water systems Decomposes in contact with water . Will likely be mobile in the environment due to its water solubility. Is not likely mobile in the environment. Highly mobile in soils

12.5. Results of PBT and vPvB assessment

Decomposes in contact with water.

12.6. Endocrine disrupting properties

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant
Ozone Depletion Potential

This product does not contain any known or suspected substance

This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

European Waste Catalogue (EWC)

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information

Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms. Do not let this chemical enter the environment.

Switzerland - Waste Ordinance

Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600
<https://www.fedlex.admin.ch/eli/cc/2015/891/en>

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number

UN2920

14.2. UN proper shipping name

Corrosive liquid, flammable, n.o.s.

Technical Shipping Name

(BENZYL CHLOROFORMATE, TOLUENE)

14.3. Transport hazard class(es)

8

Subsidiary Hazard Class

3

14.4. Packing group

I

SAFETY DATA SHEET

Benzyl chloroformate, 50 wt% solution in toluene

Revision Date 11-Oct-2023

ADR

14.1. UN number	UN2920
14.2. UN proper shipping name Technical Shipping Name	Corrosive liquid, flammable, n.o.s. (BENZYL CHLOROFORMATE, TOLUENE)
14.3. Transport hazard class(es) Subsidiary Hazard Class	8 3
14.4. Packing group	I

IATA

14.1. UN number	UN2920
14.2. UN proper shipping name Technical Shipping Name	CORROSIVE LIQUID, FLAMMABLE, N.O.S.* (BENZYL CHLOROFORMATE, TOLUENE)
14.3. Transport hazard class(es) Subsidiary Hazard Class	8 3
14.4. Packing group	I

14.5. Environmental hazards	Dangerous for the environment Product is a marine pollutant according to the criteria set by IMDG/IMO
------------------------------------	--

14.6. Special precautions for user	No special precautions required.
---	----------------------------------

14.7. Maritime transport in bulk according to IMO instruments	Not applicable, packaged goods
--	--------------------------------

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Toluene	108-88-3	203-625-9	-	-	X	X	KE-33936	X	X
Benzyl chloride	100-44-7	202-853-6	-	-	X	X	KE-05729	X	X
Benzyl chloroformate	501-53-1	207-925-0	-	-	X	X	KE-02790	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Toluene	108-88-3	X	ACTIVE	X	-	X	X	X
Benzyl chloride	100-44-7	X	ACTIVE	X	-	X	X	X
Benzyl chloroformate	501-53-1	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Toluene	108-88-3	-	Use restricted. See item 48. (see link for restriction)	-

SAFETY DATA SHEET

Benzyl chloroformate, 50 wt% solution in toluene

Revision Date 11-Oct-2023

			details) Use restricted. See item 75. (see link for restriction details)	
Benzyl chloride	100-44-7	-	Use restricted. See item 72. (see link for restriction details) Use restricted. See item 28. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-
Benzyl chloroformate	501-53-1	-	Use restricted. See item 75. (see link for restriction details)	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Toluene	108-88-3	Not applicable	Not applicable
Benzyl chloride	100-44-7	Not applicable	Not applicable
Benzyl chloroformate	501-53-1	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

Take note of Directive 94/33/EC on the protection of young people at work

Take note of Dir 92/85/EC on the protection of pregnant and breastfeeding women at work

Take note of Dir 76/769/EEC relating to restrictions on the marketing and use of certain dangerous substances and preparations

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 3 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Toluene	WGK3	
Benzyl chloride	WGK3	Krebserzeugende Stoffe - Class II : 0.5 mg/m³ (Massenkonzentration)
Benzyl chloroformate	WGK2	

Component	France - INRS (Tables of occupational diseases)
-----------	---

SAFETY DATA SHEET

Benzyl chloroformate, 50 wt% solution in toluene

Revision Date 11-Oct-2023

Toluene	Tableaux des maladies professionnelles (TMP) - RG 4bis, RG 84
---------	---

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Toluene 108-88-3 (50)	Prohibited and Restricted Substances	Group I	
Benzyl chloride 100-44-7 (>0.1)	Prohibited and Restricted Substances		
Benzyl chloroformate 501-53-1 (50)	Prohibited and Restricted Substances		

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H304 - May be fatal if swallowed and enters airways
H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H350 - May cause cancer
H361d - Suspected of damaging the unborn child
H373 - May cause damage to organs through prolonged or repeated exposure
H400 - Very toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects
H225 - Highly flammable liquid and vapor
H290 - May be corrosive to metals
H302 - Harmful if swallowed
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H331 - Toxic if inhaled

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

SAFETY DATA SHEET

Benzyl chloroformate, 50 wt% solution in toluene

Revision Date 11-Oct-2023

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data

Health Hazards Calculation method

Environmental hazards Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Creation Date 22-Oct-2009

Revision Date 11-Oct-2023

Revision Summary SDS sections updated.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006. COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No 1907/2006 .

For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2, Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and Preparations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet