

Revision Date 11-May-2023

Revision Number 2

KITS SDS COVER SHEET

Company

Thermo Fisher (Kandel) GmbH
Erlenbachweg 2, 76870 Kandel, Germany
Tel: +49 (0) 721 84007 280
Fax: +49 (0) 721 84007 300

Swiss distributor - Fisher Scientific AG
Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
e-mail - infoch@thermofisher.com

Emergency Telephone Number

Carechem 24: **+44 (0) 1235 239 670** (Multi-language emergency number)
Poison Information Center Mainz
www.giftinfo.uni-mainz.de
Telephone: +49(0)6131/19240

Exclusively for customers in Austria:
Poison Information Center (VIZ)
Emergency call 0-24 clock: **+43 1 406 43 43**
Office hours: Monday to Friday, 8am to 4pm, tel: +43 1 406 68 98

For customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

E-mail address

tech@alfa.com
www.alfa.com
Product safety Tel + +049 (0) 7275 988687-0

Product Information

Product Description:

Phenol:Chloroform:Isoamyl alcohol 25:24:1, Ready-to-Use saturated aq. soln., pH 5.2

Product Identifier

ALFAAJ62336

Cat No. :

J62336

Recommended Use

Laboratory chemicals.

Components

Description

J62336a - Phenol:Chloroform:Isoamyl alcohol 25:24:1, aqueous solution
J62336b - Alkaline buffer

Transport information

UN-No

UN2922

Proper Shipping Name

Corrosive liquid, toxic, n.o.s.

Technical Shipping Name

(PHENOL, CHLOROFORM)

Hazard Class

8

Subsidiary Hazard Class
Packing Group

6.1
II

Creation Date 21-Aug-2018

Revision Date 11-May-2023

Revision Number 3

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: **Phenol:Chloroform:Isoamyl alcohol 25:24:1, aqueous solution**
Cat No. : **J62336a**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

Thermo Fisher (Kandel) GmbH
Erlenbachweg 2, 76870 Kandel, Germany
Tel: +49 (0) 721 84007 280
Fax: +49 (0) 721 84007 300

Swiss distributor - Fisher Scientific AG
Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
e-mail - infoch@thermofisher.com

E-mail address

tech@alfa.com
www.alfa.com
Product safety Tel + +049 (0) 7275 988687-0

1.4. Emergency telephone number

Carechem 24: **+44 (0) 1235 239 670** (Multi-language emergency number)
Poison Information Center Mainz
www.giftinfo.uni-mainz.de
Telephone: +49(0)6131/19240

Exclusively for customers in Austria:
Poison Information Center (VIZ)
Emergency call 0-24 clock: **+43 1 406 43 43**
Office hours: Monday to Friday, 8am to 4pm, tel: +43 1 406 68 98

For customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

SAFETY DATA SHEET

Phenol:Chloroform:Isoamyl alcohol 25:24:1, aqueous solution

Revision Date 11-May-2023

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Based on available data, the classification criteria are not met

Health hazards

Acute oral toxicity	Category 3 (H301)
Acute dermal toxicity	Category 3 (H311)
Acute Inhalation Toxicity - Vapors	Category 3 (H331)
Skin Corrosion/Irritation	Category 1 B (H314)
Serious Eye Damage/Eye Irritation	Category 1 (H318)
Germ Cell Mutagenicity	Category 2 (H341)
Carcinogenicity	Category 2 (H351)
Reproductive Toxicity	Category 2 (H361d)
Specific target organ toxicity - (repeated exposure)	Category 1 (H372)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

- H314 - Causes severe skin burns and eye damage
- H341 - Suspected of causing genetic defects
- H351 - Suspected of causing cancer
- H361d - Suspected of damaging the unborn child
- H372 - Causes damage to organs through prolonged or repeated exposure
- H301 + H311 + H331 - Toxic if swallowed, in contact with skin or if inhaled
- EUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary Statements

- P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
- P280 - Wear protective gloves/protective clothing/eye protection/face protection
- P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
- P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
- P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- P310 - Immediately call a POISON CENTER or doctor/physician

Additional EU labelling

For use in industrial installations only

SAFETY DATA SHEET

Phenol:Chloroform:Isoamyl alcohol 25:24:1, aqueous solution

Revision Date 11-May-2023

2.3. Other hazards

Toxicity to Soil Dwelling Organisms

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Phenol	108-95-2	EEC No. 203-632-7	47.5	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) Skin Corr. 1B (H314) Eye Dam. 1 (H318) Muta. 2 (H341) STOT RE 2 (H373)
Chloroform	67-66-3	200-663-8	45.6	Acute Tox. 4 (H302) Acute Tox 3 (H331) Eye Irrit. 2 (H319) Skin Irrit. 2 (H315) Carc. 2 (H351) Repr. 2 (H361d) STOT RE 1 (H372)
Water	7732-18-5	231-791-2	5.0	-
1-Butanol, 3-methyl-	123-51-3	EEC No. 204-633-5	1.9	Flam Liq. 3 (H226) Acute Tox. 4 (H332) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) STOT SE 3 (H335) (EUH066)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Chloroform	STOT RE 2 : C ≥ 5 %	-	-

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.
Ingestion	Do NOT induce vomiting. Call a physician or poison control center immediately.
Inhalation	If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim

SAFETY DATA SHEET

Phenol:Chloroform:Isoamyl alcohol 25:24:1, aqueous solution

Revision Date 11-May-2023

ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Remove to fresh air. Immediate medical attention is required.

Self-Protection of the First Aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂), Hydrogen chloride.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal.

SAFETY DATA SHEET

Phenol:Chloroform:Isoamyl alcohol 25:24:1, aqueous solution

Revision Date 11-May-2023

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Corrosives area. Keep containers tightly closed in a dry, cool and well-ventilated place.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Storage Class/LGK 6.1C

Switzerland - Storage of hazardous substances

Storage class - SC 6.1
<https://www.kvu.ch/de/themen/stoffe-und-produkte>
<https://www.kvu.ch/fr/themes/substances-et-produits>
<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Phenol	TWA: 2 ppm (8h) TWA: 8 mg/m ³ (8h) STEL: 4 ppm (15min) STEL: 16 mg/m ³ (15min) Skin	STEL: 4 ppm 15 min STEL: 16 mg/m ³ 15 min TWA: 2 ppm 8 hr TWA: 7.8 mg/m ³ 8 hr Skin	TWA / VME: 2 ppm (8 heures). restrictive limit TWA / VME: 7.8 mg/m ³ (8 heures). restrictive limit STEL / VLCT: 4 ppm. restrictive limit STEL / VLCT: 15.6 mg/m ³ . restrictive limit Peau	TWA: 2 ppm 8 uren TWA: 8 mg/m ³ 8 uren STEL: 4 ppm 15 minuten STEL: 16 mg/m ³ 15 minuten Huid	STEL / VLA-EC: 4 ppm (15 minutos). STEL / VLA-EC: 16 mg/m ³ (15 minutos). TWA / VLA-ED: 2 ppm (8 horas) TWA / VLA-ED: 8 mg/m ³ (8 horas) Piel
Chloroform	TWA: 2 ppm (8h) TWA: 10 mg/m ³ (8h) Skin	TWA: 2 ppm TWA: 9.9 mg/m ³ STEL: 6 ppm STEL: 29.7 mg/m ³	TWA / VME: 2 ppm (8 heures). restrictive limit TWA / VME: 10 mg/m ³ (8 heures). restrictive limit	TWA: 2 ppm 8 uren TWA: 10 mg/m ³ 8 uren Huid	TWA / VLA-ED: 2 ppm (8 horas) TWA / VLA-ED: 10 mg/m ³ (8 horas) Piel

SAFETY DATA SHEET

Phenol:Chloroform:Isoamyl alcohol 25:24:1, aqueous solution

Revision Date 11-May-2023

			STEL / VLCT: 50 ppm. restrictive limit STEL / VLCT: 250 mg/m ³ . restrictive limit Peau		
1-Butanol, 3-methyl-		STEL: 125 ppm 15 min STEL: 458 mg/m ³ 15 min TWA: 100 ppm 8 hr TWA: 366 mg/m ³ 8 hr	TWA / VME: 5 ppm (8 heures). restrictive limit TWA / VME: 18 mg/m ³ (8 heures). restrictive limit STEL / VLCT: 10 ppm. restrictive limit STEL / VLCT: 37 mg/m ³ . restrictive limit	TWA: 5 ppm 8 uren TWA: 18 mg/m ³ 8 uren STEL: 10 ppm 15 minuten STEL: 37 mg/m ³ 15 minuten	STEL / VLA-EC: 10 ppm (15 minutos). STEL / VLA-EC: 37 mg/m ³ (15 minutos). TWA / VLA-ED: 5 ppm (8 horas) TWA / VLA-ED: 18 mg/m ³ (8 horas)

Component	Italy	Germany	Portugal	The Netherlands	Finland
Phenol	TWA: 2 ppm 8 ore. Time Weighted Average TWA: 8.0 mg/m ³ 8 ore. Time Weighted Average STEL: 4 ppm 15 minuti. Short-term STEL: 16 mg/m ³ 15 minuti. Short-term Pelle	TWA: 2 ppm (8 Stunden). AGW - exposure factor 2 TWA: 8 mg/m ³ (8 Stunden). AGW - exposure factor 2 Haut	STEL: 4 ppm 15 minutos STEL: 16 mg/m ³ 15 minutos TWA: 2 ppm 8 horas TWA: 8 mg/m ³ 8 horas Pele	huid TWA: 8 mg/m ³ 8 uren	TWA: 2 ppm 8 tunteina TWA: 8 mg/m ³ 8 tunteina STEL: 4 ppm 15 minuutteina STEL: 16 mg/m ³ 15 minuutteina Iho
Chloroform	TWA: 2 ppm 8 ore. Time Weighted Average TWA: 10 mg/m ³ 8 ore. Time Weighted Average Pelle	0.5 ppm TWA MAK 2.5 mg/m ³ TWA MAK	TWA: 2 ppm 8 horas TWA: 10 mg/m ³ 8 horas Pele	STEL: 25 mg/m ³ 15 minuten TWA: 5 mg/m ³ 8 uren	TWA: 2 ppm 8 tunteina TWA: 10 mg/m ³ 8 tunteina STEL: 4 ppm 15 minuutteina STEL: 20 mg/m ³ 15 minuutteina Iho
1-Butanol, 3-methyl-	TWA: 18 mg/m ³ 8 ore. Time Weighted Average TWA: 5 ppm 8 ore. Time Weighted Average STEL: 37 mg/m ³ 15 minuti. Short-term STEL: 10 ppm 15 minuti. Short-term	TWA: 20 ppm (8 Stunden). AGW - exposure factor 2 TWA: 73 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 20 ppm (8 Stunden). MAK TWA: 73 mg/m ³ (8 Stunden). MAK Höhepunkt: 40 ppm Höhepunkt: 146 mg/m ³	STEL: 10 ppm 15 minutos STEL: 37 mg/m ³ 15 minutos TWA: 5 ppm 8 horas TWA: 18 mg/m ³ 8 horas	STEL: 37 mg/m ³ 15 minuten TWA: 18 mg/m ³ 8 uren	TWA: 5 ppm 8 tunteina TWA: 18 mg/m ³ 8 tunteina STEL: 10 ppm 15 minuutteina STEL: 37 mg/m ³ 15 minuutteina

Component	Austria	Denmark	Switzerland	Poland	Norway
Phenol	Haut MAK-KZGW: 4 ppm 15 Minuten MAK-KZGW: 16 mg/m ³ 15 Minuten MAK-TMW: 2 ppm 8 Stunden MAK-TMW: 8 mg/m ³ 8 Stunden	TWA: 1 ppm 8 timer TWA: 4 mg/m ³ 8 timer STEL: 16 mg/m ³ 15 minutter STEL: 4 ppm 15 minutter Hud	Haut/Peau STEL: 5 ppm 15 Minuten STEL: 19 mg/m ³ 15 Minuten TWA: 5 ppm 8 Stunden TWA: 19 mg/m ³ 8 Stunden	STEL: 16 mg/m ³ 15 minutach TWA: 7.8 mg/m ³ 8 godzinach	TWA: 1 ppm 8 timer TWA: 4 mg/m ³ 8 timer STEL: 3 ppm 15 minutter. value from the regulation STEL: 12 mg/m ³ 15 minutter. value from the regulation Hud
Chloroform	Haut MAK-TMW: 2 ppm 8 Stunden MAK-TMW: 10 mg/m ³ 8 Stunden	TWA: 2 ppm 8 timer TWA: 10 mg/m ³ 8 timer STEL: 4 ppm 15 minutter STEL: 20 mg/m ³ 15 minutter Hud	Haut/Peau STEL: 1 ppm 15 Minuten STEL: 5 mg/m ³ 15 Minuten TWA: 0.5 ppm 8 Stunden TWA: 2.5 mg/m ³ 8 Stunden	TWA: 8 mg/m ³ 8 godzinach	TWA: 2 ppm 8 timer TWA: 10 mg/m ³ 8 timer STEL: 20 mg/m ³ 15 minutter. value calculated STEL: 4 ppm 15 minutter. value calculated Hud
1-Butanol, 3-methyl-	MAK-KZGW: 10 ppm 15 Minuten MAK-KZGW: 37 mg/m ³ 15 Minuten	TWA: 5 ppm 8 timer TWA: 18 mg/m ³ 8 timer STEL: 37 mg/m ³ 15 minutter	STEL: 40 ppm 15 Minuten STEL: 150 mg/m ³ 15 Minuten	STEL: 37 mg/m ³ 15 minutach TWA: 18 mg/m ³ 8 godzinach	TWA: 18 mg/m ³ 8 timer TWA: 5 ppm 8 timer STEL: 37 mg/m ³ 15 minutter. value from the

SAFETY DATA SHEET

Phenol:Chloroform:Isoamyl alcohol 25:24:1, aqueous solution

Revision Date 11-May-2023

	MAK-TMW: 5 ppm 8 Stunden MAK-TMW: 18 mg/m ³ 8 Stunden	STEL: 10 ppm 15 minutter	TWA: 20 ppm 8 Stunden TWA: 75 mg/m ³ 8 Stunden		regulation STEL: 10 ppm 15 minutter. value from the regulation Hud
--	---	-----------------------------	--	--	--

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Phenol	TWA: 2 ppm TWA: 8 mg/m ³ STEL : 4 ppm STEL : 16 mg/m ³ Skin notation	kože TWA-GVI: 2 ppm 8 satima. TWA-GVI: 8 mg/m ³ 8 satima. STEL-KGVI: 4 ppm 15 minutama. STEL-KGVI: 16 mg/m ³ 15 minutama.	TWA: 2 ppm 8 hr. TWA: 8 mg/m ³ 8 hr. STEL: 4 ppm 15 min STEL: 16 mg/m ³ 15 min Skin	Skin-potential for cutaneous absorption STEL: 16 mg/m ³ STEL: 4 ppm TWA: 8 mg/m ³ TWA: 2 ppm	TWA: 7.5 mg/m ³ 8 hodinách. Potential for cutaneous absorption Ceiling: 15 mg/m ³
Chloroform	TWA: 2 ppm TWA: 10.0 mg/m ³ Skin notation	kože TWA-GVI: 2 ppm 8 satima. TWA-GVI: 10 mg/m ³ 8 satima.	TWA: 2 ppm 8 hr. TWA: 9.8 mg/m ³ 8 hr. STEL: 6 ppm 15 min STEL: 29.4 mg/m ³ 15 min Skin	Skin-potential for cutaneous absorption TWA: 2 ppm TWA: 10 mg/m ³	TWA: 10 mg/m ³ 8 hodinách. Potential for cutaneous absorption Ceiling: 20 mg/m ³
1-Butanol, 3-methyl-	TWA: 18 mg/m ³ TWA: 5 ppm STEL : 37 mg/m ³ STEL : 10 ppm	TWA-GVI: 5 ppm 8 satima. TWA-GVI: 18 mg/m ³ 8 satima. TWA-GVI: 100 ppm 8 satima. regulated under 3-Methyl-1-butanol TWA-GVI: 366 mg/m ³ 8 satima. regulated under 3-Methyl-1-butanol STEL-KGVI: 10 ppm 15 minutama. STEL-KGVI: 37 mg/m ³ 15 minutama. STEL-KGVI: 125 ppm 15 minutama. regulated under 3-Methyl-1-butanol STEL-KGVI: 458 mg/m ³ 15 minutama. regulated under 3-Methyl-1-butanol	TWA: 5 ppm 8 hr. TWA: 18 mg/m ³ 8 hr. STEL: 10 mg/m ³ 15 min STEL: 37 ppm 15 min	STEL: 37 mg/m ³ STEL: 10 ppm TWA: 18 mg/m ³ TWA: 5 ppm	TWA: 18 mg/m ³ 8 hodinách. Ceiling: 37 mg/m ³

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Phenol	Nahk TWA: 2 ppm 8 tundides. TWA: 8 mg/m ³ 8 tundides. STEL: 16 mg/m ³ 15 minutites. STEL: 4 ppm 15 minutites.	Skin notation TWA: 2 ppm 8 hr TWA: 8 mg/m ³ 8 hr STEL: 16 mg/m ³ 15 min STEL: 4 ppm 15 min	skin - potential for cutaneous absorption STEL: 4 ppm STEL: 16 mg/m ³ TWA: 2 ppm TWA: 8 mg/m ³	STEL: 16 mg/m ³ 15 percekben. CK TWA: 8 mg/m ³ 8 órában. AK lehetséges borön keresztüli felszívódás	TWA: 1 ppm 8 klukkustundum. TWA: 4 mg/m ³ 8 klukkustundum. Skin notation Ceiling: 2 ppm Ceiling: 8 mg/m ³
Chloroform	Nahk TWA: 2 ppm 8 tundides. TWA: 10 mg/m ³ 8 tundides.	Skin notation TWA: 2 ppm 8 hr TWA: 10 mg/m ³ 8 hr	TWA: 10 ppm TWA: 50 mg/m ³	TWA: 10 mg/m ³ 8 órában. AK lehetséges borön keresztüli felszívódás	TWA: 2 ppm 8 klukkustundum. TWA: 10 mg/m ³ 8 klukkustundum. Skin notation Ceiling: 4 ppm Ceiling: 20 mg/m ³
1-Butanol, 3-methyl-	TWA: 5 ppm 8 tundides. TWA: 18 mg/m ³ 8 tundides. STEL: 37 mg/m ³ 15 minutites. STEL: 10 ppm 15 minutites.		STEL: 10 ppm STEL: 37 mg/m ³ TWA: 5 ppm TWA: 18 mg/m ³	STEL: 37 mg/m ³ 15 percekben. CK TWA: 18 mg/m ³ 8 órában. AK	STEL: 10 ppm STEL: 37 mg/m ³ TWA: 5 ppm 8 klukkustundum. TWA: 18 mg/m ³ 8 klukkustundum. Ceiling: 200 ppm Ceiling: 720 mg/m ³

SAFETY DATA SHEET

Phenol:Chloroform:Isoamyl alcohol 25:24:1, aqueous solution

Revision Date 11-May-2023

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Phenol	skin - potential for cutaneous exposure STEL: 4 ppm STEL: 16 mg/m ³ TWA: 2 ppm TWA: 8 mg/m ³	TWA: 2 ppm IPRD TWA: 8 mg/m ³ IPRD Oda STEL: 4 ppm STEL: 16 mg/m ³	Possibility of significant uptake through the skin TWA: 2 ppm 8 Stunden TWA: 8 mg/m ³ 8 Stunden STEL: 16 mg/m ³ 15 Minuten STEL: 4 ppm 15 Minuten	possibility of significant uptake through the skin TWA: 2 ppm TWA: 8 mg/m ³ STEL: 16 mg/m ³ 15 minuti STEL: 4 ppm 15 minuti	Skin notation TWA: 2 ppm 8 ore TWA: 8 mg/m ³ 8 ore STEL: 4 ppm 15 minute STEL: 16 mg/m ³ 15 minute
Chloroform	skin - potential for cutaneous exposure TWA: 2 ppm TWA: 10 mg/m ³	TWA: 10 mg/m ³ IPRD TWA: 2 ppm IPRD Oda	Possibility of significant uptake through the skin TWA: 2 ppm 8 Stunden TWA: 10 mg/m ³ 8 Stunden	possibility of significant uptake through the skin TWA: 2 ppm TWA: 10 mg/m ³	Skin notation TWA: 2 ppm 8 ore TWA: 10 mg/m ³ 8 ore
1-Butanol, 3-methyl-	STEL: 37 mg/m ³ STEL: 10 ppm TWA: 18 mg/m ³ TWA: 5 ppm	TWA: 18 mg/m ³ IPRD TWA: 5 ppm IPRD STEL: 37 mg/m ³ STEL: 10 ppm	TWA: 18 mg/m ³ 8 Stunden TWA: 5 ppm 8 Stunden STEL: 37 mg/m ³ 15 Minuten STEL: 10 ppm 15 Minuten		TWA: 100 mg/m ³ 8 ore STEL: 200 mg/m ³ 15 minute

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Phenol	TWA: 0.3 mg/m ³ 0539 Skin notation MAC: 1 mg/m ³	Ceiling: 16 mg/m ³ Potential for cutaneous absorption TWA: 2 ppm TWA: 8 mg/m ³	TWA: 2 ppm 8 urah TWA: 8 mg/m ³ 8 urah Koža STEL: 4 ppm 15 minutah STEL: 16 mg/m ³ 15 minutah	Binding STEL: 4 ppm 15 minuter Binding STEL: 16 mg/m ³ 15 minuter TLV: 1 ppm 8 timmar. NGV TLV: 4 mg/m ³ 8 timmar. NGV Hud	Deri TWA: 2 ppm 8 saat TWA: 8 mg/m ³ 8 saat STEL: 4 ppm 15 dakika STEL: 16 mg/m ³ 15 dakika
Chloroform	TWA: 5 mg/m ³ 2087 Skin notation MAC: 10 mg/m ³	Potential for cutaneous absorption TWA: 2 ppm TWA: 10 mg/m ³	TWA: 2 ppm 8 urah TWA: 10 mg/m ³ 8 urah Koža	Indicative STEL: 5 ppm 15 minuter Indicative STEL: 25 mg/m ³ 15 minuter TLV: 2 ppm 8 timmar. NGV TLV: 10 mg/m ³ 8 timmar. NGV Hud	Deri TWA: 2 ppm 8 saat TWA: 10 mg/m ³ 8 saat
1-Butanol, 3-methyl-	MAC: 5 mg/m ³		TWA: 18 mg/m ³ 8 urah TWA: 5 ppm 8 urah STEL: 10 ppm 15 minutah STEL: 37 mg/m ³ 15 minutah	Binding STEL: 10 ppm 15 minuter Binding STEL: 37 mg/m ³ 15 minuter TLV: 5 ppm 8 timmar. NGV TLV: 18 mg/m ³ 8 timmar. NGV Hud	

Biological limit values

List source(s):

Component	European Union	United Kingdom	France	Spain	Germany
Phenol			Total Phenol: 250 mg/g creatinine urine end of shift	: 120 mg/g Creatinine urine end of shift	Phenol (after hydrolysis): 120 mg/g Creatinine urine (end of shift)

Component	Italy	Finland	Denmark	Bulgaria	Romania
Phenol		Total phenol: 1.3 mmol/L urine after the shift.		Phenol: 200 µg/L urine at the end of exposure or end of work shift	total Phenol: 120 mg/g Creatinine urine end of shift

Component	Gibraltar	Latvia	Slovak Republic	Luxembourg	Turkey
-----------	-----------	--------	-----------------	------------	--------

SAFETY DATA SHEET

Phenol:Chloroform:Isoamyl alcohol 25:24:1, aqueous solution

Revision Date 11-May-2023

Phenol			Phenol: 200 mg/L urine end of exposure or work shift		
--------	--	--	--	--	--

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Phenol 108-95-2 (47.5)				DNEL = 1.23mg/kg bw/day
Chloroform 67-66-3 (45.6)				DNEL = 0.94mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Phenol 108-95-2 (47.5)	DNEL = 16mg/m ³			DNEL = 8mg/m ³
Chloroform 67-66-3 (45.6)		DNEL = 333mg/m ³	DNEL = 2.5mg/m ³	DNEL = 2.5mg/m ³
1-Butanol, 3-methyl- 123-51-3 (1.9)	DNEL = 292mg/m ³		DNEL = 73.16mg/m ³	

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Phenol 108-95-2 (47.5)	PNEC = 0.0077mg/L	PNEC = 0.0915mg/kg sediment dw	PNEC = 0.031mg/L	PNEC = 2.1mg/L	PNEC = 0.136mg/kg soil dw
Chloroform 67-66-3 (45.6)	PNEC = 0.146mg/L	PNEC = 0.45mg/kg sediment dw	PNEC = 0.133mg/L	PNEC = 0.048mg/L	PNEC = 0.56mg/kg soil dw
1-Butanol, 3-methyl- 123-51-3 (1.9)	PNEC = 0.12mg/L	PNEC = 0.496mg/kg sediment dw	PNEC = 1.2mg/L	PNEC = 37mg/L	PNEC = 0.0287mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Phenol 108-95-2 (47.5)	PNEC = 0.00077mg/L	PNEC = 0.00915mg/kg sediment dw			
Chloroform 67-66-3 (45.6)	PNEC = 0.015mg/L	PNEC = 0.09mg/kg sediment dw			
1-Butanol, 3-methyl- 123-51-3 (1.9)	PNEC = 0.012mg/L	PNEC = 0.0496mg/kg sediment dw			

8.2. Exposure controls

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location.

SAFETY DATA SHEET

Phenol:Chloroform:Isoamyl alcohol 25:24:1, aqueous solution

Revision Date 11-May-2023

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Viton (R)	See manufacturers recommendations	-	EN 374	(minimum requirement)

Skin and body protection Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced
Recommended Filter type: low boiling organic solvent Type AX Brown conforming to EN371 or Organic gases and vapours filter Type A Brown conforming to EN14387

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141
When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls Prevent product from entering drains. Do not allow material to contaminate ground water system. Local authorities should be advised if significant spillages cannot be contained.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance	Colorless	
Odor	No information available	
Odor Threshold	No data available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flammability (liquid)	No data available	
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	Lower 1.3 Vol % Upper 9.5 Vol %	
Flash Point	No information available	Method - No information available
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
pH	5.2	
Viscosity	No data available	
Water Solubility	Miscible	

SAFETY DATA SHEET

Phenol:Chloroform:Isoamyl alcohol 25:24:1, aqueous solution

Revision Date 11-May-2023

Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Phenol	1.5	
Chloroform	2	
1-Butanol, 3-methyl-	1.35	
Vapor Pressure	No data available	
Density / Specific Gravity	No data available	
Bulk Density	Not applicable	Liquid
Vapor Density	No data available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity
None known, based on information available

10.2. Chemical stability
Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization No information available.
Hazardous Reactions None under normal processing.

10.4. Conditions to avoid
Heat.

10.5. Incompatible materials
Oxidizing agent.

10.6. Hazardous decomposition products
Carbon monoxide (CO). Carbon dioxide (CO₂). Hydrogen chloride.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;
Oral Category 3
Dermal Category 3
Inhalation Category 3

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Phenol	LD50 = 340 mg/kg (Rat)	LD50 = 630 mg/kg (Rabbit)	LC50 = 316 mg/m ³ (Rat) 4 h
Chloroform	LD50 = 450 mg/kg (Rat)	LD50 > 20 g/kg (Rabbit)	47,702 mg/L (Rat) 4 h
Water	-	-	-
1-Butanol, 3-methyl-	LD50 = 5770 mg/kg (Rat)	LD50 = 3250 mg/kg (Rabbit)	LC50 > 2000 ppm (Rat) 8 h

SAFETY DATA SHEET

Phenol:Chloroform:Isoamyl alcohol 25:24:1, aqueous solution

Revision Date 11-May-2023

--	--	--	--

(b) skin corrosion/irritation; Category 1 B

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;

Respiratory No data available
Skin No data available

(e) germ cell mutagenicity; Category 2

(f) carcinogenicity; Category 2

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Phenol			Cat. 3B	
Chloroform				Group 2B

(g) reproductive toxicity; Category 2

(h) STOT-single exposure; No data available

(i) STOT-repeated exposure; Category 1

Target Organs Kidney, Liver, Skin, Central nervous system (CNS).

(j) aspiration hazard; No data available

Symptoms / effects, both acute and delayed Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

Contains a substance which is: The product contains following substances which are hazardous for the environment. Very toxic to aquatic organisms.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Phenol	4-7 mg/L LC50 96 h 32 mg/L LC50 96 h	EC50: 10.2 - 15.5 mg/L, 48h (Daphnia magna) EC50: 4.24 - 10.7 mg/L, 48h Static (Daphnia magna)	EC50: 187 - 279 mg/L, 72h static (Desmodesmus subspicatus) EC50: 0.0188 - 0.1044 mg/L, 96h static (Pseudokirchneriella)

SAFETY DATA SHEET

Phenol:Chloroform:Isoamyl alcohol 25:24:1, aqueous solution

Revision Date 11-May-2023

			subcapitata) EC50: = 46.42 mg/L, 96h (Pseudokirchneriella subcapitata)
Chloroform	LC50: = 300 mg/L, 96h static (Poecilia reticulata) LC50: = 18 mg/L, 96h flow-through (Oncorhynchus mykiss) LC50: = 18 mg/L, 96h flow-through (Lepomis macrochirus) LC50: = 71 mg/L, 96h flow-through (Pimephales promelas)	EC50 = 28.9 mg/L/48h	EC50 = 560 mg/L/48h
1-Butanol, 3-methyl-	LC50 96 h 700 mg/L (rainbow trout)	EC50: = 260 mg/L, 48h (Daphnia magna)	EC50: = 181 mg/L, 96h (Desmodesmus subspicatus) EC50: = 493 mg/L, 72h (Desmodesmus subspicatus)

Component	Microtox	M-Factor
Phenol	EC50 21 - 36 mg/L 30 min EC50 = 23.28 mg/L 5 min EC50 = 25.61 mg/L 15 min EC50 = 28.8 mg/L 5 min EC50 = 31.6 mg/L 15 min	
Chloroform	Photobacterium phosphoreum: EC50 = 520 mg/L/5 min Photobacterium phosphoreum: EC50 = 670 mg/L/15 min Photobacterium phosphoreum: EC50 = 670 mg/L/30min	
1-Butanol, 3-methyl-	EC50 = 2500 mg/L 17 h	

12.2. Persistence and degradability

Persistence

Miscible with water, Persistence is unlikely, based on information available.

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Phenol	1.5	17.5 dimensionless 647 dimensionless
Chloroform	2	1.4 - 13 dimensionless
1-Butanol, 3-methyl-	1.35	No data available

12.4. Mobility in soil

The product is water soluble, and may spread in water systems Will likely be mobile in the environment due to its water solubility. Highly mobile in soils

12.5. Results of PBT and vPvB assessment

No data available for assessment.

12.6. Endocrine disrupting properties

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

SAFETY DATA SHEET

Phenol:Chloroform:Isoamyl alcohol 25:24:1, aqueous solution

Revision Date 11-May-2023

Persistent Organic Pollutant
Ozone Depletion Potential

This product does not contain any known or suspected substance
This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point.

European Waste Catalogue (EWC)

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information

Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms.

Switzerland - Waste Ordinance

Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600
<https://www.fedlex.admin.ch/eli/cc/2015/891/en>

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number

UN2922

14.2. UN proper shipping name

Corrosive liquid, toxic, n.o.s.
(PHENOL, CHLOROFORM)

Technical Shipping Name

14.3. Transport hazard class(es)

8

Subsidiary Hazard Class

6.1

14.4. Packing group

II

Marine Pollutant

No

ADR

14.1. UN number

UN2922

14.2. UN proper shipping name

Corrosive liquid, toxic, n.o.s.
(PHENOL, CHLOROFORM)

Technical Shipping Name

14.3. Transport hazard class(es)

8

Subsidiary Hazard Class

6.1

14.4. Packing group

II

IATA

14.1. UN number

UN2922

14.2. UN proper shipping name

Corrosive liquid, toxic, n.o.s.
(PHENOL, CHLOROFORM)

Technical Shipping Name

14.3. Transport hazard class(es)

8

Subsidiary Hazard Class

6.1

14.4. Packing group

II

14.5. Environmental hazards

No hazards identified

14.6. Special precautions for user

No special precautions required.

SAFETY DATA SHEET

Phenol:Chloroform:Isoamyl alcohol 25:24:1, aqueous solution

Revision Date 11-May-2023

14.7. Maritime transport in bulk according to IMO instruments Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Phenol	108-95-2	203-632-7	-	-	X	X	X	X	X
Chloroform	67-66-3	200-663-8	-	-	X	X	KE-34076	X	X
Water	7732-18-5	231-791-2	-	-	X	X	KE-35400	X	-
1-Butanol, 3-methyl-	123-51-3	204-633-5	-	-	X	X	KE-23575	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Phenol	108-95-2	X	ACTIVE	X	-	X	X	X
Chloroform	67-66-3	X	ACTIVE	X	-	X	X	X
Water	7732-18-5	X	ACTIVE	X	-	X	X	X
1-Butanol, 3-methyl-	123-51-3	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Phenol	108-95-2	-	Use restricted. See item 75. (see link for restriction details)	-
Chloroform	67-66-3	-	Use restricted. See item 32. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-
Water	7732-18-5	-	-	-
1-Butanol, 3-methyl-	123-51-3	-	-	-

<https://echa.europa.eu/substances-restricted-under-reach>

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Phenol	108-95-2	Not applicable	Not applicable
Chloroform	67-66-3	Not applicable	Not applicable
Water	7732-18-5	Not applicable	Not applicable
1-Butanol, 3-methyl-	123-51-3	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

SAFETY DATA SHEET

Phenol:Chloroform:Isoamyl alcohol 25:24:1, aqueous solution

Revision Date 11-May-2023

Component	ANNEX I - PART 1 List of chemicals subject to export notification procedure (referred to in Article 8)	ANNEX I - PART 2 List of chemicals qualifying for PIC notification (referred to in Article 11)	ANNEX I - PART 3 List of chemicals subject to the PIC procedure (referred to in Articles 13 and 14)
Chloroform 67-66-3 (45.6)	b — ban (for the category or categories concerned) b — ban (for the category or categories concerned) i(2) — industrial chemical for public	-	-

<https://eur-lex.europa.eu/legal-content/EN/TXT/?uri=CELEX%3A32012R0649&qid=1604065742303>.

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

Take note of Directive 94/33/EC on the protection of young people at work

Take note of Dir 92/85/EC on the protection of pregnant and breastfeeding women at work

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 3 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Phenol	WGK2	Class I : 20 mg/m ³ (Massenkonzentration)
Chloroform	WGK3	Class I : 20 mg/m ³ (Massenkonzentration)
1-Butanol, 3-methyl-	WGK1	

Component	France - INRS (Tables of occupational diseases)
Phenol	Tableaux des maladies professionnelles (TMP) - RG 14
Chloroform	Tableaux des maladies professionnelles (TMP) - RG 12
1-Butanol, 3-methyl-	Tableaux des maladies professionnelles (TMP) - RG 84

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Phenol 108-95-2 (47.5)	Prohibited and Restricted Substances		
Chloroform 67-66-3 (45.6)	Prohibited and Restricted Substances		Annex I - industrial chemical

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H301 - Toxic if swallowed

H311 - Toxic in contact with skin

SAFETY DATA SHEET

Phenol:Chloroform:Isoamyl alcohol 25:24:1, aqueous solution

Revision Date 11-May-2023

H331 - Toxic if inhaled
H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage
H341 - Suspected of causing genetic defects
H351 - Suspected of causing cancer
H361d - Suspected of damaging the unborn child
H372 - Causes damage to organs through prolonged or repeated exposure
EUH066 - Repeated exposure may cause skin dryness or cracking
H226 - Flammable liquid and vapor
H302 - Harmful if swallowed
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H332 - Harmful if inhaled
H335 - May cause respiratory irritation

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadviser - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data

Health Hazards Calculation method

Environmental hazards Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Prepared By Health, Safety and Environmental Department

Creation Date 21-Aug-2018

Revision Date 11-May-2023

Revision Summary Initial Release.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.

SAFETY DATA SHEET

Phenol:Chloroform:Isoamyl alcohol 25:24:1, aqueous solution

Revision Date 11-May-2023

COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No 1907/2006

For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2, Number 3, Chemo (SR 813.11 - Ordinance on Protection against Dangerous Substances and Preparations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet

Creation Date 21-Aug-2018

Revision Date 11-May-2023

Revision Number 2

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: Alkaline buffer
Cat No. : J62336b

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

Thermo Fisher (Kandel) GmbH
Erlenbachweg 2, 76870 Kandel, Germany
Tel: +49 (0) 721 84007 280
Fax: +49 (0) 721 84007 300

Swiss distributor - Fisher Scientific AG
Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
e-mail - infoch@thermofisher.com

E-mail address

tech@alfa.com
www.alfa.com
Product safety Tel + +049 (0) 7275 988687-0

1.4. Emergency telephone number

Carechem 24: **+44 (0) 1235 239 670** (Multi-language emergency number)
Poison Information Center Mainz
www.giftinfo.uni-mainz.de
Telephone: +49(0)6131/19240

Exclusively for customers in Austria:
Poison Information Center (VIZ)
Emergency call 0-24 clock: **+43 1 406 43 43**
Office hours: Monday to Friday, 8am to 4pm, tel: +43 1 406 68 98

For customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

SAFETY DATA SHEET

Alkaline buffer

Revision Date 11-May-2023

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Based on available data, the classification criteria are not met

Health hazards

Based on available data, the classification criteria are not met

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements

None required

2.3. Other hazards

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Water	7732-18-5	231-791-2	98.8	-
1,3-Propanediol, 2-amino-2-(hydroxymethyl)-	77-86-1	201-064-4	1.2	-

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. Get medical attention immediately if symptoms occur.

SAFETY DATA SHEET

Alkaline buffer

Revision Date 11-May-2023

Ingestion Clean mouth with water and drink afterwards plenty of water. Get medical attention if symptoms occur.

Inhalation Remove to fresh air. Get medical attention immediately if symptoms occur.

Self-Protection of the First Aider No special precautions required.

4.2. Most important symptoms and effects, both acute and delayed

None reasonably foreseeable.

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

None reasonably foreseeable.

Hazardous Combustion Products

Nitrogen oxides (NO_x).

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required.

6.2. Environmental precautions

Should not be released into the environment. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Sweep up and shovel into suitable containers for disposal.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

ALFAAJ62336B

SAFETY DATA SHEET

Alkaline buffer

Revision Date 11-May-2023

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Avoid contact with skin, eyes or clothing. Avoid ingestion and inhalation.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Technical Rules for Hazardous Substances (TRGS) 510 Storage Class (LGK) (Germany)

Storage Class/LGK 12

Switzerland - Storage of hazardous substances

Storage class - SC 10/12
<https://www.kvu.ch/de/themen/stoffe-und-produkte>
<https://www.kvu.ch/fr/themes/substances-et-produits>
<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

This product, as supplied, does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local	Acute effects	Chronic effects local	Chronic effects
-----------	---------------------	---------------	-----------------------	-----------------

SAFETY DATA SHEET

Alkaline buffer

Revision Date 11-May-2023

	(Dermal)	systemic (Dermal)	(Dermal)	systemic (Dermal)
1,3-Propanediol, 2-amino-2-(hydroxymethyl)- 77-86-1 (1.2)				DNEL = 166.7mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
1,3-Propanediol, 2-amino-2-(hydroxymethyl)- 77-86-1 (1.2)				DNEL = 117.5mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
1,3-Propanediol, 2-amino-2-(hydroxymethyl)- - 77-86-1 (1.2)				PNEC = 300mg/L	

8.2. Exposure controls

Engineering Measures

None under normal use conditions.

Personal protective equipment

Eye Protection

Wear safety glasses with side shields (or goggles) (European standard - EN 166)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Natural rubber	See manufacturers	-	EN 374	(minimum requirement)
Nitrile rubber	recommendations			
Neoprene				
PVC				

Skin and body protection

Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

No protective equipment is needed under normal use conditions.

Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: Particle filter

Small scale/Laboratory use

Maintain adequate ventilation

Environmental exposure controls

No information available.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

SAFETY DATA SHEET

Alkaline buffer

Revision Date 11-May-2023

9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance		
Odor	No information available	
Odor Threshold	No data available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flammability (liquid)	No data available	
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Flash Point	No information available	Method - No information available
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
pH	No information available	
Viscosity	No data available	
Water Solubility	Difficult solubility	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Vapor Pressure	No data available	
Density / Specific Gravity	No data available	
Bulk Density	Not applicable	Liquid
Vapor Density	No data available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization	No information available.
Hazardous Reactions	None under normal processing.

10.4. Conditions to avoid

Incompatible products. Excess heat.

10.5. Incompatible materials

Oxidizing agent.

10.6. Hazardous decomposition products

Nitrogen oxides (NO_x).

SECTION 11: TOXICOLOGICAL INFORMATION

SAFETY DATA SHEET

Alkaline buffer

Revision Date 11-May-2023

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral

Based on available data, the classification criteria are not met

Dermal

No data available

Inhalation

No data available

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Water	-	-	-
1,3-Propanediol, 2-amino-2-(hydroxymethyl)-	LD50 = 5900 mg/kg (Rat)	LD50 > 5000 mg/kg (Rat)	-

(b) skin corrosion/irritation;

No data available

(c) serious eye damage/irritation;

No data available

(d) respiratory or skin sensitization;

Respiratory

No data available

Skin

No data available

(e) germ cell mutagenicity;

No data available

(f) carcinogenicity;

No data available

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity;

No data available

(h) STOT-single exposure;

No data available

(i) STOT-repeated exposure;

No data available

Target Organs

No information available.

(j) aspiration hazard;

No data available

Symptoms / effects, both acute and delayed No information available.

11.2. Information on other hazards

Endocrine Disrupting Properties

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

.

SAFETY DATA SHEET

Alkaline buffer

Revision Date 11-May-2023

12.2. Persistence and degradability No information available

12.3. Bioaccumulative potential No information available

12.4. Mobility in soil No information available

12.5. Results of PBT and vPvB assessment No data available for assessment.

12.6. Endocrine disrupting properties

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant

This product does not contain any known or suspected substance

Ozone Depletion Potential

This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Contaminated Packaging

Empty remaining contents. Dispose of in accordance with local regulations. Do not re-use empty containers.

European Waste Catalogue (EWC)

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information

Waste codes should be assigned by the user based on the application for which the product was used.

Switzerland - Waste Ordinance

Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600
<https://www.fedlex.admin.ch/eli/cc/2015/891/en>

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

Not regulated

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

ADR

Not regulated

ALFAAJ62336B

SAFETY DATA SHEET

Alkaline buffer

Revision Date 11-May-2023

14.1. UN number
14.2. UN proper shipping name
14.3. Transport hazard class(es)
14.4. Packing group

IATA Not regulated

14.1. UN number
14.2. UN proper shipping name
14.3. Transport hazard class(es)
14.4. Packing group

14.5. Environmental hazards No hazards identified

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Water	7732-18-5	231-791-2	-	-	X	X	KE-35400	X	-
1,3-Propanediol, 2-amino-2-(hydroxymethyl)-	77-86-1	201-064-4	-	-	X	X	KE-01403	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Water	7732-18-5	X	ACTIVE	X	-	X	X	X
1,3-Propanediol, 2-amino-2-(hydroxymethyl)-	77-86-1	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Not applicable

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Water	7732-18-5	-	-	-
1,3-Propanediol, 2-amino-2-(hydroxymethyl)-	77-86-1	-	-	-

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Water	7732-18-5	Not applicable	Not applicable
1,3-Propanediol, 2-amino-2-(hydroxymethyl)-	77-86-1	Not applicable	Not applicable

ALFAAJ62336B

SAFETY DATA SHEET

Alkaline buffer

Revision Date 11-May-2023

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals
Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification Water endangering class = non-hazardous to waters (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
1,3-Propanediol, 2-amino-2-(hydroxymethyl)-	WGK1	

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

SAFETY DATA SHEET

Alkaline buffer

Revision Date 11-May-2023

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health Hazards	Calculation method
Environmental hazards	Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Prepared By	Health, Safety and Environmental Department
Creation Date	21-Aug-2018
Revision Date	11-May-2023
Revision Summary	Initial Release.

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.
COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No
1907/2006 .**

**For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2,
Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and
Preparations).**

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet