

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
Product Identifier

Perihalan Produk:

Chromium(III) 2-ethylhexanoate, 65-70% in mineral spirits

Product Description:

Chromium(III) 2-ethylhexanoate, 65-70% in mineral spirits

Cat No. :

S33703

Relevant identified uses of the substance or mixture and uses advised against

Recommended Use

Laboratory chemicals.

Uses advised against

No Information available

Company

 Thermo Fisher Scientific Fisher Scientific (M) Sdn Bhd
 Hap Seng Business Park, Lot 01-03, 01-04 Aras 1 Unity Square,
 No 12, Persiaran Perusahaan, Seksyen 23, 40300 Shah Alam,
 Selangor Darul Ehsan, Malaysia.
 Main line: +60 3-5525 7888

Supplier

E-mail address

Enquiry.my@thermofisher.com

Emergency Telephone Number

 Tel: +03-5525 7888
 CHEMTREC Malaysia 1-800-815-308 (Malay)
 CHEMTREC Malaysia (Kuala Lumpur) +(60)-327884561 (Malay)

SECTION 2: HAZARDS IDENTIFICATION
Classification of the substance or mixture

Carcinogenicity	Category 2 (H351)
Reproductive Toxicity	Category 1B (H360D)

Label Elements


Signal Word

Danger

Hazard Statements

H351 - Suspected of causing cancer

H360D - May damage the unborn child

SAFETY DATA SHEET

Chromium(III) 2-ethylhexanoate, 65-70% in mineral spirits

Revision Date 31-Mar-2025

Precautionary Statements

Prevention

P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood

P280 - Wear protective gloves/protective clothing/eye protection/face protection

Response

P308 + P313 - IF exposed or concerned: Get medical advice/attention

Storage

P403 - Store in a well-ventilated place

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Other Hazards

This product does not contain any known or suspected endocrine disruptors
Toxic to terrestrial vertebrates

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No	Weight %
Hexanoic acid, 2-ethyl-, chromium(3+) salt	3444-17-5	68
Fuels, diesel, no. 2	68476-34-6	28
2-Ethylhexanoic acid	149-57-5	4

SECTION 4: FIRST AID MEASURES

Description of first aid measures

General Advice

If symptoms persist, call a physician.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.

Ingestion

Clean mouth with water and drink afterwards plenty of water.

Inhalation

Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.

Self-Protection of the First Aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

None reasonably foreseeable. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

SAFETY DATA SHEET

Chromium(III) 2-ethylhexanoate, 65-70% in mineral spirits

Revision Date 31-Mar-2025

Extinguishing media

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Extinguishing media which must not be used for safety reasons

No information available.

Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors.

Hazardous Combustion Products

Carbon oxides, Chromium oxide.

Advice for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Ensure adequate ventilation. Use personal protective equipment as required.

Environmental precautions

Should not be released into the environment. Do not flush into surface water or sanitary sewer system. Do not allow material to contaminate ground water system.

Methods and Material for Containment and Cleaning Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation.

Conditions for Safe Storage, Including any Incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Specific End Uses

Use in laboratories.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Component	Malaysia	ACGIH TLV	OSHA PEL
-----------	----------	-----------	----------

SAFETY DATA SHEET

Chromium(III) 2-ethylhexanoate, 65-70% in mineral spirits

Revision Date 31-Mar-2025

Hexanoic acid, 2-ethyl-, chromium(3+) salt			(Vacated) TWA: 0.5 mg/m ³
Fuels, diesel, no. 2		TWA: 100 mg/m ³ Skin	
2-Ethylhexanoic acid		TWA: 5 mg/m ³	

Component	European Union	The United Kingdom	Germany
Hexanoic acid, 2-ethyl-, chromium(3+) salt		STEL: 1.5 mg/m ³ 15 min TWA: 0.5 mg/m ³ 8 hr	

Exposure Controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Wear safety glasses with side shields (or goggles)

Hand Protection

Protective gloves

Skin and body protection

Long sleeved clothing

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves.

(Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators

Recommended Filter type:

Organic gases and vapours filter Type A Brown conforming to EN14387

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

When RPE is used a face piece Fit Test should be conducted

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice

Environmental exposure controls

Prevent product from entering drains

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Green
Physical State	Liquid
Odor	No information available
Odor Threshold	No data available
pH	Not applicable

Melting Point/Range	No data available
Softening Point	No data available
Boiling Point/Range	265 °C / 509 °F
Flash Point	110 °C / 230 °F

Method - No information available

SAFETY DATA SHEET

Chromium(III) 2-ethylhexanoate, 65-70% in mineral spirits

Revision Date 31-Mar-2025

Evaporation Rate	No data available	
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Vapor Pressure	No data available	
Vapor Density	No data available	(Air = 1.0)
Specific Gravity / Density	1.01	
Bulk Density	Not applicable	Liquid
Water Solubility	No information available	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
2-Ethylhexanoic acid	2.7	
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
Viscosity	No data available	
Explosive Properties	No information available	
Oxidizing Properties	No information available	

SECTION 10: STABILITY AND REACTIVITY

Reactivity

None known, based on information available.

Chemical Stability

Stable under normal conditions.

Possibility of Hazardous Reactions

Hazardous Polymerization	No information available.
Hazardous Reactions	None under normal processing.

Conditions to Avoid

None known.

Incompatible Materials

None known.

Hazardous Decomposition Products

Carbon oxides. Chromium oxide.

SAFETY DATA SHEET

Chromium(III) 2-ethylhexanoate, 65-70% in mineral spirits

Revision Date 31-Mar-2025

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects

Product Information

(a) acute toxicity;

Oral

Based on available data, the classification criteria are not met

Dermal

Based on available data, the classification criteria are not met

Inhalation

Based on available data, the classification criteria are not met

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Hexanoic acid, 2-ethyl-, chromium(3+) salt	-	LD50 > 2000 mg/kg (Rat)	-
Fuels, diesel, no. 2	-	LD50 > 2000 mg/kg (Rabbit)	LC50 = 5.4 mg/L (Rat) 4 h LC50 = 3.6 mg/L (Rat) 4 h
2-Ethylhexanoic acid	LD50 = 1600 mg/kg (Rat)	LD50 = 1140 mg/kg (Rabbit)	-

(b) skin corrosion/irritation;

No data available

(c) serious eye damage/irritation;

No data available

(d) respiratory or skin sensitization;

Respiratory

No data available

Skin

No data available

(e) germ cell mutagenicity;

No data available

(f) carcinogenicity;

Category 2

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity;

Category 1B

(h) STOT-single exposure;

No data available

(i) STOT-repeated exposure;

No data available

Target Organs

None known.

(j) aspiration hazard;

No data available

Symptoms / effects, both acute and delayed

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Endocrine Disrupting Properties

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

SAFETY DATA SHEET

Chromium(III) 2-ethylhexanoate, 65-70% in mineral spirits

Revision Date 31-Mar-2025

Ecotoxicity effects

Contains a substance which is: Harmful to aquatic organisms. The product contains following substances which are hazardous for the environment. May cause long-term adverse effects in the environment. Do not allow material to contaminate ground water system.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Fuels, diesel, no. 2	LC50: = 35 mg/L, 96h flow-through (Pimephales promelas)			
2-Ethylhexanoic acid	LC50: = 70 mg/L, 96h (Pimephales promelas)	EC50: = 85.4 mg/L, 48h (Daphnia magna)	EC50: = 41 mg/L, 96h (Desmodesmus subspicatus) EC50: = 61 mg/L, 72h (Desmodesmus subspicatus)	EC50 = 110 mg/L 17 h EC50 = 670 mg/L 30 min

Persistence and degradability

Product contains heavy metals. Discharge into the environment must be avoided. Special pre-treatment is necessary

Persistence
Degradation in sewage
treatment plant

May persist.

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

Bioaccumulative potential

Product has a high potential to bioconcentrate

Component	log Pow	Bioconcentration factor (BCF)
2-Ethylhexanoic acid	2.7	No data available

Mobility in soil

No information available.

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

Other adverse effects

No information available

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous Dispose of in accordance with the European Directives on waste and hazardous waste Dispose of in accordance with local regulations

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point.

Other Information

Do not flush to sewer Waste codes should be assigned by the user based on the application for which the product was used Do not empty into drains

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

Not regulated

Road and Rail Transport

Not regulated

SAFETY DATA SHEET

Chromium(III) 2-ethylhexanoate, 65-70% in mineral spirits

Revision Date 31-Mar-2025

IATA Not regulated

Special Precautions for User No special precautions required

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories China X = listed Australia U.S.A. (TSCA) Canada (DSL/NDSL) Europe (EINECS/ELINCS/NLP) Australia (AICS) Korea (KECL) China (IECSC) Japan (ENCS) Philippines (PICCS) Taiwan (TCSI) Japan (ISHL) New Zealand (NZIoC) Japan (ISHL)

Component	EINECS	TSCA	DSL	PICCS	ENCS	ISHL	IECSC	AICS	KECL
Hexanoic acid, 2-ethyl-, chromium(3+) salt	222-357-3	X	X	X	-		X	X	KE-14-0060
Fuels, diesel, no. 2	270-676-1	X	X	X	-		X	X	KE-17287
2-Ethylhexanoic acid	205-743-6	X	X	X	X	X	X	X	KE-13740

Component	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
2-Ethylhexanoic acid				Annex I - Y34

National Regulations

Persistent Organic Pollutant This product does not contain any known or suspected substance
Ozone Depletion Potential This product does not contain any known or suspected substance

SECTION 16: OTHER INFORMATION

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

POW - Partition coefficient Octanol:Water

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

SAFETY DATA SHEET

Chromium(III) 2-ethylhexanoate, 65-70% in mineral spirits

Revision Date 31-Mar-2025

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Prepared By

Health, Safety and Environmental Department

Revision Date

31-Mar-2025

Revision Summary

SDS sections updated.

**In accordance with local and national regulations: Occupational Safety and Health
(Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013**

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet