

Creation Date 05-Jan-2011

Revision Date 20-Oct-2023

Revision Number 12

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: Aqualine™ Electrolyte A. An anolyte for general use
Cat No. : AL2500-500
Synonyms Karl Fischer reagent

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

EU entity/business name
Thermo Fisher Scientific
Janssen Pharmaceuticaaan 3a
2440 Geel, Belgium

UK entity/business name
Fisher Scientific UK
Bishop Meadow Road, Loughborough,
Leicestershire LE11 5RG, United Kingdom

Swiss distributor - Fisher Scientific AG
Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
e-mail - infoch@thermofisher.com

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

Tel: 01509 231166
Chemtrec US: (800) 424-9300
Chemtrec EU: 001-703-527-3887

For customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

SAFETY DATA SHEET

Aqualine™ Electrolyte A. An anolyte for general use

Revision Date 20-Oct-2023

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Flammable liquids

Category 2 (H225)

Health hazards

Acute oral toxicity

Category 3 (H301)

Acute dermal toxicity

Category 3 (H311)

Acute Inhalation Toxicity - Vapors

Category 3 (H331)

Skin Corrosion/Irritation

Category 1 B (H314)

Serious Eye Damage/Eye Irritation

Category 1 (H318)

Carcinogenicity

Category 2 (H351)

Reproductive Toxicity

Category 2 (H361d)

Specific target organ toxicity - (single exposure)

Category 1 (H370)

Specific target organ toxicity - (repeated exposure)

Category 1 (H372)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H301 + H311 + H331 - Toxic if swallowed, in contact with skin or if inhaled

H314 - Causes severe skin burns and eye damage

H351 - Suspected of causing cancer

H361d - Suspected of damaging the unborn child

H370 - Causes damage to organs

H372 - Causes damage to organs through prolonged or repeated exposure

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/physician

P308 + P311 - IF exposed or concerned: Call a POISON CENTER or doctor

Additional EU labelling

SAFETY DATA SHEET

Aqualine™ Electrolyte A. An anolyte for general use

Revision Date 20-Oct-2023

For use in industrial installations only

2.3. Other hazards

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Methanol	67-56-1	200-659-6	25-50	Flam. Liq. 2 (H225) Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370)
Chloroform	67-66-3	200-663-8	10-20	Acute Tox. 4 (H302) Acute Tox. 3 (H331) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) STOT SE 3 (H336) Carc. 2 (H351) Repr. 2 (H361d) STOT RE 1 (H372)
2-Amino-2-methyl-1-propanol	124-68-5	EEC No. 204-709-8	10-20	Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Aquatic Chronic 3 (H412)
Pyridine, 2,4,6-trimethyl-	108-75-8	EEC No. 203-613-3	10-20	Flam Liq. 3 (H226) Acute Tox. 3 (H311) Acute Tox. 4 (H302) Acute Tox. 4 (H332) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) STOT SE 3 (H335)
Sulfur dioxide	7446-09-5	EEC No. 231-195-2	5-10	Acute Tox. 3 (H331) Skin Corr. 1B (H314) Eye Dam. 1 (H318)
Iodine	7553-56-2	231-442-4	5-10	Acute Tox. 4 (H302) Acute Tox. 4 (H312) Acute Tox. 4 (H332) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) STOT SE 3 (H335) STOT RE 1 (H372) Aquatic Acute 1 (H400)
Toluene, 4-sulfonic acid, monohydrate	6192-52-5		0.1-1	Skin Corr. 1C (H314) Eye Dam. 1 (H318)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Methanol	STOT Single Exp. 1 :: >= 10 STOT Single Exp. 2 :: 3 - < 10	-	-
Chloroform	STOT RE 2 : C ≥ 5 %	-	-
Iodine	-	1	-

Components	Reach Registration Number
Methanol	01-2119433307-44
Chloroform	01-2119486657-20
2-Amino-2-methyl-1-propanol	01-2119475788-16
Sulfur dioxide	01-2119485028-34

SAFETY DATA SHEET

Aqualine™ Electrolyte A. An anolyte for general use

Revision Date 20-Oct-2023

Iodine	01-2119485285-30	
--------	------------------	--

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.
Ingestion	Do NOT induce vomiting. Call a physician or poison control center immediately.
Inhalation	If not breathing, give artificial respiration. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Remove to fresh air. Immediate medical attention is required.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. Difficulty in breathing. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically. Symptoms may be delayed.
---------------------------	---

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Water mist may be used to cool closed containers. CO₂, dry chemical, dry sand, alcohol-resistant foam.

Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂), Nitrogen oxides (NO_x), Chlorine, Hydrogen halides, Formaldehyde.

SAFETY DATA SHEET

Aqualine™ Electrolyte A. An anolyte for general use

Revision Date 20-Oct-2023

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area. Corrosives area.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Class 3

Switzerland - Storage of hazardous substances

Storage class - SC 3
<https://www.kvu.ch/de/themen/stoffe-und-produkte>
<https://www.kvu.ch/fr/themes/substances-et-produits>
<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

SAFETY DATA SHEET

Aqualine™ Electrolyte A. An anolyte for general use

Revision Date 20-Oct-2023

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Methanol	TWA: 200 ppm 8 hr TWA: 260 mg/m ³ 8 hr Skin	WEL - TWA: 200 ppm TWA: 266 mg/m ³ TWA WEL - STEL: 250 ppm STEL: 333 mg/m ³ STEL	TWA / VME: 200 ppm (8 heures). restrictive limit TWA / VME: 260 mg/m ³ (8 heures). restrictive limit STEL / VLCT: 1000 ppm. restrictive limit STEL / VLCT: 1300 mg/m ³ . restrictive limit Peau	TWA: 200 ppm 8 uren TWA: 266 mg/m ³ 8 uren STEL: 250 ppm 15 minuten STEL: 333 mg/m ³ 15 minuten Huid	TWA / VLA-ED: 200 ppm (8 horas) TWA / VLA-ED: 266 mg/m ³ (8 horas) Piel
Chloroform	TWA: 2 ppm 8 hr TWA: 10 mg/m ³ 8 hr Possibility of significant uptake through the skin	TWA: 2 ppm TWA: 9.9 mg/m ³ STEL: 6 ppm STEL: 29.7 mg/m ³	TWA / VME: 2 ppm (8 heures). restrictive limit TWA / VME: 10 mg/m ³ (8 heures). restrictive limit STEL / VLCT: 50 ppm. STEL / VLCT: 250 mg/m ³ . Peau	TWA: 2 ppm 8 uren TWA: 10 mg/m ³ 8 uren Huid	TWA / VLA-ED: 2 ppm (8 horas) TWA / VLA-ED: 10 mg/m ³ (8 horas) Piel
Sulfur dioxide	TWA: 1.3 mg/m ³ (15min) TWA: 0.5 ppm (15min) STEL: 2.7 mg/m ³ (8h) STEL: 1 ppm (8h)	STEL: 1 ppm 15 min STEL: 2.7 mg/m ³ 15 min TWA: 0.5 ppm 8 hr TWA: 1.3 mg/m ³ 8 hr	TWA / VME: 0.5 ppm (8 heures). TWA / VME: 1.3 mg/m ³ (8 heures). STEL / VLCT: 1 ppm. indicative limit STEL / VLCT: 2.7 mg/m ³ . indicative limit	TWA: 0.5 ppm 8 uren TWA: 1.3 mg/m ³ 8 uren STEL: 1 ppm 15 minuten STEL: 2.7 mg/m ³ 15 minuten	STEL / VLA-EC: 2 ppm (15 minutos). STEL / VLA-EC: 5.28 mg/m ³ (15 minutos). TWA / VLA-ED: 0.5 ppm (8 horas) TWA / VLA-ED: 1.32 mg/m ³ (8 horas)
Iodine		STEL: 0.1 ppm 15 min STEL: 1.1 mg/m ³ 15 min	STEL / VLCT: 0.1 ppm. STEL / VLCT: 1 mg/m ³ .	TWA: 0.01 ppm 8 uren TWA: 0.1 mg/m ³ 8 uren STEL: 0.1 ppm 15 minuten STEL: 1 mg/m ³ 15 minuten	STEL / VLA-EC: 0.1 ppm (15 minutos). STEL / VLA-EC: 1 mg/m ³ (15 minutos). TWA / VLA-ED: 0.01 ppm (8 horas) TWA / VLA-ED: 0.1 mg/m ³ (8 horas)

Component	Italy	Germany	Portugal	The Netherlands	Finland
Methanol	TWA: 200 ppm 8 ore. Time Weighted Average TWA: 260 mg/m ³ 8 ore. Time Weighted Average Pelle	100 ppm TWA MAK; 130 mg/m ³ TWA MAKSkin absorber	STEL: 250 ppm 15 minutos TWA: 200 ppm 8 horas TWA: 260 mg/m ³ 8 horas Pele	huid TWA: 133 mg/m ³ 8 uren	TWA: 200 ppm 8 tunteina TWA: 270 mg/m ³ 8 tunteina STEL: 250 ppm 15 minuutteina STEL: 330 mg/m ³ 15 minuutteina Iho
Chloroform	TWA: 2 ppm 8 ore. Media Ponderata nel Tempo TWA: 10 mg/m ³ 8 ore. Media Ponderata nel Tempo Pelle	0.5 ppm TWA MAK 2.5 mg/m ³ TWA MAK	TWA: 2 ppm 8 horas TWA: 10 mg/m ³ 8 horas Pele	STEL: 25 mg/m ³ 15 minuten TWA: 5 mg/m ³ 8 uren	TWA: 2 ppm 8 tunteina TWA: 10 mg/m ³ 8 tunteina STEL: 4 ppm 15 minuutteina STEL: 20 mg/m ³ 15 minuutteina Iho

SAFETY DATA SHEET

Aqualine™ Electrolyte A. An anolyte for general use

Revision Date 20-Oct-2023

2-Amino-2-methyl-1-propanol		TWA: 1 ppm (8 Stunden). AGW - exposure factor 2 TWA: 3.7 mg/m³ (8 Stunden). AGW - exposure factor 2 TWA: 1 ppm (8 Stunden). MAK can occur as vapor and aerosol at the same time TWA: 3.7 mg/m³ (8 Stunden). MAK can occur as vapor and aerosol at the same time Höhepunkt: 2 ppm Höhepunkt: 7.4 mg/m³ Haut			
Sulfur dioxide	TWA: 1.3 mg/m³ 8 ore. Time Weighted Average TWA: 0.5 ppm 8 ore. Time Weighted Average STEL: 2.7 mg/m³ 15 minuti. Short-term STEL: 1 ppm 15 minuti. Short-term	TWA: 1 ppm TWA: 2.5 mg/m³	STEL: 1 ppm 15 minutos STEL: 2.7 mg/m³ 15 minutos TWA: 0.5 ppm 8 horas TWA: 1.3 mg/m³ 8 horas	STEL: 0.7 mg/m³ MAC: 2 ppm MAC: 5 mg/m³	TWA: 0.5 ppm 8 tunteina TWA: 1.3 mg/m³ 8 tunteina STEL: 1 ppm 15 minuutteina STEL: 2.7 mg/m³ 15 minuutteina
Iodine		Haut	STEL: 0.1 ppm 15 minutos TWA: 0.01 ppm 8 horas		STEL: 0.1 ppm 15 minuutteina STEL: 1.1 mg/m³ 15 minuutteina Iho

Component	Austria	Denmark	Switzerland	Poland	Norway
Methanol	Haut MAK-KZGW: 800 ppm 15 Minuten MAK-KZGW: 1040 mg/m³ 15 Minuten MAK-TMW: 200 ppm 8 Stunden MAK-TMW: 260 mg/m³ 8 Stunden	TWA: 200 ppm 8 timer TWA: 260 mg/m³ 8 timer STEL: 400 ppm 15 minutter STEL: 520 mg/m³ 15 minutter Hud	Haut/Peau STEL: 400 ppm 15 Minuten STEL: 520 mg/m³ 15 Minuten TWA: 200 ppm 8 Stunden TWA: 260 mg/m³ 8 Stunden	STEL: 300 mg/m³ 15 minutach TWA: 100 mg/m³ 8 godzinach	TWA: 100 ppm 8 timer TWA: 130 mg/m³ 8 timer STEL: 150 ppm 15 minutter. value calculated STEL: 162.5 mg/m³ 15 minutter. value calculated Hud
Chloroform	Haut MAK-TMW: 2 ppm 8 Stunden MAK-TMW: 10 mg/m³ 8 Stunden	TWA: 2 ppm 8 timer TWA: 10 mg/m³ 8 timer Hud	Haut/Peau STEL: 1 ppm 15 Minuten STEL: 5 mg/m³ 15 Minuten TWA: 0.5 ppm 8 Stunden TWA: 2.5 mg/m³ 8 Stunden	TWA: 8 mg/m³ 8 godzinach	TWA: 2 ppm 8 timer TWA: 10 mg/m³ 8 timer 4 ppm STEL (value calculated) 15 mg/m³ STEL (value calculated) Hud
2-Amino-2-methyl-1-propanol			Haut/Peau STEL: 4.8 ppm 15 Minuten STEL: 17.4 mg/m³ 15 Minuten TWA: 2.4 ppm 8 Stunden TWA: 8.7 mg/m³ 8 Stunden		
Sulfur dioxide	MAK-KZGW: 1 ppm 15 Minuten MAK-KZGW: 2.7 mg/m³ 15 Minuten MAK-TMW: 0.5 ppm 8 Stunden MAK-TMW: 1.3 mg/m³ 8 Stunden	TWA: 0.5 ppm 8 timer TWA: 1.3 mg/m³ 8 timer STEL: 2.7 mg/m³ 15 minutter STEL: 1 ppm 15 minutter	STEL: 1 ppm 15 Minuten STEL: 2.7 mg/m³ 15 Minuten TWA: 0.5 ppm 8 Stunden TWA: 1.3 mg/m³ 8 Stunden	STEL: 2.7 mg/m³ 15 minutach TWA: 1.3 mg/m³ 8 godzinach	TWA: 0.5 ppm 8 timer TWA: 1.3 mg/m³ 8 timer STEL: 1 ppm 15 minutter. value from the regulation STEL: 2.7 mg/m³ 15 minutter. value from the regulation

SAFETY DATA SHEET

Aqualine™ Electrolyte A. An anolyte for general use

Revision Date 20-Oct-2023

Iodine	Haut MAK-KZGW: 0.1 ppm 15 Minuten MAK-KZGW: 1 mg/m ³ 15 Minuten MAK-TMW: 0.1 ppm 8 Stunden MAK-TMW: 1 mg/m ³ 8 Stunden Ceiling: 0.1 ppm Ceiling: 1 mg/m ³	Ceiling: 0.1 ppm Ceiling: 1 mg/m ³	Haut/Peau STEL: 0.1 ppm 15 Minuten STEL: 1 mg/m ³ 15 Minuten TWA: 0.1 ppm 8 Stunden TWA: 1 mg/m ³ 8 Stunden	STEL: 1 mg/m ³ 15 minutach TWA: 0.5 mg/m ³ 8 godzinach	Ceiling: 0.1 ppm Ceiling: 1 mg/m ³
--------	--	--	---	---	--

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Methanol	TWA: 200 ppm TWA: 260.0 mg/m ³ Skin notation	kože TWA-GVI: 200 ppm 8 satima. TWA-GVI: 260 mg/m ³ 8 satima.	TWA: 200 ppm 8 hr. TWA: 260 mg/m ³ 8 hr. STEL: 600 ppm 15 min STEL: 780 mg/m ³ 15 min Skin	Skin-potential for cutaneous absorption TWA: 200 ppm TWA: 260 mg/m ³	TWA: 250 mg/m ³ 8 hodinách. Potential for cutaneous absorption Ceiling: 1000 mg/m ³
Chloroform	TWA: 2 ppm TWA: 10.0 mg/m ³ Skin notation	kože TWA-GVI: 2 ppm 8 satima. TWA-GVI: 10 mg/m ³ 8 satima.	TWA: 2 ppm 8 hr. TWA: 9.8 mg/m ³ 8 hr. STEL: 6 ppm 15 min STEL: 29.4 mg/m ³ 15 min Skin	Skin-potential for cutaneous absorption TWA: 2 ppm TWA: 10 mg/m ³	TWA: 10 mg/m ³ 8 hodinách. Potential for cutaneous absorption Ceiling: 20 mg/m ³
Sulfur dioxide	TWA: 1.3 mg/m ³ TWA: 0.5 ppm STEL : 2.7 mg/m ³ STEL : 1 ppm	TWA-GVI: 0.5 ppm 8 satima. TWA-GVI: 1.3 mg/m ³ 8 satima. STEL-KGVI: 1 ppm 15 minutama. STEL-KGVI: 2.7 mg/m ³ 15 minutama.	TWA: 0.5 ppm 8 hr. TWA: 1.3 mg/m ³ 8 hr. STEL: 2.7 mg/m ³ 15 min STEL: 1 ppm 15 min	STEL: 2.7 mg/m ³ STEL: 1 ppm TWA: 1.3 mg/m ³ TWA: 0.5 ppm	TWA: 1.3 mg/m ³ 8 hodinách. Ceiling: 2.7 mg/m ³
Iodine	TWA: 3.0 mg/m ³	STEL-KGVI: 0.1 ppm 15 minutama. STEL-KGVI: 1.1 mg/m ³ 15 minutama.	TWA: 0.01 ppm 8 hr. inhalable fraction and vapour TWA: 0.01 mg/m ³ 8 hr. STEL: 0.1 ppm 15 min		TWA: 0.1 mg/m ³ 8 hodinách. Ceiling: 1 mg/m ³

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Methanol	Nahk TWA: 200 ppm 8 tundides. TWA: 250 mg/m ³ 8 tundides. STEL: 250 ppm 15 minutites. STEL: 350 mg/m ³ 15 minutites.	Skin notation TWA: 200 ppm 8 hr TWA: 260 mg/m ³ 8 hr	skin - potential for cutaneous absorption STEL: 250 ppm STEL: 325 mg/m ³ TWA: 200 ppm TWA: 260 mg/m ³	TWA: 260 mg/m ³ 8 órában. AK lehetséges borón keresztüli felszívódás	TWA: 200 ppm 8 klukkustundum. TWA: 260 mg/m ³ 8 klukkustundum. Skin notation Ceiling: 400 ppm Ceiling: 520 mg/m ³
Chloroform	Nahk TWA: 2 ppm 8 tundides. TWA: 10 mg/m ³ 8 tundides.	Skin notation TWA: 2 ppm 8 hr TWA: 10 mg/m ³ 8 hr	TWA: 10 ppm TWA: 50 mg/m ³	TWA: 10 mg/m ³ 8 órában. AK	TWA: 2 ppm 8 klukkustundum. TWA: 10 mg/m ³ 8 klukkustundum. Skin notation Ceiling: 4 ppm Ceiling: 20 mg/m ³
Sulfur dioxide	TWA: 0.5 ppm 8 tundides. TWA: 1.3 mg/m ³ 8 tundides. STEL: 1 ppm 15 minutites. STEL: 2.7 mg/m ³ 15 minutites.	TWA: 1.3 mg/m ³ 8 hr TWA: 0.5 ppm 8 hr STEL: 2.7 mg/m ³ 15 min STEL: 1 ppm 15 min	STEL: 1 ppm STEL: 2.7 mg/m ³ TWA: 0.5 ppm TWA: 1.3 mg/m ³	STEL: 2.7 mg/m ³ 15 percekben. CK TWA: 1.3 mg/m ³ 8 órában. AK	STEL: 1 ppm STEL: 2.7 mg/m ³ TWA: 0.5 ppm 8 klukkustundum. TWA: 1.3 mg/m ³ 8 klukkustundum.
Iodine	STEL: 0.1 ppm 15 minutites. STEL: 1 mg/m ³ 15 minutites.		STEL: 0.1 ppm STEL: 1 mg/m ³ TWA: 0.1 ppm TWA: 1 mg/m ³	STEL: 1 mg/m ³ 15 percekben. CK TWA: 1 mg/m ³ 8 órában. AK lehetséges borón	STEL: 0.1 ppm STEL: 1 mg/m ³

SAFETY DATA SHEET

Aqualine™ Electrolyte A. An anolyte for general use

Revision Date 20-Oct-2023

				keresztüli felszívódás	
Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Methanol	skin - potential for cutaneous exposure TWA: 200 ppm TWA: 260 mg/m ³	TWA: 200 ppm IPRD TWA: 260 mg/m ³ IPRD Oda	Possibility of significant uptake through the skin TWA: 200 ppm 8 Stunden TWA: 260 mg/m ³ 8 Stunden	possibility of significant uptake through the skin TWA: 200 ppm TWA: 260 mg/m ³	Skin notation TWA: 200 ppm 8 ore TWA: 260 mg/m ³ 8 ore
Chloroform	skin - potential for cutaneous exposure TWA: 2 ppm TWA: 10 mg/m ³	TWA: 10 mg/m ³ IPRD TWA: 2 ppm IPRD Oda	Possibility of significant uptake through the skin TWA: 2 ppm 8 Stunden TWA: 10 mg/m ³ 8 Stunden	possibility of significant uptake through the skin TWA: 2 ppm TWA: 10 mg/m ³	Skin notation TWA: 2 ppm 8 ore TWA: 10 mg/m ³ 8 ore
Sulfur dioxide	STEL: 2.7 mg/m ³ STEL: 1 ppm TWA: 1.3 mg/m ³ TWA: 0.5 ppm	TWA: 1.3 mg/m ³ IPRD TWA: 0.5 ppm IPRD STEL: 2.7 mg/m ³ STEL: 1 ppm	TWA: 1.3 mg/m ³ 8 Stunden TWA: 0.5 ppm 8 Stunden STEL: 2.7 mg/m ³ 15 Minuten STEL: 1 ppm 15 Minuten	TWA: 0.5 ppm TWA: 1.3 mg/m ³ STEL: 1 ppm 15 minuti STEL: 2.7 mg/m ³ 15 minuti	TWA: 0.5 ppm 8 ore TWA: 1.3 mg/m ³ 8 ore STEL: 1 ppm 15 minute STEL: 2.7 mg/m ³ 15 minute
Iodine	TWA: 1 mg/m ³	Ceiling: 0.1 ppm Ceiling: 1 mg/m ³			TWA: 0.09 ppm 8 ore TWA: 0.5 mg/m ³ 8 ore STEL: 0.2 ppm 15 minute STEL: 1 mg/m ³ 15 minute

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Methanol	TWA: 5 mg/m ³ 1250 Skin notation MAC: 15 mg/m ³	Potential for cutaneous absorption TWA: 200 ppm TWA: 260 mg/m ³	TWA: 200 ppm 8 urah TWA: 260 mg/m ³ 8 urah Koža STEL: 800 ppm 15 minutah STEL: 1040 mg/m ³ 15 minutah	Indicative STEL: 250 ppm 15 minuter Indicative STEL: 350 mg/m ³ 15 minuter TLV: 200 ppm 8 timmar. NGV TLV: 250 mg/m ³ 8 timmar. NGV Hud	Deri TWA: 200 ppm 8 saat TWA: 260 mg/m ³ 8 saat
Chloroform	TWA: 5 mg/m ³ 2019 Skin notation STEL: 10 mg/m ³ 2019	Potential for cutaneous absorption TWA: 2 ppm TWA: 10 mg/m ³	TWA: 2 ppm 8 urah TWA: 10 mg/m ³ 8 urah Koža	Indicative STEL: 5 ppm 15 minuter Indicative STEL: 25 mg/m ³ 15 minuter LLV: 2 ppm 8 timmar. LLV: 10 mg/m ³ 8 timmar. Hud	Deri TWA: 2 ppm 8 saat TWA: 10 mg/m ³ 8 saat
2-Amino-2-methyl-1-propanol			TWA: 3.7 mg/m ³ 8 urah TWA: 1 ppm 8 urah Koža STEL: 2 ppm 15 minutah STEL: 7.4 mg/m ³ 15 minutah		
Sulfur dioxide	Skin notation MAC: 10 mg/m ³	Ceiling: 2.7 mg/m ³ TWA: 0.5 ppm TWA: 1.3 mg/m ³	TWA: 0.5 ppm 8 urah TWA: 1.3 mg/m ³ 8 urah STEL: 1 ppm 15 minutah STEL: 2.7 mg/m ³ 15 minutah	Binding STEL: 1 ppm 15 minuter Binding STEL: 2.7 mg/m ³ 15 minuter TLV: 0.5 ppm 8 timmar. NGV TLV: 1.3 mg/m ³ 8 timmar. NGV	
Iodine	Skin notation MAC: 1 mg/m ³	Ceiling: 1.1 mg/m ³ TWA: 0.1 ppm TWA: 1.1 mg/m ³		Binding STEL: 0.1 ppm 15 minuter Binding STEL: 1 mg/m ³ 15 minuter	

Biological limit values

SAFETY DATA SHEET

Aqualine™ Electrolyte A. An anolyte for general use

Revision Date 20-Oct-2023

List source(s):

Component	European Union	United Kingdom	France	Spain	Germany
Methanol			Methanol: 15 mg/L urine end of shift	Methanol: 15 mg/L urine end of shift	Methanol: 15 mg/L urine (end of shift) Methanol: 15 mg/L urine (for long-term exposures: at the end of the shift after several shifts)

Component	Italy	Finland	Denmark	Bulgaria	Romania
Methanol					Methanol: 6 mg/L urine end of shift

Component	Gibraltar	Latvia	Slovak Republic	Luxembourg	Turkey
Methanol			Methanol: 30 mg/L urine end of exposure or work shift Methanol: 30 mg/L urine after all work shifts for long-term exposure		

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Methanol 67-56-1 (25-50)		DNEL = 20mg/kg bw/day		DNEL = 20mg/kg bw/day
Chloroform 67-66-3 (10-20)				DNEL = 0.94mg/kg bw/day
2-Amino-2-methyl-1-propanol 124-68-5 (10-20)				DNEL = 7.3mg/kg bw/day
Iodine 7553-56-2 (5-10)				DNEL = 0.01mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Methanol 67-56-1 (25-50)	DNEL = 130mg/m ³	DNEL = 130mg/m ³	DNEL = 130mg/m ³	DNEL = 130mg/m ³
Chloroform 67-66-3 (10-20)		DNEL = 333mg/m ³	DNEL = 2.5mg/m ³	DNEL = 2.5mg/m ³
2-Amino-2-methyl-1-propanol 124-68-5 (10-20)				DNEL = 6.5mg/m ³
Sulfur dioxide 7446-09-5 (5-10)	DNEL = 2.7mg/m ³		DNEL = 2.7mg/m ³	
Iodine 7553-56-2 (5-10)				DNEL = 0.07mg/m ³

SAFETY DATA SHEET

Aqualine™ Electrolyte A. An anolyte for general use

Revision Date 20-Oct-2023

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Methanol 67-56-1 (25-50)	PNEC = 20.8mg/L	PNEC = 77mg/kg sediment dw	PNEC = 1540mg/L	PNEC = 100mg/L	PNEC = 100mg/kg soil dw
Chloroform 67-66-3 (10-20)	PNEC = 0.146mg/L	PNEC = 0.45mg/kg sediment dw	PNEC = 0.133mg/L	PNEC = 0.048mg/L	PNEC = 0.56mg/kg soil dw
2-Amino-2-methyl-1-propanol 124-68-5 (10-20)	PNEC = 0.188mg/L	PNEC = 0.71mg/kg sediment dw	PNEC = 1.88mg/L	PNEC = 10mg/L	PNEC = 0.03mg/kg soil dw
Iodine 7553-56-2 (5-10)	PNEC = 18.13µg/L	PNEC = 3.99mg/kg sediment dw		PNEC = 11mg/L	PNEC = 5.95mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Methanol 67-56-1 (25-50)	PNEC = 2.08mg/L	PNEC = 7.7mg/kg sediment dw			
Chloroform 67-66-3 (10-20)	PNEC = 0.015mg/L	PNEC = 0.09mg/kg sediment dw			
2-Amino-2-methyl-1-propanol 124-68-5 (10-20)	PNEC = 0.0188mg/L	PNEC = 0.071mg/kg sediment dw			
Iodine 7553-56-2 (5-10)	PNEC = 60.01µg/L	PNEC = 20.22mg/kg sediment dw			

8.2. Exposure controls

Engineering Measures

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles (European standard - EN 166)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Viton (R)	See manufacturers recommendations	-	EN 374	(minimum requirement)

Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatibility, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced
Recommended Filter type: low boiling organic solvent Type AX Brown conforming to

SAFETY DATA SHEET

Aqualine™ Electrolyte A. An anolyte for general use

Revision Date 20-Oct-2023

EN371

Small scale/Laboratory use	Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141 When RPE is used a face piece Fit Test should be conducted
Environmental exposure controls	Prevent product from entering drains. Do not allow material to contaminate ground water system.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance		
Odor	Alcohol-like	
Odor Threshold	No data available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flammability (liquid)	Highly flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Flash Point	10 °C / 50 °F	Method - No information available
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
pH	No information available	
Viscosity	No data available	
Water Solubility	Partially soluble	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Methanol	-0.74	
Chloroform	2	
2-Amino-2-methyl-1-propanol	-0.63	
Iodine	2.49	
Vapor Pressure	No data available	
Density / Specific Gravity	1.16	
Bulk Density	Not applicable	Liquid
Vapor Density	No data available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

Explosive Properties	Vapors may form explosive mixtures with air
-----------------------------	---

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity	None known, based on information available
-------------------------	--

10.2. Chemical stability	Stable under normal conditions.
---------------------------------	---------------------------------

SAFETY DATA SHEET

Aqualine™ Electrolyte A. An anolyte for general use

Revision Date 20-Oct-2023

10.3. Possibility of hazardous reactions

Hazardous Polymerization Hazardous Reactions

Hazardous polymerization does not occur.
None under normal processing.

10.4. Conditions to avoid

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents. Strong acids. Strong bases. Finely powdered metals.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂). Nitrogen oxides (NO_x). Chlorine. Hydrogen halides. Formaldehyde.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral	Category 3
Dermal	Category 3
Inhalation	Category 3

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methanol	LD50 = 1187 – 2769 mg/kg (Rat)	LD50 = 17100 mg/kg (Rabbit)	LC50 = 128.2 mg/L (Rat) 4 h
Chloroform	LD50 = 908 mg/kg (rat) LD50 = 695 mg/kg (Rat) LD50 = 450 mg/kg (Rat)	LD50 > 20 g/kg (Rabbit)	LC50 = 10.5 mg/L (Rat) 4 h
2-Amino-2-methyl-1-propanol	LD50 = 2900 mg/kg (Rat)	>2000 mg/kg (Rabbit)	-
Pyridine, 2,4,6-trimethyl-	400 mg/kg (Rat)	1000 mg/kg (Guinea Pig)	-
Sulfur dioxide	-	-	Per CGA P-20: 2500 ppm/1hr (Rat)
Iodine	315 mg/kg (Rat)	1425 mg/kg (Rabbit)	4.588 mg/L 4h (Rat)
Toluene, 4-sulfonic acid, monohydrate	2570 mg/kg (Rat)	-	-

(b) skin corrosion/irritation; Category 1 B

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;

Respiratory	No data available
Skin	No data available

Component	Test method	Test species	Study result
Methanol 67-56-1 (25-50)	OECD Test Guideline 406 Guinea Pig Maximisation Test (GPMT)	guinea pig	non-sensitising
Iodine 7553-56-2 (5-10)	OECD Test Guideline 429 Local Lymph Node Assay	mouse	non-sensitising

SAFETY DATA SHEET

Aqualine™ Electrolyte A. An anolyte for general use

Revision Date 20-Oct-2023

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; Category 2

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Chloroform				Group 2B

(g) reproductive toxicity; Category 2

Component	Test method	Test species / Duration	Study result
Methanol 67-56-1 (25-50)	OECD Test Guideline 416	Rat / Inhalation 2 Generation	NOAEC = 1.3 mg/l (air)

(h) STOT-single exposure; Category 1

Results / Target organs Optic nerve, Respiratory system, Central nervous system (CNS).

(i) STOT-repeated exposure; Category 1

Route of exposure Inhalation
Target Organs Liver, Kidney, Thyroid.

(j) aspiration hazard; No data available

Symptoms / effects, both acute and delayed Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Methanol	Pimephales promelas: LC50 > 10000 mg/L 96h	EC50 > 10000 mg/L 24h	
Chloroform	LC50: = 300 mg/L, 96h static (Poecilia reticulata) LC50: = 18 mg/L, 96h flow-through (Lepomis macrochirus) LC50: = 18 mg/L, 96h flow-through (Oncorhynchus mykiss) LC50: = 71 mg/L, 96h flow-through (Pimephales promelas)	EC50 = 28.9 mg/L/48h	EC50 = 560 mg/L/48h

SAFETY DATA SHEET

Aqualine™ Electrolyte A. An anolyte for general use

Revision Date 20-Oct-2023

2-Amino-2-methyl-1-propanol	LC50: = 190 mg/L, 96h static (Lepomis macrochirus)	EC50: = 193 mg/L, 48h (Daphnia magna)	EC50: = 520 mg/L, 72h (Desmodesmus subspicatus)
Iodine	LC50 = 1.67 mg/L 96h	EC50 = 0.55 mg/L 48h	EC50 = 0.13 mg/L 72h

Component	Microtox	M-Factor
Methanol	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	
Chloroform	Photobacterium phosphoreum: EC50 = 520 mg/L/5 min Photobacterium phosphoreum: EC50 = 670 mg/L/15 min Photobacterium phosphoreum: EC50 = 670 mg/L/30min	
2-Amino-2-methyl-1-propanol	EC50: = 342.9 mg/L, 3 h (Activated Sludge) OECD 209	
Iodine	EC50 = 280 mg/L 3h	1

12.2. Persistence and degradability Not applicable for mixtures

Component	Degradability
Methanol 67-56-1 (25-50)	DT50 ~ 17.2d >94% after 20d

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential

There is no data for this product; Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Methanol	-0.74	<10 dimensionless
Chloroform	2	1.4 - 13 dimensionless
2-Amino-2-methyl-1-propanol	-0.63	<1 dimensionless
Iodine	2.49	No data available

12.4. Mobility in soil

Contains organic solvents. Will likely be mobile in the environment due to its volatility. Disperses rapidly in air

12.5. Results of PBT and vPvB assessment

No data available for assessment.

12.6. Endocrine disrupting properties

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance
This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and

SAFETY DATA SHEET

Aqualine™ Electrolyte A. An anolyte for general use

Revision Date 20-Oct-2023

empty container away from heat and sources of ignition.

European Waste Catalogue (EWC) According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms.

Switzerland - Waste Ordinance Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600
<https://www.fedlex.admin.ch/eli/cc/2015/891/en>

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number UN1992
14.2. UN proper shipping name Flammable liquid, toxic, n.o.s.
Technical Shipping Name Contains methanol, chloroform
14.3. Transport hazard class(es) 3
Subsidiary Hazard Class 6.1
14.4. Packing group II

ADR

14.1. UN number UN1992
14.2. UN proper shipping name Flammable liquid, toxic, n.o.s.
Technical Shipping Name Contains methanol, chloroform
14.3. Transport hazard class(es) 3
Subsidiary Hazard Class 6.1
14.4. Packing group II

IATA

14.1. UN number UN1992
14.2. UN proper shipping name Flammable liquid, toxic, n.o.s.
Technical Shipping Name Contains methanol, chloroform
14.3. Transport hazard class(es) 3
Subsidiary Hazard Class 6.1
14.4. Packing group II

14.5. Environmental hazards No hazards identified

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDL), Australia

SAFETY DATA SHEET

Aqualine™ Electrolyte A. An anolyte for general use

Revision Date 20-Oct-2023

(AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Methanol	67-56-1	200-659-6	-	-	X	X	KE-23193	X	X
Chloroform	67-66-3	200-663-8	-	-	X	X	X	X	X
2-Amino-2-methyl-1-propanol	124-68-5	204-709-8	-	-	X	X	KE-01473	X	X
Pyridine, 2,4,6-trimethyl-	108-75-8	203-613-3	-	-	X	X	-	X	X
Sulfur dioxide	7446-09-5	231-195-2	-	-	X	X	KE-32567	X	X
Iodine	7553-56-2	231-442-4	-	-	X	X	KE-21023	X	-
Toluene, 4-sulfonic acid, monohydrate	6192-52-5	-	-	-	X	X	-	-	-

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Methanol	67-56-1	X	ACTIVE	X	-	X	X	X
Chloroform	67-66-3	X	ACTIVE	X	-	X	X	X
2-Amino-2-methyl-1-propanol	124-68-5	X	ACTIVE	X	-	X	X	X
Pyridine, 2,4,6-trimethyl-	108-75-8	X	ACTIVE	X	-	X	X	X
Sulfur dioxide	7446-09-5	X	ACTIVE	X	-	X	X	X
Iodine	7553-56-2	X	ACTIVE	X	-	X	X	X
Toluene, 4-sulfonic acid, monohydrate	6192-52-5	-	-	-	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Methanol	67-56-1	-	Use restricted. See item 69. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-
Chloroform	67-66-3	-	Use restricted. See item 32. (see http://eur-lex.europa.eu/LexUriServ/LexUriServ.do?uri=CELEX:32006R1907:EN:NOT for restriction details)	-
2-Amino-2-methyl-1-propanol	124-68-5	-	Use restricted. See item 75. (see link for restriction details)	-
Pyridine, 2,4,6-trimethyl-	108-75-8	-	-	-
Sulfur dioxide	7446-09-5	-	Use restricted. See item 75. (see link for restriction details)	-
Iodine	7553-56-2	-	Use restricted. See item 75. (see link for restriction details)	-
Toluene, 4-sulfonic acid, monohydrate	6192-52-5	-	-	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

SAFETY DATA SHEET

Aqualine™ Electrolyte A. An anolyte for general use

Revision Date 20-Oct-2023

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Methanol	67-56-1	500 tonne	5000 tonne
Chloroform	67-66-3	Not applicable	Not applicable
2-Amino-2-methyl-1-propanol	124-68-5	Not applicable	Not applicable
Pyridine, 2,4,6-trimethyl-	108-75-8	Not applicable	Not applicable
Sulfur dioxide	7446-09-5	Not applicable	Not applicable
Iodine	7553-56-2	Not applicable	Not applicable
Toluene, 4-sulfonic acid, monohydrate	6192-52-5	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Component	ANNEX I - PART 1 List of chemicals subject to export notification procedure (referred to in Article 8)	ANNEX I - PART 2 List of chemicals qualifying for PIC notification (referred to in Article 11)	ANNEX I - PART 3 List of chemicals subject to the PIC procedure (referred to in Articles 13 and 14)
Chloroform 67-66-3 (10-20)	b — ban (for the category or categories concerned) b — ban (for the category or categories concerned) i(2) — industrial chemical for public	-	-

<https://eur-lex.europa.eu/legal-content/EN/TXT/?uri=CELEX%3A32012R0649&qid=1604065742303>.

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

Take note of Directive 94/33/EC on the protection of young people at work

Take note of Dir 92/85/EC on the protection of pregnant and breastfeeding women at work

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 3 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Methanol	WGK 2	Class I : 20 mg/m³ (Massenkonzentration)
Chloroform	WGK 3	Class I : 20 mg/m³ (Massenkonzentration)
2-Amino-2-methyl-1-propanol	WGK1	
Sulfur dioxide	WGK1	
Iodine	WGK2	

Component	France - INRS (Tables of occupational diseases)
Methanol	Tableaux des maladies professionnelles (TMP) - RG 84
Chloroform	Tableaux des maladies professionnelles (TMP) - RG 12

SAFETY DATA SHEET

Aqualine™ Electrolyte A. An anolyte for general use

Revision Date 20-Oct-2023

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Methanol 67-56-1 (25-50)	Prohibited and Restricted Substances	Group I	
Chloroform 67-66-3 (10-20)	Prohibited and Restricted Substances		Annex I - industrial chemical
Iodine 7553-56-2 (5-10)	Prohibited and Restricted Substances		
Toluene, 4-sulfonic acid, monohydrate 6192-52-5 (0.1-1)	Prohibited and Restricted Substances		

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H301 - Toxic if swallowed
H311 - Toxic in contact with skin
H331 - Toxic if inhaled
H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage
H370 - Causes damage to organs
H351 - Suspected of causing cancer
H361d - Suspected of damaging the unborn child
H372 - Causes damage to organs through prolonged or repeated exposure
H225 - Highly flammable liquid and vapor
H226 - Flammable liquid and vapor
H302 - Harmful if swallowed
H312 - Harmful in contact with skin
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H332 - Harmful if inhaled
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H400 - Very toxic to aquatic life
H412 - Harmful to aquatic life with long lasting effects

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

SAFETY DATA SHEET

Aqualine™ Electrolyte A. An anolyte for general use

Revision Date 20-Oct-2023

NOEC - No Observed Effect Concentration
PBT - Persistent, Bioaccumulative, Toxic

POW - Partition coefficient Octanol:Water
vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data

Health Hazards Calculation method

Environmental hazards Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Creation Date 05-Jan-2011
Revision Date 20-Oct-2023
Revision Summary Not applicable.

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.
COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No
1907/2006 .**

**For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2,
Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and
Preparations).**

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet