

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: Lithium bis(trimethylsilyl)amide, 1M solution in THF
Cat No. : **S36391**
Synonyms 1,1,1,3,3,3-Hexamethyldisilazane lithium salt; LHMDs

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company Avocado Research Chemicals Ltd.
(Part of Thermo Fisher Scientific)
Shore Road, Heysham
Lancashire, LA3 2XY,
United Kingdom
Office Tel: +44 (0) 1524 850506
Office Fax: +44 (0) 1524 850608

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

Poison Centre - Emergency information services **Ireland** : National Poisons Information Centre (NPIC) -
01 809 2166 (8am-10pm, 7 days a week)
Malta : +356 2395 2000
Cyprus : +357 2240 5611

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Physical hazards

Flammable liquids

Category 2 (H225)

Health hazards

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 1M solution in THF

Revision Date 07-Dec-2024

Skin Corrosion/Irritation
Serious Eye Damage/Eye Irritation
Carcinogenicity
Specific target organ toxicity - (single exposure)

Category 1 B (H314)
Category 1 (H318)
Category 2 (H351)
Category 3 (H335) (H336)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor
H314 - Causes severe skin burns and eye damage
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H351 - Suspected of causing cancer
EUH014 - Reacts violently with water
EUH019 - May form explosive peroxides

Precautionary Statements

P280 - Wear protective gloves/protective clothing/eye protection/face protection
P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a POISON CENTER or doctor/physician
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

2.3. Other hazards

Reacts violently with water

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
Tetrahydrofuran	109-99-9	203-726-8	70-80	Flam. Liq. 2 (H225)

ALFAAS36391

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 1M solution in THF

Revision Date 07-Dec-2024

				Acute Tox. 4 (H302) Eye Irrit. 2 (H319) STOT SE 3 (H335) STOT SE 3 (H336) Carc. 2 (H351) (EUH019)
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, lithium salt	4039-32-1	EEC No. 223-725-6	20-30	Flam. Sol. 1 (H228) Self Heat. 1 (H251) Skin Corr. 1B (H314) Eye Dam. 1 (H318) (EUH014)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Tetrahydrofuran	Acute Tox. 4 :: C>82.5% Eye Irrit. 2 :: C>=25% STOT SE 3 :: C>=25%	-	-

Components	Reach Registration Number	
Tetrahydrofuran	01-2119444314-46	
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, lithium salt	01-2119913303-51	

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Call a physician immediately.
Ingestion	Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately.
Inhalation	If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Causes central nervous system depression: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 1M solution in THF

Revision Date 07-Dec-2024

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

CO₂, dry chemical, dry sand, alcohol-resistant foam.

Extinguishing media which must not be used for safety reasons

Water.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Reacts violently with water.

Hazardous Combustion Products

Thermal decomposition can lead to release of irritating gases and vapors.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

6.2. Environmental precautions

Should not be released into the environment.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Do not expose spill to water.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Do not allow contact with water.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 1M solution in THF

Revision Date 07-Dec-2024

7.2. Conditions for safe storage, including any incompatibilities

May form explosive peroxides on prolonged storage. Containers should be dated when opened and tested periodically for the presence of peroxides. Should crystals form in a peroxidizable liquid, peroxidation may have occurred and the product should be considered extremely dangerous. In this instance, the container should only be opened remotely by professionals. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area. Keep away from water or moist air. Store under an inert atmosphere. Corrosives area.

Technical Rules for Hazardous Substances (TRGS) 510 Class 3
Storage Class (LGK) (Germany)

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Tetrahydrofuran	STEL: 100 ppm 15 min STEL: 300 mg/m ³ 15 min TWA: 50 ppm 8 hr TWA: 150 mg/m ³ 8 hr Skin	TWA: 50 ppm (8h) TWA: 150 mg/m ³ (8h) STEL: 100 ppm (15min) STEL: 300 mg/m ³ (15min) Skin	TWA: 50 ppm 8 hr. TWA: 150 mg/m ³ 8 hr. STEL: 100 ppm 15 min STEL: 300 mg/m ³ 15 min Skin

Biological limit values

List source(s):

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Tetrahydrofuran 109-99-9 (70-80)				DNEL = 12.6mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Tetrahydrofuran 109-99-9 (70-80)	DNEL = 300mg/m ³	DNEL = 96mg/m ³	DNEL = 150mg/m ³	DNEL = 72.4mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Tetrahydrofuran	PNEC = 4.32mg/L	PNEC = 23.3mg/kg	PNEC = 21.6mg/L	PNEC = 4.6mg/L	PNEC = 2.13mg/kg

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 1M solution in THF

Revision Date 07-Dec-2024

109-99-9 (70-80)		sediment dw			soil dw
--------------------	--	-------------	--	--	---------

Component	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air
Tetrahydrofuran 109-99-9 (70-80)	PNEC = 0.432mg/L	PNEC = 2.33mg/kg sediment dw		PNEC = 67mg/kg food	

8.2. Exposure controls

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection Goggles (European standard - EN 166)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Nitrile rubber	See manufacturers	-	EN 374	(minimum requirement)
Viton (R)	recommendations			
Butyl rubber				
Neoprene gloves				

Skin and body protection Long sleeved clothing.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced
Recommended Filter type: low boiling organic solvent Type AX Brown conforming to EN371

Small scale/Laboratory use Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141
When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls No information available.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 1M solution in THF

Revision Date 07-Dec-2024

Physical State	Liquid	
Appearance	Light yellow	
Odor	No information available	
Odor Threshold	No data available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	65 °C / 149 °F	@ 760 mmHg
Flammability (liquid)	Highly flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Flash Point	-21 °C / -5.8 °F	Method - (based on components)
Autoignition Temperature	215 °C / 419 °F	
Decomposition Temperature	No data available	
pH	No information available	
Viscosity	No data available	
Water Solubility	Reacts violently with water	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Tetrahydrofuran	0.45	
Vapor Pressure	No data available	
Density / Specific Gravity	0.9	
Bulk Density	Not applicable	Liquid
Vapor Density	No data available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

Explosive Properties Vapors may form explosive mixtures with air

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

Yes

10.2. Chemical stability

Air sensitive. May form explosive peroxides on prolonged storage.

10.3. Possibility of hazardous reactions

Hazardous Polymerization

Hazardous polymerization does not occur.

Hazardous Reactions

None under normal processing. Reacts violently with water.

10.4. Conditions to avoid

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition. Exposure to air. Exposure to moist air or water. Exposure to moisture.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 11: TOXICOLOGICAL INFORMATION

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 1M solution in THF

Revision Date 07-Dec-2024

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral No data available
Dermal No data available
Inhalation No data available

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Tetrahydrofuran	1650 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	180 mg/L (Rat) 1 h 53.9 mg/L (Rat) 4 h

(b) skin corrosion/irritation; No data available

(c) serious eye damage/irritation; No data available

(d) respiratory or skin sensitization;

Respiratory No data available
Skin No data available

Component	Test method	Test species	Study result
Tetrahydrofuran 109-99-9 (70-80)	Local Lymph Node Assay OECD Test Guideline 429	mouse	non-sensitising

(e) germ cell mutagenicity; No data available

Component	Test method	Test species	Study result
Tetrahydrofuran 109-99-9 (70-80)	OECD Test Guideline 476 Gene cell mutation	in vivo Mammalian	negative
	OECD Test Guideline 473 Chromosomal aberration assay	in vitro Mammalian	negative

(f) carcinogenicity; No data available

Limited evidence of a carcinogenic effect

Component	EU	UK	Germany	IARC
Tetrahydrofuran				Group 2B

(g) reproductive toxicity; No data available

Component	Test method	Test species / Duration	Study result
Tetrahydrofuran 109-99-9 (70-80)	OECD Test Guideline 416	Rat 2 Generation	NOAEL = 3,000 ppm

(h) STOT-single exposure; No data available

Results / Target organs Respiratory system, Central nervous system (CNS).

(i) STOT-repeated exposure; No data available

Target Organs No information available.

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 1M solution in THF

Revision Date 07-Dec-2024

(j) aspiration hazard; No data available

Symptoms / effects, both acute and delayed Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation. Causes central nervous system depression. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects Reacts with water so no ecotoxicity data for the substance is available.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Tetrahydrofuran	2160 mg/l LC50 = 96 h Pimephales promelas Leuciscus idus: LC50: 2820 mg/L/48h	EC50 48 h 3485 mg/l EC50: >10000 mg/L/24h	

12.2. Persistence and degradability No information available

Persistence

Persistence is unlikely, based on information available.

Degradability

Reacts with water.

Degradation in sewage treatment plant

Reacts violently with water.

12.3. Bioaccumulative potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Tetrahydrofuran	0.45	No data available

12.4. Mobility in soil

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in air.

12.5. Results of PBT and vPvB assessment

Reacts violently with water.

12.6. Endocrine disrupting properties

Endocrine Disruptor Information

Component	EU - Endocrine Disruptors Candidate List	EU - Endocrine Disruptors - Evaluated Substances
Tetrahydrofuran	Group III Chemical	

12.7. Other adverse effects

Persistent Organic Pollutant
Ozone Depletion Potential

This product does not contain any known or suspected substance
This product does not contain any known or suspected substance

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 1M solution in THF

Revision Date 07-Dec-2024

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products	Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.
Contaminated Packaging	Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.
European Waste Catalogue (EWC)	According to the European Waste Catalog, Waste Codes are not product specific, but application specific.
Other Information	Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms.

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number	UN2924
14.2. UN proper shipping name	Flammable liquid, corrosive, n.o.s.
Technical Shipping Name	Tetrahydrofuran, Lithium bis(trimethylsilyl)amide
14.3. Transport hazard class(es)	3
Subsidiary Hazard Class	8
14.4. Packing group	II

ADR

14.1. UN number	UN2924
14.2. UN proper shipping name	Flammable liquid, corrosive, n.o.s.
Technical Shipping Name	Tetrahydrofuran, Lithium bis(trimethylsilyl)amide
14.3. Transport hazard class(es)	3
Subsidiary Hazard Class	8
14.4. Packing group	II

IATA

14.1. UN number	UN2924
14.2. UN proper shipping name	Flammable liquid, corrosive, n.o.s.
Technical Shipping Name	Tetrahydrofuran, Lithium bis(trimethylsilyl)amide
14.3. Transport hazard class(es)	3
Subsidiary Hazard Class	8
14.4. Packing group	II

14.5. Environmental hazards	No hazards identified
14.6. Special precautions for user	No special precautions required.
14.7. Maritime transport in bulk according to IMO instruments	Not applicable, packaged goods

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 1M solution in THF

Revision Date 07-Dec-2024

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Tetrahydrofuran	109-99-9	203-726-8	-	-	X	X	KE-33454	X	X
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, lithium salt	4039-32-1	223-725-6	-	-	-	X	-	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Tetrahydrofuran	109-99-9	X	ACTIVE	X	-	X	X	X
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, lithium salt	4039-32-1	X	ACTIVE	-	X	-	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Tetrahydrofuran	109-99-9	-	Use restricted. See entry 75. (see link for restriction details)	-
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, lithium salt	4039-32-1	-	-	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Tetrahydrofuran	109-99-9	Not applicable	Not applicable
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, lithium salt	4039-32-1	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 1M solution in THF

Revision Date 07-Dec-2024

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification Water endangering class = 2 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Tetrahydrofuran	WGK1	
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, lithium salt	WGK2	

Component	France - INRS (Tables of occupational diseases)
Tetrahydrofuran	Tableaux des maladies professionnelles (TMP) - RG 84

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Tetrahydrofuran 109-99-9 (70-80)		Group I	

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness

H351 - Suspected of causing cancer

EUH014 - Reacts violently with water

EUH019 - May form explosive peroxides

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

SAFETY DATA SHEET

Lithium bis(trimethylsilyl)amide, 1M solution in THF

Revision Date 07-Dec-2024

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards

On basis of test data

Health Hazards

Calculation method

Environmental hazards

Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Chemical incident response training.

Prepared By

Health, Safety and Environmental Department

Creation Date

20-Feb-2015

Revision Date

07-Dec-2024

Revision Summary

Not applicable.

This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet