

SAFETY DATA SHEET

Creation Date 21-May-2012

Revision Date 28-Mar-2024

Revision Number 14

1. Identification

Product Name Peroxyacetic acid, ca. 35 wt.% solution in diluted acetic acid, stabilized

Cat No. : AC257750000; AC257750250; AC257751000; AC257755000

Synonyms Peracetic acid

Recommended Use Laboratory chemicals.

Uses advised against Food, drug, pesticide or biocidal product use.

Details of the supplier of the safety data sheet

Company

Fisher Scientific Company
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410

Emergency Telephone Number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids	Category 4
Organic peroxides	Type D
Acute oral toxicity	Category 4
Acute dermal toxicity	Category 4
Acute Inhalation Toxicity - Vapors	Category 4
Skin Corrosion/Irritation	Category 1 A
Serious Eye Damage/Eye Irritation	Category 1
Specific target organ toxicity (single exposure)	Category 3
Target Organs - Respiratory system.	

Label Elements

Signal Word

Danger

Hazard Statements

Combustible liquid
Heating may cause a fire
Harmful if swallowed, in contact with skin or if inhaled
Causes severe skin burns and eye damage
May cause respiratory irritation



Precautionary Statements

Prevention

Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product
Wear protective gloves/protective clothing/eye protection/face protection
Use only outdoors or in a well-ventilated area
Do not breathe dust/fume/gas/mist/vapors/spray
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Keep/Store away from clothing/ other combustible materials
Keep only in original container
Keep cool

Response

Immediately call a POISON CENTER or doctor/physician

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Skin

Wash contaminated clothing before reuse
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Ingestion

Rinse mouth
Do NOT induce vomiting

Fire

In case of fire: Use CO₂, dry chemical, or foam for extinction

Storage

Store locked up
Store in a well-ventilated place. Keep container tightly closed
Store at temperatures not exceeding 50 °C/ 122 °F. Keep cool
Protect from sunlight
Store away from other materials

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Very toxic to aquatic life

3. Composition/Information on Ingredients

Component	CAS No	Weight %
Acetic acid	64-19-7	46-55
Peroxyacetic acid	79-21-0	34-39

Hydrogen peroxide	7722-84-1	11-15
-------------------	-----------	-------

4. First-aid measures

General Advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Call a physician immediately.
Inhalation	If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately.
Ingestion	Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately.
Most important symptoms and effects	Causes burns by all exposure routes. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media	Water mist may be used to cool closed containers. CO ₂ , dry chemical, dry sand, alcohol-resistant foam.
Unsuitable Extinguishing Media	No information available
Flash Point	62 °C / 143.6 °F
Method -	No information available
Autoignition Temperature	No information available
Explosion Limits	
Upper	No data available
Lower	No data available
Oxidizing Properties	Oxidizer
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes.

Hazardous Combustion Products

Carbon monoxide (CO). Carbon dioxide (CO₂). Sulfur oxides.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

Health
3

Flammability
3

Instability
4

Physical hazards
OX

6. Accidental release measures

Personal Precautions

Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Environmental Precautions

Should not be released into the environment.

Methods for Containment and Clean Up Keep in suitable, closed containers for disposal. Soak up with inert absorbent material.

7. Handling and storage

Handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance.

Storage.

Keep refrigerated. Corrosives area. Organic peroxides. Keep away from heat, sparks and flame. Do not store near combustible materials. Keep container tightly closed. Incompatible Materials. Strong oxidizing agents. Finely powdered metals. Organic materials. Metals. Reducing Agent. Strong reducing agents. Combustible material.

8. Exposure controls / personal protection

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH	Mexico OEL (TWA)
Acetic acid	TWA: 10 ppm STEL: 15 ppm	(Vacated) TWA: 10 ppm (Vacated) TWA: 25 mg/m ³ TWA: 10 ppm TWA: 25 mg/m ³	IDLH: 50 ppm TWA: 10 ppm TWA: 25 mg/m ³ STEL: 15 ppm STEL: 37 mg/m ³	TWA: 10 ppm STEL: 15 ppm
Peroxyacetic acid	STEL: 0.4 ppm			
Hydrogen peroxide	TWA: 1 ppm	(Vacated) TWA: 1 ppm (Vacated) TWA: 1.4 mg/m ³ TWA: 1 ppm TWA: 1.4 mg/m ³	IDLH: 75 ppm TWA: 1 ppm TWA: 1.4 mg/m ³	TWA: 1 ppm

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH: NIOSH - National Institute for Occupational Safety and Health

Engineering Measures

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/face Protection

Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Recommended Filter type: Particulates filter conforming to EN 143. Acid gases filter. Type E. Yellow. conforming to EN14387.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical State	Liquid
Appearance	Clear Colorless
Odor	Strong pungent
Odor Threshold	No information available
pH	-1.2
Melting Point/Range	-44 °C / -47.2 °F
Boiling Point/Range	105 °C / 221 °F @ 760 mmHg
Flash Point	62 °C / 143.6 °F
Evaporation Rate	No information available
Flammability (solid,gas)	Not applicable
Flammability or explosive limits	
Upper	No data available
Lower	No data available
Vapor Pressure	20 hPa @ 20 °C
Vapor Density	No information available
Specific Gravity	1.130
Solubility	Soluble in water
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	No information available
Decomposition Temperature	No information available
Viscosity	No information available
Molecular Formula	C2 H4 O3
Molecular Weight	76.05

10. Stability and reactivity

Reactive Hazard	Yes
Stability	Stable under normal conditions. Oxidizer: Contact with combustible/organic material may cause fire.
Conditions to Avoid	Heat, flames and sparks. Keep away from open flames, hot surfaces and sources of ignition. Incompatible products. Combustible material. Excess heat.
Incompatible Materials	Strong oxidizing agents, Finely powdered metals, Organic materials, Metals, Reducing Agent, Strong reducing agents, Combustible material
Hazardous Decomposition Products	Carbon monoxide (CO), Carbon dioxide (CO ₂), Sulfur oxides
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information

Oral LD50

Category 4. ATE = 300 - 2000 mg/kg.

Dermal LD50

Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg. Category 4.

Vapor LC50

ATE = 1000 - 2000 mg/kg.
Category 4. ATE = 10 - 20 mg/l.

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Acetic acid	3310 mg/kg (Rat)	-	> 40 mg/L (Rat) 4 h
Peroxyacetic acid	1540 µL/kg (Rat)	1410 µL/kg (Rabbit)	LC50 = 213 mg/m ³ (Rat) 4 h LC50 = 186 mg/m ³ (Rat) 4 h
Hydrogen peroxide	376 mg/kg (Rat) (90%) 910 mg/kg (Rat) (20-60%) 1518 mg/kg (Rat) (8-20% sol)	>2000 mg/kg (Rabbit)	LC50 = 2000 mg/m ³ (Rat) 4 h

Toxicologically Synergistic Products

No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation

Causes severe burns by all exposure routes

Sensitization

No information available

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No	IARC	NTP	ACGIH	OSHA	Mexico
Acetic acid	64-19-7	Not listed	Not listed	Not listed	Not listed	Not listed
Peroxyacetic acid	79-21-0	Not listed	Not listed	Not listed	Not listed	Not listed
Hydrogen peroxide	7722-84-1	Not listed	Not listed	A3	Not listed	A3

ACGIH: (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen
A2 - Suspected Human Carcinogen
A3 - Animal Carcinogen

Mexico - Occupational Exposure Limits - Carcinogens

ACGIH: (American Conference of Governmental Industrial Hygienists)
Mexico - Occupational Exposure Limits - Carcinogens
A1 - Confirmed Human Carcinogen
A2 - Suspected Human Carcinogen
A3 - Confirmed Animal Carcinogen
A4 - Not Classifiable as a Human Carcinogen
A5 - Not Suspected as a Human Carcinogen

Mutagenic Effects

No information available

Reproductive Effects

No information available.

Developmental Effects

No information available.

Teratogenicity

No information available.

STOT - single exposure

Respiratory system

STOT - repeated exposure

None known

Aspiration hazard

No information available

Symptoms / effects, both acute and delayed

Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

Endocrine Disruptor Information

No information available

Other Adverse Effects

The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

The product contains following substances which are hazardous for the environment. Very toxic to aquatic organisms.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Acetic acid	-	Pimephales promelas: LC50 = 88 mg/L/96h Lepomis macrochirus: LC50 = 75 mg/L/96h	Photobacterium phosphoreum: EC50 = 8.8 mg/L/15 min Photobacterium phosphoreum: EC50 = 8.8 mg/L/25 min Photobacterium phosphoreum: EC50 = 8.8 mg/L/5 min	EC50 = 95 mg/L/24h
Peroxyacetic acid	Not listed	LC50: = 1.1 mg/L, 96h semi-static (Lepomis macrochirus)	Not listed	Not listed
Hydrogen peroxide	EC50 2.5 mg/L/72h	LC50: 16.4 mg/L/96h (P.promelas)	Not listed	EC50 7.7 mg/L/24h

Persistence and Degradability Soluble in water Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation No information available.

Mobility . Will likely be mobile in the environment due to its water solubility.

Component	log Pow
Acetic acid	-0.2
Peroxyacetic acid	-0.46
Hydrogen peroxide	-1.1

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

14. Transport information

DOT

UN-No UN3105
Proper Shipping Name ORGANIC PEROXIDE TYPE D, LIQUID (PEROXYACETIC ACID, TYPE D, STABILIZED)
Hazard Class 5.2
Subsidiary Hazard Class 8
Packing Group II

TDG

UN-No UN3105
Proper Shipping Name ORGANIC PEROXIDE TYPE D, LIQUID (PEROXYACETIC ACID, TYPE D, STABILIZED)
Hazard Class 5.2
Subsidiary Hazard Class 8
Packing Group II

IATA

FORBIDDEN FOR IATA TRANSPORT
UN-No UN3105
Proper Shipping Name ORGANIC PEROXIDE TYPE D, LIQUID (PEROXYACETIC ACID, TYPE D, STABILIZED)
FORBIDDEN FOR IATA TRANSPORT
Hazard Class 5.2
Subsidiary Hazard Class 8

IMDG/IMO

UN-No UN3105
Proper Shipping Name ORGANIC PEROXIDE TYPE D, LIQUID (PEROXYACETIC ACID, TYPE D, STABILIZED)
Hazard Class 5.2
Subsidiary Hazard Class 8

15. Regulatory information

United States of America Inventory

Peroxyacetic acid, ca. 35 wt.% solution in diluted acetic acid, stabilized

Revision Date 28-Mar-2024

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	TSCA - EPA Regulatory Flags
Acetic acid	64-19-7	X	ACTIVE	-
Peroxyacetic acid	79-21-0	X	ACTIVE	-
Hydrogen peroxide	7722-84-1	X	ACTIVE	-

Legend:

TSCA US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

X - Listed

- - Not Listed

TSCA - Per 40 CFR 751, Regulation of Certain Chemical Substances & Mixtures, Under TSCA Section 6(h) (PBT)

Not applicable

TSCA 12(b) - Notices of Export

Not applicable

International Inventories

Canada (DSL/NDL), Europe (EINECS/ELINCS/NLP), Philippines (PICCS), Japan (ENCS), Japan (ISHL), Australia (AICS), China (IECSC), Korea (KECL).

Component	CAS No	DSL	NDL	EINECS	PICCS	ENCS	ISHL	AICS	IECSC	KECL
Acetic acid	64-19-7	X	-	200-580-7	X	X	X	X	X	X
Peroxyacetic acid	79-21-0	X	-	201-186-8	X	X	X	X	X	2005-3-3198
Hydrogen peroxide	7722-84-1	X	-	231-765-0	X	X	X	X	X	KE-20204

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

U.S. Federal Regulations

SARA 313

Component	CAS No	Weight %	SARA 313 - Threshold Values %	SARA 313 - Reporting thresholds
Peroxyacetic acid	79-21-0	34-39	1.0 %	-

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

Component	CWA - Hazardous Substances	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants
Acetic acid	X	5000 lb	-	-

Clean Air Act

Not applicable

OSHA - Occupational Safety and Health Administration

OSHA - United States Occupational Safety and Health Administration

Component	Specifically Regulated Chemicals	Highly Hazardous Chemicals
Peroxyacetic acid	-	TQ: 1000 lb
Hydrogen peroxide	-	TQ: 7500 lb

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355).

Component	Hazardous Substances RQs	CERCLA Extremely Hazardous Substances RQs	SARA Reportable Quantity (RQ)
Acetic acid	5000 lb	-	5000 lb 2270 kg
Peroxyacetic acid	-	500 lb	-
Hydrogen peroxide	-	1000 lb	-

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Acetic acid	X	X	X	-	X
Peroxyacetic acid	X	X	X	X	X
Hydrogen peroxide	X	X	X	-	X

U.S. Department of Transportation

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland Security

This product contains the following DHS chemicals:

Legend - STQs = Screening Threshold Quantities, APA = A placarded amount

Component	DHS Chemical Facility Anti-Terrorism Standard
Peroxyacetic acid	Release STQs - 10000lb
Hydrogen peroxide	Theft STQs - 400lb (concentration >=35%)

Other International Regulations

Mexico - Grade

No information available

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Acetic acid	64-19-7	-	Use restricted. See item 75. (see link for restriction details)	-
Peroxyacetic acid	79-21-0	-	Use restricted. See item 75. (see link for restriction details)	-
Hydrogen peroxide	7722-84-1	-	Use restricted. See item 75. (see link for restriction details)	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential	Restriction of Hazardous Substances (RoHS)
Acetic acid	64-19-7	Listed	Not applicable	Not applicable	Not applicable
Peroxyacetic acid	79-21-0	Listed	Not applicable	Not applicable	Not applicable
Hydrogen peroxide	7722-84-1	Listed	Not applicable	Not applicable	Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Other International Regulations

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Acetic acid	64-19-7	Not applicable	Not applicable	Not applicable	Annex I - Y34
Peroxyacetic acid	79-21-0	Not applicable	Not applicable	Not applicable	Not applicable
Hydrogen peroxide	7722-84-1	Not applicable	Not applicable	Not applicable	Not applicable

16. Other information

Prepared By Regulatory Affairs
Thermo Fisher Scientific
Email: EMSDS.RA@thermofisher.com

Creation Date 21-May-2012

Revision Date 28-Mar-2024

Print Date 28-Mar-2024

Revision Summary This document has been updated to comply with the US OSHA HazCom 2012 Standard replacing the current legislation under 29 CFR 1910.1200 to align with the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS