

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: **Silicon(IV) oxide, 30% in Ethylene glycol, colloidal dispersion**
Cat No. : **43093**
Molecular Formula **O2 Si**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

Thermo Fisher (Kandel) GmbH
Erlenbachweg 2, 76870 Kandel, Germany
Tel: +49 (0) 721 84007 280
Fax: +49 (0) 721 84007 300

Swiss distributor - Fisher Scientific AG
Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
<https://www.fishersci.ch/ch/en/customer-help-support/forms/email-us.html>

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

Poison Centre - Emergency information services

Ireland : National Poisons Information Centre (NPIC) -
01 809 2166 (8am-10pm, 7 days a week)
Malta : +356 2395 2000
Cyprus : +357 2240 5611

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

SAFETY DATA SHEET

Silicon(IV) oxide, 30% in Ethylene glycol, colloidal dispersion

Revision Date 30-Nov-2024

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Based on available data, the classification criteria are not met

Health hazards

Acute oral toxicity
Specific target organ toxicity - (repeated exposure)

Category 4 (H302)
Category 2 (H373)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Warning

Hazard Statements

H302 - Harmful if swallowed
H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary Statements

P301 + P330 + P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting
P312 - Call a POISON CENTER or doctor if you feel unwell
P264 - Wash face, hands and any exposed skin thoroughly after handling
P260 - Do not breathe dust/fume/gas/mist/vapors/spray

2.3. Other hazards

Toxic to terrestrial vertebrates
This product does not contain any known or suspected endocrine disruptors

Section 3: Composition/information on ingredients

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Ethylene glycol	107-21-1	EEC No. 203-473-3	70.00	Acute Tox. 4 (H302) STOT RE 2 (H373)
Silica, amorphous	7631-86-9	EEC No. 231-545-4	30.00	-

SAFETY DATA SHEET

Silicon(IV) oxide, 30% in Ethylene glycol, colloidal dispersion

Revision Date 30-Nov-2024

Full text of Hazard Statements: see section 16

Section 4: First aid measures

4.1. Description of first aid measures

General Advice	If symptoms persist, call a physician.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
Ingestion	Clean mouth with water and drink afterwards plenty of water.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

None reasonably foreseeable.

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically.
---------------------------	------------------------

Section 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media

Carbon dioxide (CO₂). Powder. Water spray. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors.

Hazardous Combustion Products

Silicon dioxide.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6: ACCIDENTAL RELEASE MEASURES

SAFETY DATA SHEET

Silicon(IV) oxide, 30% in Ethylene glycol, colloidal dispersion

Revision Date 30-Nov-2024

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required.

6.2. Environmental precautions

Should not be released into the environment. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

Section 7: Handling and storage

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Storage Class/LGK 12

Switzerland - Storage of hazardous substances

Storage class - SC 10/12
<https://www.kvu.ch/de/themen/stoffe-und-produkte>
<https://www.kvu.ch/fr/themes/substances-et-produits>
<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

Section 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

SAFETY DATA SHEET

Silicon(IV) oxide, 30% in Ethylene glycol, colloidal dispersion

Revision Date 30-Nov-2024

Component	European Union	The United Kingdom	France	Belgium	Spain
Ethylene glycol	TWA: 20 ppm (8h) TWA: 52 mg/m ³ (8h) STEL: 40 ppm (15min) STEL: 104 mg/m ³ (15min) Skin	STEL: 40 ppm 15 min STEL: 104 mg/m ³ 15 min STEL: 30 mg/m ³ 15 min TWA: 10 mg/m ³ 8 hr TWA: 20 ppm 8 hr TWA: 52 mg/m ³ 8 hr Skin	TWA / VME: 20 ppm (8 heures). indicative limit TWA / VME: 52 mg/m ³ (8 heures). indicative limit STEL / VLCT: 40 ppm. indicative limit STEL / VLCT: 104 mg/m ³ . indicative limit Peau	TWA: 20 ppm 8 uren TWA: 52 mg/m ³ 8 uren STEL: 40 ppm 15 minuten STEL: 104 mg/m ³ 15 minuten Huid	STEL / VLA-EC: 40 ppm (15 minutos). STEL / VLA-EC: 104 mg/m ³ (15 minutos). TWA / VLA-ED: 20 ppm (8 horas) TWA / VLA-ED: 52 mg/m ³ (8 horas) Piel
Silica, amorphous		STEL: 18 mg/m ³ 15 min STEL: 7.2 mg/m ³ 15 min TWA: 6 mg/m ³ 8 hr TWA: 2.4 mg/m ³ 8 hr			

Component	Italy	Germany	Portugal	The Netherlands	Finland
Ethylene glycol	TWA: 20 ppm 8 ore. Time Weighted Average TWA: 52 mg/m ³ 8 ore. Time Weighted Average STEL: 40 ppm 15 minuti. Short-term STEL: 104 mg/m ³ 15 minuti. Short-term Pelle	TWA: 10 ppm (8 Stunden). AGW - exposure factor 2 TWA: 26 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 10 ppm (8 Stunden). MAK can occur as vapor and aerosol at the same time TWA: 26 mg/m ³ (8 Stunden). MAK can occur as vapor and aerosol at the same time Höhepunkt: 20 ppm Höhepunkt: 52 mg/m ³ Haut	STEL: 40 ppm 15 minutos STEL: 104 mg/m ³ 15 minutos Ceiling: 100 mg/m ³ TWA: 20 ppm 8 horas TWA: 52 mg/m ³ 8 horas Pele	huid STEL: 40 ppm 15 minuten STEL: 104 mg/m ³ 15 minuten TWA: 52 mg/m ³ 8 uren TWA: 10 mg/m ³ 8 uren	TWA: 20 ppm 8 tunteina TWA: 50 mg/m ³ 8 tunteina STEL: 40 ppm 15 minuutteina STEL: 100 mg/m ³ 15 minuutteina Iho
Silica, amorphous		TWA: 4 mg/m ³ (8 Stunden). AGW - TWA: 0.02 mg/m ³ (8 Stunden). MAK Höhepunkt: 0.16 mg/m ³			TWA: 5 mg/m ³ 8 tunteina

Component	Austria	Denmark	Switzerland	Poland	Norway
Ethylene glycol	Haut MAK-KZGW: 20 ppm 15 Minuten MAK-KZGW: 52 mg/m ³ 15 Minuten MAK-TMW: 10 ppm 8 Stunden MAK-TMW: 26 mg/m ³ 8 Stunden	TWA: 10 ppm 8 timer TWA: 26 mg/m ³ 8 timer TWA: 10 mg/m ³ 8 timer STEL: 104 mg/m ³ 15 minutter STEL: 40 ppm 15 minutter STEL: 20 mg/m ³ 15 minutter Hud	Haut/Peau STEL: 20 ppm 15 Minuten STEL: 52 mg/m ³ 15 Minuten TWA: 10 ppm 8 Stunden TWA: 26 mg/m ³ 8 Stunden	STEL: 50 mg/m ³ 15 minutach TWA: 15 mg/m ³ 8 godzinach	TWA: 20 ppm 8 timer TWA: 52 mg/m ³ 8 timer STEL: 104 mg/m ³ 15 minutter. total sum of gas and particulate matter (aerosol) of the substance;value from the regulation STEL: 40 ppm 15 minutter. total sum of gas and particulate matter (aerosol) of the substance;value from the regulation Hud
Silica, amorphous	MAK-TMW: 4 mg/m ³ 8 Stunden		TWA: 4 mg/m ³ 8 Stunden		TWA: 1.5 mg/m ³ 8 timer STEL: 3 mg/m ³ 15 minutter. value calculated respirable dust

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Ethylene glycol	TWA: 52 mg/m ³ TWA: 20 ppm STEL : 40 ppm	kože TWA-GVI: 20 ppm 8 satima.	TWA: 20 ppm 8 hr. TWA: 52 mg/m ³ 8 hr. STEL: 40 ppm 15 min	Skin-potential for cutaneous absorption STEL: 40 ppm	TWA: 50 mg/m ³ 8 hodinách. Potential for cutaneous

SAFETY DATA SHEET

Silicon(IV) oxide, 30% in Ethylene glycol, colloidal dispersion

Revision Date 30-Nov-2024

	STEL : 104 mg/m ³ Skin notation	TWA-GVI: 52 mg/m ³ 8 satima. STEL-KGVI: 40 ppm 15 minutama. STEL-KGVI: 104 mg/m ³ 15 minutama.	STEL: 104 mg/m ³ 15 min Skin	STEL: 104 mg/m ³ TWA: 20 ppm TWA: 52 mg/m ³	absorption Ceiling: 100 mg/m ³
Silica, amorphous			TWA: 6 mg/m ³ 8 hr. total inhalable dust TWA: 2.4 mg/m ³ 8 hr. respirable dust STEL: 18 mg/m ³ 15 min STEL: 7.2 mg/m ³ 15 min		TWA: 0.1 mg/m ³ 8 hodinách. respirable fraction TWA: 4.0 mg/m ³ 8 hodinách. amorphous SiO ₂

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Ethylene glycol	Nahk TWA: 20 ppm 8 tundides. total concentration of aerosol and vapor TWA: 52 mg/m ³ 8 tundides. total concentration of aerosol and vapor STEL: 40 ppm 15 minutites. total concentration of aerosol and vapor STEL: 104 mg/m ³ 15 minutites. total concentration of aerosol and vapor	Skin notation TWA: 20 ppm 8 hr TWA: 52 mg/m ³ 8 hr STEL: 40 ppm 15 min STEL: 104 mg/m ³ 15 min	STEL: 50 ppm STEL: 125 mg/m ³ TWA: 50 ppm TWA: 125 mg/m ³	STEL: 40 ppm 15 percekben. CK STEL: 104 mg/m ³ 15 percekben. CK TWA: 20 ppm 8 órában. AK TWA: 52 mg/m ³ 8 órában. AK lehetséges bőrön keresztüli felszívódás	STEL: 40 ppm STEL: 104 mg/m ³ TWA: 10 ppm 8 klukkustundum. mist TWA: 26 mg/m ³ 8 klukkustundum. mist Skin notation Ceiling: 20 ppm mist Ceiling: 52 mg/m ³ mist
Silica, amorphous	TWA: 2 mg/m ³ 8 tundides. amorphous respirable dust				

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Ethylene glycol	skin - potential for cutaneous exposure STEL: 40 ppm STEL: 104 mg/m ³ TWA: 20 ppm TWA: 52 mg/m ³	TWA: 10 ppm aerosol and vapor IPRD TWA: 25 mg/m ³ aerosol and vapor IPRD Oda STEL: 20 ppm STEL: 50 mg/m ³	Possibility of significant uptake through the skin TWA: 20 ppm 8 Stunden TWA: 52 mg/m ³ 8 Stunden STEL: 40 ppm 15 Minuten STEL: 104 mg/m ³ 15 Minuten	possibility of significant uptake through the skin TWA: 20 ppm TWA: 52 mg/m ³ STEL: 40 ppm 15 minuti STEL: 104 mg/m ³ 15 minuti	Skin notation TWA: 20 ppm 8 ore TWA: 52 mg/m ³ 8 ore STEL: 40 ppm 15 minute STEL: 104 mg/m ³ 15 minute
Silica, amorphous	TWA: 1 mg/m ³				

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Ethylene glycol	TWA: 5 mg/m ³ 2388 MAC: 10 mg/m ³	Ceiling: 104 mg/m ³ Potential for cutaneous absorption TWA: 20 ppm TWA: 52 mg/m ³	TWA: 20 ppm 8 urah TWA: 52 mg/m ³ 8 urah Koža STEL: 40 ppm 15 minutah STEL: 104 mg/m ³ 15 minutah	Binding STEL: 40 ppm 15 minuter Binding STEL: 104 mg/m ³ 15 minuter TLV: 10 ppm 8 timmar. NGV TLV: 25 mg/m ³ 8 timmar. NGV Hud	Deri TWA: 20 ppm 8 saat TWA: 52 mg/m ³ 8 saat STEL: 40 ppm 15 dakika STEL: 104 mg/m ³ 15 dakika
Silica, amorphous	TWA: 1 mg/m ³ 1151 in the form of condensation aerosol, containing >60% Silicon dioxide; limit is for total mass of aerosols TWA: 2 mg/m ³ 1152 in the form of condensation aerosol, containing 10-60% Silicon dioxide; limit is for		TWA: 4 mg/m ³ 8 urah inhalable fraction, gel		

SAFETY DATA SHEET

Silicon(IV) oxide, 30% in Ethylene glycol, colloidal dispersion

Revision Date 30-Nov-2024

	total mass of aerosols TWA: 1 mg/m ³ 1153 also vitreous, in the form of disintegration aerosol; limit is for total mass of aerosols MAC: 3 mg/m ³ MAC: 6 mg/m ³				
--	---	--	--	--	--

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Ethylene glycol 107-21-1 (70.00)				DNEL = 106mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Ethylene glycol 107-21-1 (70.00)			DNEL = 35mg/m ³ DNEL = 33.5mg/m ³	DNEL = 70mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Ethylene glycol 107-21-1 (70.00)	PNEC = 10mg/L PNEC = 85.9mg/L	PNEC = 37mg/kg sediment dw PNEC = 312mg/kg sediment dw PNEC = 317mg/kg sediment dw	PNEC = 10mg/L PNEC = 130mg/L	PNEC = 199.5mg/L PNEC = 200mg/L	PNEC = 1.53mg/kg soil dw PNEC = 12.7mg/kg soil dw PNEC = 13.1mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Ethylene glycol 107-21-1 (70.00)	PNEC = 1mg/L PNEC = 8.59mg/L	PNEC = 3.7mg/kg sediment dw PNEC = 31.2mg/kg sediment dw PNEC = 31.7mg/kg sediment dw	PNEC = 10mg/L		

8.2. Exposure controls

SAFETY DATA SHEET

Silicon(IV) oxide, 30% in Ethylene glycol, colloidal dispersion

Revision Date 30-Nov-2024

Engineering Measures

Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Wear safety glasses with side shields (or goggles) (European standard - EN 166)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Natural rubber	See manufacturers	-	EN 374	(minimum requirement)
Nitrile rubber	recommendations			
Neoprene				
PVC				

Skin and body protection

Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: Organic gases and vapours filter Particulates filter conforming to EN 143

Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Particle filtering: EN149:2001
When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

No information available.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State Liquid dispersion

Appearance

White

Odor

sweet

Odor Threshold

No data available

Melting Point/Range

No data available

Softening Point

No data available

Boiling Point/Range

196 °C / 384.8 °F

Flammability (liquid)

No data available

Flammability (solid,gas)

Not applicable

Liquid

Explosion Limits

No data available

Flash Point

No information available

Method - No information available

Autoignition Temperature

No data available

Decomposition Temperature

No data available

pH

No information available

Viscosity

No data available

ALFAA43093

SAFETY DATA SHEET

Silicon(IV) oxide, 30% in Ethylene glycol, colloidal dispersion

Revision Date 30-Nov-2024

Water Solubility	Immiscible	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Ethylene glycol	-1.36	
Vapor Pressure	<=1100 hPa @ 50 °C	
Density / Specific Gravity	1.3 g/cm3	@ 20 °C
Bulk Density	Not applicable	Liquid
Vapor Density	No data available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

Molecular Formula	O2 Si
Molecular Weight	60.09

Section 10: Stability and reactivity

<u>10.1. Reactivity</u>	None known, based on information available
-------------------------	--

<u>10.2. Chemical stability</u>	Stable under normal conditions.
---------------------------------	---------------------------------

10.3. Possibility of hazardous reactions

Hazardous Polymerization	No information available.
Hazardous Reactions	None under normal processing.

<u>10.4. Conditions to avoid</u>	Incompatible products. Excess heat.
----------------------------------	-------------------------------------

<u>10.5. Incompatible materials</u>	Oxidizing agent.
-------------------------------------	------------------

<u>10.6. Hazardous decomposition products</u>	Silicon dioxide.
---	------------------

Section 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;	
Oral	Category 4
Dermal	Based on available data, the classification criteria are not met
Inhalation	Based on available data, the classification criteria are not met

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethylene glycol	7712 mg/kg (Rat) Human LD50 estimate: 1,400–1,600 mg/kg	LD50 = 9530 µL/kg (Rabbit) LD50 = 10600 mg/kg (Rat) LD50 > 3500 mg/kg (mice)	LC50 > 2.5 mg/L (Rat) 6 h
Silica, amorphous	>5000 mg/kg (Rat)	>2000 mg/kg (Rabbit)	-

SAFETY DATA SHEET

Silicon(IV) oxide, 30% in Ethylene glycol, colloidal dispersion

Revision Date 30-Nov-2024

- (b) skin corrosion/irritation; No data available
- (c) serious eye damage/irritation; No data available
- (d) respiratory or skin sensitization;
Respiratory No data available
Skin No data available
- (e) germ cell mutagenicity; No data available
- (f) carcinogenicity; No data available
There are no known carcinogenic chemicals in this product
- (g) reproductive toxicity; No data available
- (h) STOT-single exposure; No data available
- (i) STOT-repeated exposure; Category 2
Target Organs Kidney.
- (j) aspiration hazard; No data available
- Symptoms / effects, both acute and delayed No information available.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity effects

Component	Freshwater Fish	Water Flea	Freshwater Algae
Ethylene glycol	LC50: = 41000 mg/L, 96h (Oncorhynchus mykiss) LC50: = 27540 mg/L, 96h static (Lepomis macrochirus) LC50: 14 - 18 mL/L, 96h static (Oncorhynchus mykiss) LC50: = 40761 mg/L, 96h static (Oncorhynchus mykiss) LC50: 40000 - 60000 mg/L, 96h static (Pimephales promelas) LC50: = 16000 mg/L, 96h static (Poecilia reticulata)	EC50: = 46300 mg/L, 48h (Daphnia magna)	EC50: 6500 - 13000 mg/L, 96h (Pseudokirchneriella subcapitata)
Silica, amorphous	LC50: 5000 mg/L/96 h	EC50: 7600 mg/L/48h	EC50: 440 mg/L/72h

SAFETY DATA SHEET

Silicon(IV) oxide, 30% in Ethylene glycol, colloidal dispersion

Revision Date 30-Nov-2024

12.2. Persistence and degradability

Persistence

Immiscible with water, May persist, based on information available.

12.3. Bioaccumulative potential

May have some potential to bioaccumulate

Component	log Pow	Bioconcentration factor (BCF)
Ethylene glycol	-1.36	No data available

12.4. Mobility in soil

Spillage unlikely to penetrate soil The product is insoluble and sinks in water The product evaporates slowly Is not likely mobile in the environment due its low water solubility. Spillage unlikely to penetrate soil

12.5. Results of PBT and vPvB assessment

No data available for assessment.

12.6. Endocrine disrupting properties

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance
This product does not contain any known or suspected substance

Section 13: Disposal considerations

13.1. Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point.

European Waste Catalogue (EWC)

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information

Waste codes should be assigned by the user based on the application for which the product was used. Do not empty into drains.

Switzerland - Waste Ordinance

Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600
<https://www.fedlex.admin.ch/eli/cc/2015/891/en>

Section 14: Transport information

IMDG/IMO

Not regulated

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

ADR

Not regulated

SAFETY DATA SHEET

Silicon(IV) oxide, 30% in Ethylene glycol, colloidal dispersion

Revision Date 30-Nov-2024

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

IATA

Not regulated

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

14.5. Environmental hazards

No hazards identified

14.6. Special precautions for user

No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable, packaged goods

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Ethylene glycol	107-21-1	203-473-3	-	-	X	X	KE-13169	X	X
Silica, amorphous	7631-86-9	231-545-4	-	-	X	X	KE-31032	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Ethylene glycol	107-21-1	X	ACTIVE	X	-	X	X	X
Silica, amorphous	7631-86-9	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Not applicable

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Ethylene glycol	107-21-1	-	-	-
Silica, amorphous	7631-86-9	-	-	-

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Ethylene glycol	107-21-1	Not applicable	Not applicable
Silica, amorphous	7631-86-9	Not applicable	Not applicable

SAFETY DATA SHEET

Silicon(IV) oxide, 30% in Ethylene glycol, colloidal dispersion

Revision Date 30-Nov-2024

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 1 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Ethylene glycol	WGK1	
Silica, amorphous	nwg	

Component	France - INRS (Tables of occupational diseases)
Ethylene glycol	Tableaux des maladies professionnelles (TMP) - RG 84
Silica, amorphous	Tableaux des maladies professionnelles (TMP) - RG 25

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Ethylene glycol 107-21-1 (70.00)	Prohibited and Restricted Substances		

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

Section 16: Other information

Full text of H-Statements referred to under sections 2 and 3

H302 - Harmful if swallowed

H373 - May cause damage to organs through prolonged or repeated exposure

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

SAFETY DATA SHEET

Silicon(IV) oxide, 30% in Ethylene glycol, colloidal dispersion

Revision Date 30-Nov-2024

WEL - Workplace Exposure Limit
ACGIH - American Conference of Governmental Industrial Hygienists
DNEL - Derived No Effect Level
RPE - Respiratory Protective Equipment
LC50 - Lethal Concentration 50%
NOEC - No Observed Effect Concentration
PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average
IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)
LD50 - Lethal Dose 50%
EC50 - Effective Concentration 50%
POW - Partition coefficient Octanol:Water
vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road
IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code
OECD - Organisation for Economic Co-operation and Development
BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association
MARPOL - International Convention for the Prevention of Pollution from Ships
ATE - Acute Toxicity Estimate
VOC - (volatile organic compound)

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health Hazards	Calculation method
Environmental hazards	Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Prepared By	Health, Safety and Environmental Department
Revision Date	30-Nov-2024
Revision Summary	Not applicable.

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.
COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No
1907/2006 .**

**For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2,
Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and
Preparations).**

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet