

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: SAF Fixative Solution
Cat No. : MV1290, MV1291

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company Thermo Fisher Scientific
20 Dalglish Street
Thebarton
Adelaide
South Australia 5031
AUSTRALIA
Tel: 61 8 8238 9050 or 1800 33 11 63 (Toll Free)
Fax: 61 8 8238 9060 or 1800 00 70 54 (Toll Free)

E-mail address mbd-sds@thermofisher.com

1.4. Emergency telephone number

1800 331 163

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Based on available data, the classification criteria are not met

Health hazards

Skin Sensitization
Carcinogenicity

Category 1 (H317)
Category 2 (H351)

Environmental hazards

Based on available data, the classification criteria are not met

SAFETY DATA SHEET

SAF Fixative Solution

Revision Date 10-Dec-2021

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Warning

Hazard Statements

H317 - May cause an allergic skin reaction

H351 - Suspected of causing cancer

Precautionary Statements

P201 - Obtain special instructions before use

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water

P308 + P313 - IF exposed or concerned: Get medical advice/attention

P280 - Wear protective gloves/protective clothing/eye protection/face protection

2.3. Other hazards

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Acetic acid	64-19-7	200-580-7	2	Flam. Liq. 3 (H226) Skin Corr. 1A (H314) Eye Dam. 1 (H318)
Formaldehyde	50-00-0	200-001-8	1.5	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) Skin Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1 (H317) Carc. 1B (H350) Muta. 2 (H341) STOT SE 3 (H335)
Methanol	67-56-1	200-659-6	0.5	Flam. Liq. 2 (H225) Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Acetic acid	Skin Corr. 1A (H314) :: C>=90% Skin Corr. 1B (H314) :: 25%<=C<90% Eye Irrit. 2 (H319) ::	-	-

SAFETY DATA SHEET

SAF Fixative Solution

Revision Date 10-Dec-2021

	10%≤C<25% Skin Irrit. 2 (H315) :: 10%≤C<25%		
Formaldehyde	Skin Corr. 1B :: C≥25% Eye Irrit. 2 :: 5%≤C<25% Skin Irrit. 2 :: 5%≤C<25% Skin Sens. 1 :: C≥0.2% STOT SE 3 :: C≥5%	-	-
Methanol	STOT SE 1 (H370) :: C≥10% STOT SE 2 (H371) :: 3%≤C<10%	-	-

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Get medical attention.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Get medical attention.
Inhalation	Remove to fresh air. If breathing is difficult, give oxygen. Get medical attention.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

May cause allergic skin reaction. . Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically.
---------------------------	------------------------

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam.

Extinguishing media which must not be used for safety reasons

None.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors.

Hazardous Combustion Products

None under normal use conditions.

SAFETY DATA SHEET

SAF Fixative Solution

Revision Date 10-Dec-2021

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required. Ensure adequate ventilation.

6.2. Environmental precautions

Should not be released into the environment.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Do not get in eyes, on skin, or on clothing. Ensure adequate ventilation. Wear personal protective equipment/face protection. Avoid ingestion and inhalation.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Storage Class/LGK 12

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Third edition. Published 2018. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

SAFETY DATA SHEET

SAF Fixative Solution

Revision Date 10-Dec-2021

Component	European Union	The United Kingdom	France	Belgium	Spain
Acetic acid	TWA: 25 mg/m ³ (15min) TWA: 10 ppm (15min) STEL: 50 mg/m ³ (8h) STEL: 20 ppm (8h)	STEL: 37 mg/m ³ STEL: 15 ppm TWA: 10 ppm TWA: 25 mg/m ³	STEL / VLCT: 10 ppm. STEL / VLCT: 25 mg/m ³ .	TWA: 10 ppm 8 uren TWA: 25 mg/m ³ 8 uren STEL: 15 ppm 15 minuten STEL: 38 mg/m ³ 15 minuten	STEL / VLA-EC: 20 ppm (15 minutos). STEL / VLA-EC: 50 mg/m ³ (15 minutos). TWA / VLA-ED: 10 ppm (8 horas) TWA / VLA-ED: 25 mg/m ³ (8 horas)
Formaldehyde	TWA: 0.37 mg/m ³ (8h) TWA: 0.3 ppm (8h) Skin STEL: 0.74 mg/m ³ (8h) STEL: 0.6 ppm (8h)	STEL: 2 ppm 15 min STEL: 2.5 mg/m ³ 15 min TWA: 2 ppm 8 hr TWA: 2.5 mg/m ³ 8 hr Carc.	TWA / VME: 0.5 ppm (8 heures). STEL / VLCT: 1 ppm.		STEL / VLA-EC: 0.6 ppm (15 minutos). STEL / VLA-EC: 0.74 mg/m ³ (15 minutos). TWA / VLA-ED: 0.3 ppm (8 horas) TWA / VLA-ED: 0.37 mg/m ³ (8 horas)
Methanol	TWA: 200 ppm 8 hr TWA: 260 mg/m ³ 8 hr Skin	WEL - TWA: 200 ppm TWA: 266 mg/m ³ TWA WEL - STEL: 250 ppm STEL: 333 mg/m ³ STEL	TWA / VME: 200 ppm (8 heures). restrictive limit TWA / VME: 260 mg/m ³ (8 heures). restrictive limit STEL / VLCT: 1000 ppm. STEL / VLCT: 1300 mg/m ³ . Peau	TWA: 200 ppm 8 uren TWA: 266 mg/m ³ 8 uren STEL: 250 ppm 15 minuten STEL: 333 mg/m ³ 15 minuten Huid	TWA / VLA-ED: 200 ppm (8 horas) TWA / VLA-ED: 266 mg/m ³ (8 horas) Piel

Component	Italy	Germany	Portugal	The Netherlands	Finland
Acetic acid	TWA: 25 ppm 8 ore. Media Ponderata nel Tempo TWA: 10 mg/m ³ 8 ore. Media Ponderata nel Tempo STEL: 50 mg/m ³ 15 minuti. Breve termine STEL: 20 ppm 15 minuti. Breve termine	TWA: 10 ppm (8 Stunden). AGW - exposure factor 2 TWA: 25 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 10 ppm (8 Stunden). MAK TWA: 25 mg/m ³ (8 Stunden). MAK Höhepunkt: 20 ppm Höhepunkt: 50 mg/m ³	STEL: 20 ppm 15 minutos STEL: 50 mg/m ³ 15 minutos TWA: 10 ppm 8 horas TWA: 25 mg/m ³ 8 horas	MAC-TGG 25 mg/m ³	TWA: 5 ppm 8 tunteina TWA: 13 mg/m ³ 8 tunteina STEL: 10 ppm 15 minuutteina STEL: 25 mg/m ³ 15 minuutteina
Formaldehyde	TWA: 0.37 mg/m ³ 8 ore. Media Ponderata nel Tempo TWA: 0.3 ppm 8 ore. Media Ponderata nel Tempo TWA: 0.62 mg/m ³ 8 ore. Media Ponderata nel Tempo for the health care, funeral and embalming sectors until July 11, 2024 TWA: 0.5 ppm 8 ore. Media Ponderata nel Tempo for the health care, funeral and embalming sectors until July 11, 2024 STEL: 0.74 mg/m ³ 15 minuti. Breve termine STEL: 0.6 mg/m ³ 15 minuti. Breve termine Pelle	TWA: 0.3 ppm (8 Stunden). AGW - exposure factor 2 TWA: 0.37 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 0.3 ppm (8 Stunden). MAK no irritation should occur during mixed exposure TWA: 0.37 mg/m ³ (8 Stunden). MAK no irritation should occur during mixed exposure Höhepunkt: 0.6 ppm Höhepunkt: 0.74 mg/m ³	STEL: 0.6 ppm 15 minutos STEL: 0.74 mg/m ³ 15 minutos Ceiling: 0.3 ppm TWA: 0.3 ppm 8 horas TWA: 0.37 mg/m ³ 8 horas TWA: 0.62 mg/m ³ 8 horas TWA: 0.5 ppm 8 horas	STEL: 0.5 mg/m ³ 15 minuten TWA: 0.15 mg/m ³ 8 uren	TWA: 0.3 ppm 8 tunteina TWA: 0.37 mg/m ³ 8 tunteina STEL: 0.6 ppm 15 minuutteina STEL: 0.74 mg/m ³ 15 minuutteina
Methanol	TWA: 200 ppm 8 ore. Media Ponderata nel Tempo TWA: 260 mg/m ³ 8 ore. Media Ponderata nel	100 ppm TWA MAK; 130 mg/m ³ TWA MAKSkin absorber	STEL: 250 ppm 15 minutos TWA: 200 ppm 8 horas TWA: 260 mg/m ³ 8 horas	huid TWA: 133 mg/m ³ 8 uren	TWA: 200 ppm 8 tunteina TWA: 270 mg/m ³ 8 tunteina STEL: 250 ppm 15

SAFETY DATA SHEET

SAF Fixative Solution

Revision Date 10-Dec-2021

	Tempo Pelle		Pele		minuutteina STEL: 330 mg/m ³ 15 minuutteina Iho
--	-------------	--	------	--	--

Component	Austria	Denmark	Switzerland	Poland	Norway
Acetic acid	MAK-KZGW: 20 ppm 15 Minuten MAK-KZGW: 50 mg/m ³ 15 Minuten MAK-TMW: 10 ppm 8 Stunden MAK-TMW: 25 mg/m ³ 8 Stunden	TWA: 10 ppm 8 timer TWA: 25 mg/m ³ 8 timer	STEL: 20 ppm 15 Minuten STEL: 50 mg/m ³ 15 Minuten TWA: 10 ppm 8 Stunden TWA: 25 mg/m ³ 8 Stunden	STEL: 50 mg/m ³ 15 minutach TWA: 25 mg/m ³ 8 godzinach	TWA: 10 ppm 8 timer TWA: 25 mg/m ³ 8 timer STEL: 20 ppm 15 minutter. value from the regulation STEL: 50 mg/m ³ 15 minutter. value from the regulation
Formaldehyde	MAK-KZGW: 0.6 ppm 15 Minuten MAK-KZGW: 0.74 mg/m ³ 15 Minuten MAK-TMW: 0.3 ppm 8 Stunden MAK-TMW: 0.37 mg/m ³ 8 Stunden	Ceiling: 0.3 ppm Ceiling: 0.4 mg/m ³	STEL: 0.6 ppm 15 Minuten STEL: 0.74 mg/m ³ 15 Minuten TWA: 0.3 ppm 8 Stunden TWA: 0.37 mg/m ³ 8 Stunden	STEL: 0.74 mg/m ³ 15 minutach TWA: 0.37 mg/m ³ 8 godzinach	TWA: 0.5 ppm 8 timer TWA: 0.6 mg/m ³ 8 timer Ceiling: 1 ppm Ceiling: 1.2 mg/m ³
Methanol	Haut MAK-KZGW: 800 ppm 15 Minuten MAK-KZGW: 1040 mg/m ³ 15 Minuten MAK-TMW: 200 ppm 8 Stunden MAK-TMW: 260 mg/m ³ 8 Stunden	TWA: 200 ppm 8 timer TWA: 260 mg/m ³ 8 timer Hud	Haut/Peau STEL: 400 ppm 15 Minuten STEL: 520 mg/m ³ 15 Minuten TWA: 200 ppm 8 Stunden TWA: 260 mg/m ³ 8 Stunden	STEL: 300 mg/m ³ 15 minutach TWA: 100 mg/m ³ 8 godzinach	TWA: 100 ppm 8 timer TWA: 130 mg/m ³ 8 timer STEL: 150 ppm 15 minutter. value calculated STEL: 162.5 mg/m ³ 15 minutter. value calculated Hud

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Acetic acid	TWA: 25 mg/m ³ TWA: 10 ppm STEL : 50 mg/m ³ STEL : 20 ppm	TWA-GVI: 10 ppm 8 satima. TWA-GVI: 25 mg/m ³ 8 satima. STEL-KGVI: 20 ppm 15 minutama. STEL-KGVI: 50 mg/m ³ 15 minutama.	TWA: 20 ppm 8 hr. TWA: 50 mg/m ³ 8 hr. STEL: 20 ppm 15 min STEL: 50 mg/m ³ 15 min	STEL: 50 mg/m ³ STEL: 20 ppm TWA: 10 ppm TWA: 25 mg/m ³	TWA: 25 mg/m ³ 8 hodinách. Ceiling: 50 mg/m ³
Formaldehyde	TWA: 1.0 mg/m ³ STEL : 2.0 mg/m ³	TWA-GVI: 0.3 ppm 8 satima. TWA-GVI: 0.37 mg/m ³ 8 satima. TWA-GVI: 0.5 ppm 8 satima. for health, funeral and embalming sector applies until July 11, 2024 TWA-GVI: 0.62 mg/m ³ 8 satima. for health, funeral and embalming sector applies until July 11, 2024 STEL-KGVI: 0.6 ppm 15 minutama. STEL-KGVI: 0.74 mg/m ³ 15 minutama.	TWA: 0.3 ppm 8 hr. TWA: 0.5 ppm 8 hr. for the healthcare, funeral and embalming sectors until July 11, 2024 TWA: 0.37 mg/m ³ 8 hr. TWA: 0.62 mg/m ³ 8 hr. for the healthcare, funeral and embalming sectors until July 11, 2024 STEL: 0.6 ppm 15 min STEL: 0.738 mg/m ³ 15 min STEL: 0.62 mg/m ³ 15 min		TWA: 0.5 mg/m ³ 8 hodinách. Potential for cutaneous absorption Ceiling: 1 mg/m ³
Methanol	TWA: 200 ppm TWA: 260.0 mg/m ³ Skin notation	kože TWA-GVI: 200 ppm 8 satima. TWA-GVI: 260 mg/m ³ 8 satima.	TWA: 200 ppm 8 hr. TWA: 260 mg/m ³ 8 hr. STEL: 600 ppm 15 min STEL: 780 mg/m ³ 15 min Skin	Skin-potential for cutaneous absorption TWA: 200 ppm TWA: 260 mg/m ³	TWA: 250 mg/m ³ 8 hodinách. Potential for cutaneous absorption Ceiling: 1000 mg/m ³

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Acetic acid	TWA: 10 ppm 8 tundides.	TWA: 25 mg/m ³ 8 hr TWA: 10 ppm 8 hr	STEL: 15 ppm STEL: 37 mg/m ³	STEL: 50 mg/m ³ 15 percekken. CK	STEL: 20 ppm STEL: 50 mg/m ³

SAFETY DATA SHEET

SAF Fixative Solution

Revision Date 10-Dec-2021

	TWA: 25 mg/m ³ 8 tündides. STEL: 10 ppm 15 minutites. STEL: 25 mg/m ³ 15 minutites.	STEL: 50 mg/m ³ 15 min STEL: 20 ppm 15 min	TWA: 10 ppm TWA: 25 mg/m ³	TWA: 25 mg/m ³ 8 órában. AK	TWA: 10 ppm 8 klukkustundum. TWA: 25 mg/m ³ 8 klukkustundum.
Formaldehyde	TWA: 0.5 ppm 8 tündides. TWA: 0.6 mg/m ³ 8 tündides. STEL: 1 ppm 15 minutites. STEL: 1.2 mg/m ³ 15 minutites.		STEL: 0.6 ppm STEL: 0.74 mg/m ³ TWA: 0.3 ppm TWA: 0.37 mg/m ³	STEL: 0.6 mg/m ³ 15 percekben. CK TWA: 0.6 mg/m ³ 8 órában. AK lehetséges borön keresztül felszívódás	STEL: 0.6 ppm STEL: 0.74 mg/m ³ TWA: 0.3 ppm 8 klukkustundum. TWA: 0.37 mg/m ³ 8 klukkustundum. Skin notation
Methanol	Nahk TWA: 200 ppm 8 tündides. TWA: 250 mg/m ³ 8 tündides. STEL: 250 ppm 15 minutites. STEL: 350 mg/m ³ 15 minutites.	Skin notation TWA: 200 ppm 8 hr TWA: 260 mg/m ³ 8 hr	skin - potential for cutaneous absorption STEL: 250 ppm STEL: 325 mg/m ³ TWA: 200 ppm TWA: 260 mg/m ³	TWA: 260 mg/m ³ 8 órában. AK lehetséges borön keresztül felszívódás	TWA: 200 ppm 8 klukkustundum. TWA: 260 mg/m ³ 8 klukkustundum. Skin notation Ceiling: 400 ppm Ceiling: 520 mg/m ³

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Acetic acid	STEL: 50 mg/m ³ STEL: 20 ppm TWA: 10 ppm TWA: 25 mg/m ³	TWA: 10 ppm IPRD TWA: 25 mg/m ³ IPRD STEL: 50 mg/m ³ STEL: 20 ppm	TWA: 10 ppm 8 Stunden TWA: 25 mg/m ³ 8 Stunden STEL: 50 mg/m ³ 15 Minuten STEL: 20 ppm 15 Minuten	TWA: 10 ppm TWA: 25 mg/m ³ STEL: 20 ppm 15 minuti STEL: 50 mg/m ³ 15 minuti	TWA: 10 ppm 8 ore TWA: 25 mg/m ³ 8 ore STEL: 20 ppm 15 minute STEL: 50 mg/m ³ 15 minute
Formaldehyde	TWA: 0.5 mg/m ³	TWA: 0.3 ppm IPRD TWA: 0.37 mg/m ³ IPRD TWA: 0.62 mg/m ³ IPRD for healthcare, funeral, and embalming industries TWA: 0.5 ppm IPRD for healthcare, funeral, and embalming industries STEL: 0.74 mg/m ³ STEL: 0.6 ppm			TWA: 1 ppm 8 ore TWA: 1.2 mg/m ³ 8 ore STEL: 2 ppm 15 minute STEL: 3 mg/m ³ 15 minute
Methanol	skin - potential for cutaneous exposure TWA: 200 ppm TWA: 260 mg/m ³	TWA: 200 ppm IPRD TWA: 260 mg/m ³ IPRD Oda	Possibility of significant uptake through the skin TWA: 200 ppm 8 Stunden TWA: 260 mg/m ³ 8 Stunden	possibility of significant uptake through the skin TWA: 200 ppm TWA: 260 mg/m ³	Skin notation TWA: 200 ppm 8 ore TWA: 260 mg/m ³ 8 ore

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Acetic acid	Skin notation MAC: 5 mg/m ³	Ceiling: 50 mg/m ³ TWA: 10 ppm TWA: 25 mg/m ³	TWA: 10 ppm 8 urah TWA: 25 mg/m ³ 8 urah STEL: 50 mg/m ³ 15 minutah STEL: 20 ppm 15 minutah	Binding STEL: 10 ppm 15 minuter Binding STEL: 25 mg/m ³ 15 minuter TLV: 5 ppm 8 timmar. NGV TLV: 13 mg/m ³ 8 timmar. NGV	TWA: 10 ppm 8 saat TWA: 25 mg/m ³ 8 saat
Formaldehyde	Skin notation MAC: 0.5 mg/m ³	Ceiling: 0.74 mg/m ³ TWA: 0.3 ppm TWA: 0.37 mg/m ³	TWA: 0.62 mg/m ³ 8 urah applies for health care, funeral and embalming activities until July 11, 2024 TWA: 0.5 ppm 8 urah applies for health care, funeral and embalming activities until July 11,	Binding STEL: 0.6 ppm 15 minuter Binding STEL: 0.74 mg/m ³ 15 minuter TLV: 0.3 ppm 8 timmar. NGV TLV: 0.37 mg/m ³ 8 timmar. NGV Hud	

SAFETY DATA SHEET

SAF Fixative Solution

Revision Date 10-Dec-2021

			2024 TWA: 0.37 mg/m ³ 8 urah TWA: 0.3 ppm 8 urah Koža STEL: 0.6 ppm 15 minutah STEL: 0.74 mg/m ³ 15 minutah		
Methanol	TWA: 5 mg/m ³ 1250 Skin notation MAC: 15 mg/m ³	Potential for cutaneous absorption TWA: 200 ppm TWA: 260 mg/m ³	TWA: 200 ppm 8 urah TWA: 260 mg/m ³ 8 urah Koža STEL: 800 ppm 15 minutah STEL: 1040 mg/m ³ 15 minutah	Indicative STEL: 250 ppm 15 minuter Indicative STEL: 350 mg/m ³ 15 minuter TLV: 200 ppm 8 timmar. NGV TLV: 250 mg/m ³ 8 timmar. NGV Hud	Deri TWA: 200 ppm 8 saat TWA: 260 mg/m ³ 8 saat

Biological limit values

List source(s):

Component	European Union	United Kingdom	France	Spain	Germany
Methanol			Methanol: 15 mg/L urine end of shift	Methanol: 15 mg/L urine end of shift	Methanol: 15 mg/L urine (end of shift) Methanol: 15 mg/L urine (for long-term exposures: at the end of the shift after several shifts)

Component	Italy	Finland	Denmark	Bulgaria	Romania
Methanol					Methanol: 6 mg/L urine end of shift

Component	Gibraltar	Latvia	Slovak Republic	Luxembourg	Turkey
Methanol			Methanol: 30 mg/L urine end of exposure or work shift Methanol: 30 mg/L urine after all work shifts for long-term exposure		

Monitoring methods

MDHS78 Formaldehyde in air. Laboratory method using a diffusive sampler, solvent desorption and high performance liquid chromatography

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Formaldehyde 50-00-0 (1.5)			DNEL = 37µg/cm ²	DNEL = 240mg/kg bw/day
Methanol 67-56-1 (0.5)		DNEL = 20mg/kg bw/day		DNEL = 20mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Acetic acid 64-19-7 (2)	DNEL = 25mg/m ³		DNEL = 25mg/m ³	

SAFETY DATA SHEET

SAF Fixative Solution

Revision Date 10-Dec-2021

Formaldehyde 50-00-0 (1.5)	DNEL = 0.75mg/m ³		DNEL = 0.375mg/m ³	DNEL = 9mg/m ³
Methanol 67-56-1 (0.5)	DNEL = 130mg/m ³	DNEL = 130mg/m ³	DNEL = 130mg/m ³	DNEL = 130mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Acetic acid 64-19-7 (2)	PNEC = 3.058mg/L	PNEC = 11.36mg/kg sediment dw	PNEC = 30.58mg/L	PNEC = 85mg/L	PNEC = 0.47mg/kg soil dw
Formaldehyde 50-00-0 (1.5)	PNEC = 0.44mg/L	PNEC = 2.3mg/kg sediment dw	PNEC = 4.44mg/L	PNEC = 0.19mg/L	PNEC = 0.2mg/kg soil dw
Methanol 67-56-1 (0.5)	PNEC = 20.8mg/L	PNEC = 77mg/kg sediment dw	PNEC = 1540mg/L	PNEC = 100mg/L	PNEC = 100mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Acetic acid 64-19-7 (2)	PNEC = 0.3058mg/L	PNEC = 1.136mg/kg sediment dw			
Formaldehyde 50-00-0 (1.5)	PNEC = 0.44mg/L	PNEC = 2.3mg/kg sediment dw			
Methanol 67-56-1 (0.5)	PNEC = 2.08mg/L	PNEC = 7.7mg/kg sediment dw			

8.2. Exposure controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Wear safety glasses with side shields (or goggles) (European standard - EN 166)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Disposable gloves	See manufacturers recommendations	-	EN 374	(minimum requirement)

Skin and body protection

Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use

In case of insufficient ventilation, wear suitable respiratory equipment

Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure

SAFETY DATA SHEET

SAF Fixative Solution

Revision Date 10-Dec-2021

limits are exceeded or if irritation or other symptoms are experienced.
When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls No information available.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance	No information available	
Odor	No information available	
Odor Threshold	No data available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flammability (liquid)	No data available	
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Flash Point	No information available	Method - No information available
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
pH	No information available	
Viscosity	No data available	
Water Solubility	No information available	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Acetic acid	-0.2	
Formaldehyde	-0.35	
Methanol	-0.74	
Vapor Pressure	No data available	
Density / Specific Gravity	No data available	
Bulk Density	Not applicable	Liquid
Vapor Density	No data available	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization Hazardous polymerization does not occur.
Hazardous Reactions None under normal processing.

10.4. Conditions to avoid

Incompatible products. Excess heat.

SAFETY DATA SHEET

SAF Fixative Solution

Revision Date 10-Dec-2021

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

None under normal use conditions.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral

Based on available data, the classification criteria are not met

Dermal

Based on available data, the classification criteria are not met

Inhalation

Based on available data, the classification criteria are not met

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Acetic acid	3310 mg/kg (Rat)	-	> 40 mg/L (Rat) 4 h
Formaldehyde	500 mg/kg (Rat)	LD50 = 270 mg/kg (Rabbit)	0.578 mg/L (Rat) 4 h
Methanol	LD50 = 1187 – 2769 mg/kg (Rat)	LD50 = 17100 mg/kg (Rabbit)	LC50 = 128.2 mg/L (Rat) 4 h

(b) skin corrosion/irritation;

No data available

(c) serious eye damage/irritation;

No data available

(d) respiratory or skin sensitization;

Respiratory

No data available

Skin

Category 1

Component	Test method	Test species	Study result
Formaldehyde 50-00-0 (1.5)	Skin sensitization Test method Patch Test Respiratory sensitization in vitro	Man guinea pig	Sensitizer Sensitization
Methanol 67-56-1 (0.5)	OECD Test Guideline 406 Guinea Pig Maximisation Test (GPMT)	guinea pig	non-sensitising

No information available

(e) germ cell mutagenicity;

No data available

None known

(f) carcinogenicity;

Category 2

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Formaldehyde	Carc Cat. 1B	Cat 3		Group 1

(g) reproductive toxicity;

No data available

SAFETY DATA SHEET

SAF Fixative Solution

Revision Date 10-Dec-2021

Component	Test method	Test species / Duration	Study result
Methanol 67-56-1 (0.5)	OECD Test Guideline 416	Rat / Inhalation 2 Generation	NOAEC = 1.3 mg/l (air)

Reproductive Effects
Developmental Effects

None known.
None known.

(h) STOT-single exposure; No data available

(i) STOT-repeated exposure; No data available

Target Organs No information available.

(j) aspiration hazard; No data available

Symptoms / effects, both acute and delayed Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

Contains no substances known to be hazardous to the environment or that are not degradable in waste water treatment plants.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Acetic acid	Pimephales promelas: LC50 = 88 mg/L/96h Lepomis macrochirus: LC50 = 75 mg/L/96h	EC50 = 95 mg/L/24h	-
Formaldehyde	Leuciscus idus: LC50 = 15 mg/L/96h	EC50 = 20 mg/L/96h EC50 = 2 mg/L/48h	
Methanol	Pimephales promelas: LC50 > 10000 mg/L/96h	EC50 > 10000 mg/L/24h	

Component	Microtox	M-Factor
Acetic acid	Photobacterium phosphoreum: EC50 = 8.8 mg/L/15 min Photobacterium phosphoreum: EC50 = 8.8 mg/L/25 min Photobacterium phosphoreum: EC50 = 8.8 mg/L/5 min	
Methanol	EC50 = 39000 mg/L/25 min EC50 = 40000 mg/L/15 min EC50 = 43000 mg/L/5 min	

12.2. Persistence and degradability

No information available

Component	Degradability
Methanol 67-56-1 (0.5)	DT50 ~ 17.2d >94% after 20d

SAFETY DATA SHEET

SAF Fixative Solution

Revision Date 10-Dec-2021

12.3. Bioaccumulative potential No information available

Component	log Pow	Bioconcentration factor (BCF)
Acetic acid	-0.2	No data available
Formaldehyde	-0.35	No data available
Methanol	-0.74	<10

12.4. Mobility in soil No information available

12.5. Results of PBT and vPvB assessment No data available for assessment.

12.6. Endocrine disrupting properties

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant

This product does not contain any known or suspected substance

Ozone Depletion Potential

This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products

Dispose of in accordance with federal, state and local regulations.

Contaminated Packaging

Empty remaining contents. Dispose of in accordance with local regulations. Do not re-use empty containers.

European Waste Catalogue (EWC)

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information

Waste codes should be assigned by the user based on the application for which the product was used.

Switzerland - Waste Ordinance

Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600
<https://www.fedlex.admin.ch/eli/cc/2015/891/en>

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

Not regulated

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

ADR

Not regulated

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

OXDAUMV1290

SAFETY DATA SHEET

SAF Fixative Solution

Revision Date 10-Dec-2021

IATA Not regulated

14.1. UN number

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

14.5. Environmental hazards No hazards identified

14.6. Special precautions for user No special precautions required

14.7. Maritime transport in bulk according to IMO instruments Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Acetic acid	64-19-7	200-580-7	-	-	X	X	X	X	X
Formaldehyde	50-00-0	200-001-8	-	-	X	X	KE-17074	X	X
Methanol	67-56-1	200-659-6	-	-	X	X	KE-23193	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Acetic acid	64-19-7	X	ACTIVE	X	-	X	X	X
Formaldehyde	50-00-0	X	ACTIVE	X	-	X	X	X
Methanol	67-56-1	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Acetic acid	-	Use restricted. See item 75. (see link for restriction details)	-
Formaldehyde	-	Use restricted. See item 72. (see link for restriction details) Use restricted. See item 28. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-
Methanol	-	Use restricted. See item 69. (see link for restriction details)	-

<https://echa.europa.eu/substances-restricted-under-reach>

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Acetic acid	64-19-7	Not applicable	Not applicable

SAFETY DATA SHEET

SAF Fixative Solution

Revision Date 10-Dec-2021

Formaldehyde	50-00-0	5 tonne	50 tonne
Methanol	67-56-1	500 tonne	5000 tonne

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work. Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 1 (self classification)

Component	Germany - Water Classification (VwVwS)	Germany - TA-Luft Class
Acetic acid	WGK1	Class II : 0.10 g/m ³ (Massenkonzentration)
Formaldehyde	WGK 3	Class I : 20 mg/m ³ (Massenkonzentration)
Methanol	WGK 2	

Component	France - INRS (Tables of occupational diseases)
Formaldehyde	Tableaux des maladies professionnelles (TMP) - RG 43
Methanol	Tableaux des maladies professionnelles (TMP) - RG 84

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Acetic acid 64-19-7 (2)	Prohibited and Restricted Substances	Group I	
Formaldehyde 50-00-0 (1.5)		Group I	
Methanol 67-56-1 (0.5)	Prohibited and Restricted Substances	Group I	

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H301 - Toxic if swallowed

H311 - Toxic in contact with skin

H331 - Toxic if inhaled

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

H317 - May cause an allergic skin reaction

H351 - Suspected of causing cancer if inhaled

H226 - Flammable liquid and vapor

SAFETY DATA SHEET

SAF Fixative Solution

Revision Date 10-Dec-2021

H370 - Causes damage to organs if inhaled
H225 - Highly flammable liquid and vapor
H351 - Suspected of causing cancer

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadviser - LOLI, Merck index, RTECS

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data

Health Hazards Calculation method

Environmental hazards Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Prepared By Regulatory Affairs on behalf of Thermo Fisher Scientific Australia

Creation Date 23-Nov-2012

Revision Date 10-Dec-2021

Revision Summary Not applicable.

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.
COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No
1907/2006 .**

**For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2,
Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and
Preparations).**

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

SAFETY DATA SHEET

SAF Fixative Solution

Revision Date 10-Dec-2021

End of Safety Data Sheet