

Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**
**Product Identifier**

Perihal Produk:

Product Description:

Cat No. :

Molecular Formula

**n-Butyllithium, 2.5M solution in hexanes**
**n-Butyllithium, 2.5M solution in hexanes**

213350000; 213350500; 213351000; 213358000

C4 H9 Li

**Relevant identified uses of the substance or mixture and uses advised against**

Recommended Use

Laboratory chemicals.

Uses advised against

No Information available

**Company**

 Thermo Fisher Scientific Fisher Scientific (M) Sdn Bhd  
 Hap Seng Business Park, Lot 01-03, 01-04 Aras 1 Unity Square,  
 No 12, Persiaran Perusahaan, Seksyen 23, 40300 Shah Alam,  
 Selangor Darul Ehsan, Malaysia.  
 Main line: +60 3-5525 7888

**E-mail address**

Enquiry.my@thermofisher.com

**Emergency Telephone Number**

Tel: +03-5525 7888

 CHEMTREC Malaysia **1-800-815-308** (Malay)

 CHEMTREC Malaysia (Kuala Lumpur) **+(60)-327884561** (Malay)

**SECTION 2: HAZARDS IDENTIFICATION**
**Classification of the substance or mixture**

|                                                                        |                     |
|------------------------------------------------------------------------|---------------------|
| Flammable liquids                                                      | Category 2 (H225)   |
| Substances/mixtures which, in contact with water, emit flammable gases | Category 1 (H260)   |
| Pyrophoric liquids                                                     | Category 1 (H250)   |
| Aspiration Toxicity                                                    | Category 1 (H304)   |
| Skin Corrosion/Irritation                                              | Category 1 B (H314) |
| Serious Eye Damage/Eye Irritation                                      | Category 1 (H318)   |
| Reproductive Toxicity                                                  | Category 2 (H361f)  |
| Specific target organ toxicity - (single exposure)                     | Category 3 (H336)   |
| Specific target organ toxicity - (repeated exposure)                   | Category 2 (H373)   |
| Chronic aquatic toxicity                                               | Category 2 (H411)   |

**Label Elements**


# SAFETY DATA SHEET

n-Butyllithium, 2.5M solution in hexanes

Revision Date 22-Mar-2025

## Signal Word

## Danger

### Hazard Statements

H225 - Highly flammable liquid and vapor  
H250 - Catches fire spontaneously if exposed to air  
H260 - In contact with water releases flammable gases which may ignite spontaneously  
H304 - May be fatal if swallowed and enters airways  
H314 - Causes severe skin burns and eye damage  
H336 - May cause drowsiness or dizziness  
H361f - Suspected of damaging fertility  
H373 - May cause damage to organs through prolonged or repeated exposure  
H411 - Toxic to aquatic life with long lasting effects

### Precautionary Statements

#### Prevention

P201 - Obtain special instructions before use  
P202 - Do not handle until all safety precautions have been read and understood  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P222 - Do not allow contact with air  
P231 + P232 - Handle and store contents under inert gas. Protect from moisture  
P240 - Ground and bond container and receiving equipment  
P241 - Use explosion-proof electrical/ ventilating/ lighting equipment  
P242 - Use non-sparking tools  
P243 - Take action to prevent static discharges  
P264 - Wash face, hands and any exposed skin thoroughly after handling  
P271 - Use only outdoors or in a well-ventilated area  
P280 - Wear protective gloves/protective clothing/eye protection/face protection

#### Response

P302 + P334 - IF ON SKIN: Immerse in cool water or wrap in wet bandages  
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P310 - Immediately call a POISON CENTER or doctor  
P330 - Rinse mouth  
P331 - Do NOT induce vomiting  
P363 - Wash contaminated clothing before reuse  
P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

#### Storage

P402 + P404 - Store in a dry place. Store in a closed container  
P422 - Store contents under inert gas

#### Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

### Other Hazards

EUH014 - Reacts violently with water  
This product does not contain any known or suspected endocrine disruptors  
Toxic to terrestrial vertebrates

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

| Component     | CAS No   | Weight % |
|---------------|----------|----------|
| Hexane        | 110-54-3 | 77       |
| Butyl lithium | 109-72-8 | 23       |

# SAFETY DATA SHEET

n-Butyllithium, 2.5M solution in hexanes

Revision Date 22-Mar-2025

## SECTION 4: FIRST AID MEASURES

### Description of first aid measures

|                                           |                                                                                                                                                                                                                                                                                                                                                                                     |
|-------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>General Advice</b>                     | Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.                                                                                                                                                                                                                                                                                   |
| <b>Eye Contact</b>                        | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.                                                                                                                                                                                                                                                   |
| <b>Skin Contact</b>                       | Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Call a physician immediately.                                                                                                                                                                                             |
| <b>Ingestion</b>                          | Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.                                                                                                                                 |
| <b>Inhalation</b>                         | If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately. Risk of serious damage to the lungs (by aspiration). |
| <b>Self-Protection of the First Aider</b> | Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.                                                                                                                                                                                                                                    |

### Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation.

### Indication of any immediate medical attention and special treatment needed

**Notes to Physician** Treat symptomatically. Symptoms may be delayed.

## SECTION 5: FIREFIGHTING MEASURES

### Extinguishing media

#### **Suitable Extinguishing Media**

Water spray, fog or alcohol-resistant foam. Water mist may be used to cool closed containers.

#### **Extinguishing media which must not be used for safety reasons**

Water. Carbon dioxide (CO<sub>2</sub>). Foam.

### Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Reacts violently with water. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

### **Hazardous Combustion Products**

Butane, Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>).

### Advice for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

# SAFETY DATA SHEET

n-Butyllithium, 2.5M solution in hexanes

Revision Date 22-Mar-2025

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### Personal Precautions, Protective Equipment and Emergency Procedures

Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

### Environmental precautions

Do not flush into surface water or sanitary sewer system.

### Methods and Material for Containment and Cleaning Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Do not expose spill to water. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

### Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

## SECTION 7: HANDLING AND STORAGE

### Precautions for Safe Handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Do not allow contact with water. Handle under an inert atmosphere. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

### Conditions for Safe Storage, Including any Incompatibilities

Store under an inert atmosphere. Keep away from water or moist air. Keep refrigerated. Keep away from heat, sparks and flame. Flammables area. Protect from moisture. Keep container tightly closed.

### Specific End Uses

Use in laboratories.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control Parameters

| Component | Malaysia | ACGIH TLV           | OSHA PEL                                                                                                     |
|-----------|----------|---------------------|--------------------------------------------------------------------------------------------------------------|
| Hexane    |          | TWA: 50 ppm<br>Skin | (Vacated) TWA: 50 ppm<br>(Vacated) TWA: 180 mg/m <sup>3</sup><br>TWA: 500 ppm<br>TWA: 1800 mg/m <sup>3</sup> |

| Component     | European Union                                       | The United Kingdom                                                                      | Germany                                                                                                                                      |
|---------------|------------------------------------------------------|-----------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| Hexane        | TWA: 20 ppm (8hr)<br>TWA: 72 mg/m <sup>3</sup> (8hr) | TWA: 72 mg/m <sup>3</sup><br>TWA: 20 ppm<br>STEL: 60 ppm<br>STEL: 216 mg/m <sup>3</sup> | TWA: 180 mg/m <sup>3</sup><br>TWA: 50 ppm                                                                                                    |
| Butyl lithium |                                                      |                                                                                         | TWA: 0.2 mg/m <sup>3</sup> (8 Stunden). MAK inorganic compounds, except Lithium and strong irritant Lithium compounds such as Lithium amide, |

# SAFETY DATA SHEET

n-Butyllithium, 2.5M solution in hexanes

Revision Date 22-Mar-2025

|  |  |  |                                                                                                                                     |
|--|--|--|-------------------------------------------------------------------------------------------------------------------------------------|
|  |  |  | Lithium hydride, Lithium hydroxide,<br>Lithium nitride, Lithium oxide,<br>Lithium tetrahydro aluminate,<br>Lithium tetrahydroborate |
|--|--|--|-------------------------------------------------------------------------------------------------------------------------------------|

## Exposure Controls

### Engineering Measures

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

## Personal protective equipment

### Eye Protection

Goggles

### Hand Protection

Protective gloves

### Skin and body protection

Long sleeved clothing

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

### Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

## Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice

## Environmental exposure controls

Prevent product from entering drains Do not allow material to contaminate ground water system

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

#### Appearance

Yellow

#### Physical State

Liquid

#### Odor

Petroleum distillates

#### Odor Threshold

No data available

#### pH

Not applicable

#### Melting Point/Range

No data available

#### Softening Point

No data available

#### Boiling Point/Range

No information available

#### Flash Point

-21 °C / -5.8 °F

Method - No information available

#### Evaporation Rate

No data available

#### Flammability (solid,gas)

Not applicable

Liquid

#### Explosion Limits

Lower 1.2 vol %

# SAFETY DATA SHEET

n-Butyllithium, 2.5M solution in hexanes

Revision Date 22-Mar-2025

Upper 7.8 vol %

|                              |                          |             |
|------------------------------|--------------------------|-------------|
| Vapor Pressure               | 160 mbar @ 20 °C         |             |
| Vapor Density                | No data available        | (Air = 1.0) |
| Specific Gravity / Density   | 0.690                    |             |
| Bulk Density                 | Not applicable           | Liquid      |
| Water Solubility             | Reacts with water        |             |
| Solubility in other solvents | No information available |             |

## Partition Coefficient (n-octanol/water)

|           |         |
|-----------|---------|
| Component | log Pow |
| Hexane    | 4.11    |

|                           |                          |                                             |
|---------------------------|--------------------------|---------------------------------------------|
| Autoignition Temperature  | No data available        |                                             |
| Decomposition Temperature | No data available        |                                             |
| Viscosity                 | No data available        |                                             |
| Explosive Properties      |                          | Vapors may form explosive mixtures with air |
| Oxidizing Properties      | No information available |                                             |

|                   |          |
|-------------------|----------|
| Molecular Formula | C4 H9 Li |
| Molecular Weight  | 64.06    |

## SECTION 10: STABILITY AND REACTIVITY

### Reactivity

Yes.

### Chemical Stability

Pyrophoric: Spontaneously flammable in air. Reacts violently with water. Air sensitive. Moisture sensitive.

### Possibility of Hazardous Reactions

|                          |                                                            |
|--------------------------|------------------------------------------------------------|
| Hazardous Polymerization | No information available.                                  |
| Hazardous Reactions      | None under normal processing. Reacts violently with water. |

### Conditions to Avoid

Incompatible products. Heat, flames and sparks. Exposure to moist air or water. Exposure to air. Exposure to moisture. Keep away from open flames, hot surfaces and sources of ignition.

### Incompatible Materials

Strong oxidizing agents. Halogens. Bases. Acids. Alcohols.

### Hazardous Decomposition Products

Butane. Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

# SAFETY DATA SHEET

n-Butyllithium, 2.5M solution in hexanes

Revision Date 22-Mar-2025

## SECTION 11: TOXICOLOGICAL INFORMATION

### Information on Toxicological Effects

#### Product Information

(a) acute toxicity;

Oral

Based on available data, the classification criteria are not met

Dermal

Based on available data, the classification criteria are not met

Inhalation

Based on available data, the classification criteria are not met

#### Toxicology data for the components

| Component | LD50 Oral              | LD50 Dermal                  | LC50 Inhalation              |
|-----------|------------------------|------------------------------|------------------------------|
| Hexane    | LD50 = 25 g/kg ( Rat ) | LD50 = 3000 mg/kg ( Rabbit ) | LC50 = 48000 ppm ( Rat ) 4 h |

(b) skin corrosion/irritation; Category 1 B

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;

Respiratory

No data available

Skin

No data available

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; No data available

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity;

Reproductive Effects

Category 2

Developmental Effects

Experiments have shown reproductive toxicity effects on laboratory animals.

Teratogenicity

Developmental effects have occurred in experimental animals.

Teratogenic effects have occurred in experimental animals.

(h) STOT-single exposure; Category 3

Results / Target organs

Central nervous system (CNS).

(i) STOT-repeated exposure; Category 2

Target Organs

Eyes, Respiratory system, Skin, Gastrointestinal tract (GI), Central nervous system (CNS), Liver, Peripheral Nervous System (PNS).

(j) aspiration hazard; Category 1

#### Other Adverse Effects

Tumorigenic effects have been reported in experimental animals.

#### Symptoms / effects, both acute and delayed

Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation.

# SAFETY DATA SHEET

n-Butyllithium, 2.5M solution in hexanes

Revision Date 22-Mar-2025

**Endocrine Disrupting Properties** Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

## SECTION 12: ECOLOGICAL INFORMATION

**Ecotoxicity effects** Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment. Reacts with water so no ecotoxicity data for the substance is available.

| Component | Freshwater Fish                                                     | Water Flea          | Freshwater Algae | Microtox |
|-----------|---------------------------------------------------------------------|---------------------|------------------|----------|
| Hexane    | LC50: 2.1 - 2.98 mg/L,<br>96h flow-through<br>(Pimephales promelas) | EC50: 3.87 mg/L/48h |                  |          |

**Persistence and degradability**  
**Persistence** Persistence is unlikely, based on information available.  
**Degradability** Reacts with water.  
**Degradation in sewage treatment plant** Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants. Water reactive.

**Bioaccumulative potential** Product does not bioaccumulate due to reaction with water

| Component | log Pow | Bioconcentration factor (BCF) |
|-----------|---------|-------------------------------|
| Hexane    | 4.11    | No data available             |

**Mobility in soil** The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Reacts with water. Will likely be mobile in the environment due to its volatility. Is not likely mobile in the environment. Disperses rapidly in air.

**Endocrine Disruptor Information** This product does not contain any known or suspected endocrine disruptors

**Other adverse effects** No information available

## SECTION 13: DISPOSAL CONSIDERATIONS

**Waste treatment methods**  
**Waste from Residues/Unused Products** Waste is classified as hazardous Dispose of in accordance with the European Directives on waste and hazardous waste Dispose of in accordance with local regulations

**Contaminated Packaging** Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous Keep product and empty container away from heat and sources of ignition

**Other Information** Do not flush to sewer Waste codes should be assigned by the user based on the application for which the product was used Can be landfilled or incinerated, when in compliance with local regulations Do not empty into drains Large amounts will affect pH and harm aquatic organisms Do not let this chemical enter the environment

## SECTION 14: TRANSPORT INFORMATION



# SAFETY DATA SHEET

n-Butyllithium, 2.5M solution in hexanes

Revision Date 22-Mar-2025

## IMDG/IMO

UN-No UN3394  
Hazard Class 4.2  
Subsidiary Hazard Class 4.3  
Packing Group I  
Proper Shipping Name ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE (N-BUTYLLITHIUM, HEXANE)

## Road and Rail Transport

UN-No UN3394  
Hazard Class 4.2  
Subsidiary Hazard Class 4.3  
Packing Group I  
Proper Shipping Name ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE (N-BUTYLLITHIUM, HEXANE)

## IATA

FORBIDDEN FOR IATA TRANSPORT  
UN-No UN3394  
Hazard Class 4.2  
Subsidiary Hazard Class 4.3  
Packing Group I  
Proper Shipping Name ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE, FORBIDDEN FOR IATA TRANSPORT (N-BUTYLLITHIUM, HEXANE)

Special Precautions for User No special precautions required

## SECTION 15: REGULATORY INFORMATION

### Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International Inventories

China X = listed Australia U.S.A. (TSCA) Canada (DSL/NDSL) Europe (EINECS/ELINCS/NLP) Australia (AICS) Korea (KECL) China (IECSC) Japan (ENCS) Philippines (PICCS) Taiwan (TCSI) Japan (ISHL) New Zealand (NZIoC) Japan (ISHL)

| Component     | EINECS    | TSCA | DSL | PICCS | ENCS | ISHL | IECSC | AICS | KECL     |
|---------------|-----------|------|-----|-------|------|------|-------|------|----------|
| Hexane        | 203-777-6 | X    | X   | X     | X    | X    | X     | X    | KE-18626 |
| Butyl lithium | 203-698-7 | X    | X   | X     | X    | X    | X     | X    | KE-04320 |

| Component | Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification | Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements | Rotterdam Convention (PIC) | Basel Convention (Hazardous Waste) |
|-----------|-------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|----------------------------|------------------------------------|
| Hexane    |                                                                                           |                                                                                          |                            | Annex I - Y42                      |

### National Regulations

Persistent Organic Pollutant  
Ozone Depletion Potential

This product does not contain any known or suspected substance  
This product does not contain any known or suspected substance

## SECTION 16: OTHER INFORMATION

### Legend

# SAFETY DATA SHEET

n-Butyllithium, 2.5M solution in hexanes

Revision Date 22-Mar-2025

**CAS** - Chemical Abstracts Service

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List

**ENCS** - Japanese Existing and New Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**NZIoC** - New Zealand Inventory of Chemicals

**WEL** - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**RPE** - Respiratory Protective Equipment

**LC50** - Lethal Concentration 50%

**POW** - Partition coefficient Octanol:Water

**TWA** - Time Weighted Average

**IARC** - International Agency for Research on Cancer

**LD50** - Lethal Dose 50%

**EC50** - Effective Concentration 50%

**ADR** - European Agreement Concerning the International Carriage of Dangerous Goods by Road

**IMO/IMDG** - International Maritime Organization/International Maritime Dangerous Goods Code

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

**ICAO/IATA** - International Civil Aviation Organization/International Air Transport Association

**MARPOL** - International Convention for the Prevention of Pollution from Ships

**ATE** - Acute Toxicity Estimate

**VOC** - (Volatile Organic Compound)

## Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Revision Date

22-Mar-2025

Revision Summary

SDS sections updated.

**In accordance with local and national regulations: Occupational Safety and Health (Classification, Labelling and Safety Data Sheet of Hazardous Chemicals) Regulations 2013**

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**