

Creation Date 16-Sep-2019

Revision Date 15-Feb-2024

Revision Number 4

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**1.1. Product identifier**

Product Description: Platinum, nominally 27%, cobalt, nominally 3% on Vulcan XC72 Carbon
Cat No. : 47395

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet**Company**

Thermo Fisher (Kandel) GmbH
Erlenbachweg 2, 76870 Kandel, Germany
Tel: +49 (0) 721 84007 280
Fax: +49 (0) 721 84007 300

Swiss distributor - Fisher Scientific AG
Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
<https://www.fishersci.ch/ch/en/customer-help-support/forms/email-us.html>

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

SECTION 2: HAZARDS IDENTIFICATION**2.1. Classification of the substance or mixture**

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

SAFETY DATA SHEET

Platinum, nominally 27%, cobalt, nominally 3% on Vulcan XC72 Carbon

Revision Date 15-Feb-2024

Flammable solids	Category 2 (H228)
Health hazards	
Respiratory Sensitization	Category 1 Sub-category 1B (H334)
Skin Sensitization	Category 1 (H317)
Germ Cell Mutagenicity	Category 2 (H341)
Carcinogenicity	Category 1B (H350)
Reproductive Toxicity	Category 1B (H360F)
Environmental hazards	
Based on available data, the classification criteria are not met	

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H228 - Flammable solid
H317 - May cause an allergic skin reaction
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled
H341 - Suspected of causing genetic defects
H350 - May cause cancer
H360F - May damage fertility

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction
P302 + P352 - IF ON SKIN: Wash with plenty of soap and water
P284 - Wear respiratory protection
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P342 + P311 - If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician
P308 + P313 - IF exposed or concerned: Get medical advice/attention

Additional EU labelling

Restricted to professional users

2.3. Other hazards

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

SAFETY DATA SHEET

Platinum, nominally 27%, cobalt, nominally 3% on Vulcan XC72 Carbon

Revision Date 15-Feb-2024

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Carbon black	1333-86-4	215-609-9	70	-
Platinum	7440-06-4	231-116-1	27	Flam. Sol. 2 (H228)
Cobalt	7440-48-4	231-158-0	3	Flam. Sol. 2 (H228) Resp. Sens. 1B (H334) Skin Sens. 1 (H317) Muta. 2 (H341) Carc. 1B (H350) Repr. 1B (H360F) Aquatic Chronic 4 (H413)

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice	If symptoms persist, call a physician.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Get medical attention if symptoms occur.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

None reasonably foreseeable. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause allergic skin reaction. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically. Symptoms may be delayed.
---------------------------	---

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

SAFETY DATA SHEET

Platinum, nominally 27%, cobalt, nominally 3% on Vulcan XC72 Carbon

Revision Date 15-Feb-2024

Thermal decomposition can lead to release of irritating gases and vapors.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂), Platinum oxide, Cobalt oxides.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Avoid dust formation.

6.2. Environmental precautions

Should not be released into the environment. Do not allow material to contaminate ground water system. Do not flush into surface water or sanitary sewer system.

6.3. Methods and material for containment and cleaning up

Sweep up and shovel into suitable containers for disposal. Keep in suitable, closed containers for disposal.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Avoid dust formation.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Storage Class/LGK 4.1B

Switzerland - Storage of hazardous substances

Storage class - SC 4.1
<https://www.kvu.ch/de/themen/stoffe-und-produkte>
<https://www.kvu.ch/fr/themes/substances-et-produits>
<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

SAFETY DATA SHEET

Platinum, nominally 27%, cobalt, nominally 3% on Vulcan XC72 Carbon

Revision Date 15-Feb-2024

Exposure limits

List source(s): **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority.

CH - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Carbon black		STEL: 7 mg/m ³ 15 min TWA: 3.5 mg/m ³ 8 hr	TWA / VME: 3.5 mg/m ³ (8 heures).	TWA: 3 mg/m ³ 8 uren	TWA / VLA-ED: 3.5 mg/m ³ (8 horas)
Platinum		STEL: 15 mg/m ³ 15 min TWA: 5 mg/m ³ 8 hr	TWA / VME: 1 mg/m ³ (8 heures).	TWA: 1 mg/m ³ 8 uren	TWA / VLA-ED: 1 mg/m ³ (8 horas)
Cobalt		STEL: 0.3 mg/m ³ 15 min TWA: 0.1 mg/m ³ 8 hr Resp. Sens.		TWA: 0.02 mg/m ³ 8 uren	TWA / VLA-ED: 0.02 mg/m ³ (8 horas)

Component	Italy	Germany	Portugal	The Netherlands	Finland
Carbon black			TWA: 3 mg/m ³ 8 horas		TWA: 3.5 mg/m ³ 8 tunteina STEL: 7 mg/m ³ 15 minuutteina
Platinum		TWA: 1 mg/m ³ (8 Stunden). AGW -	TWA: 1 mg/m ³ 8 horas	TWA: 1 mg/m ³ 8 uren	TWA: 1 mg/m ³ 8 tunteina
Cobalt		Haut	TWA: 0.02 mg/m ³ 8 horas	TWA: 0.02 mg/m ³ 8 uren	TWA: 0.02 mg/m ³ 8 tunteina

Component	Austria	Denmark	Switzerland	Poland	Norway
Carbon black		TWA: 3.5 mg/m ³ 8 timer STEL: 7 mg/m ³ 15 minutter		TWA: 4 mg/m ³ 8 godzinach	TWA: 3.5 mg/m ³ 8 timer STEL: 7 mg/m ³ 15 minutter. value calculated
Platinum	MAK-TMW: 1 mg/m ³ 8 Stunden	TWA: 1 mg/m ³ 8 timer STEL: 2 mg/m ³ 15 minutter	TWA: 1 mg/m ³ 8 Stunden	TWA: 1 mg/m ³ 8 godzinach	: 8 timer : 15 minutter. no value adopted
Cobalt	TRK-KZGW: 2 mg/m ³ 15 Minuten TRK-KZGW: 0.4 mg/m ³ 15 Minuten Haut TRK-TMW: 0.5 mg/m ³ TRK-TMW: 0.1 mg/m ³	TWA: 0.01 mg/m ³ 8 timer STEL: 0.02 mg/m ³ 15 minutter	Haut/Peau TWA: 0.05 mg/m ³ 8 Stunden	TWA: 0.02 mg/m ³ 8 godzinach	TWA: 0.02 mg/m ³ 8 timer STEL: 0.06 mg/m ³ 15 minutter. value calculated fume

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Carbon black		TWA-GVI: 3.5 mg/m ³ 8 satima. STEL-KGVI: 7 mg/m ³ 15 minutama.	TWA: 3 mg/m ³ 8 hr. inhalable fraction STEL: 15 mg/m ³ 15 min		TWA: 2.0 mg/m ³ 8 hodinách. dust
Platinum	TWA: 1.0 mg/m ³	TWA-GVI: 1 mg/m ³ 8 satima.	TWA: 1 mg/m ³ 8 hr. Pt STEL: 3 mg/m ³ 15 min	TWA: 1 mg/m ³	TWA: 0.5 mg/m ³ 8 hodinách. Ceiling: 1 mg/m ³
Cobalt	TWA: 0.1 mg/m ³	TWA-GVI: 0.1 mg/m ³ 8 satima.	TWA: 0.02 mg/m ³ 8 hr. STEL: 0.3 mg/m ³ 15 min		TWA: 0.05 mg/m ³ 8 hodinách. inhalable fraction of aerosol Ceiling: 0.1 mg/m ³

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Carbon black	TWA: 3 mg/m ³ 8 tundides. dust		STEL: 7 mg/m ³ TWA: 3.5 mg/m ³	TWA: 3 mg/m ³ 8 órában. AK	TWA: 3.5 mg/m ³ 8 klukkustundum. Ceiling: 7 mg/m ³
Platinum	TWA: 1 mg/m ³ 8 tundides.	TWA: 1 mg/m ³ 8 hr metallic;existing scientific data on health effects appear to be particularly limited	TWA: 5 mg/m ³	TWA: 1 mg/m ³ 8 órában. AK	TWA: 1 mg/m ³ 8 klukkustundum. dust and powder Ceiling: 2 mg/m ³ dust and powder
Cobalt	TWA: 0.05 mg/m ³ 8 tundides.		TWA: 0.1 mg/m ³	TWA: 0.02 mg/m ³ 8 órában. AK	TWA: 0.02 mg/m ³ 8 klukkustundum. dust and fume Ceiling: 0.04 mg/m ³ dust and fume

SAFETY DATA SHEET

Platinum, nominally 27%, cobalt, nominally 3% on Vulcan XC72 Carbon

Revision Date 15-Feb-2024

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Platinum	TWA: 1 mg/m ³	TWA: 1 mg/m ³ IPRD	TWA: 1 mg/m ³ 8 Stunden	TWA: 1 mg/m ³	TWA: 1 mg/m ³ 8 ore
Cobalt	TWA: 0.5 mg/m ³	TWA: 0.05 mg/m ³ IPRD			TWA: 0.05 mg/m ³ 8 ore STEL: 0.1 mg/m ³ 15 minute

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Carbon black		TWA: 2 mg/m ³ respirable fraction, 5% or less fibrogenic component TWA: 10 mg/m ³ respirable fraction, greater than 5% fibrogenic component TWA: 10 mg/m ³ total aerosol		TLV: 3 mg/m ³ 8 timmar. NGV	
Platinum		TWA: 1 mg/m ³	TWA: 1 mg/m ³ 8 urah inhalable fraction	TLV: 1 mg/m ³ 8 timmar. NGV	TWA: 1 mg/m ³ 8 saat
Cobalt	TWA: 0.01 mg/m ³ 1108 Skin notation MAC: 0.05 mg/m ³	TWA: 0.05 mg/m ³		TLV: 0.02 mg/m ³ 8 timmar. NGV Hud	

Biological limit values

List source(s):

Component	European Union	United Kingdom	France	Spain	Germany
Cobalt			Cobalt: 0.001 mg/L blood end of shift at end of workweek Cobalt: 0.015 mg/L urine end of shift at end of workweek	Cobalt: 15 µg/L urine end of workweek Cobalt: 1 µg/L blood end of workweek	

Component	Italy	Finland	Denmark	Bulgaria	Romania
Cobalt		Cobalt: 130 nmol/L urine after the work phase or shift after a working week or exposure period.			Cobalt: 15 µg/L urine end of work week Cobalt: 1 µg/L blood end of work week

Component	Gibraltar	Latvia	Slovak Republic	Luxembourg	Turkey
Cobalt			Cobalt: 30 µg/L urine not critical		

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust

MDHS30/2 Cobalt and cobalt compounds in air Laboratory method using flame atomic absorption spectrometry

MDHS46/2 Platinum metal and soluble platinum compounds in air Laboratory method using electrothermal atomic absorption spectrometry or inductively coupled plasma-mass spectrometry

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Carbon black 1333-86-4 (70)			DNEL = 0.5mg/m ³	DNEL = 1mg/m ³
Cobalt			DNEL = 40µg/m ³	

SAFETY DATA SHEET

Platinum, nominally 27%, cobalt, nominally 3% on Vulcan XC72 Carbon

Revision Date 15-Feb-2024

7440-48-4 (3)				
-----------------	--	--	--	--

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Cobalt 7440-48-4 (3)	PNEC = 0.62µg/L	PNEC = 53.8mg/kg sediment dw		PNEC = 0.37mg/L	PNEC = 10.9mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Cobalt 7440-48-4 (3)	PNEC = 2.36µg/L	PNEC = 69.8mg/kg sediment dw			

8.2. Exposure controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Wear safety glasses with side shields (or goggles) (European standard - EN 166)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Nitrile rubber Viton (R)	See manufacturers recommendations	-	EN 374	(minimum requirement)

Skin and body protection

Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: low boiling organic solvent Type AX Brown conforming to EN371 Type A Brown

Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

No information available.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

SAFETY DATA SHEET

Platinum, nominally 27%, cobalt, nominally 3% on Vulcan XC72 Carbon

Revision Date 15-Feb-2024

Physical State	Powder Solid	
Appearance	Black	
Odor	No information available	
Odor Threshold	No data available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flammability (liquid)	Not applicable	Solid
Flammability (solid,gas)	No information available	
Explosion Limits	No data available	
Flash Point	No information available	Method - No information available
Autoignition Temperature	Not applicable	
Decomposition Temperature	No data available	
pH	No information available	
Viscosity	Not applicable	Solid
Water Solubility	No information available	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Vapor Pressure	No data available	
Density / Specific Gravity	No data available	
Bulk Density	No data available	
Vapor Density	Not applicable	Solid
Particle characteristics	No data available	

9.2. Other information

Flammable solids	Burning rate or burning time = > 2.2 mm/s or < 45 secs
	Wetted zone passed - No
Evaporation Rate	Not applicable - Solid

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization	No information available.
Hazardous Reactions	None under normal processing.

10.4. Conditions to avoid

Incompatible products. Excess heat.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂). Platinum oxide. Cobalt oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

SAFETY DATA SHEET

Platinum, nominally 27%, cobalt, nominally 3% on Vulcan XC72 Carbon

Revision Date 15-Feb-2024

(a) acute toxicity;

Oral

Based on available data, the classification criteria are not met

Dermal

No data available

Inhalation

No data available

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Carbon black	LD50 > 15400 mg/kg (Rat)	LD50 > 3 g/kg (Rabbit)	LC50 > 4.6 mg/m ³ (Rat) 4 h
Cobalt	LD50 = 6171 mg/kg (Rat)	-	LC50 < 0.05 mg/L (Rat) 4 h

(b) skin corrosion/irritation;

No data available

(c) serious eye damage/irritation;

No data available

(d) respiratory or skin sensitization;

Respiratory

Category 1

Skin

Category 1

No information available

(e) germ cell mutagenicity;

Category 2

(f) carcinogenicity;

Category 1B

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Carbon black			Cat. 3B	Group 2B
Cobalt	Carc Cat. 1B		Cat. 2	Group 2A

(g) reproductive toxicity;

Category 1B

(h) STOT-single exposure;

No data available

(i) STOT-repeated exposure;

No data available

Target Organs

None known.

(j) aspiration hazard;

Not applicable

Solid

Symptoms / effects, both acute and delayed

Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

11.2. Information on other hazards

Endocrine Disrupting Properties

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

May cause long-term adverse effects in the environment. Do not allow material to

SAFETY DATA SHEET

Platinum, nominally 27%, cobalt, nominally 3% on Vulcan XC72 Carbon

Revision Date 15-Feb-2024

contaminate ground water system.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Carbon black		EC50: > 5600 mg/L, 24h (Daphnia magna)	
Cobalt	LC50: > 100 mg/L, 96h static (Brachydanio rerio)		

12.2. Persistence and degradability Product contains heavy metals. Discharge into the environment must be avoided. Special pre-treatment is necessary
Persistence May persist.
Degradation in sewage treatment plant Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential Product has a high potential to bioconcentrate

12.4. Mobility in soil No information available

12.5. Results of PBT and vPvB assessment No data available for assessment.

12.6. Endocrine disrupting properties
Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects
Persistent Organic Pollutant This product does not contain any known or suspected substance
Ozone Depletion Potential This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

European Waste Catalogue (EWC) According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with local regulations.

Switzerland - Waste Ordinance Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600
<https://www.fedlex.admin.ch/eli/cc/2015/891/en>

SECTION 14: TRANSPORT INFORMATION

SAFETY DATA SHEET

Platinum, nominally 27%, cobalt, nominally 3% on Vulcan XC72 Carbon

Revision Date 15-Feb-2024

IMDG/IMO

14.1. UN number UN1325
14.2. UN proper shipping name FLAMMABLE SOLID, ORGANIC, N.O.S.
Technical Shipping Name Platinum, cobalt
14.3. Transport hazard class(es) 4.1
14.4. Packing group II

ADR

14.1. UN number UN1325
14.2. UN proper shipping name FLAMMABLE SOLID, ORGANIC, N.O.S.
Technical Shipping Name Platinum, cobalt
14.3. Transport hazard class(es) 4.1
14.4. Packing group II

IATA

14.1. UN number UN1325
14.2. UN proper shipping name FLAMMABLE SOLID, ORGANIC, N.O.S.
Technical Shipping Name Platinum, cobalt
14.3. Transport hazard class(es) 4.1
14.4. Packing group II

14.5. Environmental hazards No hazards identified
14.6. Special precautions for user No special precautions required.
14.7. Maritime transport in bulk according to IMO instruments Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

X = listed. US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Carbon black	1333-86-4	215-609-9	435-640-3	-	X	X	X	X	X
Platinum	7440-06-4	231-116-1	-	-	X	X	KE-28808	X	-
Cobalt	7440-48-4	231-158-0	-	-	X	X	KE-06060	X	-

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Carbon black	1333-86-4	X	ACTIVE	X	-	X	X	X
Platinum	7440-06-4	X	ACTIVE	X	-	X	X	X
Cobalt	7440-48-4	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Carbon black	1333-86-4	-	Use restricted. See item 75. (see link for restriction)	-

SAFETY DATA SHEET

Platinum, nominally 27%, cobalt, nominally 3% on Vulcan XC72 Carbon

Revision Date 15-Feb-2024

			details)	
Platinum	7440-06-4	-	-	-
Cobalt	7440-48-4	-	Use restricted. See item 30. (see link for restriction details) Use restricted. See item 28. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Carbon black	1333-86-4	Not applicable	Not applicable
Platinum	7440-06-4	Not applicable	Not applicable
Cobalt	7440-48-4	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 94/33/EC on the protection of young people at work

Take note of Dir 92/85/EC on the protection of pregnant and breastfeeding women at work

Take note of Dir 76/769/EEC relating to restrictions on the marketing and use of certain dangerous substances and preparations

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 3 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Carbon black	nwg	
Cobalt	WGK3	Class II : 0.5 mg/m ³ (Massenkonzentration) Krebserzeugende Stoffe - Class I : 0.05 mg/m ³ (Massenkonzentration)

Component	France - INRS (Tables of occupational diseases)
Carbon black	Tableaux des maladies professionnelles (TMP) - RG 16,RG 16bis
Cobalt	Tableaux des maladies professionnelles (TMP) - RG 65,RG 70,RG 70bis,RG 70ter

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

15.2. Chemical safety assessment

SAFETY DATA SHEET

Platinum, nominally 27%, cobalt, nominally 3% on Vulcan XC72 Carbon

Revision Date 15-Feb-2024

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H228 - Flammable solid

H317 - May cause an allergic skin reaction

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled

H341 - Suspected of causing genetic defects

H350 - May cause cancer

H360F - May damage fertility

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data

Health Hazards Calculation method

Environmental hazards Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Chemical incident response training.

Prepared By

Health, Safety and Environmental Department

Creation Date

16-Sep-2019

Revision Date

15-Feb-2024

Revision Summary

New emergency telephone response service provider.

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.
COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No
1907/2006 .**

SAFETY DATA SHEET

Platinum, nominally 27%, cobalt, nominally 3% on Vulcan XC72 Carbon

Revision Date 15-Feb-2024

For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2, Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and Preparations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet