

Classified as hazardous in accordance with the criteria of EPA New Zealand

Section 1 - Identification

Product Identifier

Product Name	<u>Styrene</u>
CAS No	100-42-5
Synonyms	Ethenylbenzene
Molecular Formula	C8 H8
Molecular Weight	104.15
Recommended Use	Laboratory chemicals.
Uses advised against	No Information available

Product Code	16199
Address	Thermo Fisher Scientific New Zealand Ltd 244 Bush Road, Albany, Auckland, New Zealand
Emergency Tel.	CHEMTREC® 09 980 6780 or +64 9 980 6780
Telephone / Fax Numbers	Tel: 09 980 6700 Fax: 09 980 6788
E-mail address	ANZinfo@thermofisher.com

Section 2 - Hazard(s) Identification

Classification under Work Safe New Zealand

Classified as hazardous in accordance with the criteria of EPA New Zealand

HSNO Approval Number **HSR001221**

GHS Classification

Physical hazards

Flammable liquids

Category 3

Health hazards

Aspiration Toxicity	Category 1
Acute Oral Toxicity	Category 4
Acute Inhalation Toxicity - Vapors	Category 3
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Germ Cell Mutagenicity	Category 2
Carcinogenicity	Category 2
Reproductive Toxicity	Category 2
Specific target organ toxicity - (single exposure)	Category 3
Specific target organ toxicity - (repeated exposure)	Category 1

Environmental hazards

Acute aquatic toxicity
Chronic aquatic toxicity

Category 1
Category 1

Label Elements**Signal Word****Danger****Hazard Statements**

H226 - Flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H335 - May cause respiratory irritation
H361 - Suspected of damaging fertility or the unborn child
H372 - Causes damage to organs through prolonged or repeated exposure
H302 - Harmful if swallowed
H331 - Toxic if inhaled
H341 - Suspected of causing genetic defects if inhaled
H351 - Suspected of causing cancer
H410 - Very toxic to aquatic life with long lasting effects

Precautionary Statements**Prevention**

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P233 - Keep container tightly closed
P240 - Ground and bond container and receiving equipment
P241 - Use explosion-proof electrical/ ventilating/ lighting equipment
P242 - Use non-sparking tools
P243 - Take action to prevent static discharges
P280 - Wear eye protection/ face protection
P260 - Do not breathe dust/fume/gas/mist/vapors/spray
P264 - Wash face, hands and any exposed skin thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P271 - Use only outdoors or in a well-ventilated area
P273 - Avoid release to the environment

Response

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P332 + P313 - If skin irritation occurs: Get medical advice/attention
P308 + P313 - IF exposed or concerned: Get medical advice/attention
P331 - Do NOT induce vomiting
P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish
P362 + P364 - Take off contaminated clothing and wash it before reuse
P391 - Collect spillage

Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Other hazards which do not result in classification

Toxic to terrestrial vertebrates

Section 3 - Composition and Information on Ingredients

Component	CAS No	Weight %
Styrene	100-42-5	>95

Section 4 - First Aid Measures

Description of first aid measures

General Advice	If symptoms persist, call a physician.
New Zealand Emergency Tel.	CHEMTREC® 09 980 6780 or +64 9 980 6780
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur. Risk of serious damage to the lungs (by aspiration).
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
Self-Protection of the First Aider	Use personal protective equipment as required.
First Aid Facilities	Eyewash, safety shower and washroom.
Most important symptoms and effects	Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting
Notes to Physician	Treat symptomatically.

Section 5 - Fire Fighting Measures

Suitable Extinguishing MediaWater spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.**Extinguishing media which must not be used for safety reasons**

Water may be ineffective.

Specific Hazards Arising from the Chemical

Flammable. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Vapors may form explosive mixtures with air.

Hazardous Combustion ProductsCarbon monoxide (CO), Carbon dioxide (CO₂).**Special protective equipment and precautions for fire fighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6 - Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures

Emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions

Should not be released into the environment. See Section 12 for additional Ecological Information. Avoid release to the environment. Collect spillage. Do not flush into surface water or sanitary sewer system.

Methods for Containment and Clean Up

Keep in suitable, closed containers for disposal. Soak up with inert absorbent material. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Precautions to prevent secondary hazards

Clean contaminated objects and areas thoroughly observing environmental regulations

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

Section 7 - Handling and Storage

Precautions for Safe Handling

Advice on safe handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

Conditions for Safe Storage, Including any Incompatibilities

Storage Conditions

Keep refrigerated. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame.

Incompatible Materials

Acids. Halogenated compounds. Copper alloys. Strong oxidizing agents.

AS/NZS 2243.10:2004, Safety in laboratories - Storage of chemicals

AS 1940-2004 - The storage and handling of flammable and combustible liquids

Section 8 - Exposure Controls and Personal Protection

Control parameters

Exposure limits

NZ - Workplace Exposure Standards and Biological Exposure Indices (6th edition). New Zealand Department of Labor

UK - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020.

ACGIH - Threshold Limit Values - Ceiling (TLV-C) guidelines by the American Conference of Governmental Industrial Hygienists (ACGIH) for controlling worker exposure to airborne chemical concentrations in the workplace.

AUS - Exposure Standards for Atmospheric Contaminants in the Occupational Environment - Guidance Note on the Interpretation of Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:3008(1995)]

Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)] updated in August, 2005. Safe Work Australia

Component	New Zealand WEL	Australia	ACGIH TLV	The United Kingdom
Styrene	TWA: 20 ppm TWA: 85 mg/m ³ STEL: 40 ppm STEL: 170 mg/m ³	STEL: 100 ppm STEL: 426 mg/m ³ TWA: 50 ppm TWA: 213 mg/m ³	TWA: 10 ppm STEL: 20 ppm	STEL: 250 ppm 15 min STEL: 1080 mg/m ³ 15 min TWA: 100 ppm 8 hr TWA: 430 mg/m ³ 8 hr

Biological limit values

NZ - Substances assigned Biological Exposure Indices in the New Zealand Workplace Exposure Standards and Biological Exposure Indices (6th edition). New Zealand Department of Labor

ACGIH - American Conference of Governmental Industrial Hygienists (ACGIH) TLVs® and BEIs®- Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices. 2022 Edition

Component	New Zealand	Australia	ACGIH - Biological Exposure Indices	United Kingdom
Styrene	400 mg/g creatinine (urine) end of shift (Mandelic acid plus phenylglyoxylic acid) 40 µg/L (urine) end of shift (Styrene)		400 mg/g creatinine Medium: urine Time: end of shift Determinant: Mandelic acid plus phenylglyoxylic acid 40 µg/L Medium: urine Time: end of shift Determinant: Styrene	

Appropriate engineering controls**Engineering Measures**

Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Individual protection measures, such as personal protective equipment

Eye Protection Goggles (Australian/New Zealand Standard AS/NZS 1337 - Eye protectors for Industrial applications)

Hand Protection Protective gloves

Glove material	Breakthrough time	Glove thickness	AUS/NZ Standard	Glove comments
Nitrile rubber, Neoprene, Natural rubber, PVC.	See manufacturers recommendations	-	AS/NZS 2161	(minimum requirement)

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatibility, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Skin and body protection Long sleeved clothing

Respiratory Protection Use an AS/NZS 1716 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained in line with AS/NZS 1715 on the use and maintenance of respiratory protective devices

Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to EN14387 (or AUS/NZ equivalent)

Recommended half mask:- Valve filtering: EN405 or Half mask: EN140 plus filter, EN 141 (or AUS/NZ equivalent)

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

Environmental exposure controls Prevent product from entering drains. Do not allow material to contaminate ground water system. Local authorities should be advised if significant spillages cannot be contained.

Section 9 - Physical and Chemical Properties

Information on basic physical and chemical properties

Physical State	Liquid	
Appearance	Colorless	
Odor	pungent	
Odor Threshold	No data available	
pH	No information available	
Melting Point/Range	-31 °C / -23.8 °F	
Softening Point	No data available	
Boiling Point/Range	145 - 146 °C / 293 - 294.8 °F	@ 760 mmHg
Flammability (liquid)	Flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	Lower 1.1 Upper 6.1	
Flash Point	31 °C / 87.8 °F	Method - No information available
Autoignition Temperature	490 °C / 914 °F	
Decomposition Temperature	No data available	
Viscosity	0.695 mPa.s at 25 °C	
Water Solubility	0.3 mg/L (20°C)	
Solubility in other solvents	Soluble: Alcohols, Diethyl ether	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Styrene	2.96	
Vapor Pressure	7 mbar @ 20 °C	
Density / Specific Gravity	0.906	
Bulk Density	Not applicable	Liquid
Vapor Density	1.22	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

Other information

Molecular Formula	C8 H8
Molecular Weight	104.15
Explosive Properties	explosive air/vapour mixtures possible
Self-accelerating polymerisation temperature (SAPT)	52°C (packages up to 50kg) Inhibitor level > 8 ppm

Section 10 - Stability and Reactivity

Reactivity	Yes
Stability	Stable under normal conditions.
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available
Hazardous Polymerization	Hazardous polymerization may occur. Hazardous polymerization may occur upon depletion of inhibitor.
Hazardous Reactions	None under normal processing.
Conditions to Avoid	Excess heat, Incompatible products, Keep away from open flames, hot surfaces and sources of ignition, Temperatures above 40°C.
Incompatible Materials	Acids, Halogenated compounds, Copper alloys, Strong oxidizing agents.

Hazardous Decomposition Products Carbon monoxide (CO). Carbon dioxide (CO₂).

Section 11 - Toxicological Information

Acute Effects

Information on likely routes of exposure

Product Information

Inhalation	Harmful by inhalation. May cause irritation of respiratory tract. May be fatal if swallowed and enters airways.
Eyes	Irritating to eyes. Contact with eyes may cause irritation.
Skin	Irritating to skin. May cause eye/skin irritation.
Ingestion	Aspiration hazard if swallowed - can enter lungs and cause damage. Harmful if swallowed. Potential for aspiration if swallowed. Ingestion may cause irritation to mucous membranes.

Numerical measures of toxicity

(a) acute toxicity;

Oral	Based on available data, the classification criteria are not met
Dermal	Based on available data, the classification criteria are not met
Inhalation	Category 4

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Styrene	-	LD50 > 2000 mg/kg (Rat)	LC50 = 11.7 mg/L (Rat) 4 h

(b) skin corrosion/irritation; Category 2

(c) serious eye damage/irritation; Category 2

(d) respiratory or skin sensitization;

Respiratory	Based on available data, the classification criteria are not met
Skin	Based on available data, the classification criteria are not met

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

(f) carcinogenicity; Based on available data, the classification criteria are not met
The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	New Zealand	Australia	New South Wales	Western Australia	IARC	EU	UK	Germany
Styrene	Suspected carcinogen				Group 2A			

(g) reproductive toxicity; Reproductive Effects

Category 2
Experiments have shown reproductive toxicity effects on laboratory animals

(h) STOT-single exposure;

Category 3

Results / Target organs

Respiratory system

(i) STOT-repeated exposure;

Category 1

Target Organs Ears, Central nervous system (CNS).

(j) aspiration hazard; Category 1

Other Adverse Effects The toxicological properties have not been fully investigated.

Symptoms / effects, both acute and delayed

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Section 12 - Ecological Information

Ecotoxicity

Aquatic ecotoxicity

Do not empty into drains. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment. Contains a substance which is: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Styrene	LC50: 19.03 - 33.53 mg/L, 96h static (Lepomis macrochirus) LC50: 6.75 - 14.5 mg/L, 96h static (Pimephales promelas) LC50: 58.75 - 95.32 mg/L, 96h static (Poecilia reticulata) LC50: 3.24 - 4.99 mg/L, 96h flow-through (Pimephales promelas)	EC50: 3.3 - 7.4 mg/L, 48h (Daphnia magna)	EC50: 0.15 - 3.2 mg/L, 96h static (Pseudokirchneriella subcapitata) EC50: 0.46 - 4.3 mg/L, 72h static (Pseudokirchneriella subcapitata) EC50: = 0.72 mg/L, 96h (Pseudokirchneriella subcapitata) EC50: = 1.4 mg/L, 72h (Pseudokirchneriella subcapitata)	= 5.4 mg/L EC50 Photobacterium phosphoreum 5 min

Terrestrial ecotoxicity

Component	Earthworm	Avian	Honeybees
Styrene	Acute toxicity: LC50 = 120 mg/kg (Eisenia foetida, 14 Days, soil dry weight)		

Persistence and Degradability

Persistence

Insoluble in water, Persistence is unlikely, based on information available.

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

Bioaccumulative Potential

May have some potential to bioaccumulate

Component	log Pow	Bioconcentration factor (BCF)
Styrene	2.96	13.5 dimensionless

Mobility

Spillage unlikely to penetrate soil. The product is insoluble and floats on water. The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Is not likely mobile in the environment due its low water solubility. Will likely be mobile in the environment due to its volatility.

Other adverse effects

Endocrine Disruptor Information

Component	EU - Endocrine Disruptors Candidate List	EU - Endocrine Disruptors - Evaluated Substances	Japan - Endocrine Disruptor Information

Styrene	Group I Chemical	High Exposure Concern	
Persistent Organic Pollutant	This product does not contain any known or suspected substance		
Ozone Depletion Potential	This product does not contain any known or suspected substance		

Section 13 - Disposal Considerations

Waste treatment methods

Waste from Residues/Unused Products	Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with all federal, E.P.A., state and local regulations. Assure conformity with all applicable regulations.
Contaminated Packaging	Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.
Other Information	Disposal agencies or waste contractors must comply with the New Zealand Hazardous Substances (Disposal) Regulations . Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not let this chemical enter the environment. Do not empty into drains.

Section 14 - Transport Information

Component	Hazchem Code
Styrene 100-42-5 (>95)	3Y

NZS 5433:2020

UN-No	UN2055
Proper Shipping Name	STYRENE MONOMER, STABILIZED
Hazard Class	3
Packing Group	III

IATA

UN-No	UN2055
Proper Shipping Name	STYRENE MONOMER, STABILIZED
Hazard Class	3
Packing Group	III

IMDG/IMO

UN-No	UN2055
Proper Shipping Name	STYRENE MONOMER, STABILIZED
Hazard Class	3
Packing Group	III

Environmental hazards No hazards identified

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable, packaged goods

Special Precautions Inhibitors have been added to stabilize this product. Inhibitor levels should be maintained. Hazardous polymerization may occur upon depletion of inhibitor.

Additional information

None known

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

HSNO Approval Number	HSR001221
----------------------	-----------

National Regulations

There are no applicable tolerable exposure limits or environmental exposure limits according to the EPA Controls for Hazardous Substances

Certified handlers, tracking and controlled substance license requirements

Certified handlers are required for some substances. This includes substances requiring a controlled substance license, and most explosives, vertebrates toxic agents, and certain fumigants. Acutely toxic substances which are a Category 1 or 2, such as pesticides also require Certified handlers. Please check the Health and Safety at Work Act 2015 for further information. Tracking is required for some highly hazardous substances. These substances need to be under the control of an appropriately trained person or appropriately secured. Please check the Health and Safety at Work Act 2015 for further information.

Prohibition or notification/licensing requirements

Shown below are details of specific prohibition/notifications or licensing requirements when they apply.

Component	New Zealand
Styrene	Suspected carcinogen

International Regulations

Ozone Depletion Potential This product does not contain any known or suspected substance

Persistent Organic Pollutant This product does not contain any known or suspected substance

Rotterdam Convention (PIC) Not applicable

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Styrene	-	Use restricted. See item 75. (see link for restriction details)	-

<https://echa.europa.eu/substances-restricted-under-reach>

International Inventories

New Zealand (NZIoC), Australia (AICS), Europe (EINECS/ELINCS/NLP), Korea (KECL), China (IECSC), Taiwan (TCSI), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	NZIoC	AICS	EINECS	ELINCS	NLP	KECL	IECSC	TCSI
Styrene	100-42-5	X	X	202-851-5	-	-	KE-35342	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	PICCS	ISHL	ENCS
Styrene	100-42-5	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Section 16 - Other Information

This safety data sheet complies with the requirements of the EPA Hazardous Substances (Hazard Classification) Notice 2020 and WorkSafe New Zealand Regulations

Legend

NZIoC - New Zealand Inventory of Chemicals
TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

IECSC - Chinese Inventory of Existing Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

NZS 5433:2020 - Transport of Dangerous Goods on Land

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

WEL - Workplace Exposure Limit

DNEL - Derived No Effect Level

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

VOC - (Volatile Organic Compound)

AICS - Australian Inventory of Chemical Substances

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

ENCS - Japanese Existing and New Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

CAS - Chemical Abstracts Service

ACGIH - American Conference of Governmental Industrial Hygienists

PNEC - Predicted No Effect Concentration

OECD - Organisation for Economic Co-operation and Development

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

ADG - Australian Code for the Transport of Dangerous Goods by Road and Rail

LC50 - Lethal Concentration 50%

ATE - Acute Toxicity Estimate

RPE - Respiratory Protective Equipment

NOEC - No Observed Effect Concentration

BCF - Bioconcentration factor

PBT - Persistent, Bioaccumulative, Toxic

Key literature references and sources for data

HSNO classifications provided in the New Zealand Chemical Classification Information Database (CCID).

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

EPA Guide to classifying hazardous substances in New Zealand

EPA - Assigning a product to an existing HSNO approval guide

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Revision Date 13-Mar-2023

Revision Summary SDS sections updated 9 14

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet