

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: Graphite powder, nickel coated
Cat No. : 43215

Unique Formula Identifier (UFI) PU8F-E6AR-6X0R-NN9P

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company

Thermo Fisher (Kandel) GmbH
Erlenbachweg 2, 76870 Kandel, Germany
Tel: +49 (0) 721 84007 280
Fax: +49 (0) 721 84007 300

Swiss distributor - Fisher Scientific AG
Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
<https://www.fishersci.ch/ch/en/customer-help-support/forms/email-us.html>

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

Poison Centre - Emergency information services **Ireland** : National Poisons Information Centre (NPIC) -
01 809 2166 (8am-10pm, 7 days a week)
Malta : +356 2395 2000
Cyprus : +357 2240 5611

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

SAFETY DATA SHEET

Graphite powder, nickel coated

Revision Date 20-Feb-2024

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Flammable solids

Category 2 (H228)

Health hazards

Skin Sensitization

Category 1 (H317)

Carcinogenicity

Category 2 (H351)

Specific target organ toxicity - (repeated exposure)

Category 1 (H372)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H228 - Flammable solid

H317 - May cause an allergic skin reaction

H351 - Suspected of causing cancer

H372 - Causes damage to organs through prolonged or repeated exposure

Precautionary Statements

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water

P201 - Obtain special instructions before use

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P308 + P313 - IF exposed or concerned: Get medical advice/attention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

2.3. Other hazards

Toxicity to Soil Dwelling Organisms

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
-----------	--------	-------	----------	---

SAFETY DATA SHEET

Graphite powder, nickel coated

Revision Date 20-Feb-2024

Nickel	7440-02-0	231-111-4	60.0	Flam. Sol. 2 (H228) Skin Sens. 1 (H317) Carc. 2 (H351) STOT RE 1 (H372) Aquatic Chronic 3 (H412)
Graphite	7782-42-5	EEC No. 231-955-3	40.0	-

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice	If symptoms persist, call a physician.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Get medical attention if symptoms occur.
Inhalation	Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

May cause allergic skin reaction. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically.
---------------------------	------------------------

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media
approved class D extinguishers. Do not use water or foam.

Extinguishing media which must not be used for safety reasons
No information available.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors.

Hazardous Combustion Products
Carbon monoxide (CO), Carbon dioxide (CO₂), Heavy metal oxides.

5.3. Advice for firefighters

SAFETY DATA SHEET

Graphite powder, nickel coated

Revision Date 20-Feb-2024

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Avoid dust formation.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system. Should not be released into the environment. Do not allow material to contaminate ground water system.

6.3. Methods and material for containment and cleaning up

Sweep up and shovel into suitable containers for disposal. Keep in suitable, closed containers for disposal.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Avoid dust formation.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Storage Class/LGK 4.1B

Switzerland - Storage of hazardous substances

Storage class - SC 4.1
<https://www.kvu.ch/de/themen/stoffe-und-produkte>
<https://www.kvu.ch/fr/themes/substances-et-produits>
<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is

SAFETY DATA SHEET

Graphite powder, nickel coated

Revision Date 20-Feb-2024

administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Nickel		STEL: 1.5 mg/m ³ 15 min TWA: 0.5 mg/m ³ 8 hr Skin	TWA / VME: 1 mg/m ³ (8 heures). TWA / VME: 1 mg/m ³ (8 heures). metal gratings	TWA: 1 mg/m ³ 8 uren	TWA / VLA-ED: 1 mg/m ³ (8 horas)
Graphite		STEL: 30 mg/m ³ 15 min STEL: 12 mg/m ³ 15 min TWA: 10 mg/m ³ 8 hr TWA: 4 mg/m ³ 8 hr	TWA / VME: 2 mg/m ³ (8 heures).	TWA: 2 mg/m ³ 8 uren	TWA / VLA-ED: 2 mg/m ³ (8 horas)

Component	Italy	Germany	Portugal	The Netherlands	Finland
Nickel		TWA: 0.03 mg/m ³ (8 Stunden). AGW - exposure factor 8 TWA: 0.006 mg/m ³ (8 Stunden). AGW - exposure factor 8	TWA: 1.5 mg/m ³ 8 horas		TWA: 0.01 mg/m ³ 8 tunteina
Graphite		TWA: 1.25 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 10 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 0.3 mg/m ³ (8 Stunden). MAK multiplied by the material density;except ultrafine particles TWA: 4 mg/m ³ (8 Stunden). MAK Höhepunkt: 2.4 mg/m ³	TWA: 2 mg/m ³ 8 horas		TWA: 2 mg/m ³ 8 tunteina

Component	Austria	Denmark	Switzerland	Poland	Norway
Nickel	TRK-KZGW: 2 mg/m ³ 15 Minuten TRK-TMW: 0.5 mg/m ³	TWA: 0.05 mg/m ³ 8 timer STEL: 0.1 mg/m ³ 15 minutter	TWA: 0.5 mg/m ³ 8 Stunden	TWA: 0.25 mg/m ³ 8 godzinach	TWA: 0.05 mg/m ³ 8 timer STEL: 0.15 mg/m ³ 15 minutter. value calculated
Graphite	MAK-KZGW: 10 mg/m ³ 15 Minuten MAK-TMW: 5 mg/m ³ 8 Stunden	TWA: 2.5 mg/m ³ 8 timer STEL: 5 mg/m ³ 15 minutter	TWA: 3 mg/m ³ 8 Stunden TWA: 10 mg/m ³ 8 Stunden	TWA: 4.0 mg/m ³ 8 godzinach TWA: 1.0 mg/m ³ 8 godzinach	TWA: 5 mg/m ³ 8 timer TWA: 2 mg/m ³ 8 timer TWA: 10 mg/m ³ 8 timer TWA: 4 mg/m ³ 8 timer STEL: 10 mg/m ³ 15 minutter. natural;value calculated total dust STEL: 4 mg/m ³ 15 minutter. natural;value calculated respirable dust STEL: 20 mg/m ³ 15 minutter. synthetic;value calculated total dust STEL: 8 mg/m ³ 15 minutter. synthetic;value calculated respirable dust

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Nickel	TWA: 0.05 mg/m ³	TWA-GVI: 0.5 mg/m ³ 8 satima.	TWA: 0.5 mg/m ³ 8 hr. STEL: 1.5 mg/m ³ 15 min		TWA: 0.5 mg/m ³ 8 hodinách. respirable fraction of aerosol Ceiling: 1 mg/m ³
Graphite	TWA: 5.0 mg/m ³	TWA-GVI: 4 mg/m ³ 8 satima. respirable dust TWA-GVI: 10 mg/m ³ 8 satima. total dust, inhalable particles	TWA: 2 mg/m ³ 8 hr. all forms except fibres; respirable fraction STEL: 6 mg/m ³ 15 min		TWA: 2.0 mg/m ³ 8 hodinách. respirable fraction, <=5% Silica, Cristobalite, Tridymite and .gamma.-Aluminium oxide dust

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
-----------	---------	-----------	--------	---------	---------

SAFETY DATA SHEET

Graphite powder, nickel coated

Revision Date 20-Feb-2024

Nickel	TWA: 0.5 mg/m ³ 8 tundides.		TWA: 1 mg/m ³	TWA: 0.01 mg/m ³ 8 órában. AK	TWA: 0.05 mg/m ³ 8 klukkustundum. Ni dust and powder Ceiling: 0.1 mg/m ³ Ni dust and powder
Graphite	TWA: 5 mg/m ³ 8 tundides. total dust		TWA: 10 mg/m ³ TWA: 5 mg/m ³	TWA: 5 mg/m ³ 8 órában. AK TWA: 2 mg/m ³ 8 órában. AK	TWA: 5 mg/m ³ 8 klukkustundum. total dust TWA: 2.5 mg/m ³ 8 klukkustundum. respirable fraction Ceiling: 10 mg/m ³ total dust Ceiling: 5 mg/m ³ respirable dust

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Nickel	TWA: 0.05 mg/m ³	TWA: 0.5 mg/m ³ IPRD			TWA: 0.1 mg/m ³ 8 ore STEL: 0.5 mg/m ³ 15 minute
Graphite	TWA: 2 mg/m ³	TWA: 5 mg/m ³ dust IPRD			TWA: 2 mg/m ³ 8 ore

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Nickel	MAC: 0.05 mg/m ³	TWA: 0.5 mg/m ³ 8 hodinách STEL: 0.05 mg/m ³ 15 minútach	TWA: 0.006 mg/m ³ 8 urah respirable fraction STEL: 0.048 mg/m ³ 15 minutah respirable fraction	TLV: 0.5 mg/m ³ 8 timmar. NGV	
Graphite		TWA: 10 mg/m ³ total aerosol TWA: 2 mg/m ³ respirable fraction			

Biological limit values

List source(s):

Component	Italy	Finland	Denmark	Bulgaria	Romania
Nickel		Nickel: 0.1 µmol/L urine after the shift after a working week or exposure period.		Nickel: 45 µg/L urine after several work shifts	Nickel: 3 µg/L urine end of shift

Component	Gibraltar	Latvia	Slovak Republic	Luxembourg	Turkey
Nickel		Nickel: 3 µg/L urine	Nickel: 0.03 mg/L blood end of exposure or work shift		

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust

MDHS 91 Metals and metalloids in workplace air by X-ray fluorescence spectrometry

MDHS 99 Metals in air by ICP-AES

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Nickel 7440-02-0 (60.0)			DNEL = 0.035mg/cm2	

Component	Acute effects local	Acute effects	Chronic effects local	Chronic effects
-----------	---------------------	---------------	-----------------------	-----------------

SAFETY DATA SHEET

Graphite powder, nickel coated

Revision Date 20-Feb-2024

	(Inhalation)	systemic (Inhalation)	(Inhalation)	systemic (Inhalation)
Nickel 7440-02-0 (60.0)	DNEL = 11.9mg/m ³		DNEL = 0.05mg/m ³	DNEL = 0.05mg/m ³
Graphite 7782-42-5 (40.0)			DNEL = 1.2mg/m ³	DNEL = 1.2mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Nickel 7440-02-0 (60.0)	PNEC = 7.1µg/L	PNEC = 109mg/kg sediment dw		PNEC = 0.33mg/L	PNEC = 29.9mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Nickel 7440-02-0 (60.0)	PNEC = 8.6µg/L	PNEC = 109mg/kg sediment dw		PNEC = 0.12mg/kg food	

8.2. Exposure controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Wear safety glasses with side shields (or goggles) (European standard - EN 166)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Nitrile rubber	See manufacturers recommendations	-	EN 374	(minimum requirement)
Neoprene				
Natural rubber				
PVC				

Skin and body protection

Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: Particulates filter conforming to EN 143

Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Particle filtering: EN149:2001

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

Prevent product from entering drains. Do not allow material to contaminate ground water system. Local authorities should be advised if significant spillages cannot be contained.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

SAFETY DATA SHEET

Graphite powder, nickel coated

Revision Date 20-Feb-2024

9.1. Information on basic physical and chemical properties

Physical State	Solid	
Appearance	Black	
Odor	Odorless	
Odor Threshold	No data available	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	No information available	
Flammability (liquid)	Not applicable	Solid
Flammability (solid,gas)	No information available	
Explosion Limits	No data available	
Flash Point	No information available	Method - No information available
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
pH	No information available	
Viscosity	Not applicable	Solid
Water Solubility	Insoluble in water	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Vapor Pressure	<=1100 hPa @ 50 °C	
Density / Specific Gravity	No data available	
Bulk Density	No data available	
Vapor Density	Not applicable	Solid
Particle characteristics	No data available	

9.2. Other information

Flammable solids	Burning rate or burning time = > 2.2 mm/s or < 45 secs
Evaporation Rate	Wetted zone passed - No Not applicable - Solid

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization	No information available.
Hazardous Reactions	None under normal processing.

10.4. Conditions to avoid

Incompatible products. Excess heat.

10.5. Incompatible materials

Oxidizing agent.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂). Heavy metal oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

SAFETY DATA SHEET

Graphite powder, nickel coated

Revision Date 20-Feb-2024

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral

Based on available data, the classification criteria are not met

Dermal

No data available

Inhalation

No data available

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Nickel	LD50 > 9000 mg/kg (Rat)	-	LC50 > 10.2 mg/L (Rat) 1 h
Graphite	-	-	LC50 > 2000 mg/m ³ (Rat) 4 h

(b) skin corrosion/irritation;

No data available

(c) serious eye damage/irritation;

No data available

(d) respiratory or skin sensitization;

Respiratory

No data available

Skin

Category 1

No information available

(e) germ cell mutagenicity;

No data available

(f) carcinogenicity;

Category 2

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Nickel			Cat. 1	Group 2B

(g) reproductive toxicity;

No data available

(h) STOT-single exposure;

No data available

(i) STOT-repeated exposure;

Category 1

Route of exposure

Inhalation

Target Organs

Lungs.

(j) aspiration hazard;

Not applicable

Solid

Symptoms / effects, both acute and delayed

Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing.

11.2. Information on other hazards

Endocrine Disrupting Properties

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

SAFETY DATA SHEET

Graphite powder, nickel coated

Revision Date 20-Feb-2024

12.1. Toxicity

Ecotoxicity effects

The product contains following substances which are hazardous for the environment. Contains a substance which is: Very toxic to aquatic organisms. May cause long-term adverse effects in the environment. Do not allow material to contaminate ground water system.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Nickel	LC50: > 100 mg/L, 96h (Brachydanio rerio) LC50: = 1.3 mg/L, 96h semi-static (Cyprinus carpio) LC50: = 10.4 mg/L, 96h static (Cyprinus carpio)	EC50: = 1 mg/L, 48h Static (Daphnia magna) EC50: > 100 mg/L, 48h (Daphnia magna)	EC50: 0.174 - 0.311 mg/L, 96h static (Pseudokirchneriella subcapitata) EC50: = 0.18 mg/L, 72h (Pseudokirchneriella subcapitata)
Graphite	LC50: > 100 mg/L, 96h semi-static (Danio rerio)		

12.2. Persistence and degradability

Persistence Degradation in sewage treatment plant

Product contains heavy metals. Discharge into the environment must be avoided. Special pre-treatment is necessary
Insoluble in water, May persist.
Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential

May have some potential to bioaccumulate; Product has a high potential to bioconcentrate

12.4. Mobility in soil

Spillage unlikely to penetrate soil Is not likely mobile in the environment due its low water solubility.

12.5. Results of PBT and vPvB assessment

No data available for assessment.

12.6. Endocrine disrupting properties

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance
This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

European Waste Catalogue (EWC)

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information

Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in

SAFETY DATA SHEET

Graphite powder, nickel coated

Revision Date 20-Feb-2024

compliance with local regulations.

Switzerland - Waste Ordinance

Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600
<https://www.fedlex.admin.ch/eli/cc/2015/891/en>

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number UN3178
14.2. UN proper shipping name Flammable solid, inorganic, n.o.s.
Technical Shipping Name (graphite, Nickel powder)
14.3. Transport hazard class(es) 4.1
14.4. Packing group III

ADR

14.1. UN number UN3178
14.2. UN proper shipping name Flammable solid, inorganic, n.o.s.
Technical Shipping Name (graphite, Nickel powder)
14.3. Transport hazard class(es) 4.1
14.4. Packing group III

IATA

14.1. UN number UN3178
14.2. UN proper shipping name Flammable solid, inorganic, n.o.s.
Technical Shipping Name (graphite, Nickel powder)
14.3. Transport hazard class(es) 4.1
14.4. Packing group III

14.5. Environmental hazards No hazards identified

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Nickel	7440-02-0	231-111-4	-	-	X	X	KE-25818	X	-
Graphite	7782-42-5	231-955-3	-	-	X	X	KE-18101	-	-

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Nickel	7440-02-0	X	ACTIVE	X	-	X	X	X
Graphite	7782-42-5	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

SAFETY DATA SHEET

Graphite powder, nickel coated

Revision Date 20-Feb-2024

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Nickel	7440-02-0	-	Use restricted. See item 27. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	-
Graphite	7782-42-5	-	-	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Nickel	7440-02-0	Not applicable	Not applicable
Graphite	7782-42-5	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification Water endangering class = 2 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Nickel	WGK2	Class II : 0.5 mg/m ³ (Massenkonzentration) Krebserzeugende Stoffe - Class II : 0.5 mg/m ³ (Massenkonzentration)
Graphite	nwg	

Component	France - INRS (Tables of occupational diseases)
Graphite	Tableaux des maladies professionnelles (TMP) - RG 16 Tableaux des maladies professionnelles (TMP) - RG 25

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
-----------	--	---	---

SAFETY DATA SHEET

Graphite powder, nickel coated

Revision Date 20-Feb-2024

	814.81)		
Nickel 7440-02-0 (60.0)	Prohibited and Restricted Substances		

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H228 - Flammable solid

H317 - May cause an allergic skin reaction

H351 - Suspected of causing cancer

H372 - Causes damage to organs through prolonged or repeated exposure

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data

Health Hazards Calculation method

Environmental hazards Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Prepared By

Health, Safety and Environmental Department

Revision Date

20-Feb-2024

Revision Summary

New emergency telephone response service provider.

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.
COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No
1907/2006 .**

SAFETY DATA SHEET

Graphite powder, nickel coated

Revision Date 20-Feb-2024

For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2, Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and Preparations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet