

Classified as hazardous in accordance with the criteria of EPA New Zealand

Section 1 - Identification

Product Identifier

Product Name	DIISOBUTYLALUMINIUM HYDRIDE, 1.2M (20 wt%) SOLUTION IN TOLUENE, ACROSEAL(R)
Synonyms	DIBAL-H
Molecular Formula	C ₈ H ₁₉ Al
Molecular Weight	142.22
Recommended Use	Laboratory chemicals.
Uses advised against	No Information available

Product Code	C20108
Address	Thermo Fisher Scientific New Zealand Ltd 244 Bush Road, Albany, Auckland, New Zealand
Emergency Tel.	CHEMTREC® 09 980 6780 or +64 9 980 6780
Telephone / Fax Numbers	Tel: 09 980 6700 Fax: 09 980 6788
E-mail address	ANZinfo@thermofisher.com

Section 2 - Hazard(s) Identification

Classification under Work Safe New Zealand

Classified as hazardous in accordance with the criteria of EPA New Zealand

GHS Classification

Physical hazards

Flammable liquids	Category 2
Substances/mixtures which, in contact with water, emit flammable gases	Category 1
Pyrophoric liquids	Category 1

Health hazards

Aspiration Toxicity	Category 1
Acute Oral Toxicity	Category 4
Acute Inhalation Toxicity - Vapors	Category 4
Skin Corrosion/Irritation	Category 1 A
Serious Eye Damage/Eye Irritation	Category 1
Reproductive Toxicity	Category 2
Specific target organ toxicity - (single exposure)	Category 3
Specific target organ toxicity - (repeated exposure)	Category 2

Environmental hazards

Chronic aquatic toxicity

Category 3

Label Elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor
H260 - In contact with water releases flammable gases which may ignite spontaneously
H304 - May be fatal if swallowed and enters airways
H314 - Causes severe skin burns and eye damage
H336 - May cause drowsiness or dizziness
H361 - Suspected of damaging fertility or the unborn child
H373 - May cause damage to organs through prolonged or repeated exposure
H412 - Harmful to aquatic life with long lasting effects
H250 - Catches fire spontaneously if exposed to air
H302 + H332 - Harmful if swallowed or if inhaled

Precautionary Statements

Prevention

P201 - Obtain special instructions before use
P223 - Do not allow contact with water
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P231 + P232 - Handle and store contents under inert gas. Protect from moisture
P233 - Keep container tightly closed
P240 - Ground and bond container and receiving equipment
P242 - Use non-sparking tools
P241 - Use explosion-proof electrical/ ventilating/ lighting equipment
P243 - Take action to prevent static discharges
P260 - Do not breathe dust/fume/gas/mist/vapors/spray
P264 - Wash face, hands and any exposed skin thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves/protective clothing/eye protection/face protection

Response

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
P310 - Immediately call a POISON CENTER or doctor
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P330 - Rinse mouth
P331 - Do NOT induce vomiting
P363 - Wash contaminated clothing before reuse
P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish
P302 + P335 + P334 - IF ON SKIN: Brush off loose particles from skin. Immerse in cool water

Storage

P402 + P404 - Store in a dry place. Store in a closed container

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Other hazards which do not result in classification

Toxic to terrestrial vertebrates
This product does not contain any known or suspected endocrine disruptors
Reacts violently with water

Section 3 - Composition and Information on Ingredients

Component	CAS No	Weight %
Toluene	108-88-3	80
Diisobutylaluminum hydride	1191-15-7	20

Section 4 - First Aid Measures

Description of first aid measures

General Advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
New Zealand Emergency Tel.	CHEMTREC® 09 980 6780 or +64 9 980 6780
Inhalation	If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately. Risk of serious damage to the lungs (by aspiration).
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Call a physician immediately.
Ingestion	Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.
First Aid Facilities	Eyewash, safety shower and washroom.
Most important symptoms and effects	Causes burns by all exposure routes. Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting; Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation
Notes to Physician	Treat symptomatically. Symptoms may be delayed.

Section 5 - Fire Fighting Measures

Suitable Extinguishing Media

Dry chemical. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Water.

Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Reacts violently with water. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂), Hydrogen, Burning produces obnoxious and toxic fumes.

Decomposition Temperature

150 °C

Special protective equipment and precautions for fire fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

Section 6 - Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures

Emergency procedures

Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions

Do not flush into surface water or sanitary sewer system.

Methods for Containment and Clean Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Do not expose spill to water. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Precautions to prevent secondary hazards

Clean contaminated objects and areas thoroughly observing environmental regulations

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

Section 7 - Handling and Storage

Precautions for Safe Handling

Advice on safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Do not allow contact with water. Handle under an inert atmosphere. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

Conditions for Safe Storage, Including any Incompatibilities

Storage Conditions

Flammables area. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Keep away from water or moist air. Keep under nitrogen. Corrosives area. Store under an inert atmosphere. Protect from moisture.

Incompatible Materials

Acids. Water. Alcohols. Strong oxidizing agents.

AS/NZS 2243.10:2004, Safety in laboratories - Storage of chemicals
AS 1940-2004 - The storage and handling of flammable and combustible liquids

Section 8 - Exposure Controls and Personal Protection

Control parameters

Exposure limits

NZ - Workplace Exposure Standards and Biological Exposure Indices (6th edition). New Zealand Department of Labor

UK - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020.

ACGIH - Threshold Limit Values - Ceiling (TLV-C) guidelines by the American Conference of Governmental Industrial Hygienists (ACGIH) for controlling worker exposure to airborne chemical concentrations in the workplace.

AUS - Exposure Standards for Atmospheric Contaminants in the Occupational Environment - Guidance Note on the Interpretation of Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:3008(1995)]

Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)] updated in August, 2005. Safe Work Australia

Component	New Zealand WEL	Australia	ACGIH TLV	The United Kingdom
Toluene	TWA: 20 ppm TWA: 75 mg/m ³ STEL: 100 ppm STEL: 377 mg/m ³ Skin	STEL: 150 ppm STEL: 574 mg/m ³ TWA: 50 ppm TWA: 191 mg/m ³	TWA: 20 ppm	STEL: 100 ppm 15 min STEL: 384 mg/m ³ 15 min TWA: 50 ppm 8 hr TWA: 191 mg/m ³ 8 hr Skin
Diisobutylaluminum hydride		TWA: 2 mg/m ³		STEL: 6 mg/m ³ 15 min TWA: 2 mg/m ³ 8 hr

Biological limit values

NZ - Substances assigned Biological Exposure Indices in the New Zealand Workplace Exposure Standards and Biological Exposure Indices (6th edition). New Zealand Department of Labor

ACGIH - American Conference of Governmental Industrial Hygienists (ACGIH) TLVs® and BEIs®- Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices. 2022 Edition

Component	New Zealand	Australia	ACGIH - Biological Exposure Indices	United Kingdom
Toluene	0.03 mg/L (urine) end of exposure or end of shift (Toluene) 0.3 mg/g creatinine (urine) end of exposure or end of shift (O-Cresol)		0.02 mg/L Medium: blood Time: prior to last shift of workweek Determinant: Toluene 0.03 mg/L Medium: urine Time: end of shift Determinant: Toluene 0.3 mg/g creatinine Medium: urine Time: end of shift Determinant: o-Cresol with hydrolysis	

Appropriate engineering controls

Engineering Measures

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Individual protection measures, such as personal protective equipment

Eye Protection

Goggles (Australian/New Zealand Standard AS/NZS 1337 - Eye protectors for Industrial applications)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	AUS/NZ Standard	Glove comments
Nitrile rubber, Viton (R).	See manufacturers recommendations	-	AS/NZS 2161	(minimum requirement)

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves.
(Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure

Respiratory Protection

Use an AS/NZS 1716 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained in line with AS/NZS 1715 on the use and maintenance of respiratory protective devices

Recommended Filter type:

Organic gases and vapours filter Type A Brown conforming to EN14387 (or AUS/NZ equivalent)

Recommended half mask:-

Valve filtering: EN405 or Half mask: EN140 plus filter, EN 141 (or AUS/NZ equivalent)
When RPE is used a face piece Fit Test should be conducted

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

Environmental exposure controls

Prevent product from entering drains. Do not allow material to contaminate ground water system.

Section 9 - Physical and Chemical Properties

Information on basic physical and chemical properties

Physical State	Liquid	
Appearance	Colorless	
Odor	No information available	
Odor Threshold	No data available	
pH	Not applicable	
Melting Point/Range	No data available	
Softening Point	No data available	
Boiling Point/Range	110 °C / 230 °F	
Flammability (liquid)	Highly flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Flash Point	4 °C / 39.2 °F	Method - No information available
Autoignition Temperature	No data available	
Decomposition Temperature	150 °C	
Viscosity	No data available	
Water Solubility	Reacts violently with water	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Toluene	2.73	
Vapor Pressure	No data available	
Density / Specific Gravity	0.848	
Bulk Density	Not applicable	Liquid
Vapor Density	> 3.1	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

Other information

Molecular Formula C8 H19 Al
Molecular Weight 142.22
Explosive Properties Vapors may form explosive mixtures with air
Substances/mixtures which, in contact with water, emit flammable gases Emitted gas ignites spontaneously
Gas(es) = Hydrogen

Section 10 - Stability and Reactivity

Reactivity Yes

Stability Reacts violently with water. Moisture sensitive. Air sensitive.

Sensitivity to Mechanical Impact No information available

Sensitivity to Static Discharge No information available

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions Reacts violently with water.

Conditions to Avoid Keep away from open flames, hot surfaces and sources of ignition, Incompatible products, Exposure to moist air or water, Exposure to air, Exposure to moisture.

Incompatible Materials Acids, Water, Alcohols, Strong oxidizing agents.

Hazardous Decomposition Products Carbon monoxide (CO). Carbon dioxide (CO₂). Hydrogen. Burning produces obnoxious and toxic fumes.

Section 11 - Toxicological Information

Acute Effects

Information on likely routes of exposure

Product Information

Inhalation Not an expected route of exposure.
Eyes Avoid contact with eyes. Corrosive to the eyes and may cause severe damage including blindness. Risk of serious damage to eyes.
Skin Avoid contact with skin. Causes burns. Skin Corrosion/Irritation. Contact with moist skin may cause skin burns.
Ingestion May be harmful if swallowed. Harmful if swallowed. Potential for aspiration if swallowed.

Numerical measures of toxicity

(a) acute toxicity;

Oral Based on available data, the classification criteria are not met
Dermal Based on available data, the classification criteria are not met
Inhalation Based on available data, the classification criteria are not met

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Toluene	> 5000 mg/kg (Rat)	12000 mg/kg (Rabbit)	26700 ppm (Rat) 1 h

(b) skin corrosion/irritation;	Category 1 A
(c) serious eye damage/irritation;	Category 1
(d) respiratory or skin sensitization;	
Respiratory	No data available
Skin	No data available
(e) germ cell mutagenicity;	No data available
(f) carcinogenicity;	No data available
	There are no known carcinogenic chemicals in this product
(g) reproductive toxicity;	Category 2
Reproductive Effects	Experiments have shown reproductive toxicity effects on laboratory animals
Teratogenicity	Teratogenic effects have occurred in experimental animals.
(h) STOT-single exposure;	Category 3
Results / Target organs	Central nervous system (CNS)
(i) STOT-repeated exposure;	Category 2
Target Organs	Neuropsychological effects, Eyes, Ears.
(j) aspiration hazard;	Category 1

Symptoms / effects, both acute and delayed

Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation.

Section 12 - Ecological Information

Ecotoxicity

Aquatic ecotoxicity

The product contains following substances which are hazardous for the environment.
Contains a substance which is: Harmful to aquatic organisms.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Toluene	50-70 mg/L LC50 96 h 5-7 mg/L LC50 96 h 15-19 mg/L LC50 96 h 28 mg/L LC50 96 h 12 mg/L LC50 96 h	EC50: = 11.5 mg/L, 48h (Daphnia magna) EC50: 5.46 - 9.83 mg/L, 48h Static (Daphnia magna)	EC50: = 12.5 mg/L, 72h static (Pseudokirchneriella subcapitata) EC50: > 433 mg/L, 96h (Pseudokirchneriella subcapitata)	EC50 = 19.7 mg/L 30 min

Terrestrial ecotoxicity

There is no data for this product

Persistence and Degradability

Persistence Soluble in water, Persistence is unlikely, based on information available.

Degradability Reacts with water.

Component	Degradability
Toluene 108-88-3 (80)	86% (20d)

Degradation in sewage treatment plant Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants. Reacts violently with water.

Bioaccumulative Potential Bioaccumulation is unlikely Product does not bioaccumulate due to reaction with water

Component	log Pow	Bioconcentration factor (BCF)
Toluene	2.73	90

Mobility The product is water soluble, and may spread in water systems. Reacts violently with water. Will likely be mobile in the environment due to its water solubility. Is not likely mobile in the environment. Highly mobile in soils

Other adverse effects

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors
Persistent Organic Pollutant This product does not contain any known or suspected substance
Ozone Depletion Potential This product does not contain any known or suspected substance

Section 13 - Disposal Considerations

Waste treatment methods

Waste from Residues/Unused Products Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with all federal, E.P.A., state and local regulations. Assure conformity with all applicable regulations.

Contaminated Packaging Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

Other Information Disposal agencies or waste contractors must comply with the New Zealand Hazardous Substances (Disposal) Regulations . Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms. Do not let this chemical enter the environment.

Section 14 - Transport Information

Component	Hazchem Code
Toluene 108-88-3 (80)	3YE

NZS 5433:2020

UN-No UN3399
Proper Shipping Name ORGANOMETALLIC SUBSTANCE, LIQUID, WATER-REACTIVE, FLAMMABLE
Technical Shipping Name (DIISOBUTYLALUMINIUM HYDRIDE, TOLUENE)
Hazard Class 4.3

Subsidiary Hazard Class 3
Packing Group I

IATA

UN-No UN3399
Proper Shipping Name Organometallic substance, liquid, water-reactive, flammable
Technical Shipping Name (DIISOBUTYLALUMINIUM HYDRIDE, TOLUENE)
Hazard Class 4.3
Subsidiary Hazard Class 3
Packing Group I

IMDG/IMO

UN-No UN3399
Proper Shipping Name ORGANOMETALLIC SUBSTANCE, LIQUID, WATER-REACTIVE, FLAMMABLE
Technical Shipping Name (DIISOBUTYLALUMINIUM HYDRIDE, TOLUENE)
Hazard Class 4.3
Subsidiary Hazard Class 3
Packing Group I

Environmental hazards No hazards identified

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable, packaged goods

Special Precautions No special precautions required. Please refer to the applicable dangerous goods regulations for additional information.

Additional information None known

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National Regulations

Any applicable tolerable exposure limits and environmental exposure limits according to the EPA Controls for Hazardous Substances are listed below

Component	Tolerable Exposure Limit (TEL) Air	Tolerable Exposure Limit (TEL) Water	Tolerable Exposure Limit (TEL) Surface	Environmental Exposure Limits (EEL)
Toluene	400 µg/m ³	0.8 mg/L		330 µg/L (Water)

Certified handlers, tracking and controlled substance license requirements

Certified handlers are required for some substances. This includes substances requiring a controlled substance license, and most explosives, vertebrates toxic agents, and certain fumigants. Acutely toxic substances which are a Category 1 or 2, such as pesticides also require Certified handlers. Please check the Health and Safety at Work Act 2015 for further information. Tracking is required for some highly hazardous substances. These substances need to be under the control of an appropriately trained person or appropriately secured. Please check the Health and Safety at Work Act 2015 for further information.

Prohibition or notification/licensing requirements

Shown below are details of specific prohibition/notifications or licensing requirements when they apply.

International Regulations

Ozone Depletion Potential This product does not contain any known or suspected substance

Persistent Organic Pollutant This product does not contain any known or suspected substance

Rotterdam Convention (PIC) Not applicable

Authorisation/Restrictions
according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Toluene	-	Use restricted. See entry 48. (see link for restriction details) Use restricted. See entry 75. (see link for restriction details)	-
Diisobutylaluminum hydride	-	Use restricted. See entry 75. (see link for restriction details)	-

<https://echa.europa.eu/substances-restricted-under-reach>

International Inventories

New Zealand (NZIoC), Australia (AICS), Europe (EINECS/ELINCS/NLP), Korea (KECL), China (IECSC), Taiwan (TCSI), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	NZIoC	AICS	EINECS	ELINCS	NLP	KECL	IECSC	TCSI
Toluene	108-88-3	X	X	203-625-9	-	-	KE-33936	X	X
Diisobutylaluminum hydride	1191-15-7	X	X	214-729-9	-	-	KE-10903	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	PICCS	ISHL	ENCS
Toluene	108-88-3	X	ACTIVE	X	-	X	X	X
Diisobutylaluminum hydride	1191-15-7	X	ACTIVE	-	X	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Section 16 - Other Information

This safety data sheet complies with the requirements of the EPA Hazardous Substances
(Hazard Classification) Notice 2020 and WorkSafe New Zealand Regulations

Legend

NZIoC - New Zealand Inventory of Chemicals
TSCA - United States Toxic Substances Control Act Section 8(b)
 Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic
 Substances List
IECSC - Chinese Inventory of Existing Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
TWA - Time Weighted Average
IARC - International Agency for Research on Cancer
NZS 5433:2020 - Transport of Dangerous Goods on Land
ICAO/IATA - International Civil Aviation Organization/International Air
 Transport Association
MARPOL - International Convention for the Prevention of Pollution from
 Ships
LD50 - Lethal Dose 50%
EC50 - Effective Concentration 50%
WEL - Workplace Exposure Limit
DNEL - Derived No Effect Level
POW - Partition coefficient Octanol:Water
vPvB - very Persistent, very Bioaccumulative

AICS - Australian Inventory of Chemical Substances
EINECS/ELINCS - European Inventory of Existing Commercial Chemical
 Substances/EU List of Notified Chemical Substances
ENCS - Japanese Existing and New Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
CAS - Chemical Abstracts Service
ACGIH - American Conference of Governmental Industrial Hygienists
PNEC - Predicted No Effect Concentration
OECD - Organisation for Economic Co-operation and Development
IMO/IMDG - International Maritime Organization/International Maritime
 Dangerous Goods Code
ADG - Australian Code for the Transport of Dangerous Goods by Road
 and Rail
LC50 - Lethal Concentration 50%
ATE - Acute Toxicity Estimate
RPE - Respiratory Protective Equipment
NOEC - No Observed Effect Concentration
BCF - Bioconcentration factor
PBT - Persistent, Bioaccumulative, Toxic

VOC - (Volatile Organic Compound)

Key literature references and sources for data

HSNO classifications provided in the New Zealand Chemical Classification Information Database (CCID).

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

EPA Guide to classifying hazardous substances in New Zealand

EPA - Assigning a product to an existing HSNO approval guide

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data

Health Hazards Calculation method

Environmental hazards Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Chemical incident response training.

Revision Date 11-Dec-2024

Revision Summary Initial Release

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet