

Creation Date 27-Apr-2009

Revision Date 02-May-2025

Revision Number 7

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description:	Methanol
Cat No. :	41838
Synonyms	Methyl alcohol
Index No	603-001-00-X
CAS No	67-56-1
EC No	200-659-6
Molecular Formula	C H4 O
REACH registration number	01-2119433307-44-0306

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use	Laboratory chemicals.
Sector of use	SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites
Product category	PC21 - Laboratory chemicals
Environmental release category	ERC1 - Manufacture of substances ERC2 - Formulation of preparations (mixtures) ERC4 - Industrial use of processing aids in processes and products, not becoming part of articles ERC8a - Wide dispersive indoor use of processing aids in open systems
Uses advised against	SU21 - Consumer uses: Private households (= general public = consumers); PC13 - Fuels. REACH Annex XVII Restriction - refer to SECTION 15

1.3. Details of the supplier of the safety data sheet

Company	Thermo Fisher (Kandel) GmbH Erlenbachweg 2, 76870 Kandel, Germany Tel: +49 (0) 721 84007 280 Fax: +49 (0) 721 84007 300 Swiss distributor - Fisher Scientific AG Neuhofstrasse 11, CH 4153 Reinach Tel: +41 (0) 56 618 41 11 https://www.fishersci.ch/ch/en/customer-help-support/forms/email-us.html
E-mail address	begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

SAFETY DATA SHEET

Methanol

Revision Date 02-May-2025

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Flammable liquids

Category 2 (H225)

Health hazards

Acute oral toxicity

Category 3 (H301)

Acute dermal toxicity

Category 3 (H311)

Acute Inhalation Toxicity - Vapors

Category 3 (H331)

Specific target organ toxicity - (single exposure)

Category 1 (H370)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H301 + H311 + H331 - Toxic if swallowed, in contact with skin or if inhaled

H370 - Causes damage to organs: Optic nerve, Central nervous system (CNS)

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P240 - Ground and bond container and receiving equipment

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

P302 + P350 - IF ON SKIN: Gently wash with plenty of soap and water

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

2.3. Other hazards

Substance is not considered to be persistent, bioaccumulative and toxic (PBT). Substance is not considered to be very

SAFETY DATA SHEET

Methanol

Revision Date 02-May-2025

persistent and very bioaccumulative (vPvB).
Toxic to terrestrial vertebrates
This product does not contain any known or suspected endocrine disruptors

Section 3: Composition/information on ingredients

3.1. Substances

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Methanol	67-56-1	200-659-6	>95	Flam. Liq. 2 (H225) Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Methanol	STOT Single Exp. 1 :: >= 10 STOT Single Exp. 2 :: 3 - < 10	-	-

REACH registration number	01-2119433307-44-0306
---------------------------	-----------------------

Full text of Hazard Statements: see section 16

Section 4: First aid measures

4.1. Description of first aid measures

General Advice	Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.
Ingestion	Do NOT induce vomiting. Call a physician or poison control center immediately.
Inhalation	Remove to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Remove all sources of ignition. No artificial respiration, mouth-to-mouth or mouth to nose. Use suitable instruments/apparatus. Avoid contact with skin.

4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. May cause blindness: Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

4.3. Indication of any immediate medical attention and special treatment needed

SAFETY DATA SHEET

Methanol

Revision Date 02-May-2025

Notes to Physician

Treat symptomatically. Symptoms may be delayed.

Section 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media

Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Vapors may form explosive mixtures with air.

Hazardous Combustion Products

Carbon monoxide (CO), Formaldehyde.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Should not be released into the environment. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

Section 7: Handling and storage

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not breathe mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Hygiene Measures

When using do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.

SAFETY DATA SHEET

Methanol

Revision Date 02-May-2025

7.2. Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Flammables area.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Class 3

Switzerland - Storage of hazardous substances

Storage class - SC 3

<https://www.kvu.ch/de/themen/stoffe-und-produkte>

<https://www.kvu.ch/fr/themes/substances-et-produits>

<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

Section 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Methanol	TWA: 200 ppm 8 hr TWA: 260 mg/m ³ 8 hr Skin	WEL - TWA: 200 ppm TWA: 266 mg/m ³ TWA WEL - STEL: 250 ppm STEL: 333 mg/m ³ STEL	TWA / VME: 200 ppm (8 heures). restrictive limit TWA / VME: 260 mg/m ³ (8 heures). restrictive limit STEL / VLCT: 1000 ppm. restrictive limit: this value is not set by regulation and comes from a circular published by the Ministry of Labor. STEL / VLCT: 1300 mg/m ³ . restrictive limit: this value is not set by regulation and comes from a circular published by the Ministry of Labor. Peau	TWA: 200 ppm 8 uren TWA: 266 mg/m ³ 8 uren STEL: 250 ppm 15 minuten STEL: 333 mg/m ³ 15 minuten Huid	TWA / VLA-ED: 200 ppm (8 horas) TWA / VLA-ED: 266 mg/m ³ (8 horas) Piel

Component	Italy	Germany	Portugal	The Netherlands	Finland
Methanol	TWA: 200 ppm 8 ore. Time Weighted Average TWA: 260 mg/m ³ 8 ore. Time Weighted Average Pelle	100 ppm TWA MAK; 130 mg/m ³ TWA MAKSkin absorber	STEL: 250 ppm 15 minutos TWA: 200 ppm 8 horas TWA: 260 mg/m ³ 8 horas Pele	huid TWA: 100 ppm 8 uren TWA: 133 mg/m ³ 8 uren	TWA: 200 ppm 8 tunteina TWA: 270 mg/m ³ 8 tunteina STEL: 250 ppm 15 minuutteina STEL: 330 mg/m ³ 15 minuutteina Iho

Component	Austria	Denmark	Switzerland	Poland	Norway
Methanol	Haut	TWA: 200 ppm 8 timer	Haut/Peau	STEL: 300 mg/m ³ 15	TWA: 100 ppm 8 timer

SAFETY DATA SHEET

Methanol

Revision Date 02-May-2025

	MAK-KZGW: 800 ppm 15 Minuten MAK-KZGW: 1040 mg/m ³ 15 Minuten MAK-TMW: 200 ppm 8 Stunden MAK-TMW: 260 mg/m ³ 8 Stunden	TWA: 260 mg/m ³ 8 timer STEL: 400 ppm 15 minutter STEL: 520 mg/m ³ 15 minutter Hud	STEL: 400 ppm 15 Minuten STEL: 520 mg/m ³ 15 Minuten TWA: 200 ppm 8 Stunden TWA: 260 mg/m ³ 8 Stunden	minutach TWA: 100 mg/m ³ 8 godzinach	TWA: 130 mg/m ³ 8 timer STEL: 150 ppm 15 minutter. value calculated STEL: 162.5 mg/m ³ 15 minutter. value calculated Hud
--	---	---	--	---	---

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Methanol	TWA: 200 ppm TWA: 260.0 mg/m ³ Skin notation	kože TWA-GVI: 200 ppm 8 satima. TWA-GVI: 260 mg/m ³ 8 satima.	TWA: 200 ppm 8 hr. TWA: 260 mg/m ³ 8 hr. STEL: 600 ppm 15 min STEL: 780 mg/m ³ 15 min Skin	Skin-potential for cutaneous absorption TWA: 200 ppm TWA: 260 mg/m ³	TWA: 250 mg/m ³ 8 hodinách. Potential for cutaneous absorption Ceiling: 1000 mg/m ³

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Methanol	Nahk TWA: 200 ppm 8 tundides. TWA: 250 mg/m ³ 8 tundides. STEL: 250 ppm 15 minutites. STEL: 350 mg/m ³ 15 minutites.	Skin notation TWA: 200 ppm 8 hr TWA: 260 mg/m ³ 8 hr	skin - potential for cutaneous absorption STEL: 250 ppm STEL: 325 mg/m ³ TWA: 200 ppm TWA: 260 mg/m ³	TWA: 260 mg/m ³ 8 órában. AK TWA: 200 ppm 8 órában. AK lehetséges borón keresztüli felszívódás	TWA: 200 ppm 8 klukkustundum. TWA: 260 mg/m ³ 8 klukkustundum. Skin notation Ceiling: 400 ppm Ceiling: 520 mg/m ³

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Methanol	skin - potential for cutaneous exposure TWA: 200 ppm TWA: 260 mg/m ³	TWA: 200 ppm IPRD TWA: 260 mg/m ³ IPRD Oda	Possibility of significant uptake through the skin TWA: 200 ppm 8 Stunden TWA: 260 mg/m ³ 8 Stunden	possibility of significant uptake through the skin TWA: 200 ppm TWA: 260 mg/m ³	Skin notation TWA: 200 ppm 8 ore TWA: 260 mg/m ³ 8 ore

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Methanol	TWA: 5 mg/m ³ 1250 Skin notation MAC: 15 mg/m ³	Potential for cutaneous absorption TWA: 200 ppm TWA: 260 mg/m ³	TWA: 200 ppm 8 urah TWA: 260 mg/m ³ 8 urah Koža STEL: 800 ppm 15 minutah STEL: 1040 mg/m ³ 15 minutah	Indicative STEL: 250 ppm 15 minuter Indicative STEL: 350 mg/m ³ 15 minuter TLV: 200 ppm 8 timmar. NGV TLV: 250 mg/m ³ 8 timmar. NGV Hud	Deri TWA: 200 ppm 8 saat TWA: 260 mg/m ³ 8 saat

Biological limit values

List source(s):

Component	European Union	United Kingdom	France	Spain	Germany
Methanol			Methanol: urine end of shift	Methanol: 15 mg/L urine end of shift	Methanol: 15 mg/L urine (end of shift) Methanol: 15 mg/L urine (for long-term exposures: at the end of the shift after several shifts)

Component	Italy	Finland	Denmark	Bulgaria	Romania
Methanol					Methanol: 6 mg/L urine end of shift

Component	Gibraltar	Latvia	Slovak Republic	Luxembourg	Turkey
Methanol			Methanol: 30 mg/L urine end of exposure or work shift		

SAFETY DATA SHEET

Methanol

Revision Date 02-May-2025

			Methanol: 30 mg/L urine after all work shifts for long-term exposure		
--	--	--	--	--	--

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Methanol 67-56-1 (>95)		DNEL = 20mg/kg bw/day		DNEL = 20mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Methanol 67-56-1 (>95)	DNEL = 130mg/m ³	DNEL = 130mg/m ³	DNEL = 130mg/m ³	DNEL = 130mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Methanol 67-56-1 (>95)	PNEC = 20.8mg/L	PNEC = 77mg/kg sediment dw	PNEC = 1540mg/L	PNEC = 100mg/L	PNEC = 100mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Methanol 67-56-1 (>95)	PNEC = 2.08mg/L	PNEC = 7.7mg/kg sediment dw			

8.2. Exposure controls

Engineering Measures

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Tight sealing safety goggles (European standard - EN 166)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Butyl rubber	> 480 minutes	0.35 mm	Level 6	As tested under EN374-3 Determination of
Viton (R)	> 480 minutes	0.70 mm	EN 374	Resistance to Permeation by Chemicals

SAFETY DATA SHEET

Methanol

Revision Date 02-May-2025

Neoprene gloves	< 60 minutes	0.45 mm
Nitrile rubber	< 30 minutes	0.38 mm
Skin and body protection Long sleeved clothing.		

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Recommended Filter type: low boiling organic solvent Type AX Brown conforming to EN371

Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141
When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls No information available.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance	Colorless	
Odor	Alcohol-like	
Odor Threshold	No data available	
Melting Point/Range	-98 °C / -144.4 °F	
Softening Point	No data available	
Boiling Point/Range	64.7 °C / 148.5 °F	@ 760 mmHg
Flammability (liquid)	Highly flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	Lower 6 vol% Upper 31 vol%	
Flash Point	10 °C / 50 °F	Method - CC (closed cup) Abel-Pensky (DIN 51755) Directive 84/449/EEC, A.9
Autoignition Temperature	455 °C / 851 °F	
Decomposition Temperature	No data available	
pH	No information available	
Viscosity	0.55 cP at 20 °C	
Water Solubility	Miscible	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Methanol	-0.74	
Vapor Pressure	128 hPa @ 20 °C	
Density / Specific Gravity	0.791	
Bulk Density	Not applicable	Liquid
Vapor Density	1.11	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

SAFETY DATA SHEET

Methanol

Revision Date 02-May-2025

9.2. Other information

Molecular Formula	C H4 O
Molecular Weight	32.04
VOC Content(%)	100
Explosive Properties	Not explosive Vapors may form explosive mixtures with air
Evaporation Rate	5.2 (ether = 1)
Surface tension	0.02255 N/m @ 20°C

Section 10: Stability and reactivity

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

10.4. Conditions to avoid

Incompatible products. Heat, flames and sparks. Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents. Strong acids. Acid anhydrides. Acid chlorides. Strong bases. Metals. Peroxides.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Formaldehyde.

Section 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral	Category 3
Dermal	Category 3
Inhalation	Category 3

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methanol	LD50 = 1187 – 2769 mg/kg (Rat)	LD50 = 17100 mg/kg (Rabbit)	LC50 = 128.2 mg/L (Rat) 4 h

(b) skin corrosion/irritation; Based on available data, the classification criteria are not met

(c) serious eye damage/irritation; Based on available data, the classification criteria are not met

(d) respiratory or skin sensitization;

Respiratory	Based on available data, the classification criteria are not met
Skin	Based on available data, the classification criteria are not met

SAFETY DATA SHEET

Methanol

Revision Date 02-May-2025

Component	Test method	Test species	Study result
Methanol 67-56-1 (>95)	OECD Test Guideline 406 Guinea Pig Maximisation Test (GPMT)	guinea pig	non-sensitising

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

(f) carcinogenicity; Based on available data, the classification criteria are not met
There are no known carcinogenic chemicals in this product

(g) reproductive toxicity; Based on available data, the classification criteria are not met

Component	Test method	Test species / Duration	Study result
Methanol 67-56-1 (>95)	OECD Test Guideline 416	Rat / Inhalation 2 Generation	NOAEC = 1.3 mg/l (air)

Developmental Effects Component substance is listed on California Proposition 65 as a developmental hazard.

(h) STOT-single exposure; Category 1

Results / Target organs Optic nerve, Central nervous system (CNS).

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met

Target Organs None known.

(j) aspiration hazard; Based on available data, the classification criteria are not met

Symptoms / effects, both acute and delayed May cause blindness. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity effects

Component	Freshwater Fish	Water Flea	Freshwater Algae
Methanol	Pimephales promelas: LC50 > 10000 mg/L 96h	EC50 > 10000 mg/L 24h	

Component	Microtox	M-Factor
Methanol	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	

12.2. Persistence and degradability

Persistence Readily biodegradable
Persistence is unlikely, based on information available.

Component	Degradability
Methanol 67-56-1 (>95)	DT50 ~ 17.2d >94% after 20d

SAFETY DATA SHEET

Methanol

Revision Date 02-May-2025

12.3. Bioaccumulative potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Methanol	-0.74	<10 dimensionless

12.4. Mobility in soil

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in air.

Surface tension

0.02255 N/m @ 20°C

12.5. Results of PBT and vPvB assessment

Substance is not considered to be persistent, bioaccumulative and toxic (PBT). Substance is not considered to be very persistent and very bioaccumulative (vPvB).

12.6. Endocrine disrupting properties

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance

This product does not contain any known or suspected substance

Section 13: Disposal considerations

13.1. Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

European Waste Catalogue (EWC)

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information

Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with local regulations.

Switzerland - Waste Ordinance

Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600
<https://www.fedlex.admin.ch/eli/cc/2015/891/en>

Section 14: Transport information

IMDG/IMO

14.1. UN number

UN1230

14.2. UN proper shipping name

METHANOL

14.3. Transport hazard class(es)

3

Subsidiary Hazard Class

6.1

14.4. Packing group

II

SAFETY DATA SHEET

Methanol

Revision Date 02-May-2025

ADR

14.1. UN number	UN1230
14.2. UN proper shipping name	METHANOL
14.3. Transport hazard class(es)	3
Subsidiary Hazard Class	6.1
14.4. Packing group	II

IATA

14.1. UN number	UN1230
14.2. UN proper shipping name	METHANOL
14.3. Transport hazard class(es)	3
Subsidiary Hazard Class	6.1
14.4. Packing group	II

14.5. Environmental hazards	No hazards identified
14.6. Special precautions for user	No special precautions required.
14.7. Maritime transport in bulk according to IMO instruments	Not applicable, packaged goods

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Methanol	67-56-1	200-659-6	-	-	X	X	KE-23193	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Methanol	67-56-1	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Methanol	67-56-1	-	Use restricted. See entry 69. (see link for restriction details) Use restricted. See entry 75. (see link for restriction details)	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

SAFETY DATA SHEET

Methanol

Revision Date 02-May-2025

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Methanol	67-56-1	500 tonne	5000 tonne

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

See table for values

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Methanol	WGK 2	Class I : 20 mg/m ³ (Massenkonzentration)

Component	France - INRS (Tables of occupational diseases)
Methanol	Tableaux des maladies professionnelles (TMP) - RG 84

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Methanol 67-56-1 (>95)	Prohibited and Restricted Substances	Group I	

15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has not been conducted

Section 16: Other information

Full text of H-Statements referred to under sections 2 and 3

H225 - Highly flammable liquid and vapor

H301 - Toxic if swallowed

H311 - Toxic in contact with skin

H331 - Toxic if inhaled

H370 - Causes damage to organs

Legend

SAFETY DATA SHEET

Methanol

Revision Date 02-May-2025

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Prepared By

Health, Safety and Environmental Department

Creation Date

27-Apr-2009

Revision Date

02-May-2025

Revision Summary

Not applicable.

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.
COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No
1907/2006 .**

**For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2,
Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and
Preparations).**

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet