

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product Identifier

Product Description:	Methanol
Cat No. :	C32695
Synonyms	Methyl alcohol
CAS No	67-56-1
Molecular Formula	C H4 O

Relevant identified uses of the substance or mixture and uses advised against

Recommended Use	Laboratory chemicals.
Uses advised against	

Details of the supplier of the safety data sheet

Importer	Supplier
Fisher Scientific Korea	Thermo Fisher Scientific Chemicals, Inc.
D5,D6, Incheon Airport Logistics Complex	30 Bond Street
150, Gonghangdong-Ro 296 Beon-Gil	Ward Hill, MA 01835-8099
Jung-Gu, Incheon	
Tel: +82-1661-9555	
Fax: +82-2-2023-0603	

E-mail address	Chem.KR@thermofisher.com
-----------------------	--------------------------

Emergency Telephone Number

Emergency telephone: Medical: +(82) 070-7686-0086 or + 1-703-741-5970
 CHEMTREC: 080 822 1374 (Local), CHEMTREC: 1-800-424-9300 or + 1-703-527-3887
 Korea: 00-308-13-2549 (24 hours a day, 7 days a week)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture
Physical hazards

Flammable liquids	Category 2
-------------------	------------

Health hazards

Acute Oral Toxicity	Category 3
Acute Dermal Toxicity	Category 3
Acute Inhalation Toxicity - Vapors	Category 3
Specific target organ toxicity - (single exposure)	Category 1

Environmental hazards

Based on available data, the classification criteria are not met

SAFETY DATA SHEET

Methanol

Revision Date 25-Jun-2025

Label Elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H301 + H311 + H331 - Toxic if swallowed, in contact with skin or if inhaled

H370 - Causes damage to organs

Precautionary Statements

Prevention

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P233 - Keep container tightly closed

P240 - Ground and bond container and receiving equipment

P241 - Use explosion-proof electrical/ ventilating/ lighting equipment

P242 - Use non-sparking tools

P243 - Take action to prevent static discharges

P260 - Do not breathe dust/fume/gas/mist/vapors/spray

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray

P264 - Wash face, hands and any exposed skin thoroughly after handling

P270 - Do not eat, drink or smoke when using this product

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves/protective clothing/eye protection/face protection

Response

P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor

P330 - Rinse mouth

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P308 + P311 - IF exposed or concerned: Call a POISON CENTER or doctor

P311 - Call a POISON CENTER or doctor

P312 - Call a POISON CENTER or doctor if you feel unwell

P321 - Specific treatment (see supplemental first aid instructions on this label)

P361 + P364 - Take off immediately all contaminated clothing and wash it before reuse

P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction

Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

P403 + P235 - Store in a well-ventilated place. Keep cool

P405 - Store locked up

Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Other Hazards

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

NFPA

Health
2

Flammability
3

Instability
0

Physical hazards
N/A

SAFETY DATA SHEET

Methanol

Revision Date 25-Jun-2025

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Component	Common Name	CAS No	Index No	Weight %
Methyl alcohol	Methanol	67-56-1	KE-23193	99 - 100

SECTION 4: FIRST AID MEASURES

Description of first aid measures

General Advice

Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.

Ingestion

Do NOT induce vomiting. Call a physician or poison control center immediately.

Inhalation

Remove to fresh air. If breathing is difficult, give oxygen. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediate medical attention is required.

Self-Protection of the First Aider

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Remove all sources of ignition. No artificial respiration, mouth-to-mouth or mouth to nose. Use suitable instruments/apparatus. Avoid contact with skin.

Most important symptoms and effects, both acute and delayed

Difficulty in breathing. May cause blindness. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

Extinguishing media

Suitable Extinguishing Media

Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Vapors may form explosive mixtures with air.

Hazardous Combustion Products

Carbon monoxide (CO), Formaldehyde.

SAFETY DATA SHEET

Methanol

Revision Date 25-Jun-2025

Advice for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental precautions

Should not be released into the environment. See Section 12 for additional Ecological Information.

Methods and Material for Containment and Cleaning Up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Wear personal protective equipment/face protection. Do not breathe mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Conditions for Safe Storage, Including any Incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Flammables area.

Specific End Uses

Use in laboratories.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Component	CAS No	Korea	ACGIH TLV	OSHA PEL
Methyl alcohol	67-56-1	STEL: 250 ppm TWA: 200 ppm Skin	TWA: 200 ppm STEL: 250 ppm Skin	(Vacated) TWA: 200 ppm (Vacated) TWA: 260 mg/m ³ (Vacated) STEL: 250 ppm (Vacated) STEL: 325 mg/m ³ Skin TWA: 200 ppm TWA: 260 mg/m ³

Component	CAS No	European Union	The United Kingdom	Germany
Methyl alcohol	67-56-1	TWA: 200 ppm 8 hr TWA: 260 mg/m ³ 8 hr Skin	WEL - TWA: 200 ppm TWA; 266 mg/m ³ TWA WEL - STEL: 250 ppm STEL; 333 mg/m ³ STEL	100 ppm TWA MAK; 130 mg/m ³ TWA MAKSkin absorber

SAFETY DATA SHEET

Methanol

Revision Date 25-Jun-2025

ACGIH - Biological Exposure Indices

Component	CAS No	ACGIH - Biological Exposure Indices
Methyl alcohol	67-56-1	15 mg/L Medium: urine Time: end of shift Determinant: Methanol

Exposure Controls

Engineering Measures

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection	Tight sealing safety goggles
Hand Protection	Protective gloves
Skin and body protection	Long sleeved clothing

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatibility, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Personal protective equipment	Use only those certified by the Korea Occupational Safety and Health Administration.
Respiratory Protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators
Recommended Filter type:	low boiling organic solvent Type AX Brown conforming to EN371 To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly When RPE is used a face piece Fit Test should be conducted

Hygiene Measures	When using do not eat, drink or smoke Provide regular cleaning of equipment, work area and clothing
-------------------------	---

Environmental exposure controls	No information available
--	--------------------------

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance (Physical State, Color, etc.)	Colorless Liquid
Odor	Alcohol-like
Odor Threshold	No data available
pH	No information available

Melting Point/Range	-98 °C / -144.4 °F	
Softening Point	No data available	
Boiling Point/Range	64.7 °C / 148.5 °F	@ 760 mmHg

SAFETY DATA SHEET

Methanol

Revision Date 25-Jun-2025

Flash Point	10 °C / 50 °F	Method - CC (closed cup) Abel-Pensky (DIN 51755) Directive 84/449/EEC, A.9
Evaporation Rate	5.2 (ether = 1)	
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	Lower 6 vol% Upper 31 vol%	
Vapor Pressure	128 hPa @ 20 °C	
Vapor Density	1.11	(Air = 1.0)
Specific Gravity / Density	0.791	
Bulk Density	Not applicable	Liquid
Water Solubility	Miscible	
Solubility in other solvents	No information available	

Partition Coefficient (n-octanol/water)

Component	CAS No	log Pow
Methyl alcohol	67-56-1	-0.74

Autoignition Temperature	455 °C / 851 °F	
Decomposition Temperature	No data available	
Viscosity	0.55 cP at 20 °C	
Explosive Properties	Not explosive	Vapors may form explosive mixtures with air
Oxidizing Properties	No information available	
Molecular Formula	C H4 O	
Molecular Weight	32.04	
VOC Content(%)	100	
Surface tension	0.02255 N/m @ 20°C	

SECTION 10: STABILITY AND REACTIVITY

Reactivity None known, based on information available

Chemical Stability Stable under normal conditions.

Possibility of Hazardous Reactions

Hazardous Polymerization Hazardous Reactions Hazardous polymerization does not occur.
None under normal processing.

Conditions to Avoid Incompatible products. Heat, flames and sparks. Keep away from open flames, hot surfaces and sources of ignition.

Incompatible Materials Strong oxidizing agents. Strong acids. Acid anhydrides. Acid chlorides. Strong bases. Metals. Peroxides.

Hazardous Decomposition Products

SAFETY DATA SHEET

Methanol

Revision Date 25-Jun-2025

Carbon monoxide (CO). Formaldehyde.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

Information on expected route of exposure

Inhalation Avoid breathing vapors or mists. Harmful by inhalation.
Ingestion May be harmful if swallowed.
Eyes Avoid contact with eyes.
Skin Avoid contact with skin. Prolonged skin contact may defat the skin and produce dermatitis. Harmful in contact with skin.

Information on Health Hazards

Methanol is more toxic to humans and primates than to most experimental animals, due to differences in how it is metabolized. Non-primates do not appear to experience the acidosis or vision effects observed in humans and primates. Methanol can cause very serious irreversible effects in man by inhalation at > 0.5 mg/l/4 hour, or in contact with skin at >3.5 g/70 kg man, or by swallowing at > 1.75 g/70 kg man. Oxidation by alcohol dehydrogenase with the formation of formaldehyde and formic acid takes place mainly in the liver and kidneys. The metabolites are excreted in the urine and further metabolised to carbon dioxide and exhaled by the lungs. These metabolites are responsible for the toxic effects.

(a) acute toxicity;

Oral Category 3
Dermal Category 3
Inhalation Category 3

Component	CAS No	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methyl alcohol	67-56-1	LD50 = 1187 – 2769 mg/kg (Rat)	LD50 = 17100 mg/kg (Rabbit)	LC50 = 128.2 mg/L (Rat) 4 h

(b) skin corrosion/irritation; No data available

(c) serious eye damage/irritation; No data available

(d) respiratory or skin sensitization;

Respiratory No data available
Skin No data available

Component	CAS No	Test method	Test species	Study result
Methyl alcohol	67-56-1	OECD Test Guideline 406 Guinea Pig Maximisation Test (GPMT)	guinea pig	non-sensitising

(e) germ cell mutagenicity; No data available

Component	CAS No	Test method	Test species	Study result
Methyl alcohol	67-56-1	No data available	No data available	No data available

(f) carcinogenicity; No data available

Component	CAS No	Test method	Test species / Duration	Study result
-----------	--------	-------------	-------------------------	--------------

SAFETY DATA SHEET

Methanol

Revision Date 25-Jun-2025

Methyl alcohol	67-56-1	No data available	No data available	No data available
----------------	---------	-------------------	-------------------	-------------------

There are no known carcinogenic chemicals in this product

Component	CAS No	IARC	NTP	ACGIH	OSHA	UK
Methyl alcohol	67-56-1	Not listed	Not listed	Not listed	Not listed	Not listed

(g) reproductive toxicity; No data available

Component	CAS No	Test method	Test species / Duration	Study result
Methyl alcohol	67-56-1	OECD Test Guideline 416	Rat / Inhalation 2 Generation	NOAEC = 1.3 mg/l (air)

Developmental Effects Component substance is listed on California Proposition 65 as a developmental hazard.

(h) STOT-single exposure;
Results / Target organs Category 1
Optic nerve, Central nervous system (CNS).

(i) STOT-repeated exposure;
Target Organs No data available
None known.

(j) aspiration hazard; No data available

Other Adverse Effects

May cause blindness. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Component	CAS No	EU - Endocrine Disruptors Candidate List	EU - Endocrine Disruptors - Evaluated Substances	Japan - Endocrine Disruptor Information
Methyl alcohol	67-56-1	Not applicable	Not applicable	Not applicable

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity effects

Component	CAS No	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Methyl alcohol	67-56-1	Pimephales promelas: LC50 > 10000 mg/L 96h	EC50 > 10000 mg/L 24h	No data available	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min

Persistence and degradability Readily biodegradable
Persistence Persistence is unlikely, based on information available.

Component	Degradability
Methyl alcohol 67-56-1 (99 - 100)	DT50 ~ 17.2d >94% after 20d

Bioaccumulative potential Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Methyl alcohol	-0.74	<10 dimensionless

Mobility in soil The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces Will likely be mobile in the environment due to its volatility. Disperses rapidly in

SAFETY DATA SHEET

Methanol

Revision Date 25-Jun-2025

air.

Surface tension

0.02255 N/m @ 20°C

Ozone Depletion Potential

Component	CAS No	Ozone Depletion Potential
Methyl alcohol	67-56-1	Not listed

Other adverse effects

No information available

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose in accordance with the Wastes Control Act (폐기물관리법).

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

Other Information

Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with local regulations.

SECTION 14: TRANSPORT INFORMATION

Road and Rail Transport

UN-No UN1230
Proper Shipping Name METHANOL
Hazard Class 3
Subsidiary Hazard Class 6.1
Packing Group II

IATA

UN-No UN1230
Proper Shipping Name METHANOL
Hazard Class 3
Subsidiary Hazard Class 6.1
Packing Group II

IMDG/IMO

UN-No UN1230
Proper Shipping Name METHANOL
Hazard Class 3
Subsidiary Hazard Class 6.1
Packing Group II
Marine Pollutant No hazards identified

Special Precautions for User

No special precautions required

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Legend: X - Listed '-' - Not Listed

SAFETY DATA SHEET

Methanol

Revision Date 25-Jun-2025

International Inventories

Component	CAS No	KECL	TSCA	EINECS	IECSC	DSL	NDSL	PICCS	ENCS	ISHL	AICS
Methyl alcohol	67-56-1	KE-23193	X	200-659-6	X	X	-	X	X	X	X

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements	Rotterdam Convention (PIC)	Basel Convention (Hazardous Waste)
Methyl alcohol	67-56-1	500 tonne	5000 tonne	Not applicable	Not applicable

Component	CAS No	OECD HPV	Persistent Organic Pollutant	Ozone Depletion Potential
Methyl alcohol	67-56-1	Listed	Not applicable	Not applicable

Korean National Regulations

Component	CAS No	Act on Registration and Evaluation of Chemical Substances (K-REACH)	Authorised Chemicals	Existing Substances Subject to Registration
Methyl alcohol	67-56-1	Annex 1 - KE-23193	Not applicable	Listed

Component	CAS No	Chemical Control Act - Toxic Chemicals	Chemical Control Act - Prohibited Chemicals	Chemical Control Act - Use Restricted Chemicals
Methyl alcohol	67-56-1	1997-1-0080 (>10%)	Not applicable	Not applicable

Component	CAS No	Chemical Control Act - Accident Precaution Chemicals (% in mixtures)	Chemical Control Act - Accident Precaution Chemicals - Quantity limits Storage (% in mixtures)	Chemical Control Act - Accident Precaution Chemicals - Quantity limits Manufacture/Use (% in mixtures)
Methyl alcohol	67-56-1	>85%	200000 kg/yr	1500000 kg/yr

Component	CAS No	Waste Control Law	Ministry of Environment - CMR risk	Ministry of Environment - Critically Controlled Substance
Methyl alcohol	67-56-1	> 10% (CCA)	Not applicable	Not applicable

CCA = Chemical Control Act

Component	CAS No	ISHA - Harmful Agents Subject to Work Environment Monitoring	ISHA - Prohibited substances	ISHA - Substances requiring permission
Methyl alcohol	67-56-1	Listed	Not applicable	Not applicable

Component	CAS No	ISHA - Substances subject to control	ISHA - Harmful Agents Requiring Health Examination	ISHA - Permissible Exposure Limits
Methyl alcohol	67-56-1	Listed	Listed	200 ppm TWA 250 ppm STEL

Component	CAS No	ISHA - Subject to Process Safety Reports (minimum quantity)	ISHA - Threshold Limit Values (TLVs) Chemicals	ISHA - Special management materials
Methyl alcohol	67-56-1	5000 kg	STEL: 250 ppm TWA: 200 ppm Skin	Not applicable

National Fire Association - Dangerous Substances Minimum quantity requiring a permit

SAFETY DATA SHEET

Methanol

Revision Date 25-Jun-2025

Component	CAS No	Class 1 - Oxidising solids	Class 2 - Flammable solid	Class 3 - Spontaneously Combustible Substances and Dangerous Substances When Wet	Class 4 - Flammable liquids	Class 5 - Self-reactive substances	Class 6 - Oxidising liquids
Methyl alcohol	67-56-1	Not applicable	Not applicable	Not applicable	3. Alcohol 400 L	Not applicable	Not applicable

Control Parameters

Component	CAS No	Korea	ACGIH - Biological Exposure Indices
Methyl alcohol	67-56-1	STEL: 250 ppm TWA: 200 ppm Skin	15 mg/L Medium: urine Time: end of shift Determinant: Methanol

US Management Information

OSHA - Occupational Safety and Health Administration

Not applicable

Component	CAS No	Specifically Regulated Chemicals	Highly Hazardous Chemicals
Methyl alcohol	67-56-1	Not applicable	Not applicable

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355)

Component	CAS No	CERCLA Extremely Hazardous Substances RQs	Hazardous Substances RQs	SARA 313 - Threshold Values %
Methyl alcohol	67-56-1	Not applicable	5000 lb	1.0 %

GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

Danger.

H225 - Highly flammable liquid and vapor. H301 + H311 + H331 - Toxic if swallowed, in contact with skin or if inhaled. H370 - Causes damage to organs: Optic nerve, Central nervous system (CNS).

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P240 - Ground and bond container and receiving equipment. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P302 + P350 - IF ON SKIN: Gently wash with plenty of soap and water. P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

SECTION 16: OTHER INFORMATION

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

ALFAAC32695

SAFETY DATA SHEET

Methanol

Revision Date 25-Jun-2025

POW - Partition coefficient Octanol:Water

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Prepared By

Health, Safety and Environmental Department

Creation Date

27-Apr-2009

Revision Date

25-Jun-2025

Revision Number

7

Revision Summary

SDS sections updated.

MOEL's Public Notice No. 2023-9 (Standards for Classification and Labeling of Chemical Substances and Safety Data Sheets)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet