

Australian statement of hazardous nature : Classified as hazardous according to criteria of Safe Work Australia

Section 1 - Identification

Product Name Butan-1-ol

CAS No 71-36-3

Synonyms n-Butanol; n-Butyl alcohol, Butan-1-ol

Product Code **B/4800/MC15, B/4800/PB17, B/4800/08, B/4800/15, B/**

Address ThermoFisher Scientific Australia Pty Ltd
5 Caribbean Drive, Scoresby
VICTORIA 3179, Australia

Emergency Tel. **CHEMTREC®**
03 9757 4559 or +613 9757 4559

Telephone / Fax Numbers Tel: 1300 735 292
Fax: 1800 067 639

E-mail address ANZinfo@thermofisher.com

Recommended Use Laboratory chemicals.

Uses advised against This product does not contain any substance(s) on the Illicit Drug Precursors/Reagents list. This product does not contain any substance(s) subject to Prohibition, Authorization or Restriction. This product does not contain any substance(s) listed on the voluntary National Code of Practice for Chemicals of Security Concern.

Section 2 - Hazard(s) Identification

Classification under Safe Work Australia

Classified as hazardous according to criteria of Safe Work Australia

Physical hazards

Flammable liquids

Category 3

Health hazards

Acute Oral Toxicity
Skin Corrosion/Irritation
Serious Eye Damage/Eye Irritation
Specific target organ toxicity - (single exposure)

Category 4
Category 2
Category 1
Category 3

Environmental hazards

No hazards identified

Label Elements



Flame



Exclamation Mark



Corrosion

Signal Word**Danger****Hazard Statements**

H226 - Flammable liquid and vapor
 H302 - Harmful if swallowed
 H315 - Causes skin irritation
 H318 - Causes serious eye damage
 H335 - May cause respiratory irritation
 H336 - May cause drowsiness or dizziness

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
 P233 - Keep container tightly closed
 P240 - Ground and bond container and receiving equipment
 P241 - Use explosion-proof electrical/ ventilating/ lighting equipment
 P242 - Use non-sparking tools
 P243 - Take action to prevent static discharges
 P264 - Wash face, hands and any exposed skin thoroughly after handling
 P270 - Do not eat, drink or smoke when using this product
 P271 - Use only outdoors or in a well-ventilated area
 P280 - Wear protective gloves/protective clothing/eye protection/face protection
 P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
 P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
 P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 P310 - Immediately call a POISON CENTER or doctor
 P330 - Rinse mouth
 P363 - Wash contaminated clothing before reuse
 P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish
 P403 + P233 - Store in a well-ventilated place. Keep container tightly closed
 P501 - Dispose of contents/ container to an approved waste disposal plant

Other information

Toxic to terrestrial vertebrates

Section 3 - Composition and Information on Ingredients

Component	CAS No	Weight %
n-Butyl alcohol	71-36-3	99

Section 4 - First Aid Measures

Inhalation

Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur.

Ingestion

Clean mouth with water and drink afterwards plenty of water.

Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
General Advice	If symptoms persist, call a physician.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.
First Aid Facilities	Eyewash, safety shower and washroom.
Most important symptoms and effects	Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting
Notes to Physician	Treat symptomatically. Symptoms may be delayed.

Section 5 - Fire Fighting Measures

Suitable Extinguishing Media

Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam.

Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

Hazardous Decomposition Products

Carbon monoxide (CO), Carbon dioxide (CO₂).

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition.

Special protective equipment and precautions for fire fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6 - Accidental Release Measures

Emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation.

Environmental Precautions

Should not be released into the environment.

Methods for Containment and Clean Up

Clean-up methods - small spillage

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal.

Clean-up methods - large spillage

Typically only supplied in small quantities as packaged goods.

If extremely toxic or used in larger quantities ensure a spillage action plan is in place. Evacuate area. Control the source and/or contain the spill if safe and able to do so. Use temporary diking, sand bags, dry sand, earth or proprietary booms/absorbent pads if available. Obtain advice on containment, neutralisation and clean-up from local emergency responders.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

Section 7 - Handling and Storage

Precautions for Safe Handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation.

Conditions for Safe Storage, Including any Incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area.

AS/NZS 2243.10:2004, Safety in laboratories - Storage of chemicals

AS 1940-2004 - The storage and handling of flammable and combustible liquids

Section 8 - Exposure Controls and Personal Protection

Exposure limits

ACGIH - Threshold Limit Values - Ceiling (TLV-C) guidelines by the American Conference of Governmental Industrial Hygienists (ACGIH) for controlling worker exposure to airborne chemical concentrations in the workplace. **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **DE** - MAK and BAT values of Hazardous Chemical Compounds in the Work Area. Published by German Research Foundation on July 1, 2011

Component	Australia	New Zealand WEL	ACGIH TLV	The United Kingdom	Germany
n-Butyl alcohol		Ceiling: 50 ppm Ceiling: 150 mg/m ³ Skin	TWA: 20 ppm	50ppm STEL; 154mg/m ³ STEL	100ppm TWA; 310mg/m ³ TWA

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Component	Australia	New Zealand	European Union	United Kingdom	Germany
n-Butyl alcohol					1-Butanol (after hydrolysis): 10 mg/g Creatinine urine (end of shift) 1-Butanol (after hydrolysis): 2 mg/g Creatinine urine (before beginning of next shift)

Exposure Controls

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles (Australian/New Zealand Standard AS/NZS 1337 - Eye protectors for Industrial applications)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	AUS/NZ Standard	Glove comments
Butyl rubber	> 480 minutes	0.35 mm	AS/NZS 2161	As tested under EN374-3 Determination of Resistance to Permeation by Chemicals
Nitrile rubber	> 480 minutes	0.38 mm		
Neoprene	> 480 minutes	0.45 mm		
Viton (R)	> 480 minutes	0.7 mm		

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves.
(Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatibility, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Skin and body protection	Long sleeved clothing
Respiratory Protection	Use an AS/NZS 1716 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained in line with AS/NZS 1715 on the use and maintenance of respiratory protective devices
Recommended Filter type:	Organic gases and vapours filter Type A Brown conforming to EN14387 (or AUS/NZ equivalent)
Recommended half mask:-	Valve filtering: EN405 or Half mask: EN140 plus filter, EN 141 (or AUS/NZ equivalent) When RPE is used a face piece Fit Test should be conducted

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

Environmental exposure controls No information available.

Section 9 - Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance	Colorless	
Physical State	Liquid	
Odor	Alcohol-like	
Odor Threshold	No data available	
pH	No information available	
Melting Point/Range	-89 °C / -128.2 °F	
Softening Point	No data available	
Boiling Point/Range	117.6 °C / 243.7 °F	
Flash Point	35 °C / 95 °F	Method - CC (closed cup)
Evaporation Rate	0.46	(Butyl Acetate = 1.0)
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	Lower 1.4 Vol% Upper 11.2 Vol%	
Vapor Pressure	6.7 mbar @ 20 °C	
Vapor Density	2.6	(Air = 1.0)
Specific Gravity / Density	0.810	
Bulk Density	Not applicable	Liquid
Water Solubility	80 g/L (20°C)	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
n-Butyl alcohol	1	
Autoignition Temperature	340 °C / 644 °F	
Decomposition Temperature	No data available	
Viscosity	2.95 mPa.s (20 °C)	
Explosive Properties		explosive air/vapour mixtures possible
Oxidizing Properties	No information available	
Other information		
Molecular Formula	C4 H10 O	
Molecular Weight	74.12	
Refractive index	1.390 - 1.400	

Section 10 - Stability and Reactivity

Reactivity	None known, based on information available
Stability	Stable under normal conditions.
Conditions to Avoid	Keep away from open flames, hot surfaces and sources of ignition, Incompatible products.
Incompatible Materials	Strong oxidizing agents, Reducing Agent, Acid chlorides, copper, Copper alloys, Acid anhydrides.
Hazardous Decomposition Products	Carbon monoxide (CO). Carbon dioxide (CO ₂).
Hazardous Polymerization	Hazardous polymerization does not occur.

Section 11 - Toxicological Information

Information on Toxicological Effects

Product Information

(a) acute toxicity;	
Oral	Category 4
Dermal	Based on available data, the classification criteria are not met
Inhalation	Based on available data, the classification criteria are not met

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
n-Butyl alcohol	LD50 = 700 mg/kg (Rat)	LD50 = 3402 mg/kg (Rabbit)	LC50 > 8000 ppm (Rat) 4 h

(b) skin corrosion/irritation;	Category 2
(c) serious eye damage/irritation;	Category 1
(d) respiratory or skin sensitization;	
Respiratory	Based on available data, the classification criteria are not met
Skin	Based on available data, the classification criteria are not met
(e) germ cell mutagenicity;	Based on available data, the classification criteria are not met
(f) carcinogenicity;	Based on available data, the classification criteria are not met There are no known carcinogenic chemicals in this product
(g) reproductive toxicity;	Based on available data, the classification criteria are not met
(h) STOT-single exposure;	Category 3
Results / Target organs	Respiratory system Central nervous system (CNS)
(i) STOT-repeated exposure;	Based on available data, the classification criteria are not met
Target Organs	None known.
(j) aspiration hazard;	Based on available data, the classification criteria are not met

Symptoms / effects, both acute and delayed Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting delayed

Section 12 - Ecological Information

Ecotoxicity effects

Do not flush into surface water or sanitary sewer system.

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
n-Butyl alcohol	LC50: 1376 mg/L, 96h (Pimephales promelas) OECD Guideline 203 : 100000 - 500000 µg/L, 96h static (Lepomis macrochirus) LC50: = 1740 mg/L, 96h flow-through (Pimephales promelas) LC50: = 1910000 µg/L, 96h static (Pimephales promelas) LC50: 1730 - 1910 mg/L, 96h static (Pimephales promelas)	EC50: 1328 mg/L, 48h (Daphnia magna) OECD Guideline 202 EC50: 1897 - 2072 mg/L, 48h Static (Daphnia magna) EC50: = 1983 mg/L, 48h (Daphnia magna)	EC50: 225 mg/L, 96h (Pseudokirchneriella subcapitata) OECD Guideline 201 EC50: > 500 mg/L, 72h (Desmodesmus subspicatus) EC50: > 500 mg/L, 96h (Desmodesmus subspicatus)	EC50 = 2041.4 mg/L 5 min EC50 = 2186 mg/L 30 min EC50 = 3980 mg/L 24 h EC50 = 4400 mg/L 17 h

Persistence and Degradability

Persistence

Soluble in water, Persistence is unlikely, based on information available.

Component	Degradability
n-Butyl alcohol 71-36-3 (99)	70 %

Bioaccumulative Potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
n-Butyl alcohol	1	0.64 dimensionless

Mobility

The product is water soluble, and may spread in water systems. : Will likely be mobile in the environment due to its water solubility Highly mobile in soils

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

Persistent Organic Pollutant

This product does not contain any known or suspected substance

Ozone Depletion Potential

This product does not contain any known or suspected substance

Section 13 - Disposal Considerations

Waste from Residues/Unused Products

Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with all federal, E.P.A., state and local regulations. Assure conformity with all applicable regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

Other Information

Chemical wastes should be disposed through a licensed commercial waste collection service. Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains.

Section 14 - Transport Information

IMDG/IMO

UN-No	UN1120
Proper Shipping Name	BUTANOLS
Hazard Class	3

Packing Group III

ADG

UN-No UN1120
 Proper Shipping Name BUTANOLS
 Hazard Class 3
 Packing Group III

IATA

UN-No UN1120
 Proper Shipping Name BUTANOLS
 Hazard Class 3
 Packing Group III

Environmental hazards No hazards identified

Special Precautions No special precautions required

Additional information None known

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National Regulations Australia

See section 8 for national exposure control parameters.

Standard for the Uniform Scheduling of Medicines and Poisons

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons.

Component	Standard for the Uniform Scheduling of Medicines and Poisons
n-Butyl alcohol - 71-36-3	Schedule 5 listed - in preparations except: for preparations containing ≤5% of n-Butyl alcohol, or in preparations for cosmetic or therapeutic use other than spray form Schedule 6 listed - except: when included in Schedule 5, in preparations containing ≤5% of n-Butyl alcohol, or in preparations for cosmetic or therapeutic use other than in spray form

Australian Industrial Chemicals Introduction Scheme (AICIS)

Component	Australian Industrial Chemicals Introduction Scheme (AICIS)	Additional information
n-Butyl alcohol - 71-36-3	Present	-

Australian - Illicit Drug Precursors/Reagents Substance List

This product does not contain any substance(s) on the Illicit Drug Precursors/Reagents list.

Chemicals of Security Concern

This product does not contain any substance(s) listed on the voluntary National Code of Practice for Chemicals of Security Concern

National pollutant inventory Not applicable

Prohibition or notification/licensing requirements

Shown below are details of specific prohibition/notifications or licensing requirements when they apply.

This product does not contain any substance(s) subject to Prohibition, Authorization or Restriction.

International Inventories

Component	AICS	NZIoC	EINECS	ELINCS	TSCA	DSL	NDSL	PICCS	ENCS	ISHL	IECSC	KECL
n-Butyl alcohol	X	X	200-751-6	-	X	X	-	X	X	X	X	KE-03867

Legend: X - Listed. '-' - Not Listed. **KECL** - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

International Regulations

Ozone Depletion Potential This product does not contain any known or suspected substance

Persistent Organic Pollutant This product does not contain any known or suspected substance

Rotterdam Convention (PIC) Not applicable

Basel convention on the control of transboundary movements of hazardous wastes and their disposal

Not applicable.

Component	CAS No	OECD HPV	Restriction of Hazardous Substances (RoHS)	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
n-Butyl alcohol	71-36-3	Listed	Not applicable	Not applicable	Not applicable

Authorisation/Restrictions according to EU REACH

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
n-Butyl alcohol	-	Use restricted. See item 75. (see link for restriction details)	-

<https://echa.europa.eu/substances-restricted-under-reach>

Section 16 - Other Information**Legend**

AICS - Australian Inventory of Chemical Substances
TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
IECSC - Chinese Inventory of Existing Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
TWA - Time Weighted Average

NZIoC - New Zealand Inventory of Chemicals
EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
ENCS - Japanese Existing and New Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
CAS - Chemical Abstracts Service
ACGIH - American Conference of Governmental Industrial Hygienists

IARC - International Agency for Research on Cancer	Predicted No Effect Concentration (PNEC)
ICAO/IATA - International Civil Aviation Organization/International Air Transport Association	IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code
MARPOL - International Convention for the Prevention of Pollution from Ships	ADG Australian Code for the Transport of Dangerous Goods by Road and Rail
NZS 5433:2012 - Transport of Dangerous Goods on Land	OECD - Organisation for Economic Co-operation and Development
LD50 - Lethal Dose 50%	LC50 - Lethal Concentration 50%
EC50 - Effective Concentration 50%	ATE - Acute Toxicity Estimate
WEL - Workplace Exposure Limit	RPE - Respiratory Protective Equipment
DNEL - Derived No Effect Level	NOEC - No Observed Effect Concentration
POW - Partition coefficient Octanol:Water	BCF - Bioconcentration factor
vPvB - very Persistent, very Bioaccumulative	PBT - Persistent, Bioaccumulative, Toxic
VOC - (Volatile Organic Compound)	

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>
Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Chemical incident response training.

Revision Date	18-Nov-2022
Revision Summary	Not applicable.

This Safety Data Sheet (SDS) is prepared in accordance to and complies with the requirements of Safe Work Australia - Work Health and Safety Regulations (WHS Regulations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet