

Creation Date 11-Jun-2009

Revision Date 06-Dec-2024

Revision Number 15

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description:	<u>Tetrahydrofuran</u>
Cat No. :	T/0713/15
Synonyms	THF
Index No	603-025-00-0
CAS No	109-99-9
EC No	203-726-8
Molecular Formula	C ₄ H ₈ O
REACH registration number	01-2119444314-46

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use	Laboratory chemicals.
Sector of use	SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites
Product category	PC21 - Laboratory chemicals
Process categories	PROC15 - Use as a laboratory reagent
Environmental release category	ERC6a - Industrial use resulting in manufacture of another substance (use of intermediates)
Uses advised against	No Information available

1.3. Details of the supplier of the safety data sheet

Company

EU entity/business name

Thermo Fisher Scientific
Janssen Pharmaceuticaaan 3a
2440 Geel, Belgium

UK entity/business name

Fisher Scientific UK
Bishop Meadow Road, Loughborough,
Leicestershire LE11 5RG, United Kingdom

Swiss distributor - Fisher Scientific AG

Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
e-mail - infoch@thermofisher.com

E-mail address

begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

Tel: 01509 231166
Chemtrec US: (800) 424-9300
Chemtrec EU: 001-703-527-3887

For customers in Switzerland:

Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

SAFETY DATA SHEET

Tetrahydrofuran

Revision Date 06-Dec-2024

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Flammable liquids

Category 2 (H225)

Health hazards

Acute oral toxicity

Category 4 (H302)

Serious Eye Damage/Eye Irritation

Category 2 (H319)

Carcinogenicity

Category 2 (H351)

Specific target organ toxicity - (single exposure)

Category 3 (H335) (H336)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H302 - Harmful if swallowed

H319 - Causes serious eye irritation

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness

H351 - Suspected of causing cancer

EUH019 - May form explosive peroxides

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301 + P330 + P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P312 - Call a POISON CENTER or doctor if you feel unwell

SAFETY DATA SHEET

Tetrahydrofuran

Revision Date 06-Dec-2024

2.3. Other hazards

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)
Toxic to terrestrial vertebrates
Contains a known or suspected endocrine disruptor
Contains a substance on the National Authorities Endocrine Disruptor Lists

Section 3: Composition/information on ingredients

3.1. Substances

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Tetrahydrofuran	109-99-9	203-726-8	>95	Flam. Liq. 2 (H225) Acute Tox. 4 (H302) Eye Irrit. 2 (H319) STOT SE 3 (H335) STOT SE 3 (H336) Carc. 2 (H351) (EUH019)
Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl-	128-37-0	EEC No. 204-881-4	0.025	Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Tetrahydrofuran	Acute Tox. 4 :: C>82.5% Eye Irrit. 2 :: C>=25% STOT SE 3 :: C>=25%	-	-
Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl-	-	1	-

REACH registration number	01-2119444314-46
---------------------------	------------------

Full text of Hazard Statements: see section 16

Section 4: First aid measures

4.1. Description of first aid measures

General Advice	If symptoms persist, call a physician.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Get medical attention immediately if symptoms occur.
Ingestion	Do NOT induce vomiting. Call a physician or poison control center immediately.
Inhalation	Remove to fresh air. If breathing is difficult, give oxygen. Get medical attention.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Causes central nervous system depression

SAFETY DATA SHEET

Tetrahydrofuran

Revision Date 06-Dec-2024

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically. Symptoms may be delayed.

Section 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media

Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. May form explosive peroxides.

Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO₂), peroxides.

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges. Avoid contact with skin and eyes. Keep people away from and upwind of spill/leak.

6.2. Environmental precautions

Should not be released into the environment.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

Section 7: Handling and storage

7.1. Precautions for safe handling

Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Wear personal protective equipment/face protection. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. If peroxide formation is suspected, do not open or move container. Handle under an inert atmosphere.

SAFETY DATA SHEET

Tetrahydrofuran

Revision Date 06-Dec-2024

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Store under an inert atmosphere. Shelf life 30 months (Unopened) or Shelf life: 6 months after opening. Containers should be dated when opened. May form explosive peroxides on prolonged storage. Should crystals form in a peroxidizable liquid, peroxidation may have occurred and the product should be considered extremely dangerous. In this instance, the container should only be opened remotely by professionals. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area.

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Class 3

Switzerland - Storage of hazardous substances

Storage class - SC 3

<https://www.kvu.ch/de/themen/stoffe-und-produkte>

<https://www.kvu.ch/fr/themes/substances-et-produits>

<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

Section 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Tetrahydrofuran	TWA: 50 ppm (8h) TWA: 150 mg/m ³ (8h) STEL: 100 ppm (15min) STEL: 300 mg/m ³ (15min) Skin	STEL: 100 ppm 15 min STEL: 300 mg/m ³ 15 min TWA: 50 ppm 8 hr TWA: 150 mg/m ³ 8 hr Skin	TWA / VME: 50 ppm (8 heures). restrictive limit TWA / VME: 150 mg/m ³ (8 heures). restrictive limit STEL / VLCT: 100 ppm. restrictive limit STEL / VLCT: 300 mg/m ³ . restrictive limit Peau	TWA: 50 ppm 8 uren TWA: 150 mg/m ³ 8 uren STEL: 100 ppm 15 minuten STEL: 300 mg/m ³ 15 minuten Huid	STEL / VLA-EC: 100 ppm (15 minutos). STEL / VLA-EC: 300 mg/m ³ (15 minutos). TWA / VLA-ED: 50 ppm (8 horas) TWA / VLA-ED: 150 mg/m ³ (8 horas) Piel
Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl-		STEL: 30 mg/m ³ 15 min TWA: 10 mg/m ³ 8 hr	TWA / VME: 10 mg/m ³ (8 heures).	TWA: 2 mg/m ³ 8 uren	TWA / VLA-ED: 10 mg/m ³ (8 horas)

Component	Italy	Germany	Portugal	The Netherlands	Finland
Tetrahydrofuran	TWA: 50 ppm 8 ore. Time Weighted Average TWA: 150 mg/m ³ 8 ore. Time Weighted Average STEL: 100 ppm 15 minuti. Short-term STEL: 300 mg/m ³ 15 minuti. Short-term Pelle	TWA: 50 ppm (8 Stunden). AGW - exposure factor 2 TWA: 150 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 20 ppm (8 Stunden). MAK TWA: 60 mg/m ³ (8 Stunden). MAK	STEL: 100 ppm 15 minutos STEL: 300 mg/m ³ 15 minutos TWA: 50 ppm 8 horas TWA: 150 mg/m ³ 8 horas Pele	huid STEL: 200 ppm 15 minuten STEL: 600 mg/m ³ 15 minuten TWA: 100 ppm 8 uren TWA: 300 mg/m ³ 8 uren	TWA: 50 ppm 8 tunteina TWA: 150 mg/m ³ 8 tunteina STEL: 100 ppm 15 minuutteina STEL: 300 mg/m ³ 15 minuutteina Iho

SAFETY DATA SHEET

Tetrahydrofuran

Revision Date 06-Dec-2024

		Höhepunkt: 40 ppm Höhepunkt: 120 mg/m ³ Haut			
Phenol, 2,6-bis(1,1-dimethyle thyl)-4-methyl-		TWA: 10 mg/m ³ (8 Stunden). AGW - exposure factor 4 TWA: 10 mg/m ³ (8 Stunden). MAK can occur as vapor and aerosol at the same time Höhepunkt: 40 mg/m ³	TWA: 2 mg/m ³ 8 horas		TWA: 10 mg/m ³ 8 tunteina STEL: 20 mg/m ³ 15 minuutteina

Component	Austria	Denmark	Switzerland	Poland	Norway
Tetrahydrofuran	Haut MAK-KZGW: 100 ppm 15 Minuten MAK-KZGW: 300 mg/m ³ 15 Minuten MAK-TMW: 50 ppm 8 Stunden MAK-TMW: 150 mg/m ³ 8 Stunden	TWA: 50 ppm 8 timer TWA: 150 mg/m ³ 8 timer STEL: 300 mg/m ³ 15 minutter STEL: 100 ppm 15 minutter Hud	Haut/Peau STEL: 100 ppm 15 Minuten STEL: 300 mg/m ³ 15 Minuten TWA: 50 ppm 8 Stunden TWA: 150 mg/m ³ 8 Stunden	STEL: 300 mg/m ³ 15 minutach TWA: 150 mg/m ³ 8 godzinach	TWA: 50 ppm 8 timer TWA: 150 mg/m ³ 8 timer STEL: 75 ppm 15 minutter. value calculated STEL: 187.5 mg/m ³ 15 minutter. value calculated Hud
Phenol, 2,6-bis(1,1-dimethyle thyl)-4-methyl-	MAK-TMW: 10 mg/m ³ 8 Stunden	TWA: 10 mg/m ³ 8 timer STEL: 20 mg/m ³ 15 minutter	STEL: 40 mg/m ³ 15 Minuten TWA: 10 mg/m ³ 8 Stunden		

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Tetrahydrofuran	TWA: 50.0 ppm TWA: 150.0 mg/m ³ STEL : 100 ppm STEL : 300.0 mg/m ³ Skin notation	kože TWA-GVI: 50 ppm 8 satima. TWA-GVI: 150 mg/m ³ 8 satima. STEL-KGVI: 100 ppm 15 minutama. STEL-KGVI: 300 mg/m ³ 15 minutama.	TWA: 50 ppm 8 hr. TWA: 150 mg/m ³ 8 hr. STEL: 100 ppm 15 min STEL: 300 mg/m ³ 15 min Skin	Skin-potential for cutaneous absorption STEL: 100 ppm STEL: 300 mg/m ³ TWA: 50 ppm TWA: 150 mg/m ³	TWA: 150 mg/m ³ 8 hodinách. Potential for cutaneous absorption Ceiling: 300 mg/m ³
Phenol, 2,6-bis(1,1-dimethyle thyl)-4-methyl-	TWA: 10 mg/m ³ STEL : 50 mg/m ³	TWA-GVI: 10 mg/m ³ 8 satima.	TWA: 2 mg/m ³ 8 hr. STEL: 6 mg/m ³ 15 min		

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Tetrahydrofuran	Nahk TWA: 50 ppm 8 tundides. TWA: 150 mg/m ³ 8 tundides. STEL: 100 ppm 15 minutites. STEL: 300 mg/m ³ 15 minutites.	Skin notation TWA: 50 ppm 8 hr TWA: 150 mg/m ³ 8 hr STEL: 100 ppm 15 min STEL: 300 mg/m ³ 15 min	STEL: 250 ppm STEL: 735 mg/m ³ TWA: 200 ppm TWA: 590 mg/m ³	STEL: 300 mg/m ³ 15 percekben. CK STEL: 100 ppm 15 percekben. CK TWA: 150 mg/m ³ 8 óraban. AK TWA: 50 ppm 8 óraban. AK lehetséges borön keresztüli felszívódás	STEL: 100 ppm STEL: 300 mg/m ³ TWA: 50 ppm 8 klukkustundum. TWA: 150 mg/m ³ 8 klukkustundum. Skin notation
Phenol, 2,6-bis(1,1-dimethyle thyl)-4-methyl-			TWA: 10 mg/m ³		TWA: 10 mg/m ³ 8 klukkustundum. Ceiling: 20 mg/m ³

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Tetrahydrofuran	skin - potential for cutaneous exposure STEL: 100 ppm STEL: 300 mg/m ³ TWA: 50 ppm TWA: 150 mg/m ³	TWA: 50 ppm IPRD TWA: 150 mg/m ³ IPRD Oda STEL: 100 ppm STEL: 300 mg/m ³	Possibility of significant uptake through the skin TWA: 50 ppm 8 Stunden TWA: 150 mg/m ³ 8 Stunden STEL: 100 ppm 15 Minuten STEL: 300 mg/m ³ 15 Minuten	possibility of significant uptake through the skin TWA: 50 ppm TWA: 150 mg/m ³ STEL: 100 ppm 15 minuti STEL: 300 mg/m ³ 15 minuti	Skin notation TWA: 50 ppm 8 ore TWA: 150 mg/m ³ 8 ore STEL: 100 ppm 15 minute STEL: 300 mg/m ³ 15 minute

SAFETY DATA SHEET

Tetrahydrofuran

Revision Date 06-Dec-2024

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Tetrahydrofuran	MAC: 100 mg/m ³	Ceiling: 300 mg/m ³ Potential for cutaneous absorption TWA: 50 ppm TWA: 150 mg/m ³	TWA: 50 ppm 8 urah TWA: 150 mg/m ³ 8 urah Koža STEL: 100 ppm 15 minutah STEL: 300 mg/m ³ 15 minutah	Binding STEL: 100 ppm 15 minuter Binding STEL: 300 mg/m ³ 15 minuter TLV: 50 ppm 8 timmar. NGV TLV: 150 mg/m ³ 8 timmar. NGV	Deri TWA: 50 ppm 8 saat TWA: 150 mg/m ³ 8 saat STEL: 100 ppm 15 dakika STEL: 300 mg/m ³ 15 dakika
Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl-			TWA: 10 mg/m ³ 8 urah inhalable fraction STEL: 40 mg/m ³ 15 minutah inhalable fraction		

Biological limit values

List source(s):

Component	European Union	United Kingdom	France	Spain	Germany
Tetrahydrofuran				Tetrahydrofuran: 2 mg/L urine end of shift	Tetrahydrofuran: 2 mg/L urine (end of shift)

Component	Gibraltar	Latvia	Slovak Republic	Luxembourg	Turkey
Tetrahydrofuran			Tetrahydrofuran: 2 mg/L urine end of exposure or work shift		

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Tetrahydrofuran 109-99-9 (>95)				DNEL = 12.6mg/kg bw/day
Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl- 128-37-0 (0.025)				DNEL = 0.5mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Tetrahydrofuran 109-99-9 (>95)	DNEL = 300mg/m ³	DNEL = 96mg/m ³	DNEL = 150mg/m ³	DNEL = 72.4mg/m ³
Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl- 128-37-0 (0.025)				DNEL = 3.5mg/m ³

SAFETY DATA SHEET

Tetrahydrofuran

Revision Date 06-Dec-2024

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Tetrahydrofuran 109-99-9 (>95)	PNEC = 4.32mg/L	PNEC = 23.3mg/kg sediment dw	PNEC = 21.6mg/L	PNEC = 4.6mg/L	PNEC = 2.13mg/kg soil dw
Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl-128-37-0 (0.025)	PNEC = 0.199µg/L	PNEC = 99.6µg/kg sediment dw	PNEC = 1.99µg/L	PNEC = 0.17mg/L	PNEC = 47.69µg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Tetrahydrofuran 109-99-9 (>95)	PNEC = 0.432mg/L	PNEC = 2.33mg/kg sediment dw		PNEC = 67mg/kg food	
Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl-128-37-0 (0.025)	PNEC = 0.0199µg/L	PNEC = 9.96µg/kg sediment dw		PNEC = 8.33mg/kg food	

8.2. Exposure controls

Engineering Measures

Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles (European standard - EN 166)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Butyl rubber	< 25 minutes	0.6 mm	Level 1 EN 374	Permeation rate 106 µg/cm ² /min As tested under EN374-3 Determination of Resistance to Permeation by Chemicals
Neoprene gloves	< 15 minutes	0.45 mm		

Skin and body protection

Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced
Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to EN14387

Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN

SAFETY DATA SHEET

Tetrahydrofuran

Revision Date 06-Dec-2024

141
When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls No information available.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance	Colorless	
Odor	Petroleum distillates	
Odor Threshold	No data available	
Melting Point/Range	-108.4 °C / -163.1 °F	
Softening Point	No data available	
Boiling Point/Range	66 °C / 150.8 °F	
Flammability (liquid)	Highly flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	Lower 1.5 vol% Upper 12 vol%	
Flash Point	-21 °C / -5.8 °F	Method - No information available
Autoignition Temperature	215 - °C / 419 - °F	
Decomposition Temperature	No data available	
pH	7-8	20% aq. solution
Viscosity	0.456 mPas @ 20°C Dynamic	
Water Solubility	Miscible	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Tetrahydrofuran	0.45	
Phenol,	5.1	
2,6-bis(1,1-dimethylethyl)-4-methyl-		
Vapor Pressure	170 mbar @ 20 °C	
Density / Specific Gravity	0.880	
Bulk Density	Not applicable	Liquid
Vapor Density	2.5 (Ether = 1.0)	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

Molecular Formula	C4 H8 O
Molecular Weight	72.11
Explosive Properties	Vapors may form explosive mixtures with air
Evaporation Rate	> 1 (Ether = 1.0) - (Butyl Acetate = 1.0)

Section 10: Stability and reactivity

10.1. Reactivity

Yes. May form explosive peroxides

10.2. Chemical stability

Stable under recommended storage conditions. Reacts with air to form peroxides. May form explosive peroxides on prolonged storage. Hygroscopic.

10.3. Possibility of hazardous reactions

SAFETY DATA SHEET

Tetrahydrofuran

Revision Date 06-Dec-2024

Hazardous Polymerization Hazardous Reactions

Hazardous polymerization may occur.
None under normal processing.

10.4. Conditions to avoid

Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition. Exposure to moist air or water.

10.5. Incompatible materials

Strong oxidizing agents. Acids.

10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO₂). peroxides.

Section 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral

Category 4

Dermal

Based on available data, the classification criteria are not met

Inhalation

Based on available data, the classification criteria are not met

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Tetrahydrofuran	1650 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	180 mg/L (Rat) 1 h 53.9 mg/L (Rat) 4 h
Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl-	> 6 g/kg (Rat)	> 2 g/kg (Rat)	-

(b) skin corrosion/irritation;

Based on available data, the classification criteria are not met

(c) serious eye damage/irritation;

Category 2

(d) respiratory or skin sensitization;

Respiratory

Based on available data, the classification criteria are not met

Skin

Based on available data, the classification criteria are not met

Component	Test method	Test species	Study result
Tetrahydrofuran 109-99-9 (>95)	Local Lymph Node Assay OECD Test Guideline 429	mouse	non-sensitising

(e) germ cell mutagenicity;

Based on available data, the classification criteria are not met

Component	Test method	Test species	Study result
Tetrahydrofuran 109-99-9 (>95)	OECD Test Guideline 476 Gene cell mutation	in vivo Mammalian	negative
	OECD Test Guideline 473 Chromosomal aberration assay	in vitro Mammalian	negative

(f) carcinogenicity;

Category 2

Limited evidence of a carcinogenic effect

Component	EU	UK	Germany	IARC
Tetrahydrofuran				Group 2B

SAFETY DATA SHEET

Tetrahydrofuran

Revision Date 06-Dec-2024

(g) reproductive toxicity; Based on available data, the classification criteria are not met

Component	Test method	Test species / Duration	Study result
Tetrahydrofuran 109-99-9 (>95)	OECD Test Guideline 416	Rat 2 Generation	NOAEL = 3,000 ppm

(h) STOT-single exposure; Category 3

Results / Target organs Respiratory system, Central nervous system (CNS).

(i) STOT-repeated exposure; Based on available data, the classification criteria are not met

Test method OECD Test No. 407
Test species / Duration Rat / 28 days
Study result NOAEL = 1,000 mg/l
Route of exposure Oral
Target Organs None known.

(j) aspiration hazard; Based on available data, the classification criteria are not met

Symptoms / effects, both acute and delayed Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Causes central nervous system depression.

11.2. Information on other hazards

Endocrine Disrupting Properties
Assess endocrine disrupting properties for human health

Contains a substance on the National Authorities Endocrine Disruptor Lists

Component	EU National Authorities Endocrine Disruptor Lists - Health
Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl-128-37-0 (0.025)	List II

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity effects

Do not empty into drains.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Tetrahydrofuran	2160 mg/l LC50 = 96 h Pimephales promelas Leuciscus idus: LC50: 2820 mg/L/48h	EC50 48 h 3485 mg/l EC50: >10000 mg/L/24h	
Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl-	LC50 = 0.199 mg/L 96h	EC50 >0.31 mg/L 48h	EC50 = 0.758 mg/L 96h EC50 = 6 mg/L 72 h

Component	Microtox	M-Factor
Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl-	EC50 = 7.82 mg/L 5 min EC50 = 8.57 mg/L 15 min EC50 = 8.98 mg/L 30 min	1

12.2. Persistence and degradability

Persistence

Degradation in sewage treatment plant

Product is biodegradable

Persistence is unlikely, based on information available.

Contains no substances known to be hazardous to the environment or not degradable in waste water treatment plants.

SAFETY DATA SHEET

Tetrahydrofuran

Revision Date 06-Dec-2024

12.3. Bioaccumulative potential Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Tetrahydrofuran	0.45	No data available
Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl-	5.1	230 - 2500 dimensionless

12.4. Mobility in soil The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in air.

12.5. Results of PBT and vPvB assessment Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB).

12.6. Endocrine disrupting properties

Endocrine Disruptor Information

Component	EU - Endocrine Disruptors Candidate List	EU - Endocrine Disruptors - Evaluated Substances
Tetrahydrofuran	Group III Chemical	

12.7. Other adverse effects

Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance.
This product does not contain any known or suspected substance.

Section 13: Disposal considerations

13.1. Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

European Waste Catalogue (EWC)

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information

Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations.

Switzerland - Waste Ordinance

Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600
<https://www.fedlex.admin.ch/eli/cc/2015/891/en>

Section 14: Transport information

IMDG/IMO

14.1. UN number

UN2056

14.2. UN proper shipping name

TETRAHYDROFURAN

14.3. Transport hazard class(es)

3

14.4. Packing group

II

SAFETY DATA SHEET

Tetrahydrofuran

Revision Date 06-Dec-2024

ADR

14.1. UN number UN2056
14.2. UN proper shipping name TETRAHYDROFURAN
14.3. Transport hazard class(es) 3
14.4. Packing group II

IATA

14.1. UN number UN2056
14.2. UN proper shipping name TETRAHYDROFURAN
14.3. Transport hazard class(es) 3
14.4. Packing group II

14.5. Environmental hazards No hazards identified
14.6. Special precautions for user No special precautions required.
14.7. Maritime transport in bulk according to IMO instruments Not applicable, packaged goods

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Tetrahydrofuran	109-99-9	203-726-8	-	-	X	X	KE-33454	X	X
Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl-	128-37-0	204-881-4	-	-	X	X	KE-03079	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Tetrahydrofuran	109-99-9	X	ACTIVE	X	-	X	X	X
Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl-	128-37-0	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Tetrahydrofuran	109-99-9	-	Use restricted. See entry 75. (see link for restriction details)	-
Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl-	128-37-0	-	-	-

SAFETY DATA SHEET

Tetrahydrofuran

Revision Date 06-Dec-2024

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Tetrahydrofuran	109-99-9	Not applicable	Not applicable
Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl-	128-37-0	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

See table for values

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Tetrahydrofuran	WGK1	
Phenol, 2,6-bis(1,1-dimethylethyl)-4-methyl-	WGK 2	

Component	France - INRS (Tables of occupational diseases)
Tetrahydrofuran	Tableaux des maladies professionnelles (TMP) - RG 84

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Tetrahydrofuran 109-99-9 (>95)		Group I	

15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has been conducted by the manufacturer/importer

Section 16: Other information

SAFETY DATA SHEET

Tetrahydrofuran

Revision Date 06-Dec-2024

Full text of H-Statements referred to under sections 2 and 3

H225 - Highly flammable liquid and vapor
H302 - Harmful if swallowed
H319 - Causes serious eye irritation
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H351 - Suspected of causing cancer
EUH019 - May form explosive peroxides

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Chemical incident response training.

Creation Date

11-Jun-2009

Revision Date

06-Dec-2024

Revision Summary

SDS sections updated, 2, 7, 10, 15.

This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006. COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No 1907/2006 .

For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2, Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and Preparations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the

SAFETY DATA SHEET

Tetrahydrofuran

Revision Date 06-Dec-2024

date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet