

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

|                      |                                                       |
|----------------------|-------------------------------------------------------|
| Product Description: | <b>Petroleum ether 40-60°C</b>                        |
| Product Grade:       | ER, SQ, HPLC                                          |
| Cat No. :            | <b>Q32257, Q34507, Q32255, Q34505, Q3450C, Q43526</b> |
| Synonyms             | Ligroine                                              |
| Index No             | 649-328-00-1                                          |
| CAS No               | 64742-49-0                                            |
| EC No                | 931-254-9                                             |

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

|                                |                                                                                             |
|--------------------------------|---------------------------------------------------------------------------------------------|
| Recommended Use                | Laboratory chemicals.                                                                       |
| Sector of use                  | SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites    |
| Product category               | PC21 - Laboratory chemicals                                                                 |
| Process categories             | PROC15 - Use as a laboratory reagent                                                        |
| Environmental release category | ERC6a - Industrial use resulting in manufacture of another substance (use of intermediates) |
| Uses advised against           | No Information available                                                                    |

### 1.3. Details of the supplier of the safety data sheet

|         |                                                                                                                                   |
|---------|-----------------------------------------------------------------------------------------------------------------------------------|
| Company | Thermo Fisher Scientific India Pvt. Ltd<br>403-404, B-wing, Delphi,<br>Hiranandani Business Park,<br>Powai, Mumbai 4000076, INDIA |
|---------|-----------------------------------------------------------------------------------------------------------------------------------|

|                |                                     |
|----------------|-------------------------------------|
| E-mail address | laboratorysolution@thermofisher.com |
|----------------|-------------------------------------|

### 1.4. Emergency telephone number

India Toll Free: 18 00 22 22 30  
Chemtrec US: (800) 424-9300  
Chemtrec EU: 001 (202) 483-7616

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

#### CLP Classification - Regulation (EC) No 1272/2008

##### Physical hazards

Flammable liquids

Category 2 (H225)

##### Health hazards

# SAFETY DATA SHEET

Petroleum ether 40-60°C

Revision Date 02-May-2024

Aspiration Toxicity  
Skin Corrosion/Irritation  
Specific target organ toxicity - (single exposure)

Category 1 (H304)  
Category 2 (H315)  
Category 3 (H336)

## **Environmental hazards**

Chronic aquatic toxicity

Category 2 (H411)

Full text of Hazard Statements: see section 16

## **2.2. Label elements**



Signal Word

**Danger**

## **Hazard Statements**

H225 - Highly flammable liquid and vapor  
H304 - May be fatal if swallowed and enters airways  
H315 - Causes skin irritation  
H336 - May cause drowsiness or dizziness  
H411 - Toxic to aquatic life with long lasting effects

## **Precautionary Statements**

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P280 - Wear protective gloves/protective clothing  
P301 + P330 + P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting  
P302 + P352 - IF ON SKIN: Wash with plenty of soap and water  
P312 - Call a POISON CENTER or doctor if you feel unwell

## **2.3. Other hazards**

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)

This product does not contain any known or suspected endocrine disruptors

## **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

### **3.1. Substances**

| Component                                                  | CAS No     | EC No             | Weight % | CLP Classification - Regulation (EC) No 1272/2008                                                                 |
|------------------------------------------------------------|------------|-------------------|----------|-------------------------------------------------------------------------------------------------------------------|
| Hydrocarbons, C6, isoalkanes < 5%<br>n-hexane (Iso-Hexane) | 64742-49-0 | 931-254-9         | <100     | Flam. Liq. 2 (H225)<br>Asp. Tox. 1 (H304)<br>Skin Irrit. 2 (H315)<br>STOT SE 3 (H336)<br>Aquatic Chronic 2 (H411) |
| Hexane                                                     | 110-54-3   | EEC No. 203-777-6 | -        | Flam. Liq. 2 (H225)                                                                                               |

# SAFETY DATA SHEET

Petroleum ether 40-60°C

Revision Date 02-May-2024

|  |  |  |  |                                                                                                                                   |
|--|--|--|--|-----------------------------------------------------------------------------------------------------------------------------------|
|  |  |  |  | Asp. Tox. 1 (H304)<br>Skin Irrit. 2 (H315)<br>STOT SE 3 (H336)<br>Repr. 2 (H361f)<br>STOT RE 2 (H373)<br>Aquatic Chronic 2 (H411) |
|--|--|--|--|-----------------------------------------------------------------------------------------------------------------------------------|

| Component | Specific concentration limits (SCL's) | M-Factor | Component notes |
|-----------|---------------------------------------|----------|-----------------|
| Hexane    | STOT RE 2 (H373) :: C>=5%             | -        | -               |

## Note

UVCB Hydrocarbons  
C6, isoalkanes, < 5% n-Hexane

Reach Registration Number 01-2119484651-34

The classification as a carcinogen need not apply if the full refining history is known and it can be shown that the substance from which it is produced is not a carcinogen. This note applies only to certain complex oil derived substances in Annex I

Full text of Hazard Statements: see section 16

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

|                                           |                                                                                                                                                                                                     |
|-------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>General Advice</b>                     | If symptoms persist, call a physician.                                                                                                                                                              |
| <b>Eye Contact</b>                        | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.                                                                                     |
| <b>Skin Contact</b>                       | Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.                                                                                   |
| <b>Ingestion</b>                          | Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward. |
| <b>Inhalation</b>                         | Remove to fresh air. If not breathing, give artificial respiration. Get medical attention if symptoms occur. Risk of serious damage to the lungs (by aspiration).                                   |
| <b>Self-Protection of the First Aider</b> | Use personal protective equipment as required.                                                                                                                                                      |

### 4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting

### 4.3. Indication of any immediate medical attention and special treatment needed

|                           |                                                 |
|---------------------------|-------------------------------------------------|
| <b>Notes to Physician</b> | Treat symptomatically. Symptoms may be delayed. |
|---------------------------|-------------------------------------------------|

## SECTION 5: FIREFIGHTING MEASURES

# SAFETY DATA SHEET

Petroleum ether 40-60°C

Revision Date 02-May-2024

## 5.1. Extinguishing media

### **Suitable Extinguishing Media**

CO<sub>2</sub>, dry chemical, dry sand, alcohol-resistant foam. Water mist may be used to cool closed containers.

### **Extinguishing media which must not be used for safety reasons**

Do not use a solid water stream as it may scatter and spread fire.

## 5.2. Special hazards arising from the substance or mixture

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated. Thermal decomposition can lead to release of irritating gases and vapors. Keep product and empty container away from heat and sources of ignition.

### **Hazardous Combustion Products**

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>).

## 5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

### 6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

### 6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

### 6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

## **SECTION 7: HANDLING AND STORAGE**

### 7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Avoid ingestion and inhalation. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

### **Hygiene Measures**

Handle in accordance with good industrial hygiene and safety practice.

### 7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area.

# SAFETY DATA SHEET

Petroleum ether 40-60°C

Revision Date 02-May-2024

Technical Rules for Hazardous Substances (TRGS) 510  
Storage Class (LGK) (Germany)

Class 3

## 7.3. Specific end use(s)

Use in laboratories

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

#### Exposure limits

List source(s): **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC

| Component                                               | The United Kingdom                                                                      | European Union                                       | Ireland                                                                                                                   |
|---------------------------------------------------------|-----------------------------------------------------------------------------------------|------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| Hydrocarbons, C6, isoalkanes < 5% n-hexane (Iso-Hexane) | RCP Isohexanes, TWA (8 h)<br>250 ppm, 1000 mg/m <sup>3</sup>                            |                                                      |                                                                                                                           |
| Hexane                                                  | TWA: 72 mg/m <sup>3</sup><br>TWA: 20 ppm<br>STEL: 60 ppm<br>STEL: 216 mg/m <sup>3</sup> | TWA: 20 ppm (8hr)<br>TWA: 72 mg/m <sup>3</sup> (8hr) | TWA: 20 ppm 8 hr.<br>TWA: 72 mg/m <sup>3</sup> 8 hr.<br>STEL: 60 ppm 15 min<br>STEL: 216 mg/m <sup>3</sup> 15 min<br>Skin |

#### Biological limit values

#### Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

| Component                | Acute effects local (Dermal) | Acute effects systemic (Dermal) | Chronic effects local (Dermal) | Chronic effects systemic (Dermal) |
|--------------------------|------------------------------|---------------------------------|--------------------------------|-----------------------------------|
| Hexane<br>110-54-3 ( - ) |                              |                                 |                                | DNEL = 11mg/kg<br>bw/day          |

| Component                                                                      | Acute effects local (Inhalation) | Acute effects systemic (Inhalation) | Chronic effects local (Inhalation) | Chronic effects systemic (Inhalation) |
|--------------------------------------------------------------------------------|----------------------------------|-------------------------------------|------------------------------------|---------------------------------------|
| Hydrocarbons, C6, isoalkanes < 5% n-hexane (Iso-Hexane)<br>64742-49-0 ( <100 ) | DNEL = 1066.67mg/m <sup>3</sup>  | DNEL = 1286.4mg/m <sup>3</sup>      | DNEL = 837.5mg/m <sup>3</sup>      |                                       |
| Hexane<br>110-54-3 ( - )                                                       |                                  |                                     |                                    | DNEL = 75mg/m <sup>3</sup>            |

#### Predicted No Effect Concentration (PNEC)

Substance is complex UVCB.

### 8.2. Exposure controls

#### Engineering Measures

Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that

# SAFETY DATA SHEET

Petroleum ether 40-60°C

Revision Date 02-May-2024

eyewash stations and safety showers are close to the workstation location.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

## Personal protective equipment

**Eye Protection** Wear safety glasses with side shields (or goggles) (European standard - EN 166)

**Hand Protection** Protective gloves

| Glove material | Breakthrough time | Glove thickness | EU standard | Glove comments        |
|----------------|-------------------|-----------------|-------------|-----------------------|
| Nitrile rubber | See manufacturers | -               | EN 374      | (minimum requirement) |
| Viton (R)      | recommendations   |                 |             |                       |

**Skin and body protection** Wear appropriate protective gloves and clothing to prevent skin exposure.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves.

(Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g.

sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

**Respiratory Protection** When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.  
To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

**Large scale/emergency use** Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced  
**Recommended Filter type:** low boiling organic solvent Type AX Brown conforming to EN371

**Small scale/Laboratory use** Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.  
**Recommended half mask:-** Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141  
When RPE is used a face piece Fit Test should be conducted

**Environmental exposure controls** Prevent product from entering drains. Do not allow material to contaminate ground water system.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

|                                 |                                              |                                          |
|---------------------------------|----------------------------------------------|------------------------------------------|
| <b>Physical State</b>           | Liquid                                       |                                          |
| <b>Appearance</b>               | Colorless                                    |                                          |
| <b>Odor</b>                     | Petroleum distillates                        |                                          |
| <b>Odor Threshold</b>           | No data available                            |                                          |
| <b>Melting Point/Range</b>      | No data available                            |                                          |
| <b>Softening Point</b>          | No data available                            |                                          |
| <b>Boiling Point/Range</b>      | 40 - 70 °C / 104 - 158 °F                    |                                          |
| <b>Flammability (liquid)</b>    | Highly flammable                             | On basis of test data                    |
| <b>Flammability (solid,gas)</b> | Not applicable                               | Liquid                                   |
| <b>Explosion Limits</b>         | <b>Lower</b> 1 vol%<br><b>Upper</b> 7.4 vol% |                                          |
| <b>Flash Point</b>              | -45 °C / -49 °F                              | <b>Method -</b> No information available |
| <b>Autoignition Temperature</b> | 230 °C / 446 °F                              |                                          |

# SAFETY DATA SHEET

Petroleum ether 40-60°C

Revision Date 02-May-2024

|                                         |                                              |             |
|-----------------------------------------|----------------------------------------------|-------------|
| Decomposition Temperature               | No data available                            |             |
| pH                                      | No information available                     |             |
| Viscosity                               | 0.45 mm <sup>2</sup> /s at 25 °C (ASTM D445) |             |
| Water Solubility                        | Insoluble                                    |             |
| Solubility in other solvents            | No information available                     |             |
| Partition Coefficient (n-octanol/water) |                                              |             |
| Component                               | log Pow                                      |             |
| Hexane                                  | 4.11                                         |             |
| Vapor Pressure                          | 23 hPa @ 20 °C                               |             |
| Density / Specific Gravity              | 0.65                                         |             |
| Bulk Density                            | Not applicable                               | Liquid      |
| Vapor Density                           | >1 @ 101 kPa                                 | (Air = 1.0) |
| Particle characteristics                | (liquid) Not applicable                      |             |

## 9.2. Other information

|                      |                                             |
|----------------------|---------------------------------------------|
| Explosive Properties | Vapors may form explosive mixtures with air |
| Evaporation Rate     | 13 (Butyl acetate = 1.0)                    |

## SECTION 10: STABILITY AND REACTIVITY

|                  |                                            |
|------------------|--------------------------------------------|
| 10.1. Reactivity | None known, based on information available |
|------------------|--------------------------------------------|

|                          |                                 |
|--------------------------|---------------------------------|
| 10.2. Chemical stability | Stable under normal conditions. |
|--------------------------|---------------------------------|

## 10.3. Possibility of hazardous reactions

|                          |                                          |
|--------------------------|------------------------------------------|
| Hazardous Polymerization | Hazardous polymerization does not occur. |
| Hazardous Reactions      | None under normal processing.            |

|                           |                                                                                                       |
|---------------------------|-------------------------------------------------------------------------------------------------------|
| 10.4. Conditions to avoid | Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition. |
|---------------------------|-------------------------------------------------------------------------------------------------------|

|                              |                          |
|------------------------------|--------------------------|
| 10.5. Incompatible materials | Strong oxidizing agents. |
|------------------------------|--------------------------|

|                                        |                                                          |
|----------------------------------------|----------------------------------------------------------|
| 10.6. Hazardous decomposition products | Carbon monoxide (CO). Carbon dioxide (CO <sub>2</sub> ). |
|----------------------------------------|----------------------------------------------------------|

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Product Information

|                     |                                                                  |
|---------------------|------------------------------------------------------------------|
| (a) acute toxicity; |                                                                  |
| Oral                | Based on available data, the classification criteria are not met |
| Dermal              | Based on available data, the classification criteria are not met |
| Inhalation          | Based on available data, the classification criteria are not met |

#### Toxicology data for the components

| Component | LD50 Oral | LD50 Dermal | LC50 Inhalation |
|-----------|-----------|-------------|-----------------|
|-----------|-----------|-------------|-----------------|

# SAFETY DATA SHEET

Petroleum ether 40-60°C

Revision Date 02-May-2024

|                                                            |                           |                              |                              |
|------------------------------------------------------------|---------------------------|------------------------------|------------------------------|
| Hydrocarbons, C6, isoalkanes < 5%<br>n-hexane (Iso-Hexane) | LD50 > 5000 mg/kg ( Rat ) | LD50 > 3160 mg/kg ( Rabbit ) | LC50 = 73680 ppm ( Rat ) 4 h |
| Hexane                                                     | LD50 = 25 g/kg ( Rat )    | LD50 = 3000 mg/kg ( Rabbit ) | LC50 = 48000 ppm ( Rat ) 4 h |

(b) skin corrosion/irritation; Category 2

(c) serious eye damage/irritation; Based on available data, the classification criteria are not met

(d) respiratory or skin sensitization;

Respiratory

Based on available data, the classification criteria are not met

Skin

Based on available data, the classification criteria are not met

(e) germ cell mutagenicity;

Based on available data, the classification criteria are not met

(f) carcinogenicity;

Based on available data, the classification criteria are not met

The table below indicates whether each agency has listed any ingredient as a carcinogen. The classification as a carcinogen need not apply if the full refining history is known and it can be shown that the substance from which it is produced is not a carcinogen. This note applies only to certain complex oil derived substances in Annex I

| Component                                               | EU           | UK | Germany | IARC |
|---------------------------------------------------------|--------------|----|---------|------|
| Hydrocarbons, C6, isoalkanes < 5% n-hexane (Iso-Hexane) | Carc Cat. 1B |    |         |      |

(g) reproductive toxicity;

Reproductive Effects

Based on available data, the classification criteria are not met

California Proposition 65. Product is or contains a chemical which is a known or suspected reproductive hazard.

(h) STOT-single exposure;

Category 3

Results / Target organs

Central nervous system (CNS).

(i) STOT-repeated exposure;

Based on available data, the classification criteria are not met

Target Organs

None known.

(j) aspiration hazard;

Category 1

Symptoms / effects, both acute and delayed

Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

## 11.2. Information on other hazards

Endocrine Disrupting Properties

Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

Ecotoxicity effects

The product contains following substances which are hazardous for the environment. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.



# SAFETY DATA SHEET

Petroleum ether 40-60°C

Revision Date 02-May-2024

| Component                                               | Freshwater Fish                                                  | Water Flea          | Freshwater Algae |
|---------------------------------------------------------|------------------------------------------------------------------|---------------------|------------------|
| Hydrocarbons, C6, isoalkanes < 5% n-hexane (Iso-Hexane) | LC50: = 8.41 mg/L, 96h semi-static, closed (Oncorhynchus mykiss) |                     |                  |
| Hexane                                                  | LC50: 2.1 - 2.98 mg/L, 96h flow-through (Pimephales promelas)    | EC50: 3.87 mg/L/48h |                  |

## 12.2. Persistence and degradability

### Persistence

Persistence is unlikely, based on information available.

### Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

## 12.3. Bioaccumulative potential

Bioaccumulation is unlikely

| Component | log Pow | Bioconcentration factor (BCF) |
|-----------|---------|-------------------------------|
| Hexane    | 4.11    | No data available             |

## 12.4. Mobility in soil

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in air.

## 12.5. Results of PBT and vPvB assessment

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB).

## 12.6. Endocrine disrupting properties

### Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors.

## 12.7. Other adverse effects

### Persistent Organic Pollutant

This product does not contain any known or suspected substance.

### Ozone Depletion Potential

This product does not contain any known or suspected substance.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

#### Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

#### Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

#### European Waste Catalogue (EWC)

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

#### Other Information

Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not let this chemical enter the environment. Do not empty into drains.

# SAFETY DATA SHEET

Petroleum ether 40-60°C

Revision Date 02-May-2024

## SECTION 14: TRANSPORT INFORMATION

### IMDG/IMO

**14.1. UN number** UN1268  
**14.2. UN proper shipping name** Petroleum distillates, n.o.s.  
**14.3. Transport hazard class(es)** 3  
**14.4. Packing group** II

### ADR

**14.1. UN number** UN1268  
**14.2. UN proper shipping name** Petroleum distillates, n.o.s.  
**14.3. Transport hazard class(es)** 3  
**14.4. Packing group** II

### IATA

**14.1. UN number** UN1268  
**14.2. UN proper shipping name** Petroleum distillates, n.o.s.  
**14.3. Transport hazard class(es)** 3  
**14.4. Packing group** II

**14.5. Environmental hazards** Dangerous for the environment  
Product is a marine pollutant according to the criteria set by IMDG/IMO

**14.6. Special precautions for user** No special precautions required.

**14.7. Maritime transport in bulk according to IMO instruments** Not applicable, packaged goods

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

| Component                                               | CAS No     | EINECS    | ELINCS    | NLP | IECSC | TCSI | KECL     | ENCS | ISHL |
|---------------------------------------------------------|------------|-----------|-----------|-----|-------|------|----------|------|------|
| Hydrocarbons, C6, isoalkanes < 5% n-hexane (Iso-Hexane) | 64742-49-0 | 265-151-9 | -         | -   | X     | X    | KE-25623 | -    | -    |
| Hexane                                                  | 110-54-3   | 203-777-6 | 438-390-3 | -   | X     | X    | KE-18626 | X    | X    |

| Component                                               | CAS No     | TSCA | TSCA Inventory notification - Active-Inactive | DSL | NDSL | AICS | NZIoC | PICCS |
|---------------------------------------------------------|------------|------|-----------------------------------------------|-----|------|------|-------|-------|
| Hydrocarbons, C6, isoalkanes < 5% n-hexane (Iso-Hexane) | 64742-49-0 | X    | ACTIVE                                        | X   | -    | X    | X     | X     |
| Hexane                                                  | 110-54-3   | X    | ACTIVE                                        | X   | -    | X    | X     | X     |

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

QUAQ43526

# SAFETY DATA SHEET

Petroleum ether 40-60°C

Revision Date 02-May-2024

| Component                                               | CAS No     | REACH (1907/2006) - Annex XIV - Substances Subject to Authorization | REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances                                                                                                                                  | REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC) |
|---------------------------------------------------------|------------|---------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------|
| Hydrocarbons, C6, isoalkanes < 5% n-hexane (Iso-Hexane) | 64742-49-0 | -                                                                   | Use restricted. See item 28.<br>(see link for restriction details)<br>Use restricted. See item 29.<br>(see link for restriction details)<br>Use restricted. See item 75.<br>(see link for restriction details) | -                                                                                                     |
| Hexane                                                  | 110-54-3   | -                                                                   | Use restricted. See item 75.<br>(see link for restriction details)                                                                                                                                             | -                                                                                                     |

## REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

## Seveso III Directive (2012/18/EC)

| Component                                               | CAS No     | Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification | Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements |
|---------------------------------------------------------|------------|-------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|
| Hydrocarbons, C6, isoalkanes < 5% n-hexane (Iso-Hexane) | 64742-49-0 | Not applicable                                                                            | Not applicable                                                                           |
| Hexane                                                  | 110-54-3   | Not applicable                                                                            | Not applicable                                                                           |

## Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

## Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

## National Regulations

**UK** - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

## WGK Classification

See table for values

| Component                                               | Germany - Water Classification (AwSV) | Germany - TA-Luft Class |
|---------------------------------------------------------|---------------------------------------|-------------------------|
| Hydrocarbons, C6, isoalkanes < 5% n-hexane (Iso-Hexane) | WGK2                                  |                         |
| Hexane                                                  | WGK2                                  |                         |

| Component                      | France - INRS (Tables of occupational diseases)      |
|--------------------------------|------------------------------------------------------|
| Hydrocarbons, C6, isoalkanes < | Tableaux des maladies professionnelles (TMP) - RG 84 |

# SAFETY DATA SHEET

Petroleum ether 40-60°C

Revision Date 02-May-2024

|                          |                                                            |
|--------------------------|------------------------------------------------------------|
| 5% n-hexane (Iso-Hexane) |                                                            |
| Hexane                   | Tableaux des maladies professionnelles (TMP) - RG 59,RG 84 |

| Component              | Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81) | Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC) | Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure |
|------------------------|----------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|
| Hexane<br>110-54-3 (-) | Prohibited and Restricted Substances                                                                           | Group I                                                                         |                                                                                             |

## 15.2. Chemical safety assessment

A Chemical Safety Assessment/Report (CSA/CSR) has not been conducted

## SECTION 16: OTHER INFORMATION

### Full text of H-Statements referred to under sections 2 and 3

H225 - Highly flammable liquid and vapor  
H304 - May be fatal if swallowed and enters airways  
H315 - Causes skin irritation  
H336 - May cause drowsiness or dizziness  
H411 - Toxic to aquatic life with long lasting effects

### Legend

**CAS** - Chemical Abstracts Service

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**ENCS** - Japanese Existing and New Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**NZIoC** - New Zealand Inventory of Chemicals

**WEL** - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

**RPE** - Respiratory Protective Equipment

**LC50** - Lethal Concentration 50%

**NOEC** - No Observed Effect Concentration

**PBT** - Persistent, Bioaccumulative, Toxic

**TWA** - Time Weighted Average

**IARC** - International Agency for Research on Cancer  
Predicted No Effect Concentration (PNEC)

**LD50** - Lethal Dose 50%

**EC50** - Effective Concentration 50%

**POW** - Partition coefficient Octanol:Water

**vPvB** - very Persistent, very Bioaccumulative

**ADR** - European Agreement Concerning the International Carriage of Dangerous Goods by Road

**IMO/IMDG** - International Maritime Organization/International Maritime Dangerous Goods Code

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

### Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

**ICAO/IATA** - International Civil Aviation Organization/International Air Transport Association

**MARPOL** - International Convention for the Prevention of Pollution from Ships

**ATE** - Acute Toxicity Estimate

**VOC** - (Volatile Organic Compound)

### Training Advice

Chemical incident response training.

**Creation Date**

06-Nov-2009

**Revision Date**

02-May-2024

**Revision Summary**

Next Revision Date - Oct 2028.

# SAFETY DATA SHEET

Petroleum ether 40-60°C

Revision Date 02-May-2024

---

**This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.**

.

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**