

Creation Date 10-Mar-2010

Revision Date 09-Feb-2024

Revision Number 10

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**1.1. Product identifier**

Product Description: Dimethylamine, 26% solution in water
Cat No. : 408000000; 408000010; 408000050
Synonyms DMA; N-Methyl-Methanamine.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet**Company**

EU entity/business name
Thermo Fisher Scientific
Janssen Pharmaceuticaaan 3a, 2440 Geel, Belgium

UK entity/business name
Fisher Scientific UK
Bishop Meadow Road,
Loughborough, Leicestershire LE11 5RG, United Kingdom

Swiss distributor - Fisher Scientific AG
Neuhofstrasse 11, CH 4153 Reinach
Tel: +41 (0) 56 618 41 11
e-mail - infoch@thermofisher.com

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99
CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

customers in Switzerland:
Tox Info Suisse Emergency Number: **145 (24hr)**
Tox Info Suisse: +41-44 251 51 51 (Emergency number from abroad)
Chemtrec (24h) Toll-Free: 0800 564 402
Chemtrec Local: +41-43 508 20 11 (Zurich)

SECTION 2: HAZARDS IDENTIFICATION**2.1. Classification of the substance or mixture**

SAFETY DATA SHEET

Dimethylamine, 26% solution in water

Revision Date 09-Feb-2024

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Flammable liquids

Category 2 (H225)

Health hazards

Acute oral toxicity

Category 4 (H302)

Acute Inhalation Toxicity - Vapors

Category 4 (H332)

Skin Corrosion/Irritation

Category 1 B (H314)

Serious Eye Damage/Eye Irritation

Category 1 (H318)

Specific target organ toxicity - (single exposure)

Category 3 (H335)

Environmental hazards

Chronic aquatic toxicity

Category 3 (H412)

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor

H314 - Causes severe skin burns and eye damage

H335 - May cause respiratory irritation

H412 - Harmful to aquatic life with long lasting effects

H302 + H332 - Harmful if swallowed or if inhaled

Precautionary Statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/physician

2.3. Other hazards

This product does not contain any known or suspected endocrine disruptors

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

SAFETY DATA SHEET

Dimethylamine, 26% solution in water

Revision Date 09-Feb-2024

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Dimethylamine	124-40-3	EEC No. 204-697-4	26-45	Flam. Liq. 1 (H224) Acute Tox. 4 (H302) Acute Tox. 4 (H332) Skin Corr. 1B (H314) Eye Dam. 1 (H318) STOT SE 3 (H335) Aquatic chronic 3 (H412)
Water	7732-18-5	231-791-2	55-74	-

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Dimethylamine	STOT SE 3 :: C>=5%	-	-

Components	Reach Registration Number
Dimethylamine	01-2119475495-27

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Call a physician immediately.
Ingestion	Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately.
Inhalation	If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Causes burns by all exposure routes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically.
---------------------------	------------------------

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

SAFETY DATA SHEET

Dimethylamine, 26% solution in water

Revision Date 09-Feb-2024

Suitable Extinguishing Media

Dry chemical, Alcohol resistant foam. Water mist may be used to cool closed containers. CO₂, dry chemical, dry sand, alcohol-resistant foam.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Nitrogen oxides (NO_x).

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Should not be released into the environment. Do not flush into surface water or sanitary sewer system.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks and flame. Flammables area. Corrosives area.

SAFETY DATA SHEET

Dimethylamine, 26% solution in water

Revision Date 09-Feb-2024

Technical Rules for Hazardous Substances (TRGS) 510
Storage Class (LGK) (Germany)

Class 3

Switzerland - Storage of hazardous substances

Storage class - SC 3
<https://www.kvu.ch/de/themen/stoffe-und-produkte>
<https://www.kvu.ch/fr/themes/substances-et-produits>
<https://www.kvu.ch/it/temi/sostanze-e-prodotti>

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Forth edition. Published 2020. **IRE** - 2010 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001. Published by the Health and Safety Authority. **CH** - The Government of Switzerland has set a directive on limit values for working materials (Grenzwerte am Arbeitsplatz) which is based on the Swiss Federal Regulation "Verordnung über die Verhütung von Unfällen und Berufskrankheiten". This directive is administered, periodically revised and enforced by SUVA (Swiss National Accident Insurance Fund).

Component	European Union	The United Kingdom	France	Belgium	Spain
Dimethylamine	TWA: 2 ppm (8h) TWA: 3.8 mg/m ³ (8h) STEL: 5 ppm (15min) STEL: 9.4 mg/m ³ (15min)	STEL: 6 ppm 15 min STEL: 11 mg/m ³ 15 min TWA: 2 ppm 8 hr TWA: 3.8 mg/m ³ 8 hr	TWA / VME: 1 ppm (8 heures). restrictive limit TWA / VME: 1.9 mg/m ³ (8 heures). restrictive limit STEL / VLCT: 2 ppm. restrictive limit STEL / VLCT: 3.8 mg/m ³ . restrictive limit	TWA: 2 ppm 8 uren TWA: 3.8 mg/m ³ 8 uren STEL: 5 ppm 15 minuten STEL: 9.4 mg/m ³ 15 minuten	STEL / VLA-EC: 5 ppm (15 minutos). STEL / VLA-EC: 9.4 mg/m ³ (15 minutos). TWA / VLA-ED: 2 ppm (8 horas) TWA / VLA-ED: 3.8 mg/m ³ (8 horas)

Component	Italy	Germany	Portugal	The Netherlands	Finland
Dimethylamine	TWA: 2 ppm 8 ore. Time Weighted Average TWA: 3.8 mg/m ³ 8 ore. Time Weighted Average STEL: 5 ppm 15 minuti. Short-term STEL: 9.4 mg/m ³ 15 minuti. Short-term	TWA: 2 ppm (8 Stunden). AGW - exposure factor 2 TWA: 3.7 mg/m ³ (8 Stunden). AGW - exposure factor 2 TWA: 2 ppm (8 Stunden). MAK even if the MAK value is adhered to, "odor-associated" symptoms cannot be ruled out in individual cases TWA: 3.7 mg/m ³ (8 Stunden). MAK even if the MAK value is adhered to, "odor-associated" symptoms cannot be ruled out in individual cases Höhepunkt: 4 ppm Höhepunkt: 7.4 mg/m ³	STEL: 5 ppm 15 minutos STEL: 9.4 mg/m ³ 15 minutos TWA: 2 ppm 8 horas TWA: 3.8 mg/m ³ 8 horas	TWA: 1.8 mg/m ³ 8 uren	TWA: 2 ppm 8 tunteina TWA: 3.7 mg/m ³ 8 tunteina STEL: 5 ppm 15 minuutteina STEL: 9.4 mg/m ³ 15 minuutteina

Component	Austria	Denmark	Switzerland	Poland	Norway
Dimethylamine	MAK-KZGW: 2 ppm 15 Minuten MAK-KZGW: 3.8 mg/m ³ 15 Minuten MAK-TMW: 2 ppm 8	TWA: 2 ppm 8 timer TWA: 3.8 mg/m ³ 8 timer STEL: 9.4 mg/m ³ 15 minutter STEL: 5 ppm 15	STEL: 4 ppm 15 Minuten STEL: 8 mg/m ³ 15 Minuten TWA: 2 ppm 8 Stunden	STEL: 9 mg/m ³ 15 minutach TWA: 3 mg/m ³ 8 godzinach	TWA: 2 ppm 8 timer TWA: 4 mg/m ³ 8 timer STEL: 4 ppm 15 minutter. value calculated

SAFETY DATA SHEET

Dimethylamine, 26% solution in water

Revision Date 09-Feb-2024

	Stunden MAK-TMW: 3.8 mg/m ³ 8 Stunden Ceiling: 2 ppm Ceiling: 3.8 mg/m ³	minutter	TWA: 4 mg/m ³ 8 Stunden		STEL: 8 mg/m ³ 15 minutter. value calculated
--	--	----------	---------------------------------------	--	---

Component	Bulgaria	Croatia	Ireland	Cyprus	Czech Republic
Dimethylamine	TWA: 2 ppm TWA: 3.8 mg/m ³ STEL : 5 ppm STEL : 9.4 mg/m ³	kože TWA-GVI: 2 ppm 8 satima. TWA-GVI: 3.8 mg/m ³ 8 satima. STEL-KGVI: 5 ppm 15 minutama. STEL-KGVI: 9.4 mg/m ³ 15 minutama.	TWA: 2 ppm 8 hr. TWA: 3.8 mg/m ³ 8 hr. STEL: 5 ppm 15 min STEL: 9.4 mg/m ³ 15 min	STEL: 5.0 ppm STEL: 9.4 mg/m ³ TWA: 2 ppm TWA: 3.8 mg/m ³	TWA: 3.8 mg/m ³ 8 hodinách. Potential for cutaneous absorption Ceiling: 9 mg/m ³

Component	Estonia	Gibraltar	Greece	Hungary	Iceland
Dimethylamine	TWA: 2 ppm 8 tundides. TWA: 3.8 mg/m ³ 8 tundides. STEL: 5 ppm 15 minutites. STEL: 9.4 mg/m ³ 15 minutites.	TWA: 2 ppm 8 hr TWA: 3.8 mg/m ³ 8 hr STEL: 5 ppm 15 min STEL: 9.4 mg/m ³ 15 min	STEL: 15 ppm STEL: 27 mg/m ³ TWA: 10 ppm TWA: 18 mg/m ³	STEL: 9.4 mg/m ³ 15 percekben. CK TWA: 3.8 mg/m ³ 8 órában. AK lehetséges borón keresztüli felszívódás	STEL: 5 ppm STEL: 9.4 mg/m ³ TWA: 2 ppm 8 klukkustundum. TWA: 3.8 mg/m ³ 8 klukkustundum.

Component	Latvia	Lithuania	Luxembourg	Malta	Romania
Dimethylamine	STEL: 5 ppm STEL: 9.4 mg/m ³ TWA: 2 ppm TWA: 3.8 mg/m ³	TWA: 2 ppm IPRD TWA: 3.8 mg/m ³ IPRD STEL: 5 ppm STEL: 9.4 mg/m ³	TWA: 2 ppm 8 Stunden TWA: 3.8 mg/m ³ 8 Stunden STEL: 5 ppm 15 Minuten STEL: 9.4 mg/m ³ 15 Minuten	TWA: 2 ppm TWA: 3.8 mg/m ³ STEL: 5 ppm 15 minuti STEL: 9.4 mg/m ³ 15 minuti	TWA: 2 ppm 8 ore TWA: 3.8 mg/m ³ 8 ore STEL: 9.4 mg/m ³ 15 minute STEL: 5 ppm 15 minute

Component	Russia	Slovak Republic	Slovenia	Sweden	Turkey
Dimethylamine	Skin notation MAC: 1 mg/m ³	Ceiling: 9.4 mg/m ³ TWA: 2 ppm TWA: 3.8 mg/m ³	TWA: 2 ppm 8 urah TWA: 3.8 mg/m ³ 8 urah STEL: 5 ppm 15 minutah STEL: 9.4 mg/m ³ 15 minutah	Binding STEL: 5 ppm 15 minuter Binding STEL: 9 mg/m ³ 15 minuter TLV: 2 ppm 8 timmar. NGV TLV: 3.5 mg/m ³ 8 timmar. NGV	TWA: 2 ppm 8 saat TWA: 3.8 mg/m ³ 8 saat STEL: 5 ppm 15 dakika STEL: 9.4 mg/m ³ 15 dakika

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Monitoring methods

BS EN 14042:2003 Title Identifier: Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents.

MDHS70 General methods for sampling airborne gases and vapours

MDHS 88 Volatile organic compounds in air. Laboratory method using diffusive samplers, solvent desorption and gas chromatography

MDHS 96 Volatile organic compounds in air - Laboratory method using pumped solid sorbent tubes, solvent desorption and gas chromatography

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
-----------	---------------------------------	------------------------------------	-----------------------------------	--------------------------------------

SAFETY DATA SHEET

Dimethylamine, 26% solution in water

Revision Date 09-Feb-2024

Dimethylamine 124-40-3 (26-45)		DNEL = 1.95mg/kg bw/day		DNEL = 0.0874mg/kg bw/day
-------------------------------------	--	----------------------------	--	------------------------------

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Dimethylamine 124-40-3 (26-45)	DNEL = 12.9mg/m ³	DNEL = 9.4mg/m ³		DNEL = 3.8mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Dimethylamine 124-40-3 (26-45)	PNEC = 0.06mg/L	PNEC = 3.26mg/kg sediment dw	PNEC = 0.06mg/L	PNEC = 100mg/L	PNEC = 0.0385mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water Intermittent	Food chain	Air
Dimethylamine 124-40-3 (26-45)	PNEC = 0.006mg/L	PNEC = 0.33mg/kg sediment dw			

8.2. Exposure controls

Engineering Measures

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles (European standard - EN 166)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Nitrile rubber	< 60 minutes	0.38 mm	Level 3	Permeation rate ~2000 µg/cm ² /min
Butyl rubber	< 30 minutes	0.635 mm	Level 2 EN 374	As tested under EN374-3 Determination of Resistance to Permeation by Chemicals

Skin and body protection

Long sleeved clothing.

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: Particulates filter conforming to EN 143 or Ammonia and organic ammonia derivatives filter Type K Green

Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Particle filtering: EN149:2001; or; Valve filtering: EN405
When RPE is used a face piece Fit Test should be conducted

SAFETY DATA SHEET

Dimethylamine, 26% solution in water

Revision Date 09-Feb-2024

Environmental exposure controls Prevent product from entering drains.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance	Colorless	
Odor	Ammonia-like, Fishy, Strong	
Odor Threshold	No data available	
Melting Point/Range	-37 °C / -34.6 °F	
Softening Point	No data available	
Boiling Point/Range	54 °C / 129.2 °F	
Flammability (liquid)	Highly flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	Lower 2.6 vol % Upper 12.3 vol %	
Flash Point	-18 °C / -0.4 °F	Method - No information available
Autoignition Temperature	390 °C / 734 °F	
Decomposition Temperature	No data available	
pH	12	(1%)
Viscosity	No data available	
Water Solubility	>500 g/L (20°C)	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Dimethylamine	-0.274	
Vapor Pressure	287 mbar @ 25 °C	
Density / Specific Gravity	0.775-0.890	
Bulk Density	Not applicable	Liquid
Vapor Density	1.55	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

9.2. Other information

Explosive Properties	Vapors may form explosive mixtures with air
Evaporation Rate	No information available

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity	None known, based on information available
-------------------------	--

10.2. Chemical stability	Stable under normal conditions.
---------------------------------	---------------------------------

10.3. Possibility of hazardous reactions

Hazardous Polymerization	No information available.
Hazardous Reactions	None under normal processing.

10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition. Incompatible products. Excess heat.

10.5. Incompatible materials

Metals. Strong oxidizing agents. Acids. Halogens. Peroxides. Carbon dioxide (CO2).

SAFETY DATA SHEET

Dimethylamine, 26% solution in water

Revision Date 09-Feb-2024

10.6. Hazardous decomposition products

Nitrogen oxides (NOx).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral

Category 4

Dermal

Based on available data, the classification criteria are not met

Inhalation

Category 4

Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Dimethylamine	LD50 = 698 mg/kg (Rat)	LD50 = 3900 mg/kg (Rat)	LC50 = 7340 ppm (Rat) 20 min
Water	-	-	-

(b) skin corrosion/irritation;

Category 1 B

(c) serious eye damage/irritation;

Category 1

(d) respiratory or skin sensitization;

Respiratory

No data available

Skin

No data available

(e) germ cell mutagenicity;

No data available

(f) carcinogenicity;

No data available

There are no known carcinogenic chemicals in this product

(g) reproductive toxicity;

No data available

(h) STOT-single exposure;

Category 3

Results / Target organs

Respiratory system.

(i) STOT-repeated exposure;

No data available

Target Organs

None known.

(j) aspiration hazard;

Based on available data, the classification criteria are not met

Symptoms / effects, both acute and delayed

Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation.

11.2. Information on other hazards

Endocrine Disrupting Properties

Assess endocrine disrupting properties for human health. This product does not contain any

SAFETY DATA SHEET

Dimethylamine, 26% solution in water

Revision Date 09-Feb-2024

known or suspected endocrine disruptors.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

This product contains the following substance(s) which are hazardous for the environment. Contains a substance which is: Harmful to aquatic organisms. The product contains following substances which are hazardous for the environment. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Dimethylamine	LC50: = 396 mg/L, 96h static (Brachydanio rerio) LC50: 127 - 349 mg/L, 96h semi-static (Poecilia reticulata) LC50: = 210 mg/L, 96h static (Poecilia reticulata) LC50: = 120 mg/L, 96h static (Oncorhynchus mykiss) LC50: 111 - 125 mg/L, 96h (Oncorhynchus mykiss)	EC50: = 88.7 mg/L, 48h (Daphnia magna Straus)	EC50: = 9 mg/L, 96h (Pseudokirchneriella subcapitata)

12.2. Persistence and degradability

Persistence

Persistence is unlikely, based on information available.

Degradation in sewage treatment plant

Contains no substances known to be hazardous to the environment or not degradable in waste water treatment plants. Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Dimethylamine	-0.274	No data available

12.4. Mobility in soil

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in air.

12.5. Results of PBT and vPvB assessment

No data available for assessment.

12.6. Endocrine disrupting properties

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance
This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers

SAFETY DATA SHEET

Dimethylamine, 26% solution in water

Revision Date 09-Feb-2024

retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

European Waste Catalogue (EWC) According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

Other Information Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms. Do not let this chemical enter the environment.

Switzerland - Waste Ordinance Disposal should be in accordance with applicable regional, national and local laws and regulations. Ordinance on the Avoidance and the Disposal of Waste (Waste Ordinance, ADWO) SR 814.600
<https://www.fedlex.admin.ch/eli/cc/2015/891/en>

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number UN1160
14.2. UN proper shipping name DIMETHYLAMINE, AQUEOUS SOLUTION
14.3. Transport hazard class(es) 3
Subsidiary Hazard Class 8
14.4. Packing group II

ADR

14.1. UN number UN1160
14.2. UN proper shipping name DIMETHYLAMINE AQUEOUS SOLUTION
14.3. Transport hazard class(es) 3
Subsidiary Hazard Class 8
14.4. Packing group II

IATA

14.1. UN number UN1160
14.2. UN proper shipping name DIMETHYLAMINE, AQUEOUS SOLUTION
14.3. Transport hazard class(es) 3
Subsidiary Hazard Class 8
14.4. Packing group II

14.5. Environmental hazards No hazards identified

14.6. Special precautions for user No special precautions required.

14.7. Maritime transport in bulk according to IMO instruments Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Dimethylamine	124-40-3	204-697-4	-	-	X	X	KE-11124	X	X
Water	7732-18-5	231-791-2	-	-	X	X	KE-35400	X	-

SAFETY DATA SHEET

Dimethylamine, 26% solution in water

Revision Date 09-Feb-2024

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Dimethylamine	124-40-3	X	ACTIVE	X	-	X	X	X
Water	7732-18-5	X	ACTIVE	X	-	X	X	X

Legend: X - Listed '-' - Not Listed

KECL - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Dimethylamine	124-40-3	-	Use restricted. See item 75. (see link for restriction details)	-
Water	7732-18-5	-	-	-

REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Dimethylamine	124-40-3	Not applicable	Not applicable
Water	7732-18-5	Not applicable	Not applicable

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

National Regulations

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

WGK Classification

Water endangering class = 1 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Dimethylamine	WGK1	Class I : 20 mg/m ³ (Massenkonzentration)

Component	France - INRS (Tables of occupational diseases)
Dimethylamine	Tableaux des maladies professionnelles (TMP) - RG 49,RG 49bis

Swiss Regulations

Article 4 para. 4 of the Ordinance on the protection of young people in the workplace (SR 822.115) and Article 1 lit. f of the EAER regulation on hazardous work and young people (SR 822.115.2).

Take note on Article 13 Maternity Ordinance (SR 822.111.52) with regards expectant and nursing mothers.

SAFETY DATA SHEET

Dimethylamine, 26% solution in water

Revision Date 09-Feb-2024

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

H302 - Harmful if swallowed
H332 - Harmful if inhaled
H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage
H335 - May cause respiratory irritation
H412 - Harmful to aquatic life with long lasting effects
H224 - Extremely flammable liquid and vapor

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

IPCCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer
Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadviser - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (volatile organic compound)

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data

Health Hazards Calculation method

Environmental hazards Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Creation Date 10-Mar-2010

Revision Date 09-Feb-2024

Revision Summary Not applicable.

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.
COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No
1907/2006 .**

SAFETY DATA SHEET

Dimethylamine, 26% solution in water

Revision Date 09-Feb-2024

For Switzerland - Compiled in accordance with the technical provisions referred to in Annex 2, Number 3, ChemO (SR 813.11 - Ordinance on Protection against Dangerous Substances and Preparations).

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet